




SKIMMERS




Skimmers are important accessories for the removal of floating debris on free board type pools and should be installed on the basis of one per 25-50m² of pool area. Options are:

Dayliff: Two models are available, standard mouth flap type and slim line skimmers both moulded from ABS

Certikin: A premium quality wide mouth collar weir type skimmer moulded from ABS

Dimensions (mm)				
	A	B	C	D
Certikin	365	430	600	154
Dayliff Standard	405	416	484	167
Dayliff Slim line	539	484	634	148
Quality	250	480	430	194


LADDERS



Tubular ladders from Dayliff and Certikin, both made from 42mm polished stainless steel. Dayliff is available in two designs Standard and Club. Ladders are supplied complete with stainless steel treads, anchor sockets and rubber end pads and are available in two, three and four step configurations. Other designs and tread types are available on special order.

Model	Dimensions (mm)						
	A	B	C	D			E
				2 STEP	3 STEP	4 STEP	G
DAYLIFF STD	580	720		1300	1550	1800	170
DAYLIFF CLUB	600	720	250	1300	1550	1800	280

SUCTION OUTLETS




A selection of suction outlets are available, either the chamber type with integral grilles for casting into the pool floor or gratings for covering pre-cast sumps.

Suction Chambers: PVC moulded chamber with screwed grille covers. Two types are available both including anti-vortex gratings. Recommended maximum flow is 13m³/hr for Certikin and 33m³/hr for Dayliff.

Dayliff Suction Gratings: GRP and S/S suction gratings available in 300mm and 450mm sizes.


Dimensions (mm)		
Model	A	B
Certikin	220	150
Dayliff	193	200

DECK LEVEL GRILLES



Dayliff grilles are specially designed to cover the overflow channels in Deck Level pools and due to the central tongue and socket connection are suitable for both straight and curved edges. They are made from hard wearing UV treated moulded plastic and are available in five standard colours (blue, white, sand brown, terracota red and grey) and two widths (200 and 250mm). Also available are GRP spacer corner pieces for corners. Due to the grilles strength no special channel edging is necessary, and they should be supported by a counter sunk recess moulded in the channel rim.

INLETS



Various Certikin inlets are offered for both wall and floor applications, all being suitable for up to 5m³/hr flow rates.

Wall Inlet: Moulded PVC with 1½" internal and 2" external BSP threads and fitted with adjustable eyeball flow director. Inlets are available either loose or with a 450mm PVC connecting pipe and water bar for easy fitting in the pool wall.

Vacuum Outlet: A standard inlet body fitted with a screwed cover

Floor Inlet: Two options are offered in rectangular and circular designs. Both can also be used as gutter and surround drains. Outlet connection is 50mm.

HAND RAILS



Stainless steel 32mm handrails with blanked ends available in lengths of 1m, 1.9m, 2.9m & 3.9m or alternatively sized to order for straight wall installations only.

Stocks of 12mm stainless steel open and closed anchors with stoppers are available. The recommended anchors interval is not more than 1.5m. The anchors are secured in apertures in the pool wall using concrete glue also available in stock.

Also available is a detached **pool step S/S handrail** for support to swimmer accessing the pool through steps. The curved handrail is anchored on the pool deck only thereby making it easy for installation on a ready swimming pool.