



PUMP

Pedrollo 6SR44 submersible pumps are specifically designed for supply from boreholes, though can also be used in other submersible applications in either vertical or horizontal configuration. They feature a hydraulic design that incorporates floating impellers which together with especially resistant component materials provide high resistance to sand content in the pumped water.

The pump impellers and diffusers are made from technopolymer while the stage casings, top housing, suction connector, pump sleeve and shaft are made of AISI 304 stainless steel. The pump is supplied with a 4m tail cable.

MOTOR

Pumps are coupled to a two pole sealed motor constructed principally from stainless steel. Motors require a remote direct in-line starter and if irregular electrical supply is prevalent an additional quick tripping multi function protection relay is recommended.

Enclosure Class : IP68 **Insulation Class :** F **Speed:** 2900rpm **Voltage:** 3x415V

OPERATING CONDITIONS

Pumped Liquid: Thin, clean, chemically non aggressive liquids with a maximum sand content of 100gm/m³.

Max. Liquid Temperature: +35°C

Max. Immersion Depth: 200m

Min. Borehole Diameter: 200mm

PUMP DATA

Model	Motor		Current (A) 3x415V	DN (")	Dimensions(mm)		Weight (Kg)
	kW	HP			H1	H2	
6SR44/8	11	15	24	3	1275	826	32
6SR44/11	15	20	32		1613	894	40
6SR44/13	18.5	25	39		1839	959	45
6SR44/16	22	30	47		2178	1116	54
6SR44/21	30	40	64		2743	1243	63

