




6SR12

Submersible Borehole Pumps



PUMP

Pedrollo 6SR12 submersible pumps are specifically designed for supply from boreholes, though can also be used in other submersible applications in either vertical or horizontal configuration. They feature a hydraulic design that incorporates floating impellers which together with especially resistant component materials provide high resistance to sand content in the pumped water.

The pump impellers and diffusers are made from technopolymer while the stage casings, top housing, suction connector, pump sleeve and shaft are made of AISI 304 stainless steel. The pump is supplied with a 4m tail cable.

MOTOR

Pumps are coupled to a two pole sealed motor constructed principally from stainless steel. Motors require a remote direct in-line starter and if irregular electrical supply is prevalent an additional quick tripping multi function protection relay is recommended.

Enclosure Class: IP68 Insulation Class: F Speed: 2900rpm Voltage: 3x415V

OPERATING CONDITIONS

Pumped Liquid: Thin, clean, chemically non aggressive liquids with a maximum sand content of 100gm/m³.

Max. Liquid Temperature: +35°C Max. Immersion Depth: 200m Min. Borehole Diameter: 200mm

PUMP DATA

Model	Motor		Current	DN	Dimensions(mm)		Weight
	kW	НР	(A)	(")	Н1	H2	(Kg)
6SR12/11	5.5	7.5	13	3	849	667	61
6SR12/15	7.5	10	17		1068	698	67
6SR12/18	9.2	12.5	22		1198	731	73
6SR12/21	11	15	24		1328	826	84
6SR12/25	15	20	32		1502	894	96
6SR12/28					1632		98

