KODENSHI AUK

SMK1625D2

Advanced N-Ch Power MOSFET

DC-DC CONVERTER APPLICATION
HIGH VOLTAGE SWITCHING APPLICATIONS

Features

- High Voltage : BV_{DSS}=250V (Min.)
- Low C_{rss} : C_{rss}=49pF (Typ.)
- Low gate charge : Q_g=22nC (Typ.)
- Low $R_{DS(on)}$: $R_{DS(on)}$=0.27Ω (Max.)

PIN Connection



D2-PAK

Ordering Information

Type No.	Marking	Package Code
SMK1625D2	SMK1625	D2-PAK

Marking Diagram



Column 1 : Manufacturer

Column 2 : Production Information
e.g.) GYMDD
-. G : Factory management code
-. YMDD : Date Code (year, month, date)

Column 3 : Device Code

Absolute maximum ratings (T_C=25°C unless otherwise noted)

Characteristic		Symbol		Rating	Unit
Drain-source voltage		V_{DSS}		250	V
Gate-source voltage		V_{GSS}		±30	V
Drain current (DC) *		I_D	(T_C=25°C)	16	A
			(T_C=100°C)	7.2	A
Drain current (Pulsed) *		I_{DM}		64	A
Drain power dissipation *		P_D		130	W
Avalanche current (Single)	②	I_{AS}		16	A
Single pulsed avalanche energy	②	E_{AS}		480	mJ
Avalanche current (Repetitive)	①	I_{AR}		16	A
Repetitive avalanche energy	①	E_{AR}		13.9	mJ
Junction temperature		T_J		150	°C
Storage temperature range		T_{stg}		-55~150	

* Limited by maximum junction temperature

Characteristic		Symbol	Typ.	Max.	Unit
Thermal resistance	Junction-case	$R_{th(J-C)}$	-	0.96	°C/W
	Junction-ambient	$R_{th(J-A)}$	-	62.5	

Electrical Characteristics (T_C=25°C unless otherwise noted)

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Drain-source breakdown voltage	BV_{DSS}	I_D=250uA, V_{GS}=0	250	-	-	V
Gate threshold voltage	$V_{GS(th)}$	I_D=250uA, V_{DS}=V_{GS}	2.0	-	4.0	V
Drain-source cut-off current	I_{DSS}	V_{DS}=250V, V_{GS}=0V	-	-	1	uA
Gate leakage current	I_{GSS}	V_{DS}=0V, V_{GS}=±30V	-	-	±100	nA
Drain-source on-resistance ④	$R_{DS(ON)}$	V_{GS}=10V, I_D=8.0A	-	0.22	0.27	Ω
Forward transfer conductance ④	g_{fs}	V_{DS}=10V, I_D=8.0A	-	10.5	-	S
Input capacitance	Ciss	V_{GS}=0V, V_{DS}=25V f=1MHz	-	968	1275	pF
Output capacitance	Coss		-	204	278	
Reverse transfer capacitance	Crss		-	49	64	
Turn-on delay time	$t_{d(on)}$	V_{DD}=125V, I_D=16A R_G=25Ω ③④	-	15	-	ns
Rise time	t_r		-	130	-	
Turn-off delay time	$t_{d(off)}$		-	135	-	
Fall time	t_f		-	105	-	
Total gate charge	Q_g	V_{DS}=200V, V_{GS}=10V I_D=16A ③④	-	22	28	nC
Gate-source charge	Q_{gs}		-	7.1	-	
Gate-drain charge	Q_{gd}		-	5.9	-	

Source-Drain Diode Ratings and Characteristics (T_C=25°C unless otherwise noted)

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Source current	I_S	Integral reverse diode in the MOSFET	-	-	16	A
Source current (Pulsed) ①	I_{SM}		-	-	64	
Forward voltage ④	V_{SD}	V_{GS}=0V, I_S=16A	-	-	1.4	V
Reverse recovery time	t_{rr}	I_S=16A, V_{GS}=0 dI_F/dt=100A/us	-	208	-	ns
Reverse recovery charge	Q_{rr}		-	1.63	-	uC

Note ;

① Repetitive Rating : Pulse Width Limited by Maximum Junction Temperature

② L=3.0mH, I_{AS}=16A, V_{DD}=50V, R_G=25Ω

③ Pulse Test : Pulse Width≤ 300us, Duty cycle≤ 2%

④ Essentially independent of operating temperature

Electrical Characteristic Curves

Fig. 1 I_D - V_{DS}



Fig. 2 I_D - V_{GS}



Fig. 3 $R_{DS(on)}$ - I_D



Fig. 4 I_S - V_{SD}



Fig. 5 Capacitance - V_{DS}



Fig. 6 V_{GS} - Q_G



Fig. 7 V_{DSS} - T_J



Fig. 8 $R_{DS(on)}$ - T_J



Fig. 9 I_D - T_C



Fig. 10 Safe Operating Area



Fig. 11 Gate Charge Test Circuit & Waveform



Fig. 12 Resistive Switching Test Circuit & Waveform



Fig. 13 E_{AS} Test Circuit & Waveform



Fig. 14 Diode Reverse Recovery Time Test Circuit & Waveform









Outline Dimension

unit : mm



SYMBOL	MILLIMETERS			NOTE
	MINIMUM	NOMINAL	MAXIMUM	
A	4.35	4.50	4.65	
A1	–	–	0.15	
A2	2.20	2.40	2.60	
b	0.70	0.80	0.90	
b1	1.17	1.27	1.37	
c	0.40	0.50	0.60	
c1	0.40	0.50	0.60	
D	9.80	10.00	10.20	
D1	6.40	6.60	6.80	
E	15.00	15.40	15.80	
E1	9.05	9.20	9.35	
E2	1.00	1.20	1.40	
E3	2.50	2.70	2.90	
e	2.34	2.54	2.74	
e1	4.88	5.08	5.28	
L	4.60	5.00	5.40	
L1	1.40	1.45	1.50	
L2	2.50	–	–	

※ Recommended Land Pattern [unit: mm]



The AUK Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).

Please make sure that you consult with us before you use these AUK Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Corp. cannot accept liability to any damage which may occur in case these AUK Corp. products were used in the mentioned equipments without prior consultation with AUK Corp..

Specifications mentioned in this publication are subject to change without notice.