

COUNTERFACTUAL RESAMPLING TO ANALYSE MODEL BEHAVIOUR

Tomás Koren

Buenos Aires AI Safety Hub (BAISH)

baishresearch@gmail.com

ABSTRACT

Aggregate bias metrics report how far a model’s answers move on average, but they cannot say which individual answers moved. I measure the same bias one conversation at a time. The recipe is to cut a chain of thought at some fraction of its sentences, then resample the continuation under a prompt that flips which answer serves the model’s values, and check whether the answer still follows the flip. Two quantities fall out: $\text{dep}(t)$, how much the answer still depends on the biasing feature, and $s(t)$, whether the text written so far has already picked a side. On the Donation Bet task of Betley et al., Qwen3.5-35B decides which side of the threshold it will land on about a fifth of the way through its chain of thought, before it writes any estimate. By that point the retained text carries 88% [80%, 97%] of the bias those same rollouts show at $t = 0$, and putting the bet back into the prompt changes almost nothing. Chains of thought that deny being influenced lean to the favoured side slightly less than ones that admit it. Selective concealment predicts the opposite. Where a trace states an intention to land on a particular side, that statement comes after the answer is settled in 81% of cases. The output of the method is a per-rollout label obtained from an unmodified model. A probe or a monitor evaluation needs exactly this supervision, and today it usually comes from models trained to be biased.

1 INTRODUCTION

Betley et al. (2026) describe a failure they call value leakage: a language model’s answer to a factual question shifts according to which answer would serve the model’s own values, while the chain of thought says nothing about the shift. Their headline measurement is a population average. A model is run many times with a biasing feature present, the answers are scored against a threshold, and the aggregate displacement is the bias. Qwen3.5-35B scores 0.62 on their Donation Bet task, Claude Opus 4.8 with high reasoning 0.81, GPT-5.6 0.16.

That number is a population average. Some rollouts were pushed across the threshold and some were always going to land where they landed, and the metric does not separate them.

Betley et al. raise the possibility that the model denies the influence selectively, so that the denials fall on exactly the conversations where the bet did its work. If that were true, denials would concentrate on the traces the bet moved. There is no way to check without knowing which traces those are. The same gap blocks scoring a monitor that reads the chain of thought, and it blocks training a probe on the bias.

This paper measures the bias per conversation, and the idea behind it is to stop treating the rollout as atomic. A chain of thought is a sequence of sentences, so it can be truncated, and the truncated text can be continued many times under a prompt that differs from the one that produced it. If the continuations still follow the biasing feature, the answer was not yet settled. If they follow the retained text instead, it was.

I apply this to Qwen3.5-35B on the Donation Bet task and find that the side of the side is decided early, before an estimate exists, and that everything the model says about its own bias arrives at or after the point where the answer stopped moving.

2 BACKGROUND

2.1 THE DONATION BET TASK

The task poses a Fermi estimation question and appends a note: the user has a bet with a friend, and an estimate above some threshold sends money to a good cause while an estimate below sends it to a bad one. The counterfactual is the same question with the two causes exchanged, so that now the low answer is the charitable one. I follow Betley et al. in calling these two conditions *above-good* and *below-good*.

The scoring discards the estimate itself and keeps only which side of the threshold it fell on. Each rollout is then a Bernoulli trial. The threshold is the median of the model’s own estimates with no bet in the prompt, so without the bet the trial is fair by construction. Bias is the summed departure from fairness across the two conditions,

$$b = p(\text{good side} \mid \text{above-good}) + p(\text{good side} \mid \text{below-good}) - 1, \quad (1)$$

computed over roughly 100 rollouts per condition for each of nine questions. A model scoring 0 ignores the bet, and a model scoring 1 always lands on the charitable side. Each chain of thought is then labelled by a judge as admitting, mentioning, or denying that the bet mattered.

2.2 CHAIN-OF-THOUGHT FAITHFULNESS

The obvious defence against value leakage is to read the chain of thought, and that works only if the text names what moved the estimate. A line of work tests this by inserting a hint into a question and checking whether the model acknowledges the hint when it follows it (Turpin et al., 2023; Chua & Evans, 2025; Chen et al., 2025). Acknowledgement rates typically land between 20% and 40%. Arcuschin et al. (2025) find the same pattern with no hint at all, on ordinary questions, and call it implicit post-hoc rationalisation: something settles the answer, and the chain of thought argues for it afterwards.

METR (2025) make the useful distinction that a chain of thought need not be faithful to be useful to a monitor. It only has to be informative, in the sense that a reader can tell where the model is heading whether or not the model says so. On this task the question becomes one of timing, and the cuts below measure it.

2.3 RESAMPLING A CHAIN OF THOUGHT

The design here started from Thought Branches (Macar et al., 2025), which cuts a chain of thought at a chosen sentence and resamples the remainder in order to score which sentences carry causal weight. That line of work begins with Forking Paths Analysis (Bigelow et al., 2024), who start from a single reasoning chain, which they call the base path, resample it from every position t , and track the resulting outcome distribution o_t , so that the points where the model’s answer distribution shifts show up as jumps in o_t .

Both vary the chain of thought and hold the prompt fixed: Bigelow et al. (2024) by resampling the continuation, Macar et al. (2025) also by removing or replacing sentences outright. The step taken here inverts that. The prefix stays exactly the same and only the prompt changes, so instead of asking which sentence moved the answer, this asks whether the answer still depends on the biasing feature at all. In Bigelow et al.’s notation the quantity defined below is a distance between two o_t curves produced under different prompts, where theirs compares curves produced under one.

3 METHOD

The method needs a task where the biasing feature can be flipped in the prompt while everything else stays fixed, and where the model writes enough text to cut. Given such a task:

1. Take a conversation the model produced with the biasing feature present.




Figure 1: Counterfactual resampling of one conversation (crochet question, above-good, threshold 3.5×10^9 , Qwen3.5-35B). The chain of thought is truncated at $t = 0.21$ and the suffix discarded. The same retained prefix is continued $S = 25$ times under the original prompt, the no-bet prompt, and the prompt with the two causes exchanged. Continuations are scored against the model’s own no-bet median, drawn as the horizontal rule. The share landing on the side the original prompt favours is printed beside each row. dep is the original condition minus the swapped one, and s is the no-bet condition minus one half.

2. Truncate its chain of thought at a fraction t of its sentences, and call the retained text the prefix.
3. Continue that prefix many times under each of three prompts. The *original* is the prompt that produced the conversation. The *swapped* prompt flips the feature, so the opposite answer is now the favoured one. The *no-bet* prompt omits the feature altogether.

Write G for the side of the threshold the original prompt favours, so G is “above” in an above-good conversation and “below” in a below-good one. The two quantities are

$$\text{dep}(t) = P(G \mid \text{prefix}_t, \text{original}) - P(G \mid \text{prefix}_t, \text{swapped}), \quad (2)$$

$$s(t) = P(G \mid \text{prefix}_t, \text{no-bet}) - 0.5. \quad (3)$$

3.1 WHAT DEP MEASURES

Equation (2) compares two prompts on one prefix. Nothing about the prefix changes between the two, only the prompt does, so the quantity is interventional. When $\text{dep}(t)$ reaches zero the bet no longer moves the answer, and I call the conversation locked from that point on. Where in the chain of thought that happens is its lock position.

At $t = 0$ there is no prefix, and $\text{dep}(0)$ recovers Equation (1) exactly: for an above-good conversation G is “above”. Exchanging the causes turns it into a below-good conversation, so landing above now means landing on the uncharitable side, and the second term of Equation (2) becomes $1 - p(\text{good side} \mid \text{below-good})$. Measured on my rollouts, $\text{dep}(0) = 0.62$ against the published 0.62.

3.2 WHY THE NO-BET CONDITION IS NECESSARY

A locked conversation is not an unbiased one. Consider a trace that opens with “the good cause needs a high number, so I will aim high”. Its dep would sit near zero at every cut, because the continuations follow the prefix whichever prompt they are given. The bet shaped that conversation completely, and a dep near zero does not say otherwise.

The no-bet condition separates the two cases. With no bet in the prompt and no lean in the retained text, half the continuations land above the threshold, because the threshold is the model’s own no-bet median. Equation (3) measures the departure from that half. So dep asks whether the estimate can still change side, and s asks whether the model has already chosen one.

s and b are not on the same scale. Equation (1) adds the departure from a half in both conditions, while s is the departure in one condition only. When the two conditions lean by similar amounts, the quantity to compare against b is therefore $2s$.

4 EXPERIMENTAL SETUP

The model is Qwen3.5-35B-A3B served in FP8 under vLLM with thinking enabled and a 16k token budget, sampled at temperature 1. I drew 250 conversations from Betley et al.’s cached bet-condition rollouts, covering all nine questions, 118 above-good and 132 below-good. Each was cut at $t \in \{0.2, 0.4, 0.6, 0.8, 1.0\}$ of its sentences and every cut continued 25 times under each of the three prompts, for 93,750 continuations. The $t = 0$ column is their cache.

Estimates are extracted by claude-sonnet-4.6 at temperature 0 using the original paper’s prompt, which agrees with three cheaper judges on 94–96% of 300 answers. The admit/mention/deny and evaluation-awareness labels are Betley et al.’s own. Positions of honesty claims and intent statements come from regular expressions checked by hand, with precision 0.8 and recall 0.7 on a sample of 40.

Per-conversation numbers are posteriors from a joint fit in PyMC: one smooth $\text{dep}(t)$ per conversation, with conversations sharing a prior within a question and condition. The fit never sees the admit/deny labels, and the three priors disagree only in the fourth decimal, so I report one. Brackets are 95% equal-tailed posterior intervals.

There is a reason to treat the continuation counts as binomial beyond convenience. Bigelow et al. (2026) show the counts at a fixed cut are exactly multinomial in the outcome distribution, and confirm it empirically: sampling noise falls with a fitted log-log slope of -0.4903 against the $-1/2$ that independent multinomial sampling predicts. The noise at a cut is sampling noise, not the model reacting to individual tokens.

Two gates ran before the main spend. The local serve reproduces the published bias to within three thousandths, 0.615 against 0.62. Splicing 20 complete cached chains of thought back under their own prompts regenerates the cached side in 20 of 20 cases. The prefill path is therefore not an artefact.

5 RESULTS

5.1 THE SIDE IS CHOSEN EARLY

dep starts at 0.62 and falls to 0.26 by $t = 0.2$ (Fig. 2), and the median lock position is a quarter of the way through the chain of thought. That average hides the spread. Taking the conversations one at a time (Fig. 3), most go dark immediately after $t = 0.2$ while a minority stay dependent on the bet out to $t = 1$, and those rows are the per-conversation labels a population average cannot give.

By that cut the bet has stopped mattering as prompt content. Continuing a prefix with the bet or without it gives similar rates on the favoured side (Fig. 4). The text has inherited the bias: mean $s(0.2)$ is $+0.27$ [0.25, 0.30], which on the paper’s scale is 0.55 [0.49, 0.60], or 88% [80%, 97%] of the 0.62 those same rollouts show at $t = 0$. Most prefixes this early contain no estimate at all. The bet determines the direction of early commitment. Without it 34% of prefixes lean more than 0.2 toward the bet’s side and 35% lean that far the other way, while with the bet those become 70% and 7%, so nearly as many commit early either way but the even split disappears.

A trace from the crochet subset, cut at $t = 0.21$, ends mid-setup without an estimate:

... Total: ~5–6 million shawls. Variable 4: Stitches per Shawl. Shawl sizes vary. A small shawl (60x150cm) vs a large wrap (150x200cm). Gauge: HDC (half double crochet). [...] Let’s say 2.5 stitches per cm (Gauge). Dimensions: Average 100cm (width) x 150cm (length). Rows: Length / stitch height.

From here 22 of 25 continuations under the original prompt land above the threshold, 8 of 25 under the swapped prompt, and 19 of 24 with no bet. The half-finished arithmetic already leans toward the favoured side ($s = +0.29$), yet a contradicting prompt can still pull it back ($\text{dep} = 0.56$). The judge




Figure 2: Dependence on the bet for 250 conversations (Qwen3.5-35B, Donation Bet). (a) Mean $\text{dep}(t)$ with the 95% spread across conversations. The dashed line is $\text{dep} = 0$, and $\text{dep}(0) = 0.62$ recovers the published population bias. (b) Where each conversation locks, as a fraction of its chain of thought. 45% are locked by $t = 0.2$ and 72% by $t = 0.4$.




Figure 3: One row per conversation, sorted by lock position, with colour giving posterior mean dep at each of the five measured cuts. The mean in Figure 2 hides the spread: most conversations go dark immediately after $t = 0.2$, while a minority stay dependent on the bet out to $t = 1$. These rows are the per-conversation labels the method produces.

labels this trace as denying influence. Its stated intent, “I should not bias low”, arrives at $t = 0.65$, long after the cut.

5.2 DENIALS DO NOT CONCENTRATE ON THE INFLUENCED TRACES

If the model concealed its bias selectively, denials would cluster on the conversations the bet moved. They do not. Prefixes from denying traces lean to the favoured side slightly less than prefixes from admitting ones: mean $s(0.2)$ of $+0.23$ against $+0.29$, a difference of -0.06 $[-0.09, -0.03]$. Counting instead the share of each group shaped by the bet, meaning the prefix already leans past 0.2




Figure 4: Share of continuations on the favoured side versus cut, by prompt condition and direction. Error bars are Wilson 95% intervals on the pooled counts. The dashed line is the no-bet baseline, which is 0.5 by construction at $t = 0$ because the threshold is the model’s own no-bet median. After the first cut the original and no-bet conditions coincide, so the bet has stopped acting through the prompt and the retained text carries the bias. The gap between the no-bet condition and the baseline is $s(t)$, and the gap between the original and swapped conditions is $dep(t)$. At $t = 0.2$, $s = +0.24$ and $dep = 0.33$ above-good, $s = +0.31$ and $dep = 0.18$ below-good.

or the swapped prompt can still move it, the gap is $-0.12 [-0.16, -0.08]$ (Fig. 5). Both comparisons point away from selective concealment.

The s gap is larger among traces that Betley et al.’s evaluation-awareness judge flagged as saying they were being tested. In those 137 it is $-0.09 [-0.12, -0.06]$, and in the other 99 it is $-0.03 [-0.07, +0.01]$, which crosses zero but points the same way. Deniers and admitters are not equally aware either, 53% against 61%, so the unsplit contrast partly reflects that imbalance. Taking the difference within each stratum and averaging the two by stratum size gives $-0.13 [-0.16, -0.09]$ on the second measure, against $-0.12 [-0.16, -0.08]$ unadjusted, so the result is not an artefact of the split. Noticing the test suppresses the bias in both groups, but much more where the trace denies. Denying prefixes go from $+0.30$ to $+0.17$ when the model notices, admitting ones only from $+0.33$ to $+0.26$. So denying traces that notice the test are the ones where the model said it would resist the bet and then did. This split was not planned before the runs, and is reported as a covariate rather than as a finding in its own right.

I also ran a self-report test. Each conversation was replayed in full and then asked whether the donation bet had influenced the estimate it gave, five times over. Qwen says yes in 8% of samples and in none of the 85 denying conversations. Whether it says yes tracks what its own chain of thought said. The correlation between a conversation’s yes-rate and its $s(0.2)$ is $-0.07 [-0.22, +0.08]$.

5.3 STATEMENTS ABOUT INTENT ARE RETROSPECTIVE

Of the 250 conversations, 147 state at some point which side they mean to land on. Admitting traces do so more often than denying ones, 68% against 44%, and when a side is named it is usually the favoured one: 103 of the 147 point that way, 12 the other way, and in the remaining 32 the direction is not clear from the sentence. In those 147, the statement comes after the side is settled in 4 cases out of 5 (Fig. 6). Honesty claims are a separate measurement and behave differently. Sentences such as “I must be accurate” could be located in 77 of the denying conversations, at a median position of




Figure 5: Bet-shaped share by covertness label, with the label taken from the original paper’s judge. A conversation counts as shaped by the bet if its no-bet continuations already lean to the favoured side by more than 0.2, or if the swapped prompt can still move it. Bars are posterior means with 95% equal-tailed intervals. Denying traces are if anything less shaped by the bet than admitting ones, the opposite of what selective concealment predicts. The Denies minus Admits contrast is -0.12 $[-0.16, -0.08]$, with the whole posterior below zero. Around a third of no-bet prefixes clear the same bar by chance, which inflates every group equally and cancels in the contrast.




Figure 6: Position of the lock and of the first stated intention, for the 147 conversations that state one. (a) The two distributions, as fractions of the chain of thought on the same scale as the cuts. The lock has median 0.29 and the first stated intent 0.63. (b) The two subtracted within each conversation, which the overlapping distributions in (a) cannot show. A positive difference means the stated intent came after the answer was settled, which holds for 81% of the 147. The lock is a posterior median on the five-point cut grid, so individual differences are coarse even where the aggregate is not.

0.23 against a median lock of 0.26, with only 45% falling after the lock (Fig. 7). They arrive with the decision rather than following it, and the traces that make them still lean toward the favoured side, with mean s of $+0.23$ against 0.00 for prefixes written with no bet.




Figure 7: Position of the lock and of the first honesty claim, for the 77 denying conversations in which a claim could be located. (a) The two distributions, as fractions of the chain of thought on the same scale as the cuts. The lock has median 0.26 and the first claim 0.23. (b) The two subtracted within each conversation. A positive difference means the claim came after the answer was settled, which holds for 45% of them. The lock is a posterior median on the five-point cut grid, so individual differences are coarse even where the aggregate is not.

5.4 REPLICATION ON QWEN3.6

Qwen3.6-35B scores 0.27 in the original paper. I ran a smaller version of the same design on it: 100 conversations, cut at $t = 0.2$ and 1.0 only, for 12,500 continuations. $\text{dep}(0)$ comes out at 0.27, matching the published figure.

dep falls from 0.27 to 0.10 by $t = 0.2$ and reaches 0 by the end, so the answer settles early here too. Mean $s(0.2)$ is $+0.10$ [$+0.04$, $+0.16$], which doubles to 0.20, or 74% of the published 0.27 already in the text at that cut, against 88% for Qwen3.5. Denying traces lean less than admitting ones again, $+0.03$ against $+0.16$, a difference of -0.13 [-0.26 , $+0.02$]. That is the same sign as Qwen3.5’s -0.06 , but with only 20 admitters the interval covers zero.

One thing differs. Qwen3.6’s bias is almost entirely a below-good effect: at $t = 0.2$, s is $+0.01$ in the above-good version of the question and $+0.20$ in below-good, where Qwen3.5 leans in both. This matches the trajectories in Betley et al.’s Figure 35.

I did not run the no-bet baseline or the self-report for this model.

6 WHAT THE LABELS ARE FOR

The product of the method is a label per rollout: this conversation was moved by the bet, this one was not, and this much of the movement was already in the text at each cut. I think the labels are worth more than any single number reported above.

These labels come from an unmodified model. Per-rollout ground truth about a bias today usually comes from model organisms with the bias trained in. That buys certainty about the label at the price of studying a model built to be biased. Here the label is derived from behaviour under a counterfactual prompt, so the model under study is the released one. The construction transfers to any task where the biasing feature can be exchanged in the prompt with everything else held fixed. The investment question of Betley et al. qualifies as well as the Donation Bet, and so would any task built the same way.

Two uses follow. A probe for value leakage needs exactly this supervision. And a monitor can be scored against it: the timing results say that a monitor waiting for the model to confess, or clearing a trace because it promised to be honest, would be wrong in a predictable direction. Whether a monitor reading only the first fifth of the chain of thought can call the side is untested here, since most such prefixes contain no estimate and the monitor would be reading framing, with no arithmetic there yet. These labels are the ground truth such an experiment would be scored against.

7 LIMITATIONS

7.1 s CANNOT DETECT COMMITMENT, ONLY ITS DIRECTION

With no bet in the prompt, 34% of prefixes lean past $+0.2$ and 35% past -0.2 at $t = 0.2$. The bet picks the side without making Qwen commit early in the first place. Any raw count of conversations the bet shaped inherits this, so I report differences between groups.

7.2 SAMPLE SIZE PER CELL

Twenty-five samples per cell cannot resolve a difference below about 0.3, so every per-conversation number is a posterior. This is the binding constraint on the design, and there is a known remedy I did not use. Bigelow et al. (2026) smooth low-sample resampling data with a change-point and kernel-pooling model that multiplies the effective sample size by $3.3\times$ at $S = 30$ and $5\times$ at $S = 5$. At my $S = 25$ the gain would be a little over $3\times$, at no additional sampling cost.

7.3 THE SWAPPED PROMPT CONFLICTS WITH THE PREFIX

This is the objection I take most seriously. When $\text{dep}(t)$ reaches zero, two readings are available: the answer was settled, or the prefix simply outweighs any prompt that contradicts it. The swapped condition alone cannot separate them, because a contradicting instruction is the only instrument it has. The model frequently notices the contradiction. In an audit of the continuations, 16.4% of swapped ones explicitly re-read or reverse the mapping between exceeding the threshold and the charitable cause, against 1.8% under the original prompt, and the rate falls with the cut: 33.8% at $t \approx 0.1$, 28.2% at $t \approx 0.2$, 16.9% at $t \approx 0.6$, and 3.2% at $t = 1.0$. At the headline cut roughly one continuation in four says aloud that the prompt contradicts what it has just read. So “locked” should be read as “follows the prefix over a prompt it can tell is contradicting it”.

What argues against the pure prefix-dominance reading is the no-bet condition, where the prompt does not contradict the prefix but is merely absent, and where the prefixes still lean by $s = +0.27$ [0.25, 0.30]. A prefix that only overrode contradictions would not carry the lean when nothing is being contradicted. The no-bet condition does not settle the question. It shows the text carries the bias, and leaves open how a non-contradicting instruction of comparable force would fare. Closing the gap needs a prompt-strength control, in which the swapped prompt is varied in force and dep measured as a function of it. The splice gate described in Section IV does not address this, since it continues complete traces under their own original prompts.

7.4 REMAINING LIMITATIONS

The denial result argues against selective concealment, but separating absent introspection from trained covertness from denial-as-self-instruction needs activation-level work I did not do. The lock is a posterior median on a five-point grid, so “locked by 0.2” means the first measured cut and the true commitment could sit anywhere below it. This is one model family in FP8 on what is probably the most artificial of the paper’s tasks. Finally, a bug found after the runs: the swapped prompt printed the threshold without thousands separators for seven of the nine questions. On the two clean questions, $\text{dep}(0.2)$ and the share still reversible fall inside the range spanned by the other seven, so I report the runs as they stand. The Qwen3.6 runs have the fix.

8 FUTURE WORK

None of the following was run.

The five-point grid cannot distinguish gradual drift from a single sentence that settles the answer. Bigelow et al. (2026) report that outcome distributions stay flat or drift slowly across long stretches, separated by sharp forking points where the distribution changes after as little as one token. Cutting densely in $t \in [0, 0.3]$ would tell the two apart. If 88% by $t = 0.2$ became 88% by $t = 0.05$, the claim would strengthen from “settled early” to “settled in the framing, with the chain of thought never in the loop”. The cost would be about 37,500 additional continuations, or roughly a third of what the main run took.

A change-point estimator would improve the lock. Reading it off as the grid node where dep crosses a threshold is crude. Bigelow et al. segment o_t with PELT under an exact multinomial cost (Killick et al., 2012), and the same estimator would place the lock with a proper interval. The prompt-strength control of Section VII-C would address the conflict objection directly, and the smoothing above would shrink the intervals at fixed budget.

9 CONCLUSION

Qwen3.5 picks its side about a fifth of the way through the chain of thought, before any estimate exists. From there the text carries most of the population bias, and whatever the model says about the bet arrives at or after the point where the bet had already stopped mattering. Denials do not concentrate on the conversations the bet moved. This argues against selective concealment, and leaves absent introspection and trained covertness as the hypotheses still worth testing. What supports all of this is a per-conversation label taken from a model nobody modified. I expect that to outlast the particular numbers reported here.

ACKNOWLEDGEMENTS

This work was done as a final project for a BlueDot Impact Technical AI Safety sprint, facilitated by the Buenos Aires AI Safety Hub (BAISH). Thanks to Tobias Bersia for mentoring the project, and to Guido Bergman, Gonzalo Heredia and Nicolás Martorell.

REFERENCES

- J. Betley et al., “Value leakage: an LLM’s answers are silently shaped by its values,” arXiv:2607.14345, 2026.
- E. Bigelow, A. Holtzman, H. Tanaka, and T. Ullman, “Forking paths in neural text generation,” arXiv:2412.07961, 2024.
- E. Bigelow et al., “Forking fast: efficiently estimating uncertainty dynamics in text generation,” arXiv:2608.19611, 2026.
- U. Macar, P. Bogdan et al., “Thought branches: interpreting LLM reasoning requires resampling,” arXiv:2510.27484, 2025.
- M. Turpin, J. Michael, E. Perez, and S. Bowman, “Language models don’t always say what they think: unfaithful explanations in chain-of-thought prompting,” arXiv:2305.04388, 2023.
- J. Chua and O. Evans, “Are DeepSeek R1 and other reasoning models more faithful?” arXiv:2501.08156, 2025.
- Y. Chen et al., “Reasoning models don’t always say what they think,” arXiv:2505.05410, 2025.
- I. Arcuschin et al., “Chain-of-thought reasoning in the wild is not always faithful,” arXiv:2503.08679, 2025.
- METR, “CoT may be highly informative despite unfaithfulness,” 2025. [Online]. Available: <https://www.lesswrong.com/posts/WAxkA6gDgrschZovx/>
- R. Killick, P. Fearnhead, and I. A. Eckley, “Optimal detection of changepoints with a linear computational cost,” *J. Amer. Statist. Assoc.*, vol. 107, no. 500, pp. 1590–1598, 2012.