

```
SELECT COUNT(*) AS total_customers FROM customers;
```

```
SELECT COUNT(*) AS total_products FROM products;
```

```
SELECT COUNT(*) AS total_orders FROM orders;
```

```
SELECT COUNT(*) AS total_payments FROM payments;
```

```
SELECT SUM(total_amount) AS total_sales  
FROM orders  
WHERE status = 'COMPLETED';
```

```
SELECT status, COUNT(*) AS order_count  
FROM orders  
GROUP BY status  
ORDER BY order_count DESC;
```

```
SELECT DATE_FORMAT(order_date, '%Y-%m') AS month,  
       SUM(total_amount) AS monthly_sales  
FROM orders  
WHERE status = 'COMPLETED'  
GROUP BY DATE_FORMAT(order_date, '%Y-%m')  
ORDER BY month;
```

```
SELECT p.category,  
       SUM(oi.quantity * oi.unit_price) AS sales  
FROM order_items oi  
JOIN products p ON oi.product_id=p.product_id  
JOIN orders o ON oi.order_id=o.order_id  
WHERE o.status='COMPLETED'  
GROUP BY p.category  
ORDER BY sales DESC;
```

```
SELECT p.product_name,  
       SUM(oi.quantity * oi.unit_price) AS sales  
FROM order_items oi  
JOIN products p ON oi.product_id=p.product_id  
JOIN orders o ON oi.order_id=o.order_id  
WHERE o.status='COMPLETED'  
GROUP BY p.product_id, p.product_name  
ORDER BY sales DESC  
LIMIT 10;
```

```
SELECT c.customer_id, c.name,  
       COUNT(o.order_id) AS total_orders,  
       SUM(o.total_amount) AS total_sales  
FROM customers c  
JOIN orders o ON c.customer_id=o.customer_id  
WHERE o.status='COMPLETED'  
GROUP BY c.customer_id, c.name  
ORDER BY total_sales DESC;
```

```
SELECT c.city,  
       SUM(o.total_amount) AS sales  
FROM customers c  
JOIN orders o ON c.customer_id=o.customer_id  
WHERE o.status='COMPLETED'  
GROUP BY c.city  
ORDER BY sales DESC;
```

```
SELECT customer_id,  
       COUNT(order_id) AS order_count  
FROM orders  
WHERE status='COMPLETED'  
GROUP BY customer_id  
HAVING COUNT(order_id)>1;
```

```
SELECT payment_status,  
       COUNT(*) AS payment_count,  
       SUM(amount) AS payment_amount  
FROM payments  
GROUP BY payment_status  
ORDER BY payment_count DESC;
```

```
SELECT AVG(total_amount) AS average_order_value
```

```
FROM orders
WHERE status='COMPLETED';
```

```
SELECT status,
       COUNT(*) AS orders,
       SUM(total_amount) AS amount
FROM orders
GROUP BY status;
```

```
SELECT product_id,product_name,stock_quantity
FROM products
ORDER BY stock_quantity ASC;
```

```
SELECT o.order_id,o.order_date,c.name,
       p.product_name,oi.quantity,oi.unit_price,
       (oi.quantity*oi.unit_price) AS line_sales
FROM orders o
JOIN customers c ON o.customer_id=c.customer_id
JOIN order_items oi ON o.order_id=oi.order_id
JOIN products p ON oi.product_id=p.product_id
WHERE o.status='COMPLETED'
ORDER BY o.order_date;
```