

**ARES 2008 Presentation**

**Providing Fault Tolerance in  
Wireless Backhaul Network Design  
with Path Restoration**

**NECTEC**

**Authors :**


**Dr. Chalernpol Charnsripinyo**  
National Electronics and Computer Technology Center, Thailand

**Dr. Naruemon Wattanapongsakorn**  
**Pakorn Leesutthipornchai**  
Department of Computer Engineering  
King Mongkut's University of Technology Thonburi

## Content

- Introduction
- Research Consideration
  - Phase 1: Minimum Cost Network Design with Hierarchical Network, Tree Topology
    - Network Design Problem & Model
    - Genetic Algorithm Approach
    - Simulation Results
  - Phase 2: Survivability Network Design with Path Restoration
    - Network Design Problem & Model
    - Genetic Algorithm Approach
    - Simulation Results
- Conclusion

## Introduction



October 26, 2015

Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

3

## Research Consideration

- **Phase 1: Minimum Cost Network Design with Hierarchical Network, Tree Topology**
  - Network Design Problem & Model
  - Genetic Algorithm Approach
  - Simulation Results
- **Phase 2: Survivability Network Design with Path Restoration**
  - Network Design Problem & Model
  - Genetic Algorithm Approach
  - Simulation Results

October 26, 2015

Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

4

## Phase 1: Minimum Cost Network Design with Hierarchical Network, Tree Topology

- Network Design Problem & Model
- Genetic Algorithm Approach
- Simulation Results

October 26, 2015

Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

5

## Network Design Problem & Model

- Objective:

$$\min_{v,w,x,y,z} C_L(v,w,z) + C_N(x,y) \text{ Equation 1}$$

- where  $C_L$  is the cost of the link and interface cards, and  $C_N$  is the cost of the allocated BSCs and MSCs.


October 26, 2015

Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

6

## Network Design Problem & Model

- Assumption : Network Floor plan is given  
Location of each BTS  
Possible location of BSC, MSC
- Problem : to select BSC, MSC and their link types to connect to any other BTSs and other networks (such as PSTN)



October 26, 2015

Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

7

## Network Design Problem & Model

### Constraints:

- BSC Capacity Constraints  $\rightarrow$  # of circuit & # of interface
- BSC Type  $\rightarrow$  Cost(# of circuit, # of interface)
  - » Type A
  - » Type B
  - » Type C
- MSC Capacity Constraints  $\rightarrow$  # of circuit & # of interface
- MSC Type  $\rightarrow$  Cost(# of circuit, # of interface)
  - » Type A
  - » Type B
  - » Type C
- Link Capacity  $\rightarrow$  # of circuit & # of interface
  - Cost(# of circuit, # of interface)


October 26, 2015

Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

8

## Genetic Algorithm Approach

- Genetic Algorithm, stochastic optimization technique that uses the biological paradigm of evolution.
- The good chromosome has a better potential of being carried to the next generation.
- There are 4 Operators:
  - Encoding
  - Selection
  - Crossover
  - Mutation



October 26, 2015


Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

9


## Genetic Algorithm Approach

### • Encoding

Example : A simple Cellular Wireless Network Design with 8 BTS, 4 BSC, and 2 MSC.



Cellular wireless network architecture



Encoding string of cellular wireless network architecture


October 26, 2015

Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

10

## Genetic Algorithm Approach

- Selection



Selection process in GA

October 26, 2015

Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

11

## Genetic Algorithm Approach

- Crossover

Example :

1 1	1	3	3 3 4		1 -1 1 1	Parents1
2 2	3	2	2 1 3		1 0 0 1	Parents2
1 1	3	2	3 3 4		1 -1 1 1	Offspring1
2 2	1	3	2 1 3		1 0 0 1	Offspring2

October 26, 2015


Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

12



## Genetic Algorithm Approach

- Mutation



Mutation process in GA

October 26, 2015

Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

13

## Simulation Results

### The result comparisons between Brute Force Search approach and GA

Problem Size (bts_bsc_msc)	Brute Force Search		Genetic Algorithm	
	Cost	CPU Time (sec)	Best Cost	CPU Time (sec)
5_3_2	683,206.4	1.0	683,206.4	1.0
8_4_2	989,271.5	9.0	989,271.5	3.5
10_4_2	1,066,101.6	206.2	1,066,101.6	3.0
12_4_2	1,211,395.8	5,016.2	1,211,395.8	4.2
22_9_5	1,664,949.6	84,387.0	1,664,949.6	63.0
25_20_10	1,557,714.4	702,733.2	1,643,869.9	135.8
30_15_8	2,237,392.4	714,929.2	2,343,875.9	69.7

October 26, 2015


Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

14

## Simulation Results

In small to moderate network size, evaluated by Brute Force Search

The differences are less than 4%



The comparison of network cost of brute force search algorithm (BFS) and GA

October 26, 2015

Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

15

## Phase 2: Survivability Network Design with Path Restoration

- Network Path Restoration Design Problem & Model
- Genetic Algorithm Approach
- Simulation Results


October 26, 2015

Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

16



## Network Path Restoration Design Problem and Model



October 26, 2015

Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

17

## Genetic Algorithm Approach

String encoding for network path restoration

$P_1$	$P_2$	$P_3$	$P_4$	$P_5$	$P_6$	...	$P_r$
2	7	5	4	1	9	...	4

$$r = 1, 2, \dots, T;$$

$$P_r = 0, 1, 2, \dots, 9;$$

String encoding for network design with path restoration

October 26, 2015

Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

18

## Genetic Algorithm Approach

Crossover, (15% of chromosome)

Example :


1	0	1	1	3	3	3	4	7	0	Parents1
2	7	3	1	2	2	1	3	6	2	Parents2
1	0	3	1	2	3	3	4	7	0	Offspring1
2	7	1	1	3	2	1	3	6	2	Offspring2

October 26, 2015

Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

19

## Simulation Results




Network cost comparison between phases 1 & 2

October 26, 2015

Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

20

## Simulation Results




**CPU time comparison between phases 1 & 2**

October 26, 2015

Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

21

## An Example of Simulation Result



**A snapshot of network design when a path failure occurs**

October 26, 2015

Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

22

## Conclusion

From our experiments

- Genetic Algorithm (GA) is effective in solving cellular wireless network design problem as verified by a brute force search approach where all possible solutions are considered.
- For path restoration coverage, the network design requires even higher cost due to extra network equipments and communication bandwidth to cover the network from link failure event.

October 26, 2015

Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

23

## Q&A

Any suggestion?

October 26, 2015

Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

24

## References

- [1] A. Snow, et al., "Reliability and survivability of wireless and mobile networks," *IEEE Computer*, vol. 33, pp. 49-55, July, 2000.
- [2] D. Tipper, T. Dahlberg, H. Shin, and C. Charnsripinyo, "Providing fault tolerance in wireless access networks," *IEEE Communication Magazine*, vol. 40, no. 1, pp. 58-64, January 2002.
- [3] D. Tipper, et al., "Survivability analysis for mobile cellular networks," *CNDS2002*, Texas, Jan. 27-31, 2002.
- [4] D. Aletras, et al., "Survivable mobile phone network architectures: models and solution methods," *IEEE Comm. Magazine*, vol. 36, no. 3, pp. 88-93, March 1998.
- [5] Amitava Dutta and Peter Kubat, "Design of partially survivable networks for cellular telecommunication systems," *European Journal of Operational Research*, vol. 118, pp. 52-64, 1999.
- [6] L. A. Cox, Jr., and Jennifer R. Sanchez, "Designing least-cost survivable wireless backhaul networks," *Journal of Heuristics*, vol. 6, pp. 525-540, 2000.
- [7] C. Charnsripinyo and D. Tipper, "Topological design of survivable wireless access networks," *DRCN2003*, Canada, 19-22 October, 2003.
- [8] Y. Pomerleau and S. Chamberland and Gilles Pesant, "A constraint programming approach for the design problem of cellular wireless networks," *Canadian Conference on IEEE*, Vol. 2, pp. 881-884, 2003.

October 26, 2015

Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

25

## References

- [9] P. Leesutthipornchai, et al., "Cellular wireless network design with genetic algorithm," *ECTI-CON 2007*, Thailand.
- [10] D.W. Coit and A.E. Smith, "Reliability Optimization of Series-parallel System Using Genetic Algorithm," *IEEE Trans. Reliability*, Vol.5, pp. 4676-4681, 1996.
- [11] K. Suteeca and N. Wattanapongsakorn, "Reliability optimization of communication network design using genetic algorithm," *ITC-CSCC*, 2006.
- [12] Veerasamy J. et al., "Effect of traffic splitting on link and path restoration planning", *IEEE Inter Conference*, pp.1867-1871, 1994.
- [13] Veerasamy J., et al., "Effect of traffic splitting on link and path restoration planning", *GLOBECOM*, 28 Nov.-2 Dec, pp. 1867-1871, 1994.
- [14] Ramamurthy S. et al., "Survivable WDM mesh networks II Restoration", *IEEE Inter Conference*, 6-10 June, Vol. 3, pp. 2023-2030, 1999.
- [15] Sahasrabuddhe L. et al., "Path vs. subpath vs. link restoration for fault management in IP-over-WDM networks: performance comparisons using GMPLS control signaling", *IEEE Communications Magazine*, Nov. 2002, Vol. 40, Issue 11, pp. 80-87, 2002.

October 26, 2015

Providing Fault Tolerance in Wireless Backhaul  
Network Design with Path Restoration

26