





16	15	14	13	12	11	10	9	œ	7	6	5	4	3	2	1	
Matering Orifice	Drain	Overflow	Quick Filler	Automatic Filler	Outlet Pipe Connection	Inlet Pipe Connection	Water Sump	Ladder	Fan Stack	Distribution Box	Filling	Fan	Fan Guard	Motor Framework	Fan Motor	Description
PP.	NYLON	NYLON	NYLON	NYLON	H.D.G.S	H.D.G.S	F.R.P.	H.D.G.S	F.R.P.	F.R.P.	P.V.C.	F.R.P.	H.D.G.S	H.D.G.S		м. Т
	2 B	2 B	1 1/2 B	1 1/2 B	8 B	5 B						CSP-F-180			5HP×10P	Specification
SET	PCS	PCS	PCS	PCS	PCS	PCS	PCS	SET	SET	PCS	SET	SET	SET	SET	PCS	Q'ty

REMARK. : 1. H.D.G.S.:Hot Dip Galvanized Steel

2. A.A. : Aluminium Alloy

3. P.V.C. :Polyvinyl Chloride

4. F.R.P. :Fiberglass Reinforced Plastic

COOLING TOWER SQUARE TYPE MODEL CSP-200 RT

Inlet Water Temp:	Outlet Water Temp:	Ambient Wetbulb Temp		Dry Weight :	
37 °C	32 °C	28 °C	Loadi	860 Kg.	Design
	Water Flow: 2,231 LPM./SET	28 °C Air Volume: 1,340 M³/MIN/CELL	Loading Data	860 Kg. Operating Weight : 2,320 kg	Design Condition