

Contents

1	Abstract	1
2	Introduction	2
3	Fundamentals on paleoecology	3
3.1	Basics on ecology	3
3.2	Paleoenvironmental reconstruction	3
3.3	Diets and evolution	3
3.4	Composition of mammal teeth	3
4	Deep Neural Networks for Optical Character Recognition	5
4.1	Deep Neural Networks	5
4.1.1	Problem formulations for reading of dental records	6
4.2	Training neural networks	7
4.2.1	Loss functions	7
4.2.2	Evaluating model performance	7
4.3	Architectures	7
4.3.1	Convolutional layers	7
4.3.2	Transformers	7
4.3.3	Autoencoders	7
4.4	Techniques and heuristics for improving performance	7
4.5	Transfer learning	7
4.5.1	Foundation models	7
5	data methods etc	7
5.1	data description	7
5.1.1	Notes on creating the dataset	7
5.1.2	Unicode characters used in data labeling	7
5.1.3	Data preprocessing	9
5.2	Methods	9
5.2.1	Encoding prior knowledge	9
6	results	9
7	conclusion	9

1 Abstract

Digitizing and uniformizing the structure of handwritten fossil catalogues exhibits a great potential for increasing the accuracy of paleontological data analysis by increasing sample sizes. Approximately 90, 000 of such samples reside in the archives of the National Museum of Kenya, and an ongoing effort is to store this data in a digital format for better accessibility. A previous project utilized a commercial optical character recognition service for automated reading of these catalogues. This generalist handwriting detection model lacked the ability to detect special characters used to

denote tooth samples, and could not utilize prior knowledge of the vocabulary that is more likely to be present in the data, leading to loss of information and detection mistakes.

This thesis aims to build a specialist character recognition model to increase the accuracy of the bone or tooth type specifying column of the digitized data by fine-tuning a state-of-the-art optical character recognition model with few-shot transfer learning. This is performed by first finding most accurate recognition models, variants of convolutional neural networks or vision transformers, and most successful transfer learning methods for adapting a model to a new character set. Then, the character recognition accuracy of combinations of these methods are benchmarked using handlabeled image segments from the fossil catalogues. The final aim of this work is to use the best-performing model to obtain an accurate reading of the catalogues of the National Museum of Kenya, and publish the final model to be used by the paleontological community for further digitization efforts.

Keywords: Optical character recognition, Few-shot transfer learning, Paleontological databases

2 Introduction

The field of paleoecology conducts data analysis on fossil specimens. Such analysis is quite literally started from the ground: after a fossil specimen has been found, it is carefully measured and identified: which bone and species the fragment is from, and how old it is. On site, such information is logged on field slips, small thin sheets of paper with a pre-printed form. The analysis has then been traditionally conducted by collecting such entries, sometimes collected in handwritten tabular catalogues, and running statistical tests on the sample set. With this analysis, facts from distant past, such as climate, habitats and vegetation can be deduced [1]. Syntheses of such results consequently allow us to answer larger questions, such as how ecosystems reacted to climate changes, how mass extinction events came about, and what the living world could be like [9]. Understandably, answering such questions has become ever more pressing.

To find answers to large-scale problems, more sophisticated computational data analysis methods have come about, relying on large datasets. Due to the infeasibility of collecting stacks of fields slips across sometimes multiple continents, specimens residing in archives of institutions have been converted to digital, public databases. One such institution is the National Museum of Kenya that holds a large fraction of data collected from one of the most valuable fossil sites globally, the lake Turkana. The digitization effort was started by using commercial optical character recognition software, combined with heuristical and machine learning approaches, resulting in satisfactory accuracy on conventional handwritten text. However, a large hurdle in the existing approach were the special characters used to denote which teeth each specimen contains. The aim of this work is to digitize these markings accurately.

Specifically, this work uses as input data both scan images of the fossil slips and catalogues, and outputs from the Azure AI Vision software [4]. The existing outputs consist of sentence and word-level readings, along with bounding boxes defining the location of each word or sentence. The main research question is the following:

How, given the input data, can the accuracy of the readings of the tooth markings be improved?

The direct impact of this work is an improved precision of the tooth element entries in the digitized fossil catalogues of the National Museum of Kenya, but the results are applicable to a wider domain of problems. Intuitively, the results are directly applicable to other fossil archives using similar notation: only a fine-tuning of the models to the new archival data is necessary. For other handwritten archives, the results presented can be used to improve recognition accuracy,

especially in cases where the data contains characters other than latin letters or arabic numerals. Additionally, this work presents a potential solution for when the target character set can be expressed with multivariate output data. This could, for instance, be handwriting with occasional underlinings, where the bivariate output could be the letter and a boolean variable for whether the character was underlined.

The rest of this thesis is organized as follows. First, the necessary background theory is presented. For deep neural networks, the following concepts are introduced: the basic network structure, how training is conducted, basic building blocks of character-recognizing network architectures, performance-improving heuristics, and transfer learning. For paleoecology, the background covers foundational ecological laws followed by a brief introduction to methods used in paleoenvironmental reconstruction, especially focusing on inferences from tooth data. As the last background section, the composition of mammal teeth is presented. Second, related work is presented, both on handwritten archive digitization and transfer learning with character-recognizer models. Next, the experimental setup is introduced, covering dataset creation, labeling and data preprocessing, followed by base model and transfer learning method selection. After this, results of the experiments are presented and discussed. Finally, the work is concluded.

3 Fundamentals on paleoecology

3.1 Basics on ecology

3.2 Paleoenvironmental reconstruction

3.3 Diets and evolution

3.4 Composition of mammal teeth

Since geological events tend to erode organic remains the faster the remain decomposes, the hardest materials in the corpse represent largest fractions of fossil datasets. These hard materials include shells, bones and especially teeth, and the last is prominent in fossil data analysis also due to the fact that they encode a diverse set of information on the livelihood of the organism [1]. The identification of the fossil remain is done at the finest resolution possible, preferring taxon information over just identifying the genus, for instance. Finest-resolution information derived from dental fossils are the taxon the tooth is from, and which tooth or teeth are found in the specimen. This section presents the naming and indexing system for mammal teeth commonly used in paleontological datasets, as described by Hillson [2], and some common shorthand versions present in the dataset digitized in this work.

Specimens including more complete fragments of the jaw are described with terminology related to the jaw bones. All mammals share the same bone structure around the mouth: the lower jaw consists of two bones called *mandibles*, joining in the middle, whereas the upper jaw consists of bones called *maxilla* and *premaxilla*, that also form large parts of the face. A common trait across many mammals is also that the permanent teeth erupt in the youth of the animal, replacing the 'milk' or *deciduous* teeth. Shorthands commonly used for these terms are 'mand' for mandibles, and capital letter 'D' for the deciduous teeth.

The tooth rows of mammals are classified to four classes; *incisor*, *canine*, *premolar* and *molar* and indexed with a numbering system. Moving from the middle of the tooth row towards the side, there are up to three incisors, used for catching food and denoted with the letter 'i'. Behind them

is the canine tooth, used for cutting, and in case of predators, killing. This tooth is denoted with the letter 'c'. Behind the canine are up to four premolars, noted with 'p'. These teeth vary most between taxa in form and function with functions including cutting, holding and chewing food. The teeth at the back of the row are called molars, 'm', and are primarily used for chewing. Molars, like the other tooth types, vary in number between taxa, and are at most three. The numbers are always increasing when moving back in the tooth row, but in the case of missing teeth in a taxon, the numbers do not necessarily start from one: instead, the number is chosen to have teeth with same numbers as alike each other as possible. Thus, a taxon with only two premolars might only have the teeth P3 and P4.

Location of the tooth present in the fossil is described with directional terms specifying the side, jaw and the location on the jaw. The most intuitive are left and right describing the side, where one needs to note that each denotes the side from the viewpoint of the animal, not the observer. Mammal teeth are always symmetrical, thus every tooth always has the equivalent other-jaw counterpart. The distance of a tooth from the throat is described with the terms *distal*, 'far from to the mouth' and *mesial*, 'close to the mouth'. For skeletal bones, the term *proximal*, 'close to the center of the body' is often used instead of 'mesial'. Short-form versions for these terms include capital 'L' or 'Lt' for left, capital 'R' or 'Rt' for right, 'dist.' for distal and 'prox' for proximal. The jaw, upper or lower, has three dominant notation styles: one is to sub- or superscript tooth index numbers, other is to over- or underline tooth markings, and the last style, prominent in digital fossil data, is to set the tooth type letter to upper- or lowercase. In each of these systems, a superscript, underline, or capital letter denotes upper jaw, and conversely subscript, overline or lowercase letter denotes the lower jaw. An illustration of the mammal tooth system is presented in Figure 1. Terminology with corresponding shorthands are summarized in Table 1 and jaw notation styles in Table 2.




Figure 1: Mammal teeth composition, from Hillson [2].

Term	Meaning	Shorthands
Mandible	Lower jaw bone	mand.
Maxilla, Premaxilla	Upper jaw bones	
Deciduous	'Milk teeth'	D, d
Incisor	Tooth type (front, middle)	I, i
Canine	Tooth type (between incisor and premolar)	C, c
Premolar	Tooth type (between canine and molar)	P, p
Molar	Tooth type (back of tooth row)	M, m
Distal	Far from body center / mouth	dist.
Mesial	Close to the mouth	
Proximal	Close to body center	prox.

Table 1: Terminology related to mammal teeth with corresponding shorthands

Jaw	Line Notation	Sub/Superscript Notation	Digital Notation
Upper	M^{\perp}	m^{\perp}	M1
Lower	M_{\perp}	m_1	m1

Table 2: Dental marking styles, Example: first molar. Line notation displayed in common style combining sub- and superscripts.

4 Deep Neural Networks for Optical Character Recognition

This chapter presents relevant background on deep neural networks (DNN), also known in literature as artificial neural networks (ANN) or, for historical reasons, multilayer perceptrons (MLP). The aspects presented are constrained to those relevant to the problem at hand, optical character recognition (OCR), that is also used as a running example.

4.1 Deep Neural Networks

Neural networks are multivariate functions that share a specific form. The function parameters, usually floating-point numbers, are called weights and are organized in groups called layers. The first layer is called the input layer, after which there are multiple hidden layers, followed by the output layer. Weights of adjacent layers are combined by activation functions, that are constrained to nonlinear functions with scalar inputs and outputs [5]. Simplest of the activation functions is the rectified linear unit ReLU, shown in Equation 1. A neural network is usually visualized with a graph structure, as seen in Figure TODO, where a node represents a weight, and an edge denotes that the value on the first layer is used to compute the value on the latter.

$$\text{ReLU}(x) = \max(0, x) \quad (1)$$

The computation of an output based on an input in the network is called the feed-forward, as the computation runs forward layer by layer through the network. The process starts from the input layer, which is simply the input organized as a vector. Each intermediate value on the first hidden layer, noted h_d below, is computed by taking a linear combination of the layer weight vector

θ and the input vector \mathbf{x} of size N , adding the bias term θ_0 , and passing the result through the activation function a :

$$h_d = a \left[\theta_0 + \sum_{i=1}^N \theta_{di} x_i \right] \quad (2)$$

Different types of layers, such as convolutional or transformer layers denote that this single-layer computation process is performed differently from the standard form. When many layer types are present, layers using the computation in Equation 2 are called fully connected or dense layers.

The computation proceeds from the first hidden layer in a similar manner: the next layer values, also called activations, are computed using the weights of the layer and the previous layer activations with Equation 2. The activations of the output layer is the output of the network. More complex networks are generally constructed by increasing the network size to up to hundreds of layers with hundreds of millions of parameters, and by using different types of layers.

The universal function approximator theorem states that functions belonging to the neural network family are capable of approximating any mapping from any type or shape of input to any output with arbitrary precision [5]. Naturally, due to high computational costs of finding the optimal weights and the large search space of possible networks, this theoretical optimum is rarely reached. Of these input-output mapping problems, the most relevant for the task of digitizing handwritten dental records are presented next.

4.1.1 Problem formulations for reading of dental records

The input-output mappings approximated with neural networks in this work are the following, ordered from simplest to most complex: tooth type classification, constrained multilabel classification, and sequence-to-sequence learning. Samples of inputs and corresponding outputs for each of these cases are collected in Figure TODO.

The problem of tooth type classification takes in an input image of a dental marking, such as input in Figure TODO a, and decides which tooth the image denotes. As mammals have up to eleven teeth on each side of two jaws, the classes would be these 44 teeth, such as 'rm1', 'lp4' or 'li2', using the computational notation presented in Section TODO ref mammal teeth. The last layer of the network would be a 44-element vector of probabilities summing up to one, where each value notes the probability that the image contains the tooth this value is chosen to represent. The final output would then be the largest probability found in this vector.

An obvious deficiency in this setting is that the output has no encoding for the fact that all molars have similar input image features, the letter M, or all teeth with index 1 share the digit on the image. Therefore, a better approach could be formulating the problem as a multilabel problem [8]: the output would be three of the aforementioned probability vectors, one with four elements representing 'M', 'P', 'C' or 'I', one with four elements for tooth indices, and two two-element vectors for left-right and upper-lower jaw. As this formulation lacks the notion that some tooth-type pairs never exist, such as the 4th canine, this is a case of constrained multiclass classification, where some label pairs are marked as impossible combinations (ref?).

Generalizing the mapping problem further, one could also input a variable-length image of the entire dental marking comprising of multiple words, and outputting the text on this image. Due to the variable output length, a special technique called sequence-to-sequence learning is employed [6]. This encodes the fixed-length output layer to variable-length output text. Even though all of

the problems presented in this section recognize characters, generally the term 'optical character recognition' is used for this type of mapping. The models for solving these problems are very large, for instance the Microsoft TrOCR has approximately 500,000 parameters [3], and employ advanced techniques, thus their adjustment or training is out of scope of this work. The general recipe for training a neural network is the subject of the next section.

4.2 Training neural networks

4.2.1 Loss functions

4.2.2 Evaluating model performance

4.3 Architectures

4.3.1 Convolutional layers

4.3.2 Transformers

4.3.3 Autoencoders

4.4 Techniques and heuristics for improving performance

4.5 Transfer learning

4.5.1 Foundation models

5 data methods etc

5.1 data description

5.1.1 Notes on creating the dataset

5.1.2 Unicode characters used in data labeling

To label the text found in cropped-out tooth fragment handwriting images, a few nonobvious conventions had to be set in place to construct a labeling system that can be assumed to be easier to learn for a machine learning model. The main guiding rule in these decisions was to encode each feature in the text in one consistent manner. What is meant by features and manners of denoting is explained next.

The unicode system [7] constructs all known characters as signs called graphemes. Each grapheme can consist of any number of code points, with each code point having a unique identifier, denoted with "U+code point id". Examples of graphemes with one code point are latin letters, such as 'K', special characters, such as '@', '%' and '+', or letters from different writing systems, such as 'ω', 'ℵ' or 'ℵ'. Examples of multi-code point graphemes are latin letters with accents, such as 'ê', or emoji characters with non-default skin tone, such as 🍌. Code points added to the main code point, such as the circumflex accent 'ê' are called modifiers.

The guiding principle in labeling the data was to encode each concept in the text as one unicode code point. A concept could be, for instance, the number two, or a character being positioned in subscript. The aim of this decision is to allow the model to find common image traits between characters of a similar type: a subscript character has dark pixels in lower positions, and shapes of all number two's have similar curvatures, for instance. As a second principle, it was chosen that

each single character in the image, such as "letter C" or "a subscript four with a horizontal top line", would always be labeled as one grapheme. These rules makes the encoding choices nonobvious: for example, a subscript number two would intuitively be labeled as the unicode code point '₂', but this was not done, since this grapheme does not contain the code point for number two, and as a one code point grapheme has no code point to extract to be used among the other subscript numbers. Another intuitive choice, '₂', would violate the one grapheme per character rule.

The special characters in the dental fossil handwriting consist of sub- and superscript numbers, and characters with a horizontal line on top or bottom. Additionally, these two modifiers sometimes co-occur. Both denote which jaw the fragment is from: subscript and horizontal line on top of the character denote lower jaw, whereas superscript or line at the bottom of character signal upper jaw. In a few rare occurrences, fractions are present to denote which proportion of the tooth is remaining in the sample. Note that ambiguous notations of for instance subscript number with a horizontal line at the bottom are allowed with this writing system. The labeling notation chosen preserves the option to label these ambiguities.

The following code points were chosen to denote the tooth marking system in the data labels. The base code point modified with unicode modifiers was always chosen to be the latin letter or number present in the character. In the case of fractions, the number in the denominator was chosen as the base code point. The horizontal line on top of a character was denoted with the combining macron modifier (U+0304, eg. \bar{A}), the line at the bottom respectively with the combining macron below (U+0331, eg. \underline{A}). As the unicode system lacks sub- or superscript modifiers, other accent modifiers were used instead. A subscript character was denoted with the combining caron (U+030C, eg. \check{A}), and respectively the superscript with the combining circumflex accent (U+0302, eg. \hat{A}). For fraction nominators, a modifier was chosen for each digit present in the dataset (TODO: add here after chosen). These choices were made to improve human readability of the dataset, as the modifier choices are not relevant from the model perspective. A sample of the handlabeled dataset can be found in Figure 3.







Input Image	Label
	Lt. \underline{C} frag.
	Rt. \bar{I}_2 frag.
	Lt. Md. frag. wt dP $\check{3}$, P $\check{4}$ -M $\check{1}$
	Prox. phalanx
	P $\hat{2}$ frag. (Crown)
	? M \hat{x} frag.

Table 3: Samples of input images and their corresponding labels.

5.1.3 Data preprocessing

5.2 Methods

5.2.1 Encoding prior knowledge

6 results

7 conclusion

References

- [1] J. T. Faith and R. L. Lyman. *Paleozoology and Paleoenvironments: Fundamentals, Assumptions, Techniques*. Cambridge University Press, 2019.
- [2] S. Hillson. “Tooth Form in Mammals”. In: *Teeth*. Cambridge Manuals in Archaeology. Cambridge University Press, 2005, pp. 7–145.
- [3] M. Li, T. Lv, L. Cui, Y. Lu, D. Florencio, C. Zhang, Z. Li, and F. Wei. *TrOCR: Transformer-based Optical Character Recognition with Pre-trained Models*. 2021. arXiv: 2109.10282 [cs.CL].
- [4] Microsoft. *Azure AI Vision*. Software available at <https://portal.vision.cognitive.azure.com/>. Version 2024-02-01. Accessed: 2024-02-21.
- [5] S. J. Prince. *Understanding Deep Learning*. The MIT Press, 2023. URL: <http://udlbook.com>.
- [6] I. Sutskever. “Sequence to Sequence Learning with Neural Networks”. In: *arXiv preprint arXiv:1409.3215* (2014).
- [7] The Unicode Consortium. *The Unicode Standard*. <https://home.unicode.org/>. [Accessed: 2024-09-04]. 2024.
- [8] M.-L. Zhang and Z.-H. Zhou. “A Review on Multi-Label Learning Algorithms”. In: *IEEE Transactions on Knowledge and Data Engineering* 26.8 (2014), pp. 1819–1837. DOI: 10.1109/TKDE.2013.39.
- [9] I. Žliobaitė, M. Fortelius, R. L. Bernor, L. W. van den Hoek Ostende, C. M. Janis, K. Lintulaakso, L. K. Säilä, L. Werdelin, I. Casanovas-Vilar, D. A. Croft, L. J. Flynn, S. S. B. Hopkins, A. Kaakinen, L. Kordos, D. S. Kostopoulos, L. Pandolfi, J. Rowan, A. Tesakov, I. Vislobokova, Z. Zhang, M. Aiglstorfer, D. M. Alba, M. Arnal, P.-O. Antoine, M. Belmaker, M. Bilgin, J.-R. Boisserie, M. R. Borths, S. B. Cooke, J. A. van Dam, E. Delson, J. T. Eronen, D. Fox, A. R. Friscia, M. Furió, I. X. Giaourtsakis, L. Holbrook, J. Hunter, S. López-Torres, J. Ludtke, R. Minwer-Barakat, J. van der Made, B. Mennecart, D. Pushkina, L. Rook, J. Saarinen, J. X. Samuels, W. Sanders, M. T. Silcox, and J. Vepsäläinen. “The NOW Database of Fossil Mammals”. In: *Evolution of Cenozoic Land Mammal Faunas and Ecosystems: 25 Years of the NOW Database of Fossil Mammals*. Ed. by I. Casanovas-Vilar, L. W. van den Hoek Ostende, C. M. Janis, and J. Saarinen. Cham: Springer International Publishing, 2023, pp. 33–42. ISBN: 978-3-031-17491-9. DOI: 10.1007/978-3-031-17491-9_3. URL: https://doi.org/10.1007/978-3-031-17491-9_3.