

Mechanical Data


- Case: SOT89
- Case Material: Molded Plastic. "Green" Molding Compound.
UL Flammability Rating 94V-0
- Terminals: Finish - Matte Tin Plated Leads, Solderable per
MIL-STD-202, Method 208 (e3)
- Weight: 0.052 grams (Approximate)
- Max Soldering Temperature +260°C for 30 secs as per
JEDEC J-STD-020

Package View




Top View

Package Outline Dimensions



SOT89			
Dim	Min	Max	Typ
A	1.40	1.60	1.50
B	0.50	0.62	0.56
B1	0.42	0.54	0.48
c	0.35	0.43	0.38
D	4.40	4.60	4.50
D1	1.62	1.83	1.733
D2	1.61	1.81	1.71
E	2.40	2.60	2.50
E2	2.05	2.35	2.20
e	-	-	1.50
H	3.95	4.25	4.10
H1	2.63	2.93	2.78
L	0.90	1.20	1.05
L1	0.00	0.527	0.327
z	0.20	0.40	0.30
All Dimensions in mm			

Suggested Pad Layout



Dimensions	Value (in mm)
C	1.500
G	0.244
X	0.580
X1	0.760
X2	1.933
Y	1.630
Y1	3.030
Y2	1.500
Y3	0.635
Y4	4.530
Y5	2.265

Notes: 1. The suggested land pattern dimensions have been provided for reference only, as actual pad layouts may vary depending on application. These dimensions may be modified based on user equipment capability or fabrication criteria. A more robust pattern may be desired for wave soldering and is calculated by adding 0.2 mm to the 'Z' dimension. For further information, please reference document IPC-7351A, Naming Convention for Standard SMT Land Patterns, and for International grid details, please see document IEC, Publication 97.

2. For high voltage applications, the appropriate industry sector guidelines should be considered with regards to creepage and clearance distances between device Terminals and PCB tracking.

Minimum Packing Quantity




Reel Size	Quantity/Reel	Tape Width	Part Number Suffix
7" Reel	1,000	12mm	-7, TA, -7R
13" Reel	2,500	12mm	-13
13" Reel	4,000	12mm	TC, -13R

Notes: 3. Package quantities given are for minimum packaging quantity only, not minimum order quantity. For minimum order quantity, please contact Sales Department.

4. No mixed date codes or partial quantity (less than minimum packaging quantity) per packaging is allowed.

5. In no case shall there be two or more consecutive components missing from any reel for any reason.


Device Tape Orientation

Tape Width	Suffix	Tape Orientation	Tape Width	Suffix	Tape Orientation
12mm	-7 -13		12mm	-7R -13R	
12mm	TA TC				

Notes: 6. For part marking, refer to product datasheet.


7. Tape and package drawings are not to scale and are shown for device tape orientation only.

Embossed Carrier Tape Specifications




Tape Width (W)	Dimension	Value (mm)	Dimension	Value (mm)	Dimension	Value (mm)
12mm	E	1.75 ±0.10	K	4.5 max.	t	0.25 ±0.05
	F	5.5 ±0.10	P	8.0 ±0.10	W	12.0 ±0.30
	D	1.55 ±0.05	P0	4.0 ±0.10		
	D1	1.55 ±0.05	P2	2.0 ±0.10		
	A0 B0 K0	Determined by component size. The clearance between the component and the cavity must comply to the rotational and lateral movement requirement provided in figures in the "Maximum Component Movement in Tape Pocket" section.				

Embossed Carrier Tape Specifications (Continued)




Maximum Component Movement in Tape Pocket


Component Lateral Movement




Maximum Component Rotation (Top View)



Maximum Component Rotation (Side View)




Surface Mount Reel Specifications



* Drive spokes optional. If used, dimensions with asterisks apply.

Tape Width	Reel Size	A (mm)	B* (mm)	C (mm)	D* (mm)	N (mm)	G (mm)	T (mm)
12mm	13"	330 ±2	2.0 +0.5 -0	13 ±1	20.5 ±0.2	50 (min)	14.4 (max)	18.4 (max)

Tape Leader and Trailer Specifications



- Notes:**
- There shall be a leader of at least 230mm which may consist of carrier tape and/or cover tape or a start tape followed by at least 160mm of empty carrier tape sealed with cover tape.
 - There shall be a trailer of at least 160mm of empty carrier tape sealed with cover tape. The entire carrier tape must release from the reel hub as the last portion of the tape unwinds from the reel without damage to the carrier tape and the remaining components in the cavities.