


図面／規格
【10.9 Hexagon bolt】



[単位:mm]

呼び径 (d)	ds		K		S		e	z
	基準寸法	許容差	基準寸法	許容差	基準寸法	許容差	約	約
M5	5	0 -0.1	3.5	± 0.15	8	0 -0.2	9.2	0.9
M6	6	0	4	± 0.25	10	0 -0.6	11.5	1
M8	8	-0.2	5.5	± 0.3	13	0	15	1.2
M10	10		7		17	-0.7	19.6	1.5
M12	12		8		19		21.9	2
M14	14	0	9		22		25.4	2
M16	16	-0.25	10	± 0.35	24	0 -0.8	27.7	2
M18	18		12		27		31.2	2.5
M20	20		13		30		34.6	2.5
M22	22	0	14		32		37	2.5
M24	24	-0.35	15		36	0	41.6	3
M27	27		17		41	-1.0	47.3	3
M30	30		19	± 0.4	46		53.1	3.5
M33	33		21		50		57.7	3.5
M36	36		23		55		63.5	4
M39	39	0	25		60		69.3	4
M42	42	-0.4	26		65	0 -1.2	75	4.5
M45	45		28		70		80.8	4.5
M48	48		30		75		86.5	5

(bは $d \times 2 + 6$ 、長さ130より $d \times 2 + 12$ 、長さ220より $d \times 2 + 25$)