

A large, light gray play button icon is positioned on the left side of the slide. It consists of a white right-pointing triangle centered within a series of concentric circles in varying shades of gray.

Creating a React Web App

1. Creating a simple app
2. Creating many elements
3. Data-driven UIs


A large, light gray play button icon is positioned on the left side of the slide. It consists of a white right-pointing triangle centered within a series of concentric circles in varying shades of gray.

1. Creating a Simple App

- Scenario
- Defining a target element
- Including React libraries
- The virtual DOM
- Creating React elements
- Rendering React elements
- Viewing the React virtual DOM
- Logging a React element

Scenario

- In this chapter we show how to create simple React apps in pure React, using ES6++ language features
- See the `Demos/02-WebApp` folder
 - The first example we'll look at is `helloReact.html`
 - This is a minimalistic "Hello World" React app 😊



Defining an HTML Target Element

- A React web app has a single top-level HTML element into which React will render the UI
- You typically define it like this

```
<div id="osl-container"></div>
```

- Give it a suitable `id`
- You'll refer to this `id` when you render content (see later)

Including React Libraries

- To use React in a web page, you need 2 libraries:
 - React - Creates views
 - ReactDOM - Renders views in the web browser
- The following code downloads these libraries directly
 - Later, we'll see how to use npm to manage these libraries

```
<script src="https://unpkg.com/react@16/umd/react.development.js"></script>  
<script src="https://unpkg.com/react-dom@16/umd/react-dom.development.js"></script>
```

The Virtual DOM

- In a web app, you can manipulate elements using DOM
 - Create elements, append child element, etc.
- DOM is a very low-level API
 - It takes a lot of code to achieve simple tasks
 - It can also be really slow at run time!
- React introduces the concept of the virtual DOM
 - You create React elements (lightweight JS objects)
 - You manipulate the lightweight JS objects, and React renders the appropriate HTML as efficiently as possible

Creating React Elements

- You can create a React element programmatically by calling `React.createElement()`
 - 1st argument specifies the type of element to create
 - 2nd argument specifies the element's properties
 - 3rd argument specifies the element's children

```
<script>
  const msg = React.createElement(
    'h1',
    {id: 'msg-0', 'title': 'My message'},
    'Hello React!')
</script>
```


Rendering React Elements

- Render your top-level React element into a target node on the web page, using `ReactDOM.render()`
 - 1st argument is your top-level React element
 - 2nd argument is the target node on the web page

```
<script>
...
ReactDOM.render (
  msg,
  document.getElementById('osl-container'))
</script>
```



Viewing the React Virtual DOM

- Chrome (and other browsers) allow you to view the React elements in the virtual DOM
 - Install the React Developer Tools extension
 - Then in DevTools, click Components and select element



Logging a React Element

- A React element is a lightweight object, as shown here



A large, light gray play button icon is positioned on the left side of the slide. It consists of a white right-pointing triangle centered within a series of concentric gray circles.

2. Creating Many Elements

- Overview
- Hierarchy of React elements
- View the page in the browser
- View the virtual DOM

Overview

- In this section we'll see how to create a more ambitious virtual DOM tree, containing nested React elements
 - Then we'll render the root React element to the DOM
- Actually that's an important point...
 - You only ever render the root React element to the DOM


Hierarchy of React Elements

- `createElement()` can take a variadic list of child elements, so you can create a hierarchy of elements

```
const ul =  
  React.createElement('ul', null,  
    React.createElement('li', null, 'Item1'),  
    React.createElement('li', null, 'Item2'),  
    React.createElement('li', null, 'Item3'))
```

- For an example, see `multipleElements.html`


View the Page in the Browser



View the Virtual DOM (1 of 2)

- To view components in the virtual DOM, e.g. using React Developer Tools in Chrome:
 - Show the DevTools window (F12)
 - Click the Components tab
 - In the Search window, click the Settings icon
 - In the popup window, select the Components tab
 - Deselect the "Hide components where" option
 - You should now see a list of the components

View the Virtual DOM (2 of 2)



A large, light gray play button icon is positioned on the left side of the slide. It consists of a white right-pointing triangle centered within a series of concentric circles in varying shades of gray.

3. Data-Driven UIs

- Overview
- Defining data
- Mapping data to elements
- Example
- View the page in the browser

Overview

- The previous section created a hard-coded hierarchy of React elements
- In a real app, you'll adopt a data-driven approach
 - The elements you create will depend on data
 - We'll see how to create a data-driven UI in this section
 - See `multipleElementsViaData.html`

Defining Data

- We'll have an array of products and an array of shops

```
const products = [  
  'Swansea City shirt',  
  'Cardiff City shirt',  
  ...  
]
```

```
const shops = [  
  'London',  
  'Paris',  
  ...  
]
```

Mapping Data to Elements

- You can use `map ()` to map array item to a React elem

```
someArray.map((arrayItem, index) =>  
  React.createElement(elem,  
    {key:index},  
    arrayItem.someProperty)  
)
```

- `map ()` takes a function that typically has 2 args
 - Arg 1 is an array item, arg 2 is the index of the array item
 - The function creates a React element (with unique key)

Example (1 of 2)

- Let's map `products` and `shops` arrays to ``'s

```
let prodList = React.createElement('ul', null,  
  products.map((p, i) =>  
    React.createElement('li', {key: i}, p))  
)
```

```
let shopList = React.createElement('ul', null,  
  products.map((s, i) =>  
    React.createElement('li', {key: i}, s))  
)
```

Example (2 of 2)


- Now let's put it all together

```
let retailer = React.createElement('div', null,  
  React.createElement('h1', null, 'Catalog'),  
  prodList,  
  React.createElement('h1', null, 'Shops'),  
  shopList  
)
```

```
ReactDOM.render(  
  retailer,  
  document.getElementById('osl-container'))
```

Viewing the Page in the Browser

- Here's how the page looks in the browser



A large, light gray play button icon is positioned on the left side of the slide. It consists of a white right-pointing triangle centered within a series of concentric circles in varying shades of gray.

Summary

- Creating a simple app
- Creating many elements
- Data-driven UIs