

Implement Gradient Descent in Python





Rohan Joseph [Follow](#)

Jun 3, 2018 · 3 min read

What is gradient descent ?

It is an optimization algorithm to find the minimum of a function. We start with a random point on the function and move in the **negative direction** of the **gradient of the function** to reach the **local/global minima**.







Homer descending !



Example by hand :

Question : Find the local minima of the function $y = (x+5)^2$ starting from the point $x=3$





Solution : We know the answer just by looking at the graph. $y = (x+5)^2$ reaches it's minimum value when $x = -5$ (i.e when $x=-5, y=0$). Hence $x=-5$ is the local and global minima of the function.

Now, let's see how to obtain the same numerically using gradient descent.

Step 1 : Initialize $x = 3$. Then, find the gradient of the function, $dy/dx = 2*(x+5)$.

Step 2 : Move in the direction of the negative of the gradient (Why?). But wait, how much to move? For that, we require a learning rate. Let us assume the **learning rate $\rightarrow 0.01$**

Step 3 : Let's perform 2 iterations of gradient descent

Initialize Parameters :

$$X_0 = 3$$

$$\text{Learning rate} = 0.01$$

$$\frac{dy}{dx} = \frac{d}{dx} (x + 5)^2 = 2 * (x + 5)$$

Iteration 1 :

$$X_1 = X_0 - (\text{learning rate}) * \left(\frac{dy}{dx}\right)$$

$$X_1 = 3 - (0.01) * (2 * (3 + 5)) = 2.84$$

Iteration 2 :

$$X_2 = X_1 - (\text{learning rate}) * \left(\frac{dy}{dx}\right)$$

$$X_2 = 2.84 - (0.01) * (2 * (2.84 + 5)) = 2.6832$$

Step 4 : We can observe that the X value is slowly decreasing and should converge to -5 (the local minima). However, how many iterations should we perform?

Let us set a precision variable in our algorithm which calculates the difference between two consecutive “x” values . If the difference between x values from 2 consecutive iterations is lesser than the precision we set, stop the algorithm !

Gradient descent in Python :

Step 1 : Initialize parameters

```
cur_x = 3 # The algorithm starts at x=3
rate = 0.01 # Learning rate
precision = 0.000001 #This tells us when to stop the algorithm
previous_step_size = 1 #
max_iters = 10000 # maximum number of iterations
```

```

iters = 0 #iteration counter
df = lambda x: 2*(x+5) #Gradient of our function

```

Step 2 : Run a loop to perform gradient descent :

i. Stop loop when difference between x values from 2 consecutive iterations is less than 0.000001 or when number of iterations exceeds 10,000

```

while previous_step_size > precision and iters < max_iters:
    prev_x = cur_x #Store current x value in prev_x
    cur_x = cur_x - rate * df(prev_x) #Grad descent
    previous_step_size = abs(cur_x - prev_x) #Change in x
    iters = iters+1 #iteration count
    print("Iteration",iters,"\nX value is",cur_x) #Print iterations

print("The local minimum occurs at", cur_x)

```

Output : From the output below, we can observe the x values for the first 10 iterations- which can be cross checked with our calculation above. The algorithm runs for 595 iterations before it terminates. The code and solution is embedded below for reference.

```

Iteration 1
x value is 2.94

```

```
^ value is 2.04
Iteration 2
X value is 2.6832
Iteration 3
X value is 2.529536
Iteration 4
X value is 2.37894528
Iteration 5
X value is 2.2313663744
Iteration 6
X value is 2.0867390469119997
Iteration 7
X value is 1.9450042659737599
Iteration 8
X value is 1.8061041806542846
Iteration 9
X value is 1.669982097041199
Iteration 10
X value is 1.5365824551003748
```

. . .

Connect on LinkedIn.

```
X value is -4.277241855298507
Iteration 120
X value is -4.291697018192341
Iteration 121
X value is -4.305863077828494
Iteration 122
```

```
X value is -4.319745816271924
Iteration 123
X value is -4.333350899946486
Iteration 124
X value is -4.3466838819475555
Iteration 125
X value is -4.359750204308605
Iteration 126
X value is -4.372555200222433
Iteration 127
X value is -4.385104096217984
Iteration 128
X value is -4.3974020142936245
Iteration 129
X value is -4.409453974007752
Iteration 130
X value is -4.421264894527597
Iteration 131
X value is -4.432839596637045
Iteration 132
X value is -4.444182804704305
Iteration 133
X value is -4.4552991486102185
```

Gradient_descent.ipynb hosted with  by GitHub

[view raw](#)

[Deep Learning](#)

[Machine Learning](#)

[Data Science](#)

[Analytics](#)

[Python](#)

Discover Medium

Welcome to a place where words matter. On Medium, smart voices and original ideas take center stage - with no ads in sight. Watch

Make Medium yours

Follow all the topics you care about, and we'll deliver the best stories for you to your homepage and inbox. Explore

Become a member

Get unlimited access to the best stories on Medium — and support writers while you're at it. Just \$5/month. Upgrade

[About](#)

[Help](#)

[Legal](#)