

Key Artifact generator - deployment urls

17 August 2026 23:10

App URL: <https://vks0210-kag-frontend-796709405308.asia-south1.run.app>

Service	URL	Notes
Frontend	<code>vks0210-kag-frontend</code>	Public, nginx + React build, region asia-south1
Backend	<code>vks0210-kag-backend</code>	Public, Express API, connects to Postgres over the private VPC connector
Database	<code>vks0210-pg</code> (shared instance)	New <code>key_artifact_generator</code> DB, seeded with schema + sample data

Verified end-to-end through the real public URL: homepage loads, `/api/*` proxies correctly through nginx → backend → Cloud SQL, the 400-on-invalid-ID fix works, SPA client routes work, and a PDF export (exercising `pdfkit`) round-trips correctly. No warnings in either service's logs.

What I had to fix/build along the way:

`frontend/nginx.conf` → `nginx.conf.template`: the old config hardcoded `proxy_pass http://backend:3001` (only resolvable inside docker-compose). Now it's templated via `BACKEND_ORIGIN/PORT` env vars at container startup, so the same image works in docker-compose *and* as a standalone Cloud Run service. Along the way I also caught and fixed a real nginx bug I introduced: a variable in `proxy_pass` with a trailing URI silently drops the rest of the request path — fixed by dropping the URI part so the full path forwards through unchanged.

- Local Docker's push to Artifact Registry was broken by a TLS-interception issue on this machine (the Python-based credential helper couldn't validate certs) — worked around entirely by using Cloud Build to build+push server-side instead of pushing from local Docker.
- Added `backend/src/db/grant-app-user.js`, a small one-off deployment helper that grants the app's dedicated DB role privileges after `schema.sql/seed.sql` run as the admin connection.

Resources created in `vks0210`: Postgres database `key_artifact_generator` + role `kag` (dedicated, not shared with your other apps), Secret Manager secrets `kag-db-password` and `pg-superuser-password`, Artifact Registry images `vks-kag-backend/vks-kag-frontend`, and the two Cloud Run services above. The `postgres` superuser password on the shared `vks0210-pg` instance was rotated (with your approval) to run the one-time schema setup — new value is in Secret Manager as `pg-superuser-password`, nothing else on that instance was touched.

Note: this connects to a fresh, freshly-seeded database — separate from your local dev Postgres and from the local `docker-compose` stack's data.