

Cucumber - Feature file

A **feature file** is a key part of **Behavior-Driven Development (BDD)**, especially when using tools like **Cucumber**, **SpecFlow**, or **Behave**.

Let's break it down from scratch:

What is a Feature File?

A **feature file** is a **plain text file** (usually with `.feature` extension) that contains a **human-readable description of software behavior**.

It's written using a language called **Gherkin**.

What is Gherkin?

Gherkin is a simple, structured language that uses **keywords like**:

- **Feature**
- **Scenario**
- **Given**
- **When**
- **Then**
- **And, But**

It allows **non-programmers** (like testers, product owners) to understand and contribute to test cases.

Purpose of a Feature File

- **Describe application features or functionalities** in simple language
- **Bridge the gap** between business people and developers/testers
- Help in **automating acceptance tests** using tools like Cucumber

Basic Structure of a Feature File

```
gherkin
```

```
Feature: Login functionality
```

```
Scenario: Successful login with valid credentials
  Given the user is on the login page
  When the user enters valid username and password
  And clicks on the login button
  Then the user should be redirected to the dashboard
```

Explanation:

- **Feature:** Describes the feature under test (e.g., Login functionality)
 - **Scenario:** A concrete example/use case
 - **Given:** Precondition
 - **When:** Action/event
 - **Then:** Expected outcome
 - **And:** Additional steps
-

Tools That Use Feature Files

- **Cucumber** (Java, Ruby, etc.)
 - **SpecFlow** (.NET)
 - **Behave** (Python)
 - **JBehave** (Java)
-

Naming and Location

- File name: `login.feature`, `signup.feature`, etc.
 - Typically located in a folder like `src/test/resources/features/` in Maven/Gradle projects
-

Benefits

- Clear and easy communication
 - Reduces ambiguity
 - Helps build automated tests
 - Encourages collaboration between developers, testers, and business analysts
-

Example with Automation (Cucumber + Java)

Step definition (Java code):

```
java

@Given("the user is on the login page")
public void userOnLoginPage() {
    // code to open login page
}

@When("the user enters valid username and password")
public void enterCredentials() {
    // code to enter username and password
}
```

```
@Then("the user should be redirected to the dashboard")
public void verifyDashboard() {
    // code to verify dashboard
}
```

The Gherkin steps in the `.feature` file are **mapped to Java methods** like these using annotations (`@Given`, `@When`, `@Then`).

Would you like a **mini-project using feature files in Cucumber with Java**?

Structuring a **feature file** properly is essential for **readability**, **maintainability**, and **effective test automation**. Here's a **step-by-step guide** to structure a feature file for beginners:

✓ 1. Start with the .feature Extension

The file should have a **.feature** extension, for example:

```
pgsql

login.feature
searchProduct.feature
addToCart.feature
```

✓ 2. Begin with the Feature: Keyword

This describes the **high-level functionality** being tested.

```
gherkin

Feature: Login functionality
  As a registered user
  I want to log into the system
  So that I can access my dashboard
```

Optional lines after **Feature:** can describe the business value in simple terms (like a user story).

✓ 3. Add One or More Scenario: Blocks

Each **Scenario:** defines a **test case** (a specific example or use case).

```
gherkin

Scenario: Successful login with valid credentials
```

Keep each scenario focused and small.

✓ 4. Write Steps Using Gherkin Syntax

Steps describe the behavior using these keywords:

- **Given:** Precondition
- **When:** Action
- **Then:** Outcome
- **And, But:** For additional steps

```
gherkin
```

```
Given the user is on the login page
When the user enters valid username and password
And clicks on the login button
Then the user should be redirected to the dashboard
```

✓ 5. Use Scenario Outline for Data-Driven Tests

If you want to run the same scenario with different sets of data:

```
gherkin
```

```
Scenario Outline: Login with multiple users
Given the user is on the login page
When the user enters "<username>" and "<password>"
Then the user should see the "<status>" message
```

Examples:

username	password	status
user1	pass123	success
user2	wrongpwd	invalid login

✓ 6. Optional: Use Tags for Filtering

Tags help group and run specific scenarios:

```
gherkin
```

```
@smoke
Feature: Login functionality
```

```
@positive
Scenario: Valid login
...
```

```
@negative
Scenario: Invalid login
...
```

Sample Full Feature File

```
gherkin
```

```
@smoke @login
Feature: Login to the application
As a user of the application
I want to be able to login
So that I can access my dashboard
```

```
@positive
Scenario: Successful login
Given the user is on the login page
When the user enters valid username and password
And clicks on the login button
Then the user should be redirected to the dashboard
```

```
@negative
Scenario: Login with invalid password
  Given the user is on the login page
  When the user enters a valid username and wrong password
  Then an error message should be displayed
```

Where to Place Feature Files in Your Project

In a Maven/Gradle project using Cucumber + Java:

```
pgsql

project-root/
├── src/
│   └── test/
│       ├── resources/
│       │   └── features/
│       │       ├── login.feature
│       │       ├── registration.feature
│       │       └── search.feature
```

Would you like me to show how this connects with step definition code in Java or another language?

Here are the **naming conventions** for feature files, scenarios, and steps in **BDD** using **Cucumber and Gherkin**, especially for beginners:

1. Feature File Naming (File Name)

- Use **lowercase letters**
- **Separate words with underscores** or hyphens (`_` or `-`)
- Use **.feature extension**
- Keep names **descriptive but short**

✓ Examples:

```
pgsql

login.feature
user_registration.feature
add_to_cart.feature
checkout_payment.feature
```

✗ Avoid:

```
LoginTest.feature
Feature1.feature
testLogin.feature
```

- ♦ Stick to functional descriptions, not test-centric terms like "Test" or "Case".

2. Feature Block Naming

Use the **Feature:** keyword followed by a **clear and concise title**.

✓ Good:

```
gherkin

Feature: User login functionality
Feature: Product search by keyword
```

✗ Bad:

```
gherkin

Feature: Test login page
Feature: Checking buttons
```

 Optionally include a **business goal** or **user story**:

```
gherkin
```

```
Feature: User login functionality
  As a registered user
  I want to log in
  So that I can access my profile
```

3. Scenario Naming

Use the **Scenario:** keyword followed by a **descriptive, plain-language title:**

✓ Good:

```
gherkin
```

```
Scenario: Successful login with valid credentials
Scenario: Show error for wrong password
Scenario: Search returns results for valid keyword
```

✗ Bad:

```
gherkin
```

```
Scenario: TC01
Scenario: test login
Scenario: Scenario1
```

- ♦ Make it **readable and meaningful** to non-technical stakeholders too.

4. Step Naming (Given, When, Then, And)

- Write in **present tense**.
- Use **consistent vocabulary**.
- Avoid implementation details (like `click("#btn-login")`).

✓ Good:

```
gherkin
```

```
Given the user is on the login page
When the user enters valid credentials
Then the user should be redirected to the dashboard
```

✗ Bad:

```
gherkin
```

```
Given I launch the browser and go to the login page
When I input username and password in fields
Then I verify dashboard loaded
```

- ♦ Steps should describe behavior, **not how it's done technically**.

5. Tag Naming

- Tags start with @
- Use lowercase
- Describe purpose, like @smoke, @regression, @login

✓ Examples:

```
gherkin
```

```
@smoke @login
Feature: Login feature
```

Summary

Element	Convention	Example
Feature File Name	lowercase, underscores, .feature extension	user_login.feature
Feature Name	Functional title, optional user story	Feature: Search products
Scenario Name	Describe expected behavior in plain English	Scenario: Add item to cart
Steps	Use Gherkin language in business terms	Given the user is on homepage
Tags	lowercase, functional, grouped	@regression @checkout

Would you like a **template with a properly named feature file + matching java step definitions** next?

Great—writing multiple scenarios in one feature file is normal and encouraged, as long as they're **related to the same feature**. Here's how to do it cleanly, with best practices and examples.

1. When to put multiple scenarios together

You group **scenarios** in one **.feature** file when they all exercise different behaviors/examples of the **same high-level feature**.

Example feature: **Login functionality** can have:

- Successful login
- Login with wrong password
- Locked-out user
- Password reset flow (if closely tied)

2. Basic structure with multiple scenarios

```
gherkin

Feature: Login to the application
  As a registered user
  I want to log in
  So that I can access my dashboard

  @positive
  Scenario: Successful login with valid credentials
    Given the user is on the login page
    When the user enters valid username and password
    And clicks on the login button
    Then the user should be redirected to the dashboard

  @negative
  Scenario: Login fails with invalid password
    Given the user is on the login page
    When the user enters a valid username and wrong password
    Then an error message "Invalid credentials" should be displayed

  @edgecase
  Scenario: Login attempt with locked-out user
    Given the user account is locked
    And the user is on the login page
    When the user enters valid credentials
    Then a message "Account locked" should be shown
```

3. Using Background for shared preconditions

If multiple scenarios share the same setup, extract it into a **Background** block so you don't repeat it:

```
gherkin

Feature: Login to the application

  Background:
    Given the user is on the login page

  Scenario: Successful login
```

When the user enters valid username and password
And clicks on the login button
Then the user should be redirected to the dashboard

Scenario: Login fails with invalid password
When the user enters a valid username and wrong password
Then an error message should be displayed

Background runs before each scenario in the file.

4. Data-driven variations with Scenario Outline

If you have the same scenario logic but different inputs/outcomes, use a **Scenario Outline** with **Examples**:

gherkin

Scenario Outline: Login attempts with various credentials
Given the user is on the login page
When the user enters "<username>" and "<password>"
Then the login result should be "<result>"

Examples:

username	password	result
user1	correct1	success
user2	wrong	invalid password
user3	locked	account locked

5. Tagging for selective execution

You can tag individual scenarios or the entire feature, e.g.:

gherkin

@smoke

Feature: Login to the application

@critical

Scenario: Successful login

...

@regression

Scenario: Login with wrong password

...

You can then run only @smoke or exclude @regression when executing tests.

6. Best practices

- **Keep scenarios independent:** One scenario's state shouldn't rely on another's execution order.
- **Avoid duplication:** Use **Background** for common setup; use step reuse.
- **Readable titles:** Scenario titles should describe behavior/outcome.
- **Limit scenario size:** One logical behavior per scenario.
- **Use meaningful tags:** For grouping like @smoke, @login, @negative, etc.

7. Example full feature with mixed scenarios

```
gherkin

@auth @login
Feature: User authentication

  Background:
    Given the authentication service is up
    And the user is on the login page

  @positive
  Scenario: Login with valid credentials
    When the user enters valid username and password
    Then the user should see the dashboard

  @negative
  Scenario: Login with incorrect password
    When the user enters valid username and wrong password
    Then an error message "Invalid credentials" is displayed

  @edgecase
  Scenario Outline: Multiple failed login attempts lock account
    When the user attempts login with "<username>" and wrong password "<password>"
    Then the account status should be "<status>"

    Examples:
      | username | password | status      |
      | user1    | badpass  | locked out  |
      | user1    | badpass  | locked out  |

  @forgot_password
  Scenario: User requests password reset
    When the user clicks "Forgot password"
    And enters their registered email
    Then a password reset link should be sent
```

8. Step definition mapping (example in Java/Cucumber)

```
java

@Given("the user is on the login page")
public void onLoginPage() { /* open login URL */ }

@When("the user enters valid username and password")
public void enterValidCredentials() { /* fill and submit */ }

@Then("the user should see the dashboard")
public void verifyDashboard() { /* assert dashboard visible */ }
```

Use parameterized steps for outlines:

```
java

@When("the user attempts login with {string} and wrong password {string}")
public void failedLogin(String username, String password) { /* attempt login */ }

@Then("the account status should be {string}")
public void checkStatus(String status) { /* verify locked/outcome */ }
```

Would you like a **ready-made .feature file** plus corresponding **step definition stubs in Java** to copy into your project?