

REST Assured Extracting Response Data

In **Rest Assured**, extracting response data is essential when you need to verify response values or pass them between API calls. Here's a step-by-step guide with examples on how to extract different types of response data.

✓ Step 1: Basic Setup

Add the required Maven dependency:

```
xml

<dependency>
  <groupId>io.rest-assured</groupId>
  <artifactId>rest-assured</artifactId>
  <version>5.4.0</version>
  <scope>test</scope>
</dependency>
```

✓ Step 2: Extracting Response as a Whole

```
java

import io.restassured.response.Response;
import static io.restassured.RestAssured.*;

public class ExtractExample {
    public static void main(String[] args) {
        Response response =
            given()
                .baseUrl("https://jsonplaceholder.typicode.com")
                .when()
                .get("/posts/1");

        System.out.println("Response Body:");
        System.out.println(response.asPrettyString());
    }
}
```

✓ Step 3: Extracting Specific Values

You can extract values like **id**, **title**, **userId** etc.

◆ Using `.path()` method:

```
java

String title =
    given()
        .baseUrl("https://jsonplaceholder.typicode.com")
        .when()
        .get("/posts/1")
        .then()
        .extract()
        .path("title");
```

```
System.out.println("Title: " + title);
```

◆ Using `.jsonPath()` method:

```
java

import io.restassured.path.json.JsonPath;

Response response =
    given()
        .baseUrl("https://jsonplaceholder.typicode.com")
        .when()
            .get("/posts/1");

JsonPath json = response.jsonPath();
String body = json.getString("body");
System.out.println("Body: " + body);
```

✓ Step 4: Extracting List of Values

```
java

List<Integer> ids =
    given()
        .baseUrl("https://jsonplaceholder.typicode.com")
        .when()
            .get("/posts")
        .then()
            .extract()
                .path("id");

System.out.println("All IDs: " + ids);
```

✓ Step 5: Extracting Data from Headers

```
java

String contentType =
    given()
        .baseUrl("https://jsonplaceholder.typicode.com")
        .when()
            .get("/posts/1")
        .then()
            .extract()
                .header("Content-Type");

System.out.println("Content-Type: " + contentType);
```

✓ Step 6: Extracting Status Code

```
java

int statusCode =
    given()
        .baseUrl("https://jsonplaceholder.typicode.com")
        .when()
            .get("/posts/1")
```

```
.then()
    .extract()
    .statusCode();

System.out.println("Status Code: " + statusCode);
```

✓ Step 7: Store and Use Extracted Data

```
java

String postTitle =
    given()
        .baseUrl("https://jsonplaceholder.typicode.com")
    .when()
        .get("/posts/1")
    .then()
        .extract()
        .path("title");

// Use in another request or assertion
System.out.println("Extracted Title: " + postTitle);
```

← END Summary

Task	Method Used
Whole Response	<code>Response response = given...</code>
Single Field	<code>.extract().path("field")</code>
JSON Path	<code>.jsonPath().get("field")</code>
Header	<code>.extract().header("name")</code>
Status Code	<code>.extract().statusCode()</code>
List of Fields	<code>.extract().path("list")</code>

If you'd like, I can give you a **mini-assignment** or a **mock API lab** on extracting response data. Would you like that?

Storing response values from one API call and using them in a **subsequent API request** is a common and powerful practice in API testing and automation with **Rest Assured**.

✓ Use Case Example

1. **POST** request to create a user → Get the **id** from the response.
2. **GET** request to retrieve the user → Use the stored **id**.

✓ Step-by-Step: Store and Use Response Data

● Step 1: Send POST Request and Store ID

```
java

import io.restassured.response.Response;
import static io.restassured.RestAssured.*;

public class StoreAndUse {
    public static void main(String[] args) {

        // Step 1: Create a new user (POST)
        Response postResponse =
            given()
                .baseUrl("https://reqres.in")
                .header("Content-Type", "application/json")
                .body("{ \"name\": \"Koti\", \"job\": \"QA\" }")
            .when()
                .post("/api/users");

        // Extract user ID from response
        String userId = postResponse.jsonPath().getString("id");
        System.out.println("User ID extracted: " + userId);

        // Step 2: Use the user ID in GET request (this API is dummy; modify accordingly)
        Response getResponse =
            given()
                .baseUrl("https://reqres.in")
            .when()
                .get("/api/users/" + userId);

        // Print GET response
        System.out.println("GET Response:");
        System.out.println(getResponse.asPrettyString());

    }
}
```

Reusable Version with Variables

```
java

String userId =
    given()
        .baseUrl("https://reqres.in")
        .header("Content-Type", "application/json")
        .body("{ \"name\": \"Koti\", \"job\": \"Engineer\" }")
    .when()
        .post("/api/users")
    .then()
        .extract()
        .path("id");
```

```
// Use stored userId in next API call
given()
  .baseUrl("https://reqres.in")
.when()
  .get("/api/users/" + userId)
.then()
  .statusCode(200);
```

✓ Things You Can Store:

Type	Example Extraction
Path Value	<code>.path("id")</code>
Header	<code>.header("Content-Type")</code>
Cookie	<code>.cookie("JSESSIONID")</code>
List/Array	<code>.path("data.id[0]")</code>
Status Code	<code>.statusCode()</code>

📌 Tip:

If you're doing multiple steps (e.g., login → get token → use token), store values in **String**, **Map**, or even static variables across methods/classes.

Would you like a **token-based login + protected API** flow example as well?

Great question!

In **Rest Assured**, both `extract().path()` and `extract().response()` are used to extract data **from API responses**, but they serve slightly different purposes depending on what you need:

✓ `extract().path()` – Direct Value Extraction

- Use it when you want to **directly get a value** (like an ID, name, token, etc.) from the response.
- Returns the **specific value** (not the whole response).

♦ Example:

```
java

String userId =
    given()
        .baseUrl("https://reqres.in")
        .header("Content-Type", "application/json")
        .body("{ \"name\": \"Koti\", \"job\": \"QA\" }")
    .when()
        .post("/api/users")
    .then()
        .statusCode(201)
        .extract()
        .path("id");

System.out.println("Extracted User ID: " + userId);
```

✓ `extract().response()` – Full Response Extraction

- Use this when you want to store the **entire response object** for further inspection or multiple extractions.
- You can later use `.path()`, `.jsonPath()`, `.getStatusCode()`, etc., on this **Response** object.

♦ Example:

```
java

import io.restassured.response.Response;

Response response =
    given()
        .baseUrl("https://reqres.in")
        .header("Content-Type", "application/json")
        .body("{ \"name\": \"Koti\", \"job\": \"QA\" }")
    .when()
        .post("/api/users")
    .then()
        .statusCode(201)
        .extract()
        .response();

String id = response.path("id");
String createdAt = response.path("createdAt");

System.out.println("ID: " + id);
System.out.println("Created At: " + createdAt);
```

Summary: When to Use What?

Use Case	Method	Return Type
Extract a single field	<code>.extract().path("key")</code>	Value (String, int, etc.)
Extract multiple fields later	<code>.extract().response()</code>	Response object

Best Practice

If you only need **one value**, use:

```
java
String token = extract().path("token");
```

If you need **many values or headers/status**, use:

```
java
Response response = extract().response();
```

Would you like a **real-world scenario** showing `extract().response()` for token-based auth?