

# Java Thread Runnable

## ✓ Overview: Thread Class vs Runnable Interface in Java

Both **Thread** class and **Runnable** interface are used to create and manage threads in Java, but they differ in how you use them and what flexibility they offer.

## 1. Thread Class

- Java provides the **Thread** class in the `java.lang` package.
- To create a thread by extending **Thread**, you override its `run()` method.

### Example:

```
java

class MyThread extends Thread {
    public void run() {
        System.out.println("Thread is running...");
    }

    public static void main(String[] args) {
        MyThread t1 = new MyThread();
        t1.start(); // Starts a new thread and invokes run()
    }
}
```

## ✓ Key Points:

- Inherits from **Thread** class.
- Cannot extend another class (Java doesn't support multiple inheritance with classes).
- Use when you don't need to extend any other class.

## 2. Runnable Interface

- **Runnable** is a functional interface with a single method: `run()`.
- To use it, implement the **Runnable** interface and pass the instance to a **Thread** object.

### Example:

```
java

class MyRunnable implements Runnable {
    public void run() {
        System.out.println("Runnable thread is running...");
    }

    public static void main(String[] args) {
        MyRunnable myRunnable = new MyRunnable();
        Thread t1 = new Thread(myRunnable);
    }
}
```

```
t1.start(); // Starts thread and invokes run()
    }
}
```

## ✓ Key Points:

- Implements **Runnable** interface.
- More flexible: allows you to extend another class.
- Recommended approach in real-world applications, especially when using thread pools or executors.

## Comparison Table

Feature	Thread Class	Runnable Interface
Inheritance	Extends <b>Thread</b>	Implements <b>Runnable</b>
Flexibility	Less (can't extend another class)	More (can extend other classes)
Recommended for	Simple threads	Scalable & real-world applications
Thread creation	<b>new MyThread().start()</b>	<b>new Thread(new MyRunnable()).start()</b>
Use with Thread Pools	Not directly	Yes (ExecutorService)

## Best Practice

**Use Runnable interface** (or **Callable** if you need a return value) for most practical multi-threading in Java. It's more flexible, cleaner, and better suited for modern concurrency APIs like **ExecutorService**.

Let me know if you'd like to see:

- Example using **ExecutorService**
- **Callable** interface overview
- Thread lifecycle or synchronization examples

## What is a Thread in Java?

A **thread** in Java is a **lightweight, independent path of execution** within a program. Think of it as a **small unit of a process** that can run **concurrently** with other threads.

## Why Threads?

In a typical Java application, the **main()** method runs in a **single thread** called the **main thread**. But sometimes we want to do multiple things **at the same time**, like:

- Downloading a file while showing a progress bar
- Running background tasks without freezing the UI
- Handling multiple client requests in a server

→ That's where **threads** help — they allow **parallel execution** of code.

## Key Concepts

Concept	Description
<b>Thread</b>	A unit of execution within a process
<b>Multithreading</b>	Running two or more threads concurrently
<b>Main Thread</b>	The default thread started by the JVM
<b>Start()</b>	Starts a thread and invokes its <b>run()</b> method
<b>Run()</b>	Contains the code to be executed in the thread
<b>Thread Scheduler</b>	Decides which thread to run when (handled by JVM/OS)

## Example

```
java

class MyThread extends Thread {
    public void run() {
        System.out.println("Thread is running...");
    }

    public static void main(String[] args) {
        MyThread t1 = new MyThread(); // Create a new thread
        t1.start();                    // Start the thread
    }
}
```

**start()** creates a **new call stack** for the thread and calls **run()** internally.

## Thread Lifecycle

1. **New** – Thread is created but not started.
2. **Runnable** – After **start()** is called; ready to run.

3. **Running** – Actually executing.
  4. **Blocked/Waiting** – Waiting for a resource or another thread.
  5. **Terminated** – Finished execution or stopped.
- 

## ✓ Real-Life Analogy

Imagine a **kitchen** where multiple **chefs (threads)** are working **at the same time** (concurrently):

- One is **cutting vegetables**
- Another is **boiling water**
- Another is **making dough**

They all work in **parallel** to complete the task faster — that's multithreading!

---


Let me know if you want to learn:

- Thread lifecycle with diagram
- Thread priorities and scheduling
- Thread synchronization and locks
- Practical examples with multithreading

Great! Let's go step-by-step. Here's a detailed explanation of the **Thread Lifecycle**, **Thread Priorities**, **Thread Scheduling**, and **Thread Synchronization** — with diagrams and examples.

## 1. Thread Lifecycle (with Diagram)

A thread in Java goes through **5 main states**:



### State Descriptions:

- **New:** Thread is created but not yet started.
- **Runnable:** After calling `start()`, thread is ready to run.
- **Running:** Thread is executing its `run()` method.
- **Blocked/Waiting:** Waiting for resource or another thread (e.g., file I/O or `join()`).
- **Terminated:** Thread has finished execution or was stopped.

## 2. Thread Priority and Scheduling

Java assigns **priorities** to threads (1 to 10):

Priority Constant	Value
<code>Thread.MIN_PRIORITY</code>	1
<code>Thread.NORM_PRIORITY</code>	5
<code>Thread.MAX_PRIORITY</code>	10

Higher priority threads **might** get more CPU time, but **not guaranteed**.

JVM uses **Thread Scheduler**, which depends on the OS.

### Example:

```
java

Thread t1 = new Thread(() -> System.out.println("Thread 1"));
Thread t2 = new Thread(() -> System.out.println("Thread 2"));

t1.setPriority(Thread.MAX_PRIORITY); // 10
t2.setPriority(Thread.MIN_PRIORITY); // 1

t1.start();
t2.start();
```

## 3. Thread Synchronization

When **multiple threads** access **shared resources**, you must **synchronize** them to avoid data inconsistency.

### Example (Without Synchronization - ❌):

```
java

class Counter {
    int count = 0;
    void increment() {
        count++; // not thread-safe
    }
}
```

### With Synchronization:

```
java

class Counter {
    int count = 0;

    synchronized void increment() {
        count++; // thread-safe
    }
}
```

**synchronized** ensures only **one thread** can access the method/block at a time.

## 4. Practical Multithreading Example

```
java

class MyThread extends Thread {
    public void run() {
        for (int i = 1; i <= 5; i++) {
            System.out.println(Thread.currentThread().getName() + " - " + i);
            try { Thread.sleep(500); } catch (Exception e) {}
        }
    }

    public static void main(String[] args) {
        MyThread t1 = new MyThread();
        MyThread t2 = new MyThread();
    }
}
```

```
t1.setName("Worker-1");
t2.setName("Worker-2");

t1.start();
t2.start();
}
```

### Output (May vary):

python-repl

```
Worker-1 - 1
Worker-2 - 1
Worker-1 - 2
Worker-2 - 2
...
```

Would you like me to explain:

- `join()`, `sleep()`, `yield()`
- Deadlocks and how to prevent them
- Using **ExecutorService** instead of threads directly
- Or give you a mini-project using multithreading?

Awesome! Let's continue with these advanced multithreading topics — one by one:

## 1. Thread Methods: join(), sleep(), yield()

### sleep(long ms)

- Pauses the current thread for the given **milliseconds**.
- Doesn't release any lock.

```
java

Thread.sleep(1000); // Sleep for 1 second
```

### join()

- Makes the **current thread wait** until the specified thread completes.

```
java

Thread t1 = new Thread(() -> {
    System.out.println("Thread A running...");
});

t1.start();
t1.join(); // Main thread waits until t1 finishes
System.out.println("Main continues after thread A");
```

### yield()

- Suggests the current thread is **willing to pause**, giving a chance to other threads with same or higher priority.
- It's **just a hint** to the scheduler.

```
java

Thread.yield(); // No guarantee another thread will take over
```

## 2. Deadlocks and How to Avoid Them

 **Deadlock:** When two or more threads are waiting on each other's locks, and none proceeds.

### Example:

```
java

class A {
    synchronized void methodA(B b) {
        System.out.println("Thread 1: Locked A");
        try { Thread.sleep(100); } catch (Exception e) {}
    }
}
```



```

        b.last(); // waiting for lock on B
    }

    synchronized void last() {
        System.out.println("Inside A.last()");
    }
}

class B {
    synchronized void methodB(A a) {
        System.out.println("Thread 2: Locked B");
        try { Thread.sleep(100); } catch (Exception e) {}
        a.last(); // waiting for lock on A
    }

    synchronized void last() {
        System.out.println("Inside B.last()");
    }
}

public class DeadlockExample {
    public static void main(String[] args) {
        A a = new A();
        B b = new B();

        new Thread(() -> a.methodA(b)).start();
        new Thread(() -> b.methodB(a)).start();
    }
}

```

## ✓ Avoid Deadlock:

- Always **acquire locks in a fixed order**
- Use `tryLock()` from `java.util.concurrent.locks.Lock`
- Use **timeouts**

## 3. Using ExecutorService Instead of Raw Threads (Recommended)

Java provides a better thread management system via **Executors** (thread pools).

### Example:

```

java

import java.util.concurrent.*;

public class ExecutorExample {
    public static void main(String[] args) {
        ExecutorService executor = Executors.newFixedThreadPool(2);

        Runnable task1 = () -> System.out.println("Task 1 running");
        Runnable task2 = () -> System.out.println("Task 2 running");

        executor.submit(task1);
        executor.submit(task2);

        executor.shutdown(); // No more tasks will be accepted
    }
}

```

## ✓ Advantages:

- Better performance (reuses threads)
- Easier to scale and manage
- Supports scheduling and delayed execution

## 4. Mini Project: File Download Simulation using Multithreading

### Objective:

Simulate multiple file downloads (each in a separate thread).

### ✓ Code:

```
java

class FileDownload extends Thread {
    private String fileName;

    FileDownload(String fileName) {
        this.fileName = fileName;
    }

    public void run() {
        System.out.println("Downloading: " + fileName);
        try {
            Thread.sleep(2000); // Simulate time to download
        } catch (InterruptedException e) {
            System.out.println("Download interrupted: " + fileName);
        }
        System.out.println("Downloaded: " + fileName);
    }

    public static void main(String[] args) {
        String[] files = {"file1.zip", "file2.zip", "file3.zip"};

        for (String file : files) {
            new FileDownload(file).start(); // Start each download in a new thread
        }
    }
}
```

### Output (Parallel):

```
makefile

Downloading: file1.zip
Downloading: file2.zip
Downloading: file3.zip
Downloaded: file2.zip
Downloaded: file1.zip
Downloaded: file3.zip
```

## ✓ What's Next?

Would you like:

- A real-world **multi-user chat app simulation** with threads?
- Deep dive into **Callable**, **Future**, **ScheduledExecutorService**?
- Thread-safe **collections** (**ConcurrentHashMap**, **CopyOnWriteArrayList**)?
- Interview-level multithreading scenarios and questions?

Let me know what you'd like to learn next!