

Simulating Autoregressive Memory with Square-Root Space:

From Williams’ Time–Space Theorem to Practical KV-Cache Residency

Jun Kawasaki¹

¹com-junkawasaki / etzhayyim / gftdcojp

July 2026

Abstract

Williams (STOC 2025) proved that every multitape Turing machine running in time t can be simulated in space $O(\sqrt{t \log t})$, via Tree Evaluation and the Cook–Mertz algorithm. We transfer the same *block-size optimization* to the dominant sequential memory structure in LLM serving: the key–value (KV) cache of length S . We do *not* claim that Transformers are multitape TMs. Setting checkpoint stride $b \approx \sqrt{S \log S}$ and retaining only boundary checkpoints plus one active block ($\sqrt{S}$ *residency*) reduces measured KV storage by 90–97% for $S \in [1\text{k}, 16\text{k}]$ across real models from 135M (Apple Silicon) to 14B (Modal NVIDIA A100), while host-paged online-softmax attention remains numerically exact. Naive whole-prefix recompute each token *increases* peak device memory. Code and JSON benchmarks: github.com/gftdcojp/cloud-murakumo.

1 Introduction

Autoregressive Transformers store key/value tensors for every past token. For sequence length S , layers L , KV heads H_{kv} , and head dimension d , the cache occupies

$$\text{KVBytes}(S) = 2 L H_{\text{kv}} d S \text{sizeof}(\text{dtype}), \quad (1)$$

i.e. $\Theta(S)$ for fixed model shape. Long-context and multi-tenant serving make this term the primary memory wall after weights.

Williams [3] improved the generic simulation of time by space from Hopcroft–Paul–Valiant’s $O(t/\log t)$ [2] to $O(\sqrt{t \log t})$. The proof reduces a length- t computation to Tree Evaluation of height $h = \Theta(t/b)$ with node values of size $O(b)$, then applies Cook–Mertz [1]. Optimizing $b \sim \sqrt{t \log t}$ yields square-root space.

Question. Does the same block-size optimization yield a measurable reduction in LLM decode memory when applied to KV caches?

Contributions. (1) An honest transfer map from Williams’ parameters (t, b, h) to LLM parameters (S, b, h) . (2) A closed co-scientist tournament over memory policies for product wiring in `cloud-murakumo`. (3) Empirical validation on real models (Mac Metal and Modal CUDA). (4) Negative results: whole-prefix recompute is not a peak-memory win.

2 Background and transfer

Williams (informal). For all $t(n) \geq n$, $\text{TIME}[t] \subseteq \text{SPACE}[\sqrt{t \log t}]$ on multitape Turing machines [3].

What we transfer—and do not. We transfer *parameter balancing + block recompute/paging*, not a complexity-theoretic embedding of attention into multitape TMs.

Theory object	Serving analogue
Time bound t	Sequence length S
Block length b	Checkpoint stride / active block
Tree height $h \sim t/b$	Number of checkpoints
Multitape TM	Not claimed for Transformers

3 Method: $\sqrt{S}$ KV residency

Mirror Williams’ warm-up optimum (log base absorbed in constants):

$$b(S) = \lceil \sqrt{S \ln S} \rceil, \quad h(S) = \lceil S/b(S) \rceil. \quad (2)$$

After a real model prefill producing full K/V of length S , retain only

$$\mathcal{K} = \{0, b, 2b, \dots\} \cup \{S - b, \dots, S - 1\}. \quad (3)$$

Report $\text{nbytes}(\mathcal{K})/\text{nbytes}([0..S])$. Decode may page non-resident blocks from host and combine them with *online softmax* (exact attention without materializing $S \times S$ scores for a single query).

4 Experimental setup

Apple Silicon. SmolLM-135M-Instruct-4bit and Qwen2.5-0.5B-Instruct-4bit via MLX; gemma4-E4B (8B Q4) via Ollama (process-level SIZE).

Modal NVIDIA. Qwen2.5-7B-Instruct (A100-40GB, bf16) and Qwen2.5-14B-Instruct (A100-80GB, bf16) via Hugging Face Transformers `use_cache=True`. Runner: `scripts/modal_sqrt_kv_bench.py`.

Metrics. Full vs resident KV megabytes; bytes per token (bpt); CUDA/Metal peak allocation; $\max |\Delta|$ for block-stream attention.

5 Results

5.1 Mac — SmolLM-135M

$L=30$, $H_{kv}=3$, $d=64$ (bpt=23040). At $S=8192$: full KV 188.7 MB, $\sqrt{S}$ resident 7.0 MB (**96.3%** save). Host-paged block attention at $S=2048$: $\max |\Delta|=7 \cdot 10^{-5}$.

5.2 Mac — Qwen2.5-0.5B

$L=24$, $H_{kv}=2$, $d=64$ (bpt=12288). At $S=16384$: full 201.3 MB $\rightarrow$ 5.4 MB (**97.3%**).

5.3 Modal — Qwen2.5-7B (A100-40GB, bf16)

$L=28$, $H_{kv}=4$, $d=128$ (bpt=57344).

S	full KV	$\sqrt{S}$ res.	save	peak alloc
1024	58.7 MB	5.6 MB	90.5%	15.7 GB
4096	234.9 MB	11.9 MB	94.9%	17.4 GB
8192	469.8 MB	17.3 MB	96.3%	18.9 GB
16384	939.5 MB	25.2 MB	97.3%	21.9 GB

5.4 Modal — Qwen2.5-14B (A100-80GB, bf16)

$L=48$, $H_{kv}=8$, $d=128$ (bpt=196608). At $S=16384$: full KV **3.22 GB** $\rightarrow$ **86.5 MB (97.3%**; ~ 3.1 GB freed per sequence). Save percentages match 7B/Mac to three digits—the ratio is $|\mathcal{K}|/S$, independent of width.

5.5 Negative result

Whole-prefix re-forward each decode step increases peak device memory (Mac and Modal; ratios 1.04–1.7). Williams-style recomputation must be *blocked*, not whole-trace.

5.6 Process-level mask

Ollama gemma4-E4B SIZE stays ~ 3.3 GB from 4k–32k context (weights dominate). KV savings exist but are masked until long context or large multi-batch KV.

6 Discussion

$\sqrt{S}$ residency matters operationally for long context ($S \gtrsim 32$ –128k), high bpt (MHA, many layers, fp16 KV), and multi-tenant packing. PagedAttention manages fragmentation of a still- $\Theta(S)$ cache; FlashAttention tiles for IO without reducing asymptotic stored KV. $\sqrt{S}$ residency reduces *how many token slots are stored on-device*, at the cost of paging bandwidth—the classical Williams tradeoff.

A proof that Transformer decode lies in $\text{SPACE}[\tilde{O}(\sqrt{S})]$ in the multitape sense would require full TM accounting of arithmetic and random-access issues. We explicitly do not claim that theorem.

Product surface: `cloud-murakumo:serve :kv-policy(:sqr-checkpoint / :sqr-plus-page)`.

7 Conclusion

Williams’ square-root space simulation supplies a principled block size for LLM KV residency. On real models from 135M to 14B, retaining only $\tilde{O}(\sqrt{S})$ token slots cuts KV storage by roughly an order of magnitude, while naive full recompute fails as a peak-memory strategy.

Reproducibility

```
# Mac
python scripts/bench_sqr_kv_mac.py \
```

```
--model mlx-community/SmolLM-135M-Instruct-4bit

# Modal
modal run scripts/modal_sqrt_kv_bench.py \
  --model-id Qwen/Qwen2.5-7B-Instruct --gpu A100

Artifacts: docs/benchmarks/sqrt-kv-*.json in gftdcojp/cloud-murakumo.
```

References

- [1] James Cook and Ian Mertz. Tree evaluation is in space $O(\log n \cdot \log \log n)$. In *Proceedings of the 56th Annual ACM Symposium on Theory of Computing (STOC)*, 2024.
- [2] John Hopcroft, Wolfgang Paul, and Leslie Valiant. On time versus space. *Journal of the ACM*, 24(2):332–337, 1977.
- [3] R. Ryan Williams. Simulating time with square-root space. In *Proceedings of the 57th Annual ACM Symposium on Theory of Computing (STOC)*, 2025. Best Paper Award. Also arXiv:2502.17779.