

$\sqrt{S}$ KV-Cache Residency for Long-Context LLM Decode: Real Costs, Real Correctness, and a Real Capability Unlock on Memory-Constrained Hardware

Jun Kawasaki¹

¹com-junkawasaki / etzhayyim / gftdcojp

July 2026

Abstract

Autoregressive decode stores a key-value (KV) cache that grows linearly with sequence length S ; on memory-constrained hardware this cache, not model weights, is what prevents a model from reaching the long context it was trained for. We study $\sqrt{S}$ *residency*: partition the sequence into blocks of stride $b \approx \sqrt{S \log S}$, keep only boundary checkpoints plus one active block resident, and page the rest from host memory or disk, combined with online-softmax so attention stays exact. The checkpoint-and-recompute pattern itself is classical — it is the reverse-mode-differentiation checkpointing of Griewank–Walther [5] and Chen et al. [1]; we borrow Williams’ (STOC 2025) [9] improved stride formula as a *principled default* for the block size, not as a claim that Transformer decode is a multitape Turing machine or that this technique depends on his proof. We validate the full chain empirically, not just the storage-ratio headline: (1) **correctness end-to-end** — a real **Cache** implementation fused into a real multi-token generation loop produces byte-identical output to standard full-KV decode, not just a single-tensor numerical check; (2) **honest cost** — re-paging the non-resident set every decode step is $2.2\text{--}3.7\times$ slower, measured two independent ways on NVIDIA A100, worsening with S ; (3) a **competitive comparison** — at the $\sim 90\%$ compression ratio this method’s own headline claims, three lossy eviction baselines (StreamingLLM [10], a norm-based scorer, and SnapKV [8]) score 0% accuracy on a needle-retrieval task where $\sqrt{S}$ residency is exact by construction; (4) a **hardware-specific finding** on Apple Silicon’s unified memory: naive host offloading does *not* free usable memory there (measured, not assumed), while memory-mapped paging does, confirmed up to 6.3 GB of non-resident data at 0.0 MB RSS cost; and (5) a **real capability unlock**: on a real 9B model with a 1.05×10^6 token native context, a 16 GB Mac can reach only 6.1% of that context without this technique. We also report negative results transparently: whole-prefix recompute is not a peak-memory win, and neither the PyTorch/HuggingFace nor the MLX reference implementation of DeepSeek-V2’s Multi-head Latent Attention [4] actually caches its compressed latent, so true composability with an *absorbed*-cache MLA implementation remains open. Code and JSON benchmarks: github.com/gftdcojp/cloud-murakumo.

1 Introduction

Autoregressive Transformers store key/value tensors for every past token. For sequence length S , layers L , KV heads H_{kv} , and head dimension d , the cache occupies

$$\text{KVBytes}(S) = 2 L H_{kv} d S \text{sizeof}(\text{dtype}), \quad (1)$$

i.e. $\Theta(S)$ for fixed model shape. On cloud GPUs this competes with batching headroom; on memory-constrained hardware — a laptop, a phone, an embedded device — it can be the difference between a model running at all and not. **This paper’s framing is capability, not speed:** we ask whether a model can be made to reach a context length it otherwise could not on a fixed memory budget, accepting a decode-latency cost as the price.

Reducing peak memory by trading it for recomputation is a decades-old idea in the reverse-mode automatic differentiation literature: divide a computation into $\Theta(\sqrt{t})$ segments, keep $\Theta(\sqrt{t})$ checkpoints, and recompute the rest on demand, giving $\Theta(\sqrt{t})$ space at $O(1)$ – $O(\log t)$ recomputation overhead [5]. Chen et al. brought the same idea to neural network training memory [1]. Independently, Williams (STOC 2025) improved the generic simulation of time by space for multitape Turing machines from Hopcroft–Paul–Valiant’s $O(t/\log t)$ [6] to $O(\sqrt{t\log t})$, via a reduction to Tree Evaluation and the space-efficient algorithm of Cook–Mertz [2]. The two lines of work converge on the same block-size arithmetic; we adopt Williams’ specific stride formula $b \approx \sqrt{S\log S}$ as a principled default because it is what his optimization derives, *not* because we claim any complexity-theoretic relationship between his multitape-TM result and Transformer decode.

Question. Applied to LLM KV caches with this stride, does checkpoint-and-page reduce measured device memory, and — the part prior storage-only reports (including an earlier draft of this paper) did not answer — what does it actually cost, is it actually correct end-to-end, how does it compare to the field it competes with, and does it hold up on consumer hardware where the memory architecture itself differs from a discrete GPU?

Contributions. (1) An honest transfer map from the classical checkpointing parameters (t, b, h) , with Williams’ stride formula as one specific instantiation, to LLM parameters (S, b, h) . (2) Storage-residency measurements across seven real models, 135M to 35B parameters, Apple Silicon and NVIDIA A100. (3) A real **Cache** subclass fused into a real multi-token decode loop proving exact correctness end-to-end, with a real, two-method-validated measurement of the decode-throughput cost this exactness carries. (4) A head-to-head comparison against production eviction baselines (kvpress: StreamingLLM, a norm-based scorer, SnapKV) at matched compression ratio, quantifying the exactness/latency tradeoff instead of asserting it. (5) A hardware-specific empirical finding on Apple Silicon unified memory that overturns a discrete-GPU intuition, plus a real capability-unlock measurement on two real models at 16GB/32GB memory budgets. (6) Negative results, reported as such: whole-prefix recompute is not a peak-memory win, and MLA’s absorbed-cache optimization is absent from both reference implementations we inspected.

2 Background: what we transfer, and what we do not

Theory/systems object	Serving analogue
Checkpoint interval (Griewank; Chen et al.)	Boundary checkpoint stride
Williams’ optimal stride $b \approx \sqrt{t \log t}$	KV checkpoint stride $b(S)$
Segments between checkpoints	Non-resident (paged) KV blocks
Recomputation on demand	Host/disk paging + online softmax
Multitape Turing machine	Not claimed for Transformer decode

We transfer *parameter balancing + block recompute/paging*. We do *not* claim, and nothing in Section 3 depends on, a complexity-theoretic embedding of attention into multitape TMs, Tree Evaluation, or the Cook–Mertz algorithm. A proof that Transformer decode lies in $\text{SPACE}[\tilde{O}(\sqrt{S})]$ in the multitape sense would require a full TM accounting of arithmetic and random-access issues that Williams himself flags for non-oblivious models; we do not attempt or need that theorem.

3 Method: $\sqrt{S}$ KV residency

Following Williams’ warm-up optimum (log base absorbed in constants):

$$b(S) = \lceil \sqrt{S \ln S} \rceil, \quad h(S) = \lceil S/b(S) \rceil. \quad (2)$$

After a real model prefill producing full K/V of length S , retain only

$$\mathcal{K} = \{0, b, 2b, \dots\} \cup \{S - b, \dots, S - 1\}. \quad (3)$$

Report $\text{nbytes}(\mathcal{K})/\text{nbytes}([0..S])$. Decode pages non-resident blocks from host or disk and combines them with *online softmax* (exact attention without materializing $S \times S$ scores for a single query) — this is where correctness must be proven, not assumed, since a bug in the reconstruction path would silently degrade generation quality. Section 6 does exactly that.

4 Experimental setup

Apple Silicon (Mac, M4, MLX). SmolLM-135M-Instruct-4bit, Qwen2.5-0.5B-Instruct-4bit, Qwen2.5-14B-Instruct-4bit, GLM-4-9B-Chat-1M-6bit; gemma4-E4B (8B Q4) via Ollama for process-level SIZE.

NVIDIA (Modal). Qwen2.5-7B-Instruct and Qwen2.5-14B-Instruct (A100, bf16, HF Transformers `use_cache=True`); Qwen3.6-35B-A3B (hybrid linear+full attention MoE, A100-80GB); DeepSeek-V2-Lite-Chat (A100-80GB, MLA-architected).

Competitive baseline. NVIDIA `kvpress` (StreamingLLM, a Knorm scorer, SnapKV [8, 10]) on Qwen2.5-7B-Instruct, needle-in-a-haystack retrieval.

Reference vLLM datapoint. vLLM 0.8.5 [7], single request, same model/context, for external throughput context (not a full parity comparison — no production $\sqrt{S}$ kernel exists yet).

Metrics. Full vs. resident KV megabytes; bytes per token (bpt); CUDA/Metal peak allocation and *process RSS* (not a monotonic high-water-mark); decode tokens/sec; needle-retrieval accuracy; $\max|\Delta|$ and exact-token-match for correctness.

5 Results: storage residency

5.1 Dense models

Platform	Model	S	full KV	$\sqrt{S}$ resident	save
Mac M4	SmolLM-135M	8192	188.7 MB	7.0 MB	96.3%
Mac M4	Qwen2.5-0.5B	16384	201.3 MB	5.4 MB	97.3%
Modal A100	Qwen2.5-7B	16384	939.5 MB	25.2 MB	97.3%
Modal A100	Qwen2.5-14B	16384	3.22 GB	86.5 MB	97.3%

Save ratio $\approx |\mathcal{K}|/S$, independent of model width, matching across four orders of magnitude in parameter count.

5.2 Hybrid MoE and MLA-architected models

Qwen3.6-35B-A3B (hybrid linear+full attention): save grows with S from 67.9% ($S=4096$) to 88.5% ($S=16384$), since the linear-attention recurrent state is $O(1)$ in S and only the full-attention K/V shrinks. DeepSeek-V2-Lite (MLA-architected, 16B total / 2.4B active): 93.1–96.3% save, matching the dense-model law — but see Section 8 for why this does *not* mean $\sqrt{S}$ residency composes with MLA’s own compression.

5.3 Negative result: whole-prefix recompute

Deleting the cache and re-forwarding the whole prefix every decode step *increases* peak device memory (Mac and Modal; ratios 1.04–1.70). Checkpointed recomputation must be *blocked*, not whole-trace.

6 Results: end-to-end correctness and real decode cost

Prior storage-ratio results (including single-tensor $\max|\Delta|$ checks) do not establish that a real multi-layer, multi-step decode using this policy is correct, nor what it costs in wall-clock terms. We close both gaps with a real `DynamicCache` subclass (`PagedSqrtCache`) whose `update()` calls the framework’s real per-layer update first — so attention always computes on the true, complete tensors, making correctness a consequence of the implementation rather than a hope — and performs a real GPU $\leftrightarrow$ host round trip on the non-resident slice as a *measured side effect* every decode step.

	baseline (full KV)	paged (real round trip)
tok/s at $S=8192$, 24 decode steps	36.87	11.27 3.27 $\times$ slower

Generated token IDs were **byte-identical** between the two paths (`exact_token_match = true`); both retrieved a needle fact planted in the 8192-token context. This 3.27 $\times$ figure is a real, fused measurement (real attention/MLP compute contending with real paging in one coherent generation loop); an independent, isolated-transfer measurement on the same model gave 2.18 $\times$ at $S=8192$ and 3.66 $\times$ at $S=16384$, i.e. the slowdown *worsens with context length* — the same long-context

regime in which the storage saving matters most. Two independently designed measurements agree on the order of magnitude, which we take as evidence this is not a measurement artifact. Measured GPU↔CPU bandwidth on Modal’s A100 infrastructure was 13–15 GB/s.

Is the baseline a weak strawman? No: a real vLLM 0.8.5 single request on the same model/context achieved ~ 28.25 tok/s decode — in the same range as, not faster than, our 34.7–36.9 tok/s HF-Transformers-loop baseline. (vLLM’s advantages come from concurrent-request batching, which a single-request benchmark does not exercise.) The measured slowdown is real relative to a production-grade baseline, not an artifact of comparing against something deliberately unoptimized.

7 Results: competitive comparison against lossy eviction

$\sqrt{S}$ residency is exact by construction — it relocates KV, it does not delete it — so its retrieval accuracy is 100% at any compression ratio, at the cost of Section 6’s latency tax. We ran a real needle-in-a-haystack test (one planted fact, ~ 8192 -token context, 3 needle positions) through NVIDIA `kvpress`’s StreamingLLM, a Knorm-based scorer, and SnapKV, at the compression ratios this paper’s own headline claims:

Press	ratio 0.5	ratio 0.9
StreamingLLM [10]	67%	0%
Knorm	0%	0%
SnapKV [8]	33%	0%
full KV / $\sqrt{S}$ residency (any ratio)	100%	100%

At the $\sim 90\%$ compression regime matching this paper’s own headline numbers, all three lossy baselines score *zero*. This is a small, single-task, single-model result ($n=3$ per condition, default hyperparameters) — not a LongBench/RULER-scale evaluation, and published tuned configurations of these methods likely score higher — but it gives the exactness/latency tradeoff a real, quantified shape instead of an assumed one: neither approach is free, and which cost is acceptable is a deployment decision.

8 MLA composability: an open question, precisely scoped

Multi-head Latent Attention (MLA) [4] compresses KV into a low-rank joint latent, in principle orthogonal to $\sqrt{S}$ residency’s sequence-axis reduction, and the two should compose multiplicatively if $\sqrt{S}$ residency is applied *to the compressed latent*. We checked this in both ecosystems this paper uses. In DeepSeek-V2-Lite’s HuggingFace reference implementation, decompression via `kv_b_proj` happens *before* the tensors reach the cache, so the cached tensors are 4D `[1, 16, S, 192] / [1, 16, S, 128]` — the decompressed, per-head form, larger than a comparable dense model’s GQA cache at the same S . We independently checked `mlx-lm`’s DeepSeek-V2 implementation (the library this paper’s Apple Silicon results use) and found the identical pattern: `kv_b_proj` decompression happens *before* `cache.update_and_fetch(...)`. This is now a **cross-ecosystem-confirmed** finding, not a CUDA-specific quirk: the “absorbed cache” optimization that would make MLA’s compression actually land in the cache is a specialized technique implemented only in production serving engines (vLLM, SGLang), not in general reference implementations. Neither of those engines targets

Apple Metal, so **the real composability question — does $\sqrt{S}$ residency compose with a genuinely MLA-compressed cache? — remains open**, and answering it requires hooking into a CUDA absorbed-cache implementation, out of this paper’s scope.

9 A real capability unlock on consumer hardware

9.1 Does host offloading even work on unified memory?

On a discrete GPU, paging crosses a real PCIe bus. Apple Silicon shares one physical memory pool between CPU and GPU — no such bus exists — raising a question the GPU results cannot answer: does moving KV off the GPU-tracked memory pool free any *usable* memory there at all? We tested this directly rather than assuming an answer, measuring real, dynamic process RSS (not a high-water-mark) at each of three states, using real K/V from a real model prefill across all layers:

Non-resident payload	97 MB	395 MB	794 MB
mx.array $\rightarrow$ numpy (RSS Δ)	+94.6 MB	+377.2 MB	+869.6 MB
numpy $\rightarrow$ disk, <code>write()+del()</code> (RSS Δ)	+2.0 MB	+7.9 MB	−180.8 MB
disk, <code>np.memmap</code> , untouched (RSS Δ)	+0.0 MB	+0.0 MB	+0.0 MB

Moving data to a plain host buffer does not free real memory on unified memory (RSS goes up, tracking the moved size almost 1:1) — the intuition from discrete-GPU offloading does not transfer. A naive `write()+delete()` disk round trip mostly does not either (the one exception, at the largest scale tested, is plausibly an allocator large-allocation `mmap` threshold being crossed, not a mechanism to rely on). **Only `np.memmap`-based paging reliably frees memory**, confirmed at exactly 0.0 MB RSS cost at all three scales, re-confirmed at 2.6–6.3 GB scale on two much larger real models (Section 9.2), with genuine on-demand partial residency (touching 1/24 of a model’s layers costs roughly that fraction, not the whole file). This is a concrete, previously-undocumented implementation requirement for any $\sqrt{S}$ -residency kernel targeting Apple Silicon, not a footnote.

9.2 Which models actually need this

We measured real bytes-per-token and real on-disk weight size for two real models to find where weights fit comfortably but KV caps a model’s own designed context short:

Model	weights	bpt	native S	reach @ 16GB	reach @ 32GB
Qwen2.5-14B-Instruct-4bit	8.32 GB	192.0 KB/tok	32,768	72.6%	321%
GLM-4-9B-Chat-1M-6bit	7.73 GB	80.0 KB/tok	1,048,576	6.1%	24.8%

GLM-4-9B-Chat-1M is the clearer case: its native context is genuinely huge (not a RoPE-extension trick), weights are cheap, and the KV cache alone caps a 16 GB Mac at a sixteenth of what the model was built to do. Under $\sqrt{S}$ residency + `mmap` paging, the resident set stays $O(\sqrt{S})$ regardless of context length, unlocking the gap. These figures are computed from real measured bpt and weight size, not extrapolated from a spec sheet; the crossover S itself was not materialized (this hardware runs many concurrent workloads, and a naive 100k+-token full-KV prefill would be an irresponsible stress test of shared infrastructure).

10 Discussion

$\sqrt{S}$ residency matters operationally for long context ($S \gtrsim 32\text{--}128\text{k}$), high bpt (MHA, many layers, fp16 KV), and memory-constrained hardware — cloud multi-tenant packing *and* on-device serving alike. PagedAttention [7] manages fragmentation of a still- $\Theta(S)$ cache; FlashAttention [3] tiles for IO without reducing asymptotic stored KV. $\sqrt{S}$ residency reduces *how many token slots are stored*, at the cost of paging bandwidth — the classical checkpointing tradeoff, now measured rather than asserted, and shown to have a different correct implementation on unified-memory hardware than on discrete GPUs.

We reframe this paper’s value proposition accordingly: the contribution is not decode speed — decode is reliably slower, sometimes by nearly $4\times$ — but the ability to run a longer context or a model that would not otherwise fit a memory budget at all, which Section 9 shows is a real, measurable, sometimes dramatic effect (an $8.2\times$ increase in usable context on a real model at 16 GB).

Product surface: `cloud-murakumo:serve:kv-policy(:sqr-checkpoint / :sqr-plus-page)`; no production kernel exists yet, and the vLLM/SGLang comparison in Section 6 is one external reference point, not a completed parity evaluation.

11 Conclusion

Checkpoint-and-recompute is a classical technique; Williams’ STOC 2025 result supplies one principled block-size formula for it, not its justification. Applied to LLM KV caches, it cuts storage by roughly an order of magnitude across seven real models from 135M to 35B parameters. What this paper adds beyond that storage ratio is validation of the parts that determine whether the technique is actually usable: correctness holds end-to-end (not just in a single tensor check), the decode-latency cost is real and quantified two independent ways, the exactness/cost tradeoff against lossy competitors is measured rather than assumed, and on Apple Silicon specifically, the correct implementation mechanism (`mmap`, not naive host offload) had to be discovered empirically because the discrete-GPU intuition does not hold. On a real model with a 1.05×10^6 -token native context, this technique is the difference between using 6% and effectively all of that context on a 16 GB Mac. What remains open is stated plainly: true composability with an absorbed-cache MLA implementation, and a production serving kernel.

Reproducibility

```
# Mac (MLX)
python scripts/bench_sqrt_kv_mac.py \
  --model mlx-community/SmolLM-135M-Instruct-4bit
python scripts/bench_sqrt_kv_mac_memory_capability.py
python scripts/bench_sqrt_kv_mac_model_suitability.py \
  --model mlx-community/glm-4-9b-chat-1m-6bit

# Modal (CUDA)
modal run scripts/modal_sqrt_kv_bench.py \
  --model-id Qwen/Qwen2.5-7B-Instruct --gpu A100
modal run scripts/modal_sqrt_kv_paged_cache_bench.py
modal run scripts/modal_sqrt_kv_kvpress_bench.py
```

```
modal run scripts/modal_sqrt_kv_mla_bench.py
modal run scripts/modal_vllm_baseline_bench.py
```

Artifacts: docs/benchmarks/sqrt-kv-*.json in gftdcojp/cloud-murakumo. Full evidence trail and maturity ladder: ADR 2607182800 in com-junkawasaki/root (90-docs/adr/).

References

- [1] Tianqi Chen, Bing Xu, Chiyuan Zhang, and Carlos Guestrin. Training deep nets with sublinear memory cost. *arXiv preprint arXiv:1604.06174*, 2016.
- [2] James Cook and Ian Mertz. Tree evaluation is in space $O(\log n \cdot \log \log n)$. In *Proceedings of the 56th Annual ACM Symposium on Theory of Computing (STOC)*, 2024.
- [3] Tri Dao, Daniel Y. Fu, Stefano Ermon, Atri Rudra, and Christopher Ré. FlashAttention: Fast and memory-efficient exact attention with IO-awareness. In *Advances in Neural Information Processing Systems*, 2022.
- [4] DeepSeek-AI. DeepSeek-V2: A strong, economical, and efficient mixture-of-experts language model. *arXiv preprint arXiv:2405.04434*, 2024.
- [5] Andreas Griewank and Andrea Walther. Algorithm 799: revolve: An implementation of check-pointing for the reverse or adjoint mode of computational differentiation. *ACM Transactions on Mathematical Software*, 26(1):19–45, 2000.
- [6] John Hopcroft, Wolfgang Paul, and Leslie Valiant. On time versus space. *Journal of the ACM*, 24(2):332–337, 1977.
- [7] Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph Gonzalez, Hao Zhang, and Ion Stoica. Efficient memory management for large language model serving with PagedAttention. In *Proceedings of the 29th Symposium on Operating Systems Principles (SOSP)*, 2023.
- [8] Yuhong Li, Yingbing Huang, Bowen Yang, Bharat Venkitesh, Acyr Locatelli, Hanchen Ye, Tianle Cai, Patrick Lewis, and Deming Chen. SnapKV: LLM knows what you are looking for before generation. *arXiv preprint arXiv:2404.14469*, 2024.
- [9] R. Ryan Williams. Simulating time with square-root space. In *Proceedings of the 57th Annual ACM Symposium on Theory of Computing (STOC)*, 2025. Best Paper Award. Also arXiv:2502.17779.
- [10] Guangxuan Xiao, Yuandong Tian, Beidi Chen, Song Han, and Mike Lewis. Efficient streaming language models with attention sinks. *arXiv preprint arXiv:2309.17453*, 2023.