
Sharper Boundaries: Position-Aware CRF Emissions and an Embedding Adapter for Predicting Proteolytic Peptides and Propeptides

Anonymous Author(s)

Affiliation

Address

email

Abstract

1 Proteolysis cuts precursor proteins into mature peptides and propeptides, and pre-
2 dicting where is a sequence segmentation task with direct applications in pro-
3 teomics, vaccine design, and disease research. The strongest existing approach
4 couples frozen protein language model (pLM) embeddings with a CNN-BiLSTM
5 encoder and an extended-state linear-chain conditional random field (CRF) de-
6 coder, but its CRF emissions are identical for every state of a given segment type
7 at a given position, even though the decoder’s own state structure already distin-
8 guishes a segment’s start, interior, and end. We close this gap with two small, inde-
9 pendent additions: a zero-initialized boundary head that adds position-specific cor-
10 rections to the relevant CRF emissions, and a lightweight adapter that re-projects
11 the pLM embedding before the encoder. Evaluated with the same 5×4 nested
12 cross-validation DeepPeptide itself uses, on a rebuilt UniProtKB/Swiss-Prot 2026
13 dataset, both additions outperform the base architecture on ESM-2 embeddings
14 individually ($+0.021$ and $+0.026$ F1) and combine to a $+0.054$ F1 gain over the
15 0.576 ± 0.029 base, close to the sum of the two. On higher-capacity ESM-C
16 6B embeddings the same protocol does not separate the base architecture from its
17 ESM-2 counterpart (0.588 ± 0.016), yet the boundary head is worth two and a half
18 times as much there and the two additions together reach 0.666 ± 0.018 : capacity
19 the base decoder cannot use is capacity the additions can.

20 1 Introduction

21 Proteomic databases record intact sequences, not what proteases leave behind, so the products of
22 cleavage have to be predicted. A multi-epitope vaccine construct can then be checked at the design
23 stage for the fragments it will yield in vivo, and since proteolysis is itself disrupted in neurodegener-
24 ative, oncological and endocrine disease, expected and observed cleavage patterns can be compared
25 between healthy and diseased tissue.

26 The benchmark for this task rewards detection, not localization. A predicted segment counts as cor-
27 rect if both of its endpoints fall within ± 3 residues of a ground-truth segment of the same type, and a
28 single F1 score at this tolerance is reported (Figure 1). Segments are only 5–50 residues long, so on a
29 short peptide this tolerance is comparable to the length of the segment itself. A model can therefore
30 raise its F1 simply by finding more segments while its boundaries stay imprecise, and conversely it
31 can place boundaries much more precisely and gain almost nothing, because predictions that close
32 already counted as correct. The second case is our concern: the metric cannot see the improvement
33 we are after.

34 We therefore make boundary localization the target of both the model and the evaluation. Our base-
35 line is DeepPeptide [Teufel et al., 2023b], the strongest general-purpose model for this formulation.




Figure 1: The problem, the two blocks and what they buy. (a) One held-out precursor, with the ± 3 acceptance window shaded around each annotated cleavage site. Both of the baseline’s cuts fall inside the window, so they count as found at the headline tolerance and not at an exact match, while ours, carrying both additions, lands on the annotated residue. (b) Where the boundary head and the adapter attach to the base pipeline. (c) The F1 gap to the ESM-2 base at each tolerance, the base itself drawn flat at zero as the reference every other line is measured against. A curve is flat only if it is a parallel translation of the baseline, and none of the six carrying an addition is. Corrected matcher throughout, means over the five outer folds.

It has three parts: a frozen protein language model, a CNN-BiLSTM encoder, and a linear-chain CRF. The CRF has separate states for the start, the interior, and the end of a segment, so any valid path must visit them in that order. The decoder is therefore boundary-aware by design. The encoder, however, gives it nothing to work with: every state of the same segment type receives the same emission score. Closing that gap is the natural way to sharpen boundaries rather than merely find more segments. We close it with two small, independent additions and evaluate them under 5×4 nested cross-validation on the DeepPeptide dataset rebuilt from the 2026 UniProtKB/Swiss-Prot release (Sections 4.1 and 5).

Our contributions are the two blocks, the decomposition of what each buys under nested cross-validation, and a quantified account of why this benchmark resists a cleaner protocol: homology-aware folds are not exchangeable, their spread exceeds either addition measured on its own, and averaging it away costs roughly 200 GPU-hours per configuration.

2 Related work

Most predictors of proteolytic cleavage are specific by construction. One line covers a fixed set of proteases with known recognition motifs, one enzyme or family at a time [Duckert et al., 2004, Song et al., 2012, Li et al., 2023, 2020a,b], a second scores cleavage near basic residues for one product class, usually neuropeptides [Southey et al., 2006, Wang et al., 2024], and neither answers what an organism’s full complement of proteases does to a precursor. General-purpose models train a compact head on frozen pLM embeddings [Lin et al., 2023, ESM Team, 2024] but mostly score peptides already excised [Du et al., 2024, Zhu et al., 2025] rather than locating them, and PeptideLocator [Mooney et al., 2013] returns a per-residue heatmap rather than a segmentation. DeepPeptide [Teufel et al., 2023b] is, to our knowledge, the only model that segments a precursor into typed peptide and propeptide spans, and it established the homology-partitioned benchmark used here [Teufel et al., 2023a], so we take both its architecture and its data pipeline as our starting point (Appendix G).

61 3 Method

62 **The base architecture.** DeepPeptide passes a frozen ESM-2 embedding through a CNN-BiLSTM
63 stack and decodes it with a linear-chain CRF [Lafferty et al., 2001] that expands each of
64 $\{\text{Peptide}, \text{Propeptide}\}$ into a chain of up to 50 position states, 101 in all, so a legal path can only
65 realize a contiguous segment of admissible length. The encoder computes one emission per label
66 and shares it across all 50 states of that label: the decoder is boundary-aware, the features feeding
67 it are not. The two additions close that gap from opposite ends of the pipeline (Figure 1b, drawn at
68 reading size in Figure 2). Other embedding sources and architectural modifications were screened
69 as well, with verdicts in Appendix F.

70 **Boundary head.** A small feed-forward block (LayerNorm, Linear, GELU, Linear, hidden size 64)
71 is applied to the contextual per-residue features. For each position and each segment type it emits
72 three numbers, scoring how much that position looks like a segment start, an interior position, or a
73 segment end, and these are added to the emissions of the corresponding position-fixed CRF states.
74 The final linear layer is initialized to zero, so training begins at exactly the base model and the head
75 only learns corrections that lower the loss. It costs 4,678 parameters on a trainable stack of 224,710.

76 **Adapter.** The second addition leaves the decoder alone and acts on the input. Before the per-
77 residue embedding reaches the CNN-BiLSTM it passes through LayerNorm, dropout, Linear,
78 GELU, dropout and a second LayerNorm, which reduces its width from 1280 to 256 for ESM-2.
79 A pLM embedding is trained on masked-residue recovery rather than cleavage-site localization, and
80 its feature distribution suits neither this task nor the small head that consumes it, so a trainable re-
81 projection in front of a frozen encoder is the standard remedy. It is the more expensive of the two, a
82 net +232,704 parameters.

83 4 Data and evaluation

84 4.1 Dataset

85 A precursor $x = (a_1, \dots, a_L)$ is labelled per residue with $y_t \in \{\text{None}, \text{Peptide}, \text{Propeptide}\}$
86 and contiguous runs of a label form typed segments, so the task is to recover which stretches of a
87 precursor become mature peptides and which become propeptides that are excised and discarded.
88 DeepPeptide built its dataset from PEPTIDE and PROPEP annotations in the 2022 Swiss-Prot release.
89 We rebuilt it with the same pipeline on the 2026 release [UniProt Consortium, 2025]. The collection
90 grows from 8,449 proteins to 9,619 (Figure 3), of which 8,897 both carry ESM-2 embeddings and
91 enter the five folds used here. Folds come from GraphPart [Teufel et al., 2023a] at a 30% pairwise-
92 identity ceiling, balanced by cleavage-motif class. Segment-length filtering, motif balancing and the
93 full composition of the rebuild are given in Appendix E.

94 4.2 Evaluation criterion

95 Peptides and propeptides are matched separately. A prediction is a true positive when its start and its
96 end both fall within $\pm\tau$ residues of a true segment of the same type. Unmatched predictions are false
97 positives and unmatched true segments false negatives. Following the original evaluation we keep
98 $\tau = 3$ as the headline setting, since annotated sites carry a few residues of experimental uncertainty.
99 Sweeping τ down to zero then asks a second question, not whether a peptide was found but how
100 precisely its ends were placed. The reference implementation of this criterion carries an upstream
101 variable-shadowing bug that marks the wrong true segment as matched, so everything reported here
102 is re-scored with a corrected matcher (Appendix C).

103 **Agreement with the published baseline.** DeepPeptide reports precision 0.68 and recall 0.49 at
104 ± 3 , both segment types together, averaged over the twenty models of its nested cross-validation on
105 the 2022 data, which implies an F1 of 0.570. Running the base architecture on that release under the
106 same protocol scores 0.574 ± 0.069 with the original matcher and 0.590 ± 0.064 with the corrected
107 one of Appendix C. The F1 reproduces, the operating point does not: our original-matcher precision
108 is 0.614 and recall 0.541. The published system tunes its hyperparameters per outer fold, while
109 we hold one configuration fixed across all 20 cells so that every row of Table 1 is measured under

Table 1: 5×4 nested cross-validation with the corrected matcher. Each cell is the mean over the five outer folds, with the standard deviation across them as a subscript. Precision and recall are at the headline ± 3 tolerance, and the four F1 columns tighten it to an exact residue. *Growth* is how much a row’s F1 advantage over the ESM-2 base widens between ± 3 and an exact match.

Additions	at ± 3		F1 by tolerance				growth
	P	R	± 3	± 2	± 1	exact	
<i>ESM-2</i>							
none	0.621 $\pm$.025	0.539 $\pm$.045	0.576 $\pm$.029	0.544 $\pm$.027	0.467 $\pm$.020	0.354 $\pm$.010	—
boundary head	0.673 $\pm$.029	0.538 $\pm$.036	0.597 $\pm$.026	0.566 $\pm$.024	0.488 $\pm$.015	0.384 $\pm$.015	+0.010 $\pm$.011
adapter	0.628 $\pm$.019	0.579 $\pm$.040	0.602 $\pm$.026	0.572 $\pm$.024	0.491 $\pm$.011	0.396 $\pm$.020	+0.016 $\pm$.009
both	0.667 $\pm$.032	0.598 $\pm$.026	0.630 $\pm$.021	0.599 $\pm$.023	0.518 $\pm$.016	0.432 $\pm$.013	+0.023 $\pm$.019
<i>ESM-C 6B</i>							
none	0.620 $\pm$.017	0.560 $\pm$.027	0.588 $\pm$.016	0.558 $\pm$.013	0.483 $\pm$.007	0.371 $\pm$.013	+0.005 $\pm$.016
boundary head	0.731 $\pm$.010	0.572 $\pm$.030	0.641 $\pm$.022	0.608 $\pm$.026	0.532 $\pm$.035	0.429 $\pm$.030	+0.010 $\pm$.017
adapter	0.598 $\pm$.012	0.607 $\pm$.031	0.602 $\pm$.017	0.573 $\pm$.019	0.497 $\pm$.016	0.394 $\pm$.031	+0.014 $\pm$.023
both	0.690 $\pm$.013	0.646 $\pm$.033	0.666 $\pm$.018	0.636 $\pm$.015	0.554 $\pm$.016	0.466 $\pm$.021	+0.021 $\pm$.023

the same setting (Appendix D). Under the corrected matcher throughout, the 2026 rebuild gives 0.576 ± 0.029 against that 0.590 ± 0.064 , so it reads 0.014 lower by a margin smaller than either run’s spread across folds.

5 Results

We ran the experiments in two stages.

Screening. We first split the data into seven GraphPart folds with fixed roles: four for training, one for epoch selection, and two held out, one for comparing architectures and one intended as a sealed test, which the screening numbers pool. Against that split we screened roughly a dozen modifications, with the protocol, the verdict table and the per-candidate figures in Appendix F, among them the segment-type trade-offs of Figure 5 and the data-scaling curves of Figure 6.

The folds of that split are not interchangeable (Figure 4), and under one assignment of roles several modifications changed the *sign* of their measured effect between the two held-out folds. A single draw of this kind cannot resolve an effect of 0.02–0.03, so none of those numbers is reported as a finding. It can, however, separate the consistently unhelpful from the worth paying for, and two cleared that bar: the boundary head and the adapter sat at or above the base throughout.

Confirmation. We then re-evaluated the two survivors with the 5×4 nested cross-validation DeepPeptide itself uses, on ESM-2 and on ESM-C 6B, so that the embedding is a factor of the design and not a third candidate. For each of five outer folds we train four models on three of the remaining folds and validate on the fourth, then test on the outer fold, which they never saw. An outer fold’s score is the mean over its four models, the estimate is the mean over the five outer folds, and the reported spread is the standard deviation across outer folds rather than across all 20 cells, since four models sharing an outer fold share a test set. Because selection happened at the screening stage, what follows is a test of two pre-specified hypotheses.

Table 1 reports the same 2×2 factorial on both embeddings under that protocol, with the corrected matcher.¹

The two additions act on different errors. On ESM-2 each improves F1 by a similar amount alone and together they give 0.054, against 0.079 on ESM-C, close to the sum of the parts in both cases. Splitting the ESM-2 rows into precision and recall shows the two are not competing for the same errors. The head is almost purely a precision effect, +0.052 against -0.001 of recall, the adapter mostly a recall effect, +0.040 against +0.007, and applied together they recover both, +0.046 and +0.059.

¹Implementation, the configuration behind every row, the per-cell scores every table is aggregated from and a script that rebuilds them: <https://anonymous.4open.science/r/cleavage-site-segmentation-5851>

141 **Tightening the tolerance.** Sweeping τ from ± 3 to an exact match, absolute F1 falls steeply for
142 every model, the strongest configuration from 0.666 to 0.466.

143 A model that is better overall retains a different fraction of its ± 3 score even when no boundary is
144 placed better, so we compare absolute gaps rather than ratios. Every gap an addition opens widens
145 as the tolerance tightens (the *growth* column of Table 1), and for each of those six the largest step
146 is the last, from ± 1 to exact. Only the embedding swap on its own does not grow. What separates
147 these models is whether they hit the exact residue.

148 A widening gap is not proof of better localization, since a model that finds more segments gains
149 ground at every tolerance. To hold detection fixed we compared each variant against the base on the
150 true segments that *both* localize within ± 3 , cell by cell. On that set the share of boundaries placed
151 on the exact residue rises from 0.630 to 0.652 for the boundary head, from 0.619 to 0.668 for the
152 adapter and from 0.621 to 0.698 for the two together, each positive on all five outer folds. A gate
153 is itself a choice, so Appendix B asks the same question with no window at all, and there the two
154 blocks part company. When a hit needs only a single residue of overlap the head covers less than
155 the base, recall -0.035 on one fold of five, while gaining precision, and the adapter covers more,
156 $+0.024$ on four of five, while losing it. Their F1 there barely moves, -0.013 and $+0.006$, because the
157 components cancel. The head’s gain is placement alone, the adapter buys placement and coverage
158 together, and a ± 3 window records the mixture as recall. Scored at individual cleavage sites the
159 head’s gain lies entirely on the C-terminal side.

160 **Capacity the base decoder cannot use.** The base architecture on ESM-C 6B reaches $0.588 \pm$
161 0.016 against 0.576 ± 0.029 on ESM-2, a paired difference of $+0.012 \pm 0.019$ over the five outer
162 folds, so an embedding twice as wide buys no confirmed improvement on its own while either
163 addition on the narrower one does. What they are worth there depends on which one. Paired by outer
164 fold against its own base, the head gains $+0.054 \pm 0.026$ on ESM-C 6B against $+0.021 \pm 0.007$ on
165 ESM-2, the adapter $+0.014 \pm 0.014$ against $+0.026 \pm 0.018$, and the two together $+0.079 \pm 0.009$
166 against $+0.054 \pm 0.016$, all six positive on five folds of five, though the ESM-C adapter’s spread
167 reaches zero. The adapter re-projects an embedding trained for masked-residue recovery, and the
168 less mismatched it is the less there is to re-project, whereas the head supplies position-specific
169 evidence and a richer embedding carries more of it. Read the other way, the swap is worth $+0.012$
170 F1 under the base architecture and $+0.036$ under both additions, a split Appendix B reproduces on
171 the protein-cells common to all runs.

172 6 Conclusion

173 A zero-initialized boundary head at the decoder and a lightweight adapter at the input improve
174 segment F1 by $+0.054$ together on ESM-2 and by $+0.079$ on ESM-C 6B. They combine because
175 they act on different errors, the head suppressing spurious segments and the adapter finding true ones
176 the base misses as well as placing them better, and both place boundaries more precisely, so their
177 advantage widens as the tolerance tightens. The evaluation carries a second message: homology-
178 aware partitioning leaves the folds taxonomically non-exchangeable, and their spread exceeds either
179 addition measured on its own.

180 **The folds stay unequal.** Averaging over folds does not make them comparable, it only stops one
181 of them deciding the result. GraphPart keeps homologs together, and taxa *are* homology clusters:
182 313 of 714 *Conus* sequences fall in fold 1 against 16 in fold 2, all 293 *Cyriopagopus* avoid fold 0
183 entirely, and the folds differ in size by a factor of two (Table 4). The base architecture scores 0.572,
184 0.599, 0.530, 0.576 and 0.604 on outer folds 0 to 4, a range of 0.074, three and a half times the
185 $+0.021$ effect the same experiment resolves once averaged over them.

186 **What the protocol does not settle.** Nothing was selected on outer-fold scores inside confirmation,
187 since every cell of the 2×2 is reported, but the screening that chose the candidates ran on the same
188 proteins the folds are drawn from, and sealing that would take a third held-out level. One cell costs
189 about 10 GPU-hours and the full grid roughly 1,600, so a third level multiplies that while cutting the
190 training fraction from $3/5$ to $2/5$ of an already small dataset. The spread covers fold composition and
191 not seed variation, and the base row is untuned rather than the tuned published system (Appendix D).

References

- José Juan Almagro Armenteros, Marco Salvatore, Olof Emanuelsson, Ole Winther, Gunnar von Heijne, Arne Elofsson, and Henrik Nielsen. Detecting sequence signals in targeting peptides using deep learning. *Life Science Alliance*, 2(5):e201900429, 2019. doi: 10.26508/lsa.201900429.
- Zhenjiao Du, Xingjian Ding, William Hsu, Arslan Munir, Yixiang Xu, and Yonghui Li. pLM4ACE: a protein language model based predictor for antihypertensive peptide screening. *Food Chemistry*, 431:137162, 2024. doi: 10.1016/j.foodchem.2023.137162.
- Peter Duckert, Søren Brunak, and Nikolaj Blom. Prediction of proprotein convertase cleavage sites. *Protein Engineering, Design and Selection*, 17(1):107–112, 2004. doi: 10.1093/protein/gzh013.
- Ahmed Elnaggar, Hazem Essam, Wafaa Salah-Eldin, Walid Moustafa, Mohamed Elkerdawy, Charlotte Rochereau, and Burkhard Rost. Ankh: Optimized protein language model unlocks general-purpose modelling, 2023. URL <https://arxiv.org/abs/2301.06568>.
- ESM Team. Esm cambrian: Revealing the mysteries of proteins with unsupervised learning. <https://www.evolutionaryscale.ai/blog/esm-cambrian>, December 2024.
- Thomas Hayes, Roshan Rao, Halil Akin, Nicholas J. Sofroniew, Deniz Oktay, Zeming Lin, Robert Verkuil, Vincent Q. Tran, Jonathan Deaton, Marius Wiggert, Rohil Badkundri, Irhum Shafkat, Jun Gong, Alexander Derry, Raul S. Molina, Neil Thomas, Yousuf A. Khan, Chetan Mishra, Carolyn Kim, Liam J. Bartie, Matthew Nemeth, Patrick D. Hsu, Tom Sercu, Salvatore Candido, and Alexander Rives. Simulating 500 million years of evolution with a language model. *Science*, 387(6736):850–858, 2025. doi: 10.1126/science.ads0018.
- Michael Heinzinger, Konstantin Weissenow, Joaquin Gomez Sanchez, Adrian Henkel, Milot Mirdita, Martin Steinegger, and Burkhard Rost. ProstT5: bilingual language model for protein sequence and structure. *NAR Genomics and Bioinformatics*, 6(4):lqae150, 2024. doi: 10.1093/nargab/lqae150.
- John D. Lafferty, Andrew McCallum, and Fernando C. N. Pereira. Conditional random fields: Probabilistic models for segmenting and labeling sequence data. In *Proceedings of the Eighteenth International Conference on Machine Learning (ICML)*, pages 282–289, 2001.
- Fuyi Li, Jinxiang Chen, André Leier, Tatiana Marquez-Lago, Quanzhong Liu, Yanze Wang, Jerico Revote, A. Ian Smith, Tatsuya Akutsu, Geoffrey I. Webb, Lukasz Kurgan, and Jiangning Song. DeepCleave: a deep learning predictor for caspase and matrix metalloprotease substrates and cleavage sites. *Bioinformatics*, 36(4):1057–1065, 2020a. doi: 10.1093/bioinformatics/btz721.
- Fuyi Li, André Leier, Quanzhong Liu, Yanan Wang, Dongxu Xiang, Tatsuya Akutsu, Geoffrey I. Webb, A. Ian Smith, Tatiana Marquez-Lago, Jian Li, and Jiangning Song. Procleave: predicting protease-specific substrate cleavage sites by combining sequence and structural information. *Genomics, Proteomics & Bioinformatics*, 18(1):52–64, 2020b. doi: 10.1016/j.gpb.2019.08.002.
- Fuyi Li, Cong Wang, Xudong Guo, Tatsuya Akutsu, Geoffrey I. Webb, Lachlan J. M. Coin, Lukasz Kurgan, and Jiangning Song. ProsperousPlus: a one-stop and comprehensive platform for accurate protease-specific substrate cleavage prediction and machine-learning model construction. *Briefings in Bioinformatics*, 24(6):bbad372, 2023. doi: 10.1093/bib/bbad372.
- Zeming Lin, Halil Akin, Roshan Rao, Brian Hie, Zhongkai Zhu, Wenting Lu, Nikita Smetanin, Robert Verkuil, Ori Kabeli, Yaniv Shmueli, Allan dos Santos Costa, Maryam Fazel-Zarandi, Tom Sercu, Salvatore Candido, and Alexander Rives. Evolutionary-scale prediction of atomic-level protein structure with a language model. *Science*, 379(6637):1123–1130, 2023. doi: 10.1126/science.ade2574.
- Catherine Mooney, Niall J. Haslam, Gianluca Pollastri, and Denis C. Shields. Towards the improved discovery and design of functional peptides: common features of diverse classes permit generalized prediction of bioactivity. *PLoS ONE*, 7(10):e45012, 2012. doi: 10.1371/journal.pone.0045012.

240 Catherine Mooney, Niall J. Haslam, Thérèse A. Holton, Gianluca Pollastri, and Denis C. Shields.
 241 PeptideLocator: prediction of bioactive peptides in protein sequences. *Bioinformatics*, 29(9):
 242 1120–1126, 2013. doi: 10.1093/bioinformatics/btt103.

243 Alexander Rives, Joshua Meier, Tom Sercu, Siddharth Goyal, Zeming Lin, Jason Liu, Demi Guo,
 244 Myle Ott, C. Lawrence Zitnick, Jerry Ma, and Rob Fergus. Biological structure and function
 245 emerge from scaling unsupervised learning to 250 million protein sequences. *Proceedings of the*
 246 *National Academy of Sciences*, 118(15):e2016239118, 2021.

247 Jiangning Song, Hao Tan, Andrew J. Perry, Tatsuya Akutsu, Geoffrey I. Webb, James C. Whisstock,
 248 and Robert N. Pike. PROSPER: an integrated feature-based tool for predicting protease substrate
 249 cleavage sites. *PLoS ONE*, 7(11):e50300, 2012. doi: 10.1371/journal.pone.0050300.

250 Jiangning Song, Fuyi Li, André Leier, Tatiana T. Marquez-Lago, Tatsuya Akutsu, Gholamreza Haf-
 251 fari, Kuo-Chen Chou, Geoffrey I. Webb, and Robert N. Pike. PROSPERous: high-throughput
 252 prediction of substrate cleavage sites for 90 proteases with improved accuracy. *Bioinformatics*,
 253 34(4):684–687, 2018. doi: 10.1093/bioinformatics/btx670.

254 Bruce R. Southey, Andinet Amare, Tyler A. Zimmerman, Sandra L. Rodriguez-Zas, and Jonathan V.
 255 Sweedler. NeuroPred: a tool to predict cleavage sites in neuropeptide precursors and provide the
 256 masses of the resulting peptides. *Nucleic Acids Research*, 34(Web Server issue):W267–W272,
 257 2006. doi: 10.1093/nar/gkl161.

258 Felix Teufel, José Juan Almagro Armenteros, Alexander Rosenberg Johansen, Magnús Halldór Gís-
 259 lason, Silas Irby Pihl, Konstantinos D. Tsirigos, Ole Winther, Søren Brunak, Gunnar von Heijne,
 260 and Henrik Nielsen. SignalP 6.0 predicts all five types of signal peptides using protein language
 261 models. *Nature Biotechnology*, 40(7):1023–1025, 2022. doi: 10.1038/s41587-021-01156-3.

262 Felix Teufel, Magnús Halldór Gíslason, José Juan Almagro Armenteros, Alexander Rosenberg Jo-
 263 hansen, Ole Winther, and Henrik Nielsen. GraphPart: homology partitioning for biological se-
 264 quence analysis. *NAR Genomics and Bioinformatics*, 5(4):lqad088, 2023a. doi: 10.1093/nargab/
 265 lqad088.

266 Felix Teufel, Jan Christian Refsgaard, Christian Toft Madsen, Carsten Stahlhut, Mads Grønborg, Ole
 267 Winther, and Dennis Madsen. Deeppeptide predicts cleaved peptides in proteins using conditional
 268 random fields. *Bioinformatics*, 39(10):btad616, 10 2023b. ISSN 1367-4811. doi: 10.1093/
 269 bioinformatics/btad616. URL <https://doi.org/10.1093/bioinformatics/btad616>.

270 UniProt Consortium. UniProt: the universal protein knowledgebase in 2025. *Nucleic Acids Re-*
 271 *search*, 53(D1):D609–D617, 2025. doi: 10.1093/nar/gkae1010. URL <https://academic.oup.com/nar/article/53/D1/D609/7902999>.

273 Michel van Kempen, Stephanie S. Kim, Charlotte Tumescheit, Milot Mirdita, Jeongjae Lee,
 274 Cameron L. M. Gilchrist, Johannes Söding, and Martin Steinegger. Fast and accurate pro-
 275 tein structure search with Foldseek. *Nature Biotechnology*, 42:243–246, 2024. doi: 10.1038/
 276 s41587-023-01773-0.

277 Lei Wang, Chen Huang, Mingxia Wang, Zhidong Xue, and Yan Wang. NeuroPred-PLM: an inter-
 278 pretable and robust model for neuropeptide prediction by protein language model. *Briefings in*
 279 *Bioinformatics*, 24(2):bbad077, 2023. doi: 10.1093/bib/bbad077.

280 Lei Wang, Zilu Zeng, Zhidong Xue, and Yan Wang. DeepNeuropePred: a robust and universal tool
 281 to predict cleavage sites from neuropeptide precursors by protein language model. *Computational*
 282 *and Structural Biotechnology Journal*, 23:309–315, 2024. doi: 10.1016/j.csbj.2023.12.004.

283 Ming Zhang, Jianren Zhou, Xiaohua Wang, Xun Wang, and Fang Ge. DeepBP: ensemble deep
 284 learning strategy for bioactive peptide prediction. *BMC Bioinformatics*, 25:352, 2024. doi: 10.
 285 1186/s12859-024-05974-5.

286 Lei Zhu, Hao Sun, and Sen Yang. BPFun: a deep learning framework for bioactive peptide function
 287 prediction using multi-label strategy by transformer-driven and sequence rich intrinsic informa-
 288 tion. *BMC Bioinformatics*, 26(1):187, 2025. doi: 10.1186/s12859-025-06190-5.

289 **Impact Statement**

290 This paper improves a computational tool for predicting proteolytic cleavage products from pro-
291 tein sequence. Potential applications include interpreting proteomics data, informing vaccine and
292 peptide-drug design, and studying disease-associated proteolysis. We are not aware of societal risks
293 specific to this work beyond those generally associated with more accurate protein sequence analysis
294 tools.

295 Appendix

296 A The architecture at reading size




Figure 2: The base architecture and the two additions, at reading size. Figure 1b shows the same diagram at the scale of a single panel, where it locates the two blocks rather than documenting them. Top: the pipeline, with the adapter between the frozen pLM and the CNN-BiLSTM encoder and the boundary head reading the encoder’s output. Bottom: what the head adds. The base model computes one emission per label and shares it across all 50 position states of that label, so the CRF’s start, interior and end states are fed identical evidence. The head emits three numbers per position and per segment type and adds them to the states they describe.

297 B Boundary placement beyond the ± 3 window

298 Section 5 makes two claims that no single tolerance can settle: that the additions place boundaries
 299 better rather than merely finding more segments, and that what they buy survives a criterion with no
 300 acceptance window at all. This appendix reports the evidence for both.

301 **Holding detection fixed.** The comparison in Section 5 is paired. For each cell we take the true
 302 segments that the variant and the base both localize within ± 3 , so both models have found the
 303 segment and only its placement is at stake, and ask how often each puts a boundary on the annotated
 304 residue. A configuration is twenty cells, five outer folds by four inner ones, and the four cells sharing
 305 an outer fold are all tested on it, so each of the 15,348 true segments in the split is scored four times:
 306 61,392 segment-instances in all, of which the base localizes 32,326. Pooled over the twenty cells
 307 the paired set holds 27,013 instances for the boundary head, 29,277 for the adapter and 29,394 for
 308 the two together. These are instances rather than distinct segments, so the paired comparison rests
 309 on about a quarter as many independent segments as the counts suggest.

310 **What each block does to the count.** Those denominators are themselves the result. Of the 32,326
 311 instances the base localizes, the boundary head localizes 320 fewer and the adapter 2,236 more, with
 312 both together 3,289 more. About 1,400 of the adapter’s gain is coverage, its recall at a one-residue
 313 gate being $+0.024$ over the base on these 61,392 instances, and the rest is segments the base already
 314 overlapped but placed outside the window. The head therefore improves placement while covering
 315 marginally less, which is the precision effect of Table 1 seen segment by segment, and the adapter
 316 does the opposite. On the paired set the head moves 13.2% of boundaries closer to the annotated
 317 residue and 11.4% further away, a near-even trade that nets out positive, while the two together move
 318 15.0% closer against 7.5% further.

319 **Dropping the window.** A gate is itself a choice, so we also score the same predictions with no
 320 tolerance. Predicted and true segments of the same type are matched greedily one to one by inter-

section over union, and a match counts as a hit when the overlap clears a threshold τ . Precision and recall use all predicted and all true segments as their denominators, so nothing is conditioned on what either model happened to find. Every configuration is scored on the 35,504 protein-cells common to all runs, which takes the coverage difference between the two embeddings (8,897 against 8,999 proteins) out of the comparison. On that common set the ESM-2 to ESM-C 6B swap is worth +0.005 F1 at IoU ≥ 0.5 under the base architecture, on two outer folds of five, and +0.024 under both additions, on five of five, reproducing the split that Section 5 measures at ± 3 .

Table 2: Segment F1 under overlap matching. The first column requires only that a predicted and a true segment of the same type share one residue, and the rest require an intersection over union of at least τ . Same cells as Table 1, restricted to the protein set common to every run, mean over the five outer folds.

	overlap	$\tau \geq 0.5$	$\tau \geq 0.8$	$\tau \geq 0.9$	$\tau \geq 0.95$
<i>ESM-2</i>					
base	0.729	0.667	0.569	0.487	0.411
+ boundary head	0.715	0.668	0.585	0.515	0.438
+ adapter	0.734	0.686	0.590	0.516	0.441
+ both	0.746	0.703	0.616	0.546	0.474
<i>ESM-C 6B</i>					
base	0.738	0.672	0.574	0.496	0.419
+ boundary head	0.735	0.704	0.624	0.555	0.478
+ adapter	0.729	0.681	0.587	0.514	0.440
+ both	0.759	0.727	0.649	0.582	0.507

Placement, not coverage. The looser the criterion, the less either addition is worth. Paired by outer fold against the ESM-2 base, at a gate that asks only for a single residue of overlap the boundary head is worth -0.013 ± 0.026 and the adapter $+0.006 \pm 0.012$, neither distinguishable from zero. At $\tau \geq 0.5$ they are worth $+0.001 \pm 0.021$ and $+0.019 \pm 0.017$, and at $\tau \geq 0.9$ $+0.028 \pm 0.004$ and $+0.028 \pm 0.015$, both on five folds of five. Underneath that near-zero F1 at the overlap gate the two move in opposite directions: the head issues 219 fewer segments per fold, buying $+0.022$ precision for -0.035 recall, while the adapter issues 130 more and buys $+0.024$ recall for -0.021 precision. Neither finds appreciably more of the annotation than the base architecture does. What changes is where the boundaries land. This is the same conclusion Table 1 reaches through a tolerance, reached without one.

The mean IoU taken over *all* true segments moves the other way for the head, 0.576 to 0.559, while its F1 rises at every threshold. That is the precision effect of Table 1 seen from another angle: the head withdraws weak predictions, so some true segments lose a poor match altogether, and the ones that keep a match are placed better.

Which end moves. Scoring cleavage sites rather than segments, at exact placement and against all annotated sites, separates the two additions again. The boundary head improves the C-side of a segment, $+0.028 \pm 0.006$ on five folds of five, and leaves the N-side alone, -0.007 ± 0.020 on two of five. The adapter improves both, the N-side by $+0.022 \pm 0.006$ and the C-side by $+0.028 \pm 0.009$, and the two together by $+0.042 \pm 0.010$ and $+0.060 \pm 0.006$ respectively. Split by segment type, the head’s C-side gain is largest on propeptides ($+0.037 \pm 0.021$, five of five), whose C-terminal cut is where the mature peptide begins and is the weaker of the two C-sides: the base model scores 0.476 there against 0.525 on peptide C-sides.

C Metric implementation bug

While auditing the DeepPeptide implementation of the matching criterion (Section 4.2), we found a bug in the function that implements it (`get_counts_for_protein`), reproduced below in simplified form:

```

354 for idx, row in true_df.iterrows():           # idx: true-segment index
355     true_start, true_stop = row['start'], row['stop']
356     for idx, row in pred_df.iterrows():       # idx overwritten with pred index
357         pred_start, pred_stop = row['start'], row['stop']

```

```

359.5     ...
360.6     if start_match and stop_match:
361.7         true_df.loc[idx, 'matched'] = True # BUG: idx is now the
362.8         pred_df.loc[idx, 'matched'] = True # predicted index, not the true one
363.9         break

```

365 The outer loop iterates over true segments and the inner loop over predicted segments, but both
 366 reuse the loop variable `idx`. By the time a match is found, `idx` refers to the predicted segment,
 367 so `true_df.loc[idx, 'matched']` marks the wrong true segment. The effect is not large on
 368 average (it is partly self-correcting), but it costs a true positive whenever it fires, so both recall and
 369 precision come out low, and F1 with them. Across the nested-CV grid the correction raises recall
 370 by 0.021 to 0.032 and precision by 0.005 to 0.010. The loss concentrates in proteins where the
 371 model predicts more segments than the protein actually has. This bug is present in the upstream
 372 DeepPeptide code, not something we introduced.

373 We did not silently patch this function in place, since that would shift absolute numbers without
 374 documenting it. Instead we implemented a separate, corrected matcher and used it to re-score the
 375 results in this paper: the earlier single-split runs reported in Appendix F, except two whose model
 376 classes no longer exist in the code and whose checkpoints cannot be rebuilt, and the full 5×4
 377 nested-cross-validation grid in Table 1 (all 160 cells of the eight configurations, and the 20 further
 378 cells of the 2022-release reproduction), by re-running test-partition inference from each cell’s saved
 379 checkpoint on the machine that held them. Every table in the main text uses the corrected matcher,
 380 and both readings of every cell are released alongside the code, with a script that rebuilds the paper’s
 381 tables from them.

382 Re-scoring the grid also recomputed the original matcher on the same decoded segments, so each
 383 cell could be checked against the number already recorded for it. Over the 160 cells for which both
 384 readings exist, the two agree to 1.2×10^{-3} F1 at worst and to 3×10^{-7} at the median, so what
 385 remains is inference nondeterminism rather than disagreement between two deterministic functions
 386 of the same segments.

387 Across configurations the correction shifts mean F1 by +0.015 to +0.022, always upward, since
 388 the bug was discarding true positives. On ESM-2 it leaves the ordering of the four configurations
 389 intact, base < boundary head < adapter < combined, before and after correction. That ordering
 390 is not robust and we build no argument on it: the boundary-head/adaptor gap is 0.005 against a
 391 fold-level standard deviation of 0.026, and per outer fold the full ordering holds in four folds of five
 392 after correction and three of five before it. On ESM-C 6B the ordering differs, base < adapter <
 393 boundary head < combined, the two middle configurations swapping places.

394 **D Relation to the published DeepPeptide system**

395 Our base architecture is DeepPeptide’s architecture, but it is not DeepPeptide’s published model,
 396 and the difference is worth stating because it is the reason Section 4.2 reproduces the published F1
 397 without reproducing the published precision and recall.

398 The released implementation spends the inner loop of its nested cross-validation on a hyperparam-
 399 eter search, and the twenty checkpoints behind the published numbers carry a different winning
 400 configuration for each outer fold: learning rate from 3.3×10^{-4} to 5.5×10^{-3} , dropout from 0.03
 401 to 0.69, convolutional dropout from 0.04 to 0.51, kernel size 3 or 5, 48 to 96 filters, hidden size 32
 402 or 48, and batch size 20 to 90. We hold a single configuration fixed across all twenty cells at the
 403 implementation’s defaults (learning rate 10^{-4} , dropout and convolutional dropout 0.1, kernel size 3,
 404 32 filters, hidden size 64, seed 42), with batch size 48 rather than the default 100, and spend the inner
 405 loop on epoch selection alone. The two added blocks carry settings of their own, chosen once at the
 406 screening stage and then held fixed as well: the adapter projects to 256 channels with a dropout of
 407 0.4, and the boundary head uses a hidden size of 64.

408 Our settings are the implementation’s defaults and they sit outside the range the published search
 409 explored: a learning rate below all five of its ESM-2 winners, fewer convolutional filters than any
 410 of them, and a wider recurrent hidden state than any of them. The base row is therefore a different
 411 model from the published one, not a worse-tuned copy of it, which is what the precision-recall
 412 difference reflects.

413 That choice is deliberate. A factorial is only interpretable if its cells differ in the factor under study
 414 and in nothing else, and per-fold tuning would confound each addition with whatever the search
 415 happened to find for it. Two consequences follow, and they are not symmetric between the two
 416 blocks.

417 The boundary head is protected by its initialization. Its final linear layer starts at zero, so at the
 418 first step the model with the head *is* the base model, and the head’s 4,678 parameters can only
 419 add corrections that lower the loss from there. Whatever setting suits the base is by construction
 420 a legitimate setting for the head, which cannot be handicapped relative to the base it is added to.
 421 The adapter has no such protection. It changes the input width from 1280 to 256 and adds 232,704
 422 parameters, roughly doubling the trainable stack, and a model of that shape may well want a different
 423 learning rate and dropout from the one we hold fixed. Its measured effect, +0.026 on ESM-2 and
 424 +0.014 on ESM-C 6B, should therefore be read as a lower bound.

425 The direction of this bias is the useful part: holding hyperparameters fixed can hide an effect but
 426 cannot manufacture one, so every gain in Table 1 is conservative. What it does not license is the
 427 reading that an untuned base makes the additions look better than they are. On the 2022 release our
 428 untuned base reaches an F1 of 0.574 against the tuned published model’s implied 0.570 (Section 4.2),
 429 so the base we improve on is not a weak one.

430 Two further notes on the reference implementation. Its recall guard tests the wrong denominator,
 431 returning zero when no segment is predicted but dividing by the true-segment count that the guard
 432 never checked. On this data the branch is unreachable, so the value is latent rather than wrong.
 433 And its evaluation script builds the ground truth with overlapping annotations kept separate while
 434 its training dataset merges them, a discrepancy we did not attempt to reconcile because our scoring
 435 rebuilds the ground truth from the labelled sequences directly.

436 E Dataset details

Table 3: Dataset composition: the 2022 release used by the original DeepPeptide against the 2026 release rebuilt here. Counts are before homology partitioning, which leaves 7,623 proteins of the 2022 release and 8,994 of the 2026 one, of which 8,897 also carry an ESM-2 embedding and form the five folds used here.

	2022	2026
Proteins	8449	9619
Peptide segments	6372	7431
Propeptide segments	8211	9140
Median peptide length (residues)	21	20

437 Two filters from the original pipeline are kept unchanged. Segments shorter than 5 or longer than
 438 50 residues are dropped: the CRF’s state count fixes the upper bound, and a segment shorter than
 439 five residues is barely scoreable at a ± 3 tolerance. Folds are then balanced by cleavage-motif class,
 440 obtained by k -means ($k = 50$) on ESM-2 embeddings of the four residues flanking each annotated
 441 boundary, on top of the 30% pairwise-identity ceiling GraphPart enforces between folds.

Table 4: Proteins per outer fold, and how three frequent genera distribute across them. *Cyriopagopus* and *Lycosa* are spider venoms, *Conus* a cone snail, and each is a homology cluster that GraphPart is obliged to keep intact. *Homo*, by contrast, is spread evenly (71/81/66/130/84).

	total	f0	f1	f2	f3	f4
All proteins	8897	1558	2572	1263	2025	1479
<i>Conus</i>	714	160	313	16	149	76
<i>Cyriopagopus</i>	293	0	62	45	9	177
<i>Lycosa</i>	163	5	42	10	106	0




Figure 3: Composition of the rebuilt 2026 dataset: segment length, type, and genus distributions.

F Screening protocol and verdicts

F.1 Protocol

Data was split into seven GraphPart folds (30% identity threshold, motif-balanced as in Section 4.1), with folds assigned fixed roles: four folds for training, one for validation (epoch selection), one for model selection (comparing architectures), and one originally intended as a fully sealed test fold. This separated architecture selection from evaluation, but the evaluation itself was still a single draw: one random assignment of roles, one pair of held-out folds. Several modifications changed the sign of their measured effect between the two held-out folds. Replacing ESM-2 with ESM-C 6B measured $+0.074$ on one and -0.011 on the other, ESM-C 6B against ESM-C 600M gave $+0.028$ and -0.021 , and the net effect of the 3Di channel gave $+0.015$ and -0.018 . Effects that kept their sign still moved by a lot: the isolated sequence adapter measured -0.001 on one fold and $+0.045$ on the other. Figure 4 shows one reason, namely that the folds differ substantially in segment-length composition. The two held-out folds turn out to be complementary in segment-length composition, fold 2 concentrated at 10–24 residues and fold 5 bimodal, so results below pool them (model-select $\cup$ sealed, $\approx 2,300$ proteins) to reduce (but not eliminate) this instability. This pooling is why the “sealed” fold is not, in practice, a held-out test set independent of model selection.

F.2 Summary of tested modifications

Table 5 summarizes the modifications tested under screening protocol, with the corrected matcher (Appendix C) applied throughout. Two of these rows were carried forward as candidates, the boundary head and the adapter (Section 3), and both were confirmed. The embedding swap was not a candidate but became a factor of the confirmation design, and it is the row this table reads least well: nested cross-validation puts ESM-C 6B at 0.588 ± 0.016 against ESM-2’s 0.576 ± 0.029 (Table 1), overlapping intervals, where this table records a confident $+0.03$. Everything else below remains at the confidence of a single pooled split.

Note the apparent tension with Table 1: under this earlier protocol, the boundary head on ESM-2 looked like it had no effect, while nested cross-validation resolved a confirmed $+0.021$ F1 gain for the same modification on the same embedding. We read this as evidence that the single-split protocol lacked the statistical power to resolve an effect of this size, not as a contradiction – and as the clearest illustration of why we do not treat single-split numbers as findings in this paper. The interaction these rows suggest, that the boundary head is worth more on the richer embedding, is




Figure 4: Why the folds of the earlier seven-fold split are not interchangeable: (a) the segment-length profile of each fold against the profile of the whole dataset, (b) the L_1 distance between the two. Fold 4 tracks the overall distribution closely (0.07) while five of the seven folds sit above 0.23. Balancing was done on cleavage motif and homology, not on segment length, so this axis was left free. The same holds for the five-fold split used in the main text, where the imbalance is taxonomic (Table 4).

not established by them: it is established under nested cross-validation in Section 5, where the same comparison is paired by outer fold and positive on five folds of five. What this table contributes is the earlier and much noisier version of it.

F.3 Additional exploratory modifications

A larger set of ideas was tried under the same single-split protocol and did not show a clear, consistent benefit. We list them for completeness and as candidates for future re-testing, without effect-size claims:

- **Known-peptide dictionary.** An Aho–Corasick index of peptides from the training data was used to flag substring matches in a query sequence, injected as a bonus on the CRF state emissions, as a bias on the start, inside and end emissions specifically, fused into the encoder hidden state, and concatenated with the embedding before the encoder. No consistent benefit was observed, and the checkpoint for one of the variants can no longer be loaded.
- **Structural features.** Features extracted from predicted 3D structures (AlphaFold2 representations via the AFToolkit codebase, with several confidence-based filtering variants) and from the ProstT5 [Heinzinger et al., 2024] structural alphabet (3Di, as used in Fold-




Figure 5: Precision/recall trade-offs by segment type when adding the 3Di channel or the bond-prediction loss, single-split protocol, pooled held-out folds.

Table 5: Modifications tested under the screening single-split protocol, with their measured effect on F1 (pooled held-out folds) and an informal verdict. None of these effect sizes should be compared directly to the nested-CV numbers in Table 1.

Modification	Type	Measured effect on F1	Verdict
ESM-C 6B instead of ESM-2	embedding swap	+0.03, unstable across folds	helps
Boundary head on ESM-C 6B	decoder addition	+0.05, +0.07, consistent	helps
Boundary head on ESM-2	decoder addition	≈ 0 (CI includes zero)	no effect
Structural channel (3Di)	extra input	propep. +0.02 / pep. -0.03, net trade-off	no effect
ESM-C 6B compression 2560→256	optimization	≈ 0 , 10× narrower input and 16× fewer trainable parameters	no effect
Sequence adapter on ESM-C 6B (pLM re-projection)	input adapter	+0.022, CI [+0.008, +0.038]	helps
Bond-prediction auxiliary loss (on ESM-C 6B)	extra loss	pep. -0.05, net -0.015, neutral on ESM-2	harmful
Telescopic segment CRF	decoder addition	≈ 0 on ESM-2, +0.022 on ESM-C 6B, no CI available	unresolved

488 seek [van Kempen et al., 2024]) were tested as additional input channels, and results were
489 mixed (Table 5).

- 490 • **LoRA fine-tuning.** Low-rank adaptation of the last few pLM layers, instead of fully frozen
491 embeddings, scored 0.558 and 0.567 against 0.621 for the frozen baseline, all three on the
492 2022 release under its own five-fold split rather than the protocol of Appendix F. It also ran
493 for fewer epochs in the same time budget, though we did not measure the cost directly.
- 494 • **Projector variants.** Multi-scale and multi-branch projectors between the embedding and
495 the CNN-BiLSTM were tried as alternative re-projection schemes to the adapter of Sec-
496 tion 3.
- 497 • **Structural-projection width and telescopic CRF.** The width of the structural-feature pro-
498 jection (16/32/48 units) left pooled F1 flat at 0.691, 0.697 and 0.693, the telescopic segment
499 CRF, an alternative decoder formulation that scores whole segments through a relative-
500 position head, came out level with the base decoder on ESM-2 and +0.022 ahead on
501 ESM-C 6B. Per-protein outputs were not retained for either run, so neither number car-

502 ries a confidence interval and we treat the modification as untested rather than as having no
 503 effect.

504 None of these modifications showed a consistent gain large enough, under the single-split protocol,
 505 to justify testing under nested cross-validation ahead of the two reported in the main text. The com-
 506 plete experiment log (including runs not summarized above) is maintained in the project repository
 507 rather than reproduced here, since it was collected under a protocol we no longer treat as sufficient
 508 evidence on its own.





Figure 6: F1 (± 3) against the number of training proteins, single-split protocol. ESM-2 rises from 0.498 at 40% of the training folds to 0.583 at 85%, then falls back to 0.572 at 100%, so it is still gaining over most of the range but not at the last point. The ESM-C 6B curves are flat from the smallest size tested, with movement smaller than the bootstrap interval, so nothing is observed saturating: they simply never climb.


509 F.4 What the screening runs looked like

510 Three figures from the screening stage are worth keeping, each for a different reason, and none of
 511 them should be read as confirmed evidence in the sense of Section 5. Figure 7 is the comparison
 512 the verdict column of Table 5 summarizes, with the bootstrap intervals that made most of those
 513 verdicts unsafe. Figure 8 is the earliest form of the interaction that Section 5 later confirms under
 514 nested cross-validation, and shows that the boundary head was already worth more on the wider
 515 embedding a protocol ago. Figure 9 asks what recall actually tracks: for both ESM-C models it
 516 follows the maximum sequence identity between a held-out peptide and any training segment far
 517 more closely than it follows how many training segments the protein’s genus contributes, which is
 518 the behaviour of a model retrieving near neighbours rather than one that has learned the cleavage
 519 grammar. On the ESM-2 baseline the two axes are closer to comparable. This is a single split and
 520 we draw no conclusion from it, but it is the observation that would most repay a proper test.



hollow markers — gated-model controls, not rungs of the ladder
dashed rule — gated adapter: +0.022 (isolated by ablation),
significant on average, but the gain is mostly on fold 5

Figure 7: Screening comparison on the pooled held-out folds at ± 3 : F1, precision and recall with bootstrap confidence intervals over 2,322 proteins. The top row is a gated-projector control at full width, not the configuration carried into the main text.



error bars — 95% percentile bootstrap CI, resampling proteins (not folds)

Figure 8: Boundary head $\times$ embedding interaction under the screening protocol: F1 gain from adding the boundary head on top of ESM-2 against on top of ESM-C 6B. This is the earlier, unconfirmed version of the interaction that Section 5 measures under nested cross-validation.




Figure 9: Recall on held-out peptides as a function of (a) how well-represented the protein’s genus is in training and (b) maximum sequence identity to a training segment, screening protocol. For the two ESM-C models recall tracks maximum identity to a training segment far more than genus abundance, while for the ESM-2 baseline the two axes are closer to comparable. The x axis in (a) counts training *segments* in the genus, not proteins.

G Extended review of prior work

Methods for predicting proteolytic peptides fall into three broad classes.

Protease-specific models. These predict cleavage only for a limited set of enzymes, most of which have a known recognition motif. ProP [Duckert et al., 2004] targets cleavage by the PACE/PC family in animals and plants. PROSPER [Song et al., 2012] and its successor PROSPERous [Song et al., 2018] predict cleavage for one chosen enzyme at a time, as does the later ProsperousPlus [Li et al., 2023]. DeepCleave [Li et al., 2020a] is restricted to caspases and matrix metalloproteinases, and Procleave [Li et al., 2020b] likewise handles one enzyme at a time and additionally requires 3D structural input. The shared limitation of this class is scope: in practice, one is usually interested in the combined effect of all proteases active in an organism, not any single enzyme.

Organism- or peptide-type-specific models. A separate class targets neuropeptides or other bioactive fragments specific to a given organism. NeuroPred [Southey et al., 2006] and the species-agnostic DeepNeuropePred [Wang et al., 2024] only detect cleavage near a handful of basic residues, while NeuroPred-PLM [Wang et al., 2023] does not localize cleavage sites at all but classifies an already-excised sequence. A related group of models finds signal subsequences rather than any bioactive peptide: SignalP [Teufel et al., 2022] and TargetP [Almagro Armenteros et al., 2019] identify the type of signal peptide, which indicates where a protein is trafficked.

General-purpose models on pLM embeddings. Protein language models (pLMs) are transformers trained without supervision on large sequence corpora, typically by masked-residue recovery, and they produce transferable per-residue embeddings: ESM-2 [Lin et al., 2023], the earlier ESM line [Rives et al., 2021], ESM Cambrian [ESM Team, 2024, Hayes et al., 2025], and Ankh [El-naggar et al., 2023]. Compact task-specific heads are then trained on top of these frozen embeddings. Besides **DeepPeptide** [Teufel et al., 2023b] itself, this recipe underlies DeepNeuropePred, NeuroPred-PLM, and SignalP 6, as well as models that score already-excised peptides rather than finding them: pLM4ACE [Du et al., 2024] predicts ACE-inhibitory activity, and BPFun [Zhu et al., 2025] and DeepBP [Zhang et al., 2024] predict broader bioactivity, building on earlier pre-pLM work such as PeptideRanker [Mooney et al., 2012]. Before pLMs, PeptideLocator [Mooney et al., 2013] addressed a problem close to ours, but its output is a per-residue heatmap of similarity to known bioactive peptides rather than an explicit segmentation, and it was the main point of comparison in the original DeepPeptide paper.

Baseline architecture: DeepPeptide. Since we build directly on it throughout this paper (Section 3), DeepPeptide’s architecture is worth describing in detail rather than treating as a black box. It first encodes a precursor sequence with a frozen pLM (ESM-2), producing a per-residue embedding that is not fine-tuned during training. This embedding is refined by a convolution, a single-layer bidirectional LSTM and a second convolution. The published description does not fix the widths: they are searched with Optuna inside the inner cross-validation loop. The configuration we train throughout uses 32 convolutional filters of width 3 and an LSTM hidden size of 64 per direction, giving 224,710 trainable parameters for the base model. These features are consumed by a linear-chain CRF decoder whose state set is extended well beyond the three raw labels {None, Peptide, Propeptide}: each of the two positive labels is expanded into a chain of states long enough to represent segments up to a fixed maximum length (101 states in total for the 50-residue cap used here, Section 4.1), so that a legal path through the CRF can only realize a contiguous segment of valid length, with dedicated states marking its first and last positions. This makes segmentation, rather than independent per-residue classification, the object the model is directly optimized for – and it is also where the gap described in Section 1 lives: every state in this extended set that shares a type receives the same emission from the encoder, regardless of whether it marks the start, interior, or end of a segment.

Baseline dataset for this task. Beyond its architecture, DeepPeptide also established the data resource this line of work relies on: precursor sequences from UniProtKB/Swiss-Prot annotated with PEPTIDE and PROPEP feature types, partitioned into homology-aware folds with GraphPart [Teufel et al., 2023a] at a 30% pairwise-identity threshold and additionally balanced by cleavage-flanking motif, then evaluated with the same family of nested cross-validation we adopt (Section 5). This gave the field a standardized, already homology-controlled benchmark rather than an ad hoc collection of previously published peptide lists, and both the curated data and the construction pipeline that produced it are public. Section 4.1 describes what we do with that resource: rebuilding it on a

575 current UniProtKB/Swiss-Prot release, which adds 1,170 proteins net and refreshes the annotations
576 behind every segment.

577 Among these, DeepPeptide is, to our knowledge, the only model that poses the task as full segmen-
578 tation of the precursor into typed peptide and propeptide segments, and it is the strongest available
579 baseline for this formulation. We therefore use its architecture and its dataset-construction method-
580 ology as the starting point for this work, rather than treating it as a system to audit: our contribution
581 is an architectural addition to this general recipe (Section 3), evaluated under the same 5×4 nested
582 cross-validation it uses (Section 4) on data rebuilt from a current release (Section 4.1).