MINI PROJECT 2: NETWORK PROTOCOL ANALYSIS USING WIRESHARK

Student Name:	Kotra balaji
Roll / Registration No.:	STU-925A2A40
Batch / Course:	Cyber Security / G17
Academic Platform:	SURE ProEd
Date of Submission:	22-10-2026

1.Introduction to Network Protocol Analysis

A network packet represents the discrete, formatted data unit transmitted across digital networks, encapsulating payload data within structured headers. A network protocol defines the authoritative syntax, semantics, and synchronization rules that communicate between computing systems. In cybersecurity operations and network engineering, packet analysis -- often termed packet sniffing or deep packet inspection (DPI) -- is the rigorous practice of capturing raw binary frames as they traverse physical or virtual network interfaces and decoding each hierarchical layer from Data Link framing up to Application Layer payloads.

Wireshark is the industry-standard network protocol analyzer. It captures live packet streams across network interface controllers (NICs) via packet capture libraries (libpcap), reconstructing the encapsulation hierarchy defined by the Open Systems Interconnection (OSI) 7-layer reference model and the practical 4-layer TCP/IP suite. For cybersecurity analysts, packet-level visibility provides definitive empirical evidence required for vulnerability assessments, malicious traffic detection, protocol compliance verification, and forensic root-cause analysis during incident investigations.

This project performs an empirical investigation of live multi-protocol network traffic captured within a virtualized Kali Linux environment running on VMware Fusion. The investigation examines core networking and transport protocols: Domain Name System (DNS), User Datagram Protocol (UDP), Internet Control Message Protocol for IPv6 (ICMPv6) alongside Neighbor Discovery Protocol (NDP), Transmission Control Protocol (TCP), Network Time Protocol (NTP), Dynamic Host Configuration Protocol (DHCP), and Transport Layer Security (TLSv1.3). The analysis correlates low-level packet fields -- such as 16-bit transaction IDs, 32-bit sequence/acknowledgement numbers, protocol flags, and cryptographic handshake extensions -- with theoretical network models and practical defensive cybersecurity principles.

2.Project Aim and Objectives

Primary Aim: To capture, decode, and evaluate live multi-layer network protocols (DNS, UDP, ICMPv6, TCP, NTP, DHCP, and TLSv1.3) using Wireshark within a controlled virtualization environment, rigorously validating protocol mechanics, state synchronization, addressing semantics, and defensive cybersecurity implications.

Key Objectives: The operational practical objectives include:

- **Interface Capture:** Configure and execute live packet capture on the Kali Linux virtual network interface (eth0) utilizing Wireshark 4.4.7.
- **Traffic Generation:** Generate reproducible network traffic using native command-line utilities, including ICMPv6 reachability tests (ping -c 6 google.com) and secure HTTP sessions (curl -I https://www.microsoft.com).
- **DNS Resolution:** Dissect DNS query-response exchanges over UDP port 53, validating 16-bit transaction ID matching, recursive resolution flags, and record type mappings.
- **ICMPv6 & NDP:** Analyze ICMPv6 Echo Request/Reply operations and IPv6 Neighbor Discovery Protocol (NDP) solicitations and advertisements, contrasting them with IPv4 ARP.
- **TCP Handshake:** Inspect the full TCP three-way handshake (SYN, SYN-ACK, ACK), verifying sequence/acknowledgement number

progression, window scale calculations, and conversation completeness.

- **UDP Services:** Evaluate connectionless UDP transport behavior across auxiliary protocols, specifically NTP Version 4 client timing requests and DHCP IPv4 lease exchanges.
- **TLSv1.3 Security:** Examine TLSv1.3 cryptographic handshake metadata (Client Hello, SNI, ALPN, cipher suites) while delineating metadata visibility from encrypted payload protection.
- **Cybersecurity Mapping:** Construct protocol-specific display filters to isolate traffic streams and map observed protocol behaviors to real-world cybersecurity threat vectors.

3.Theoretical Background and Tools Used

3.1OSI 7-Layer Reference Model vs. TCP/IP Architecture

Network communication relies on standardized architectural models that partition complex communication tasks into hierarchical layers. The ISO Open Systems Interconnection (OSI) model defines a conceptual 7-layer framework, whereas the TCP/IP model provides the pragmatic 4-layer architecture upon which the global Internet operates. Each layer encapsulates outgoing application data with specific headers containing control, addressing, and sequencing metadata, and decapsulates incoming frames upon reception.

OSI Layer	TCP/IP Layer	PDU Unit	Core Operational Role	Cybersecurity Threat Vectors
7. Application	**Application**	Data	End-user network services (HTTP, DNS, NTP)	Phishing, DNS spoofing, payload injection
6. Presentation	**Application**	Data	Data syntax, character encoding, encryption (TLS)	Cryptographic downgrade, serialization attacks
5. Session	**Application**	Data	Session establishment, coordination, and tear-down	Session hijacking, replay attacks, session fixation
4. Transport	**Transport**	Segment / Datagram	End-to-end reliability (TCP) or datagram speed (UDP)	TCP SYN flood, port scanning, connection reset
3. Network	**Internet**	Packet	Logical addressing (IPv4/IPv6) and path routing	IP spoofing, ICMP flooding, route poisoning
2. Data Link	**Network Access**	Frame	Physical MAC delivery and local segment switching	MAC flooding, ARP spoofing, rogue NDP RA
1. Physical	**Network Access**	Bits	Transmission of raw electrical, optical, or RF signals	Physical wiretapping, rogue hardware, jamming

The conceptual relationship between the seven layers of the OSI model and the four practical layers of the TCP/IP suite is illustrated in Figure 1, emphasizing how data units are transformed during transmission across networked systems.



Figure 1: Architectural Mapping of OSI 7-Layer Reference Model to TCP/IP Protocol Suite.

3.2Tools and Software Environment

- **Packet Analyzer:** Wireshark 4.4.7: High-performance packet capture and dissection engine utilized for real-time interface monitoring, protocol decoding, and forensic packet filtering.

- **Guest Operating System:** Kali Linux (64-bit): Dedicated cybersecurity Linux distribution hosted as a guest virtual machine running inside VMware Fusion on a macOS host system.
- **Network Utilities:** ping (iputils): Diagnostic utility executed to generate ICMPv6 Echo Requests and stimulate upstream DNS resolution via the glibc resolver.
- **Application Client:** curl (libcurl): Command-line HTTP/HTTPS client utilized with header-only flags (-I) to initiate structured TCP connections and TLSv1.3 handshakes.
- **Network Simulator:** Cisco Packet Tracer: Network simulation platform utilized to model the underlying switched and routed topology, validating inter-subnet packet forwarding.

4.System Configuration and Wireshark Capture Procedure

4.1System Configuration and Network Environment

A rigorous protocol analysis requires documenting the precise operating environment, hardware parameters, and network addressing scheme. Table 2 details the exact parameters extracted from the captured packet stream. The Kali Linux virtual machine operated on an IPv6-enabled local segment where the primary network interface (eth0) acquired a globally routable IPv6 address and a link-local address. Crucially, the live VM interface possessed no assigned IPv4 address or default IPv4 gateway during the primary live capture, compelling native utilities (ping, curl) to operate entirely over IPv6. In parallel, an IPv4 configuration archive containing DHCP lease exchanges was evaluated to examine legacy bootstrap mechanisms.

Host Environment / Hypervisor	macOS Host system executing VMware Fusion Hypervisor
Guest Operating System	Kali Linux Rolling Release (Terminal user context: nkt_nk5@windows)
Capture Software & Engine	Wireshark Network Analyzer Version 4.4.7 (libpcap capture engine)
Active Capture Interface	eth0 (Ethernet network interface controller, bound in promiscuous mode)
VM Virtual MAC Address	00:0c:29:c5:97:80 (Organizationally Unique Identifier decoded as VMware_c5:97:80)
VM Global IPv6 Address	2409:40e6:435:6928:2ecd:10e4:7158:11a5 (SLAAC / Router Advertised prefix)
VM Link-Local IPv6 Address	fe80::20c:29ff:fec5:9780 (Modified EUI-64 format derived from MAC)
Default Gateway Router	Link-local: fe80::824:45ff:fe96:147f | MAC: 0a:24:45:96:14:7f
Upstream DNS Resolver	2409:40e6:435:6928::91 (Queried over UDP port 53 for recursive resolution)

4.2Packet Capture Methodology and Display Filtering

The operational capture workflow commenced by launching Wireshark with elevated privileges within the Kali Linux terminal. As illustrated in Figure 2, the Wireshark 4.4.7 startup interface presents active network interfaces alongside real-time sparkline traffic monitors. The primary interface eth0 was selected, and a live promiscuous capture was initialized.




Figure 2: Wireshark 4.4.7 Interface Startup Screen Displaying Interface eth0.

Wireshark utilizes two distinct filtering paradigms: Capture Filters (BPF syntax compiled into kernel drivers) and Display Filters (applied non-destructively to the in-memory capture buffer to isolate specific conversations). Table 3 outlines the key display filters evaluated during this project.

Display Filter	Target Protocol	Filter Syntax Rationale	Project Practical Application
`tcp`	TCP Protocol	Isolates all Transmission Control Protocol segments	Verified: Filter applied in Figure 11 isolating Frames 5-7
`icmpv6`	ICMPv6 Protocol	Isolates IPv6 control, echo, and neighbor messages	Used to evaluate ping echo packets and NDP solicitations
`dns`	DNS Protocol	Filters queries/responses on standard port 53	Used to inspect A, AAAA, and PTR name resolution frames
`bootp || dhcp`	DHCP Protocol	Isolates bootstrap and DHCP IPv4 exchanges	Evaluated on Frame 49 showing DHCP Request broadcast
`ntp`	NTP Protocol	Filters Network Time Protocol packets on port 123	Evaluated on Frame 39 showing NTPv4 client time sync request

5.DNS and UDP Packet Analysis

5.1Domain Name Resolution Workflow

To initiate communication with an external domain, the OS resolves the fully qualified domain name (FQDN) into an IP address. Within the Kali Linux terminal, ping -c 6 google.com was executed. As shown in Figure 3, the host resolver mapped google.com to canonical host nw-in-f100.1e100.net at IPv6 address 2404:6800:4013:804::64, transmitting six probes with 0% loss (avg RTT 69.241 ms).




Figure 3: Terminal Output for ping -c 6 google.com.




Figure 4: Unfiltered Packet Stream (DNS & ICMPv6).

5.2Dissection of DNS Query (Frame 23) and Response (Frame 25)

DNS operates as a query-response protocol over UDP port 53. Because UDP is stateless, DNS relies on a pseudo-random 16-bit Transaction ID to correlate answers with requests. Figures 5 and 6 display the dissected protocol trees for Frame 23 (Query) and Frame 25 (Response).




Figure 5: Dissection of Frame 23 (DNS Query) Showing Transaction ID 0xeb1d and Recursion Desired.




Figure 6: Dissection of Frame 25 (DNS Response) Showing Matching ID 0xeb1d, Flags 0x8180, and 6 Answer Records.

Packet Field / Parameter	DNS Query (Frame 23)	DNS Response (Frame 25)
Source & Destination IP	VM (2409:...:11a5) -> DNS (2409:...::91)	DNS (2409:...::91) -> VM (2409:...:11a5)
UDP Transport Ports	Source Port: 52572 -> Dest Port: 53	Source Port: 53 -> Dest Port: 52572 (Swapped)

Transaction Identifier	0xeb1d (16-bit pseudo-random client token)	0xeb1d (Exact match echoed by resolver)
Protocol Flags	0x0100 (Standard Query, Recursion Desired)	0x8180 (Standard Response, Recursion Available)
Question Section	google.com: type A, class IN	google.com: type A, class IN
Resource Record Counts	Questions: 1, Answers: 0, Authority: 0	Questions: 1, Answers: 6, Authority: 0, Add: 0

5.3UDP Transport Characteristics in Auxiliary Protocols

The User Datagram Protocol (UDP, RFC 768) provides lightweight, connectionless transport lacking handshake latency, retransmission mechanisms, or window flow control. UDP encapsulates payloads within an 8-byte header (Source Port, Destination Port, Length, Checksum). In DNS, UDP enables near-instantaneous name resolution (Frame 25 arrived in 49.72 ms). UDP's minimal overhead also makes it ideal for Network Time Protocol (NTP port 123) and DHCP (ports 67/68), where message loss is handled via application-level timeouts rather than transport retransmissions.

6.ICMPv6 and Neighbor Discovery Analysis

6.1 ICMPv6 Echo Request and Reply Mechanics

The Internet Control Message Protocol for IPv6 (ICMPv6, RFC 4443) is an integral part of the IPv6 suite, assigned Next Header value 58 in the IPv6 header. Beyond diagnostics, ICMPv6 handles critical control functions, path MTU discovery, and local link-layer address resolution. Figure 7 illustrates the captured ICMPv6 stream containing the alternating Echo Request and Reply sequence alongside interleaved Neighbor Discovery Protocol packets.




Figure 7: Wireshark Packet List Showing ICMPv6 Echo Requests/Replies and Neighbor Discovery Frames.

Figure 8 and Figure 9 present the protocol dissections for Frame 27, representing the initial ICMPv6 Echo Request generated by the ping utility.




Figure 8: Frame 27 ICMPv6 Header Dissection Showing Type 128 (Echo Request), Identifier 0x0005, and Sequence 1.




Figure 9: Frame 27 IPv6 Network Header Showing Next Header 58 (ICMPv6), Hop Limit 64, and Payload Length 64.

Source IPv6 -> Destination IPv6	2409:40e6:435:6928:2ecd:10e4:7158:11a5 (VM) -> 2404:6800:4013:804::64 (google.com)
Source MAC -> Destination MAC	00:0c:29:c5:97:80 (VM NIC) -> 0a:24:45:96:14:7f (Default Gateway Router)
Captured Echo Frame Pairs	Sequence 1 (27/28), Seq 2 (31/32), Seq 3 (33/34), Seq 4 (35/36), Seq 5 (37/38), Seq 6 (41/44)
ICMPv6 Identifier & Sequence	Identifier: 0x0005 constant across all probes; Sequence increments monotonically (1 to 6)
Hop Limit Progression	Echo Requests: Hop Limit = 64 (VM OS default); Echo Replies: Hop Limit = 112 (decremented by hops)
Empirical Round-Trip Time (Seq 1)	Frame 28 timestamp (42.930843 s) - Frame 27 timestamp (42.866465 s) = 64.38 ms

6.2 IPv6 Neighbor Discovery Protocol (NDP) vs. IPv4 ARP

A fundamental distinction between IPv4 and IPv6 lies in link-layer address resolution. While IPv4 relies on Address Resolution Protocol (ARP, RFC 826) utilizing unauthenticated broadcast frames, IPv6 deprecates ARP in favor of Neighbor Discovery Protocol (NDP, RFC 4861). NDP operates at the Network Layer using dedicated ICMPv6 message types transmitted via solicited-node multicast addresses, eliminating broadcast noise on local network segments.

In the captured trace (Figure 7), Frames 42, 43, 45, and 46 demonstrate live NDP cache maintenance. In Frame 42, the default gateway router (fe80::824:45ff:fe96:147f) emitted an ICMPv6 Neighbor Solicitation (Type 135) to verify the VM's link-layer reachability. In Frame 43, the Kali VM replied with an ICMPv6 Neighbor Advertisement (Type 136) providing its physical MAC address (00:0c:29:c5:97:80). In Frames 45 and 46, the VM queried the router, which responded with an advertisement carrying the rtr (Router) and sol (Solicited) flags, ensuring bidirectional frame forwarding without broadcast overhead.

7.TCP Three-Way Handshake Analysis

7.1TCP Transport Architecture and Connection Establishment

The Transmission Control Protocol (TCP, RFC 9293) provides a reliable, connection-oriented, full-duplex byte-stream transport service at Layer 4 of the OSI model. Unlike UDP, TCP guarantees delivery order, performs congestion control, and handles retransmission of lost segments. Before upper-layer application protocols (such as HTTP or TLS) can transmit data, TCP must establish a synchronized communication session using the canonical three-way handshake: SYN -> SYN-ACK -> ACK.

To stimulate genuine TCP transport traffic, the terminal command curl -I https://www.microsoft.com was executed. As illustrated in Figure 10, the Microsoft edge server responded with HTTP/2 200 OK via the AkamaiGHost content delivery network, confirming successful TCP connection establishment and secure TLS negotiation over destination TCP port 443.




Figure 10: Terminal Output of curl -I Returning HTTP/2 200 OK from Edge Server AkamaiGHost.

Applying the Wireshark display filter tcp isolates the TCP conversation from background traffic. Figure 11 displays the three consecutive handshake segments: Frame 5 [SYN], Frame 6 [SYN, ACK], and Frame 7 [ACK].




Figure 11: Display Filter 'tcp' Isolating Handshake Frames 5 [SYN], 6 [SYN, ACK], and 7 [ACK].

7.2Dissection of Handshake Frames 5, 6, and 7

Figures 12, 13, and 14 show the exact protocol tree dissections for the three handshake frames, detailing sequence numbers, acknowledgement numbers, TCP flags, and negotiated TCP options.




Figure 12: Frame 5 Dissection (SYN from VM): Ephemeral Port 44034 -> Port 443, Raw Seq 2049886894, Flags 0x002.




Figure 13: Frame 6 Dissection (SYN-ACK from Server): Raw Seq 807259871, Raw Ack 2049886895, Flags 0x012.




Figure 14: Frame 7 Dissection (ACK from VM): Raw Seq 2049886895, Raw Ack 807259872, Flags 0x010.

7.3 TCP Handshake Parameter Verification and Mathematical Proof

The mathematical synchronization of TCP sequence and acknowledgement numbers is detailed in Table 5. The exchange begins in Frame 5 where the client chooses a pseudo-random Initial Sequence Number (ISN_c = 2049886894). In Frame 6, the server acknowledges the SYN by incrementing ISN_c by 1 (Ack = 2049886895) and presents its own random ISN_s (807259871). In Frame 7, the client acknowledges the SYN-ACK by incrementing ISN_s by 1 (Ack = 807259872). Wireshark marks this stream Conversation completeness: Complete, WITH_DATA.

Frame	Direction (Ports)	TCP Control Flags	Raw Sequence No.	Raw Ack No.	Window / Options
Frame 5	VM -> Server (44034 -> 443)	0x002 (SYN)	2049886894 (Rel: 0)	0 (Not set)	Win: 64800, MSS: 1440, WS: 128
Frame 6	Server -> VM (443 -> 44034)	0x012 (SYN, ACK)	807259871 (Rel: 0)	2049886895 (ISN_c + 1)	Win: 64260, MSS: 1440, WS: 128
Frame 7	VM -> Server (44034 -> 443)	0x010 (ACK)	2049886895 (Rel: 1)	807259872 (ISN_s + 1)	Win: 507 (x128 = 64896 bytes)

8.NTP and DHCP Protocol Analysis

8.1 Network Time Protocol (NTP) Dissection (Frame 39)

Accurate system clock synchronization is a paramount operational requirement in modern networks, particularly for correlating security events, intrusion detection logs, and digital forensics evidence. Figure 15 dissects Frame 39, displaying an outbound NTP Version client request emitted over IPv6 via UDP port 37534 to standard NTP destination port 123.




Figure 15: Dissection of Frame 39 (NTP Version 4 Client) Showing UDP Port 123 and 48-Byte Payload.

The packet carries NTP flags 0x23 (Leap Indicator 0: no warning; Version 4; Mode 3: Client). The UDP payload length is exactly 48 bytes, the standard NTP header size. Wireshark indicates Response In: 40. The Peer Clock Stratum is recorded as 0 (unspecified/invalid) because the client has not yet synchronized against an authoritative Stratum 1 or 2 time source.

8.2 Dynamic Host Configuration Protocol (DHCP) Dissection (Frame 49)

Figure 16 examines Frame 49 from the supplementary IPv4 evidence archive, capturing a DHCP Request emitted by client MAC 00:0c:29:c5:97:80 during dynamic IPv4 bootstrap. The exchange occurs over UDP source port 68 to destination port 67, using IPv4 broadcast destination 255.255.255.255.




Figure 16: Dissection of Frame 49 (DHCP Request) Displaying Transaction ID 0x29e42931 and Option 50.

The message contains Transaction ID 0x29e42931 and incorporates DHCP Option 53 (Message Type: Request), Option 50 (Requested IP Address: 10.172.213.17), and Option 54 (Server Identifier: 10.172.213.197). This confirms the standard DHCP DORA (Discover, Offer, Request, Acknowledge) state machine.

8.3Transport Layer Security (TLSv1.3) Handshake Analysis

Following successful completion of the TCP three-way handshake in Frames 5-7, the client initiates secure session negotiation via Transport Layer Security (TLSv1.3, RFC 8446). Figure 17 dissects Frame 8, representing the TLS Client Hello message transmitted over TCP port 443 with a total length of 1,652 bytes on the wire.




Figure 17: Dissection of Frame 8 (TLSv1.3 Client Hello) Showing SNI (www.microsoft.com) and 30 Cipher Suites.

Cryptographic Metadata: Key cryptographic parameters exposed within the unencrypted Client Hello metadata include:

- **Virtual Hosting:** Server Name Indication (SNI): The extension explicitly indicates 'www.microsoft.com', allowing upstream multi-tenant proxy servers and CDN edges to direct the handshake to the appropriate virtual host certificate.
- **Cipher Negotiation:** Cipher Suites: The client offers 30 cryptographic cipher suites (including modern AEAD suites like TLS_AES_256_GCM_SHA384 and TLS_CHACHA20_POLY1305_SHA256), establishing perfect forward secrecy.
- **ALPN Extension:** Application-Layer Protocol Negotiation (ALPN): Advertises support for HTTP/2 ('h2') and HTTP/1.1 ('http/1.1').

Cybersecurity Principle: Security Distinction: While TLSv1.3 provides robust payload confidentiality and integrity, the initial handshake metadata (SNI, supported extensions, cipher lists) remains fully visible to passive network sniffers. However, once key agreement concludes, all subsequent application payloads are entirely encrypted, preventing passive inspection without endpoint TLS termination or pre-shared decryption keys.

8.3Cisco Packet Tracer Topology and End-to-End Routing Context

To demonstrate how lower-layer framing, switching, and routing underpin the higher-layer protocol interactions analyzed in Wireshark, the underlying network infrastructure was modeled in Cisco Packet Tracer. Figure 18 illustrates the multi-subnet topology consisting of PCs, Layer 2 switches, and edge routers interconnected via serial links (networks 10.10.10.0/24, 20.20.20.0/24, and serial WAN 30.30.30.0/24).




Figure 18: Cisco Packet Tracer Routed Infrastructure.




Figure 19: End-to-End HTTP Delivery ('balaji').

Static routing and NAT were configured across Router 7 (Serial 2/0: 30.30.30.1) and Router 6 (Serial 2/0: 30.30.30.2). In Figure 19, an end-to-end HTTP request from PC0 across the routed topology successfully rendered the customized web page displaying 'balaji', confirming end-to-end packet delivery across all seven layers.

9.Results, Observations, Limitations, and Cybersecurity Relevance

9.1 Experimental Results Summary

Table 6 provides a consolidated technical summary of all seven network protocols captured and decoded during the experimental practical, documenting the specific protocol layer, transport mechanisms, frame identifiers, and empirical findings.

Protocol	Layer	Transport / Port	Frame Range	Empirical Observation / Validation
DNS	Application	UDP port 53	Frames 23-26, 29-30	Matched ID 0xeb1d; resolved google.com to IPv6 nw-in-f100 in 49.7 ms
UDP	Transport	Ports 53, 123, 67/68	Frames 23, 39, 49	Stateless, low-overhead transport for queries, time sync, and DHCP leases
ICMPv6	Network Helper	IPv6 Next Header 58	Frames 27-28, 31-44	Verified 6/6 Echo Request/Replies (0% loss); average RTT 69.2 ms
NDP	Network / Link	ICMPv6 (135, 136)	Frames 42-43, 45-46	Link-local MAC resolution (NS/NA) without broadcast; replaced IPv4 ARP
TCP	Transport	Ports 44034 <-> 443	Frames 5-7	Full SYN -> SYN-ACK -> ACK handshake; verified sequence math and completeness
NTP	Application	UDP port 123	Frame 39	NTPv4 client request (flags 0x23, 48 bytes); Stratum 0 awaiting server sync
DHCP	Application	UDP ports 68 -> 67	Frame 49	IPv4 broadcast request; transaction ID 0x29e42931 for IP 10.172.213.17
TLSv1.3	Security / App	TCP port 443	Frame 8	Client Hello with SNI (www.microsoft.com), 30 ciphers; payload fully encrypted

9.2Experimental Limitations

- **Network Protocol Split:** Environment Heterogeneity: The live capture on interface eth0 was exclusively IPv6-focused, whereas DHCP traffic was captured in an auxiliary IPv4 archive.
- **Packet Truncation:** Collapsed Detail Panes: In the raw DNS capture, the Answer section was collapsed, truncating trailing IPv4 octets in the packet list summary.

- **Cryptographic Boundary:** Payload Opacity: In the TLSv1.3 capture, security encryption legitimately prevented application-layer HTTP/2 payload inspection from packet captures alone.

9.3Cybersecurity Threat Relevance and Defensive Countermeasures

- **DNS Threat Vectors:** DNS Vulnerabilities: Unauthenticated DNS is susceptible to DNS Cache Poisoning (Kaminsky attacks) and DNS Spoofing, redirecting users to malicious infrastructure. Mitigation requires deploying DNSSEC (cryptographic signing of resource records) and DNS-over-HTTPS (DoH).
- **TCP Exploits:** TCP Transport Attacks: Attackers exploit TCP's connection state machine via TCP SYN Flood Denial-of-Service attacks (exhausting server connection backlogs) and TCP SYN stealth scanning (reconnaissance without completing handshakes). Defenses include SYN Cookies and stateful firewall inspection.
- **IPv6 Link Exploits:** ICMPv6 and NDP Weaknesses: Unlike ARP, IPv6 NDP relies on ICMPv6 multicast, but remains vulnerable to Rogue Router Advertisements (man-in-the-middle default gateways) and NDP Cache Poisoning. Mitigation requires implementing RA Guard and Secure Neighbor Discovery (SEND, RFC 3971).
- **Access Layer Threats:** DHCP and Cleartext Risks: Rogue DHCP servers can assign malicious DNS and gateway settings, while DHCP Starvation exhausts address pools. Defenses mandate DHCP Snooping. Cleartext protocols (HTTP/Telnet) permit credential harvesting, underscoring mandatory TLS 1.3 encryption.

10.Conclusion and References

10.1Conclusion

This project accomplished a comprehensive, multi-layer protocol analysis using Wireshark 4.4.7 within a virtualized Kali Linux environment, successfully correlating theoretical network models with genuine packet captures. The investigation provided rigorous empirical verification across all primary communication layers:

- **Application Layer:** Application Layer: Validated DNS recursive resolution, matching 16-bit transaction IDs (0xeb1d) over UDP port 53, dissecting NTP Version 4 timing requests, and examining DHCP configuration states.
- **Transport Layer:** Transport Layer: Contrasted the lightweight, connectionless operation of UDP against the synchronized, reliable state machine of TCP, verifying the full three-way handshake (SYN, SYN-ACK, ACK) and window scale factors over port 443.
- **Network Layer:** Network Layer: Analyzed IPv6 global and link-local addressing, demonstrating ICMPv6 Echo reachability (0% packet loss) and evaluating Neighbor Discovery Protocol (NDP) mechanics as the modern, multicast-based successor to IPv4 ARP.
- **Security Layer:** Cryptographic Layer: Dissected TLSv1.3 Client Hello metadata (SNI, ALPN, cipher suites), establishing the critical security boundary between unencrypted negotiation headers and cryptographically secure application payloads.

Ultimately, deep packet inspection represents an indispensable competency for cybersecurity professionals. The ability to isolate specific conversational flows using display filters, decode raw binary headers, and verify protocol state transitions enables analysts to identify network misconfigurations, detect unauthorized reconnaissance, and remediate advanced cyber threats effectively.

10.2Academic and RFC References

[1] Wireshark Foundation, "Wireshark User's Guide," Version 4.4, 2026. Available: https://www.wireshark.org/docs/wsug_html_chunked/

[2] Wireshark Foundation, "Wireshark Display Filter Reference Index," 2026. Available: https://www.wireshark.org/docs/dfref/

[3] P. Mockapetris, "Domain Names - Implementation and Specification," RFC 1035, STD 13, IETF, Nov. 1987. doi: 10.17487/RFC1035.

[4] A. Conta, S. Deering, and M. Gupta, "Internet Control Message Protocol (ICMPv6) for the IPv6 Specification," RFC 4443, Mar. 2006.

[5] T. Narten, E. Nordmark, W. Simpson, and H. Soliman, "Neighbor Discovery for IP version 6 (IPv6)," RFC 4861, Sep. 2007.

[6] W. Eddy, "Transmission Control Protocol (TCP) Specification," RFC 9293, STD 7, IETF, Aug. 2022. doi: 10.17487/RFC9293.

[7] E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.3," RFC 8446, IETF, Aug. 2018. doi: 10.17487/RFC8446.

[8] R. Droms, "Dynamic Host Configuration Protocol," RFC 2131, IETF, Mar. 1997. doi: 10.17487/RFC2131.

[9] D. Mills, J. Martin, J. Burbank, and W. Kasch, "Network Time Protocol Version 4: Specification," RFC 5905, Jun. 2010.

[10] Cisco Networking Academy, "CCNA: Introduction to Networks - Layered Protocol Architectures," Cisco Systems, 2026