



TOWARDS BUILDING NETWORK OUTLIER DETECTION SYSTEM FOR NETWORK TRAFFIC MONITORING

Josef Koumar, CESNET a.l.e. & CTU in Prague
Jaroslav Pešek, CESNET a.l.e. & CTU in Prague
Kamil Jeřábek, CESNET a.l.e. & BUT
Tomáš Čejka, CESNET a.l.e. & CTU in Prague

MOTIVATION



There are several challenges which slow Machine Learning adoption to the practise of detection of security threats in network traffic:

- Present of data drifts in normal network traffic
- Novel threats or versions of the known one
- Lack of datasets from real-world environment
- Features are often based on specific parameters of the network, thus, limited transferability

These limitation cause high false positive rates in deployment of current classification and detection approaches


OUR FOCUSE



Therefore, we focus on the detection of outliers (anomalies, abnormalities) which do not have these limitations.

The outlier is a data point that deviates significantly from other observed data points, enough to raise suspicion that it was generated by a different mechanism.

The deviation of outlier from observed data can be, for example, based on distribution, trend or seasonality.






The datapoint from the network traffic forms the time series. These time series are multivariate with following time series metrics:


- Number of IP flows, packets, bytes
- Number of unique destination IP addresses
- Number of unique destination ASNs
- Number of unique destination countries
- TCP/UDP ratio
- Packet direction ratio
- Average TTL and duration of IP flows




Point Anomaly - Global




Collective Anomaly - Subsequence




Point Anomaly - Contextual




Collective Anomaly - Pattern




Seasonal Anomaly




Trend Anomaly



NETWORK OUTLIER DETECTION SYSTEM (NODS)




- Built from open-source software
- Enable deployment of anomaly/outlier detection methods based on the **forecasting of network traffic** in real-world scenarios
- Successfully deployed on the **real-world ISP network CESNET3**



AGGREGATOR




- Aggregates IP flows into datapoints
- Push datapoints into database
- Send control signal to Trainers and Detectors modules
- Multiple Aggregators run in the system







- Trainers module **manage training** of models
- Receives signal from the Aggregator module to run processes
- **Run trainer routine of model** if the training period of model pass
- After trainer routine of model finish training process it push predictions into DB



DETECTORS





- Detectors module **manage detection process** of models
- Detection process for forecasting based outlier detectors is the **comparison of observed values with forecasted values**
- Outliers are sent to the Alert Combiner module





- Multiple detectors operate on various time series metrics, which can lead to the same anomaly being detected multiple times across different detectors.
- To reduce redundant alerts and ease the load on the SoC team, the Alert Combiner module consolidates these detections by grouping outliers with the same timestamp, and applying categorization.










In the first deployment of NODS, we used following models:

- Mean Outlier Detection (MOD)
- Differential Outlier Detector (DOD)
- Seasonal Autoregressive Integrated Moving Average (SARIMA)

By now we are ready do deploy GRU-FCN forecasting model.



DEPLOYMENT



- We deploy the system into CESNET3 network (Czech Education and Science Network)
- Monitored 100k active IP addresses
- Detected ~ 500k outliers for 10 minutes aggregation interval in one month (0.11%)
- Detected ~ 390k outliers for one hour aggregation interval in one month (0.52%)
- Marked ~ 3k incidents as crucial



- High false positives after cold start
 - use learning phase
- Alerting everything to SoC team
 - risk of all detection being ignored due to False Positives
- Only ~0.17% of datapoints marked as outliers, but the absolute number of outliers is too many to handle by SoC
 - group into incidents for SoC
- Diverse anomalies detected which are hard to evaluate for non-experts
 - consider LLM-based interpretation
- ISP-level scans add noise
 - filter early to improve detection
- IP address with sparse traffic
 - weakens forecasting and obtaining high number of False Positive

FUTURE WORK




IP Address: 10.0.0.4 | Aggregation: 1 hours | Model: mean

From: dd.mm.rrrr | Measured Value: avg_ttl

To: dd.mm.rrrr | Filter by: Metrics, Predictions, Intervals

Add + | Refresh ⏪





We created **CESNET TimeSeries24 dataset** which contains time series created from **66 billion IP flows** that contain **4 trillion packets** that carry approximately **3.7 petabytes of data**

Time Series Metrics:

- Number of IP flows, packets, bytes
- Number of unique destination IP addresses
- Number of unique destination ASNs
- Number of unique destination countries
- TCP/UDP ratio
- Packet direction ratio
- Average TTL and duration of IP flows

Aggregation:

- 10 minutes
- 1 hour
- 1 day

Identifiers:

- IP addresses
- Institutions
- Institution subnets



THANK YOU FOR YOUR ATTENTION

CESNET TimeSeries24
dataset



CESNET TS-Zoo library

