

1. _____ Consider the following method.

```
public static int mystery(int[] arr)
{
    int x = 0;

    for (int k = 0; k < arr.length; k = k + 2)
        x = x + arr[k];

    return x;
}
```

Assume that the array `nums` has been declared and initialized as follows.

```
int[] nums = {3, 6, 1, 0, 1, 4, 2};
```

What value will be returned as a result of the call `mystery(nums)` ?

- (A) 5
- (B) 6
- (C) 7
- (D) 10
- (E) 17

2. _____ Consider the following code segment.

```
int x = 7;
int y = 3;

if ((x < 10) && (y < 0))
    System.out.println("Value is: " + x * y);
else
    System.out.println("Value is: " + x / y);
```

What is printed as a result of executing the code segment?

- (A) Value is: 21
- (B) Value is: 2.3333333
- (C) Value is: 2
- (D) Value is: 0
- (E) Value is: 1

3. _____ Consider the following method.

```
public ArrayList<Integer> mystery(int n)
{
    ArrayList<Integer> seq = new ArrayList<Integer>();

    for (int k = 1; k <= n; k++)
        seq.add(new Integer(k * k + 3));

    return seq;
}
```

Which of the following is printed as a result of executing the following statement?

```
System.out.println(mystery(6));
```

- (A) [3, 4, 7, 12, 19, 28]
- (B) [3, 4, 7, 12, 19, 28, 39]
- (C) [4, 7, 12, 19, 28, 39]
- (D) [39, 28, 19, 12, 7, 4]
- (E) [39, 28, 19, 12, 7, 4, 3]

4. _____ Consider the following method that is intended to determine if the double values d1 and d2 are close enough to be considered equal. For example, given a tolerance of 0.001, the values 54.32271 and 54.32294 would be considered equal.

```
/** @return true if d1 and d2 are within the specified tolerance,
 *      false otherwise
 */
public boolean almostEqual(double d1, double d2, double tolerance)
{
    /* missing code */
}
```

Which of the following should replace */* missing code */* so that almostEqual will work as intended?

- (A) return (d1 - d2) <= tolerance;
- (B) return ((d1 + d2) / 2) <= tolerance;
- (C) return (d1 - d2) >= tolerance;
- (D) return ((d1 + d2) / 2) >= tolerance;
- (E) return Math.abs(d1 - d2) <= tolerance;

5. _____ Consider the following class declaration.

```
public class Person
{
    private String myName;
    private int myYearOfBirth;

    public Person(String name, int yearOfBirth)
    {
        myName = name;
        myYearOfBirth = yearOfBirth;
    }

    public String getName()
    { return myName; }

    public void setName(String name)
    { myName = name; }

    // There may be instance variables, constructors, and methods that are not shown.
}
```

Assume that the following declaration has been made.

```
Person student = new Person("Thomas", 1995);
```

Which of the following statements is the most appropriate for changing the name of `student` from "Thomas" to "Tom" ?

- (A) `student = new Person("Tom", 1995);`
- (B) `student.myName = "Tom";`
- (C) `student.getName("Tom");`
- (D) `student.setName("Tom");`
- (E) `Person.setName("Tom");`

6. _____ Consider the following code segment.

```
int[] arr = {7, 2, 5, 3, 0, 10};
for (int k = 0; k < arr.length - 1; k++)
{
    if (arr[k] > arr[k + 1])
        System.out.print(k + " " + arr[k] + " ");
}
```

What will be printed as a result of executing the code segment?

- (A) 0 2 2 3 3 0
- (B) 0 7 2 5 3 3
- (C) 0 7 2 5 5 10
- (D) 1 7 3 5 4 3
- (E) 7 2 5 3 3 0

7. _____ Consider the following class declaration.

```
public class Student
{
    private String myName;
    private int myAge;

    public Student()
    { /* implementation not shown */ }

    public Student(String name, int age)
    { /* implementation not shown */ }

    // No other constructors
}
```

Which of the following declarations will compile without error?

- I. `Student a = new Student();`
 - II. `Student b = new Student("Juan", 15);`
 - III. `Student c = new Student("Juan", "15");`
- (A) I only
(B) II only
(C) I and II only
(D) I and III only
(E) I, II, and III

8. _____ Consider the following method that is intended to return the sum of the elements in the array `key`.

```
public static int sumArray(int[] key)
{
    int sum = 0;

    for (int i = 1; i <= key.length; i++)
    {
        /* missing code */
    }

    return sum;
}
```

Which of the following statements should be used to replace `/* missing code */` so that `sumArray` will work as intended?

- (A) `sum = key[i];`
(B) `sum += key[i - 1];`
(C) `sum += key[i];`
(D) `sum += sum + key[i - 1];`
(E) `sum += sum + key[i];`

9. ——— Consider the following method.

```
public String mystery(String input)
{
    String output = "";

    for (int k = 1; k < input.length(); k = k + 2)
    {
        output += input.substring(k, k + 1);
    }

    return output;
}
```

What is returned as a result of the call `mystery("computer")` ?

- (A) "computer"
- (B) "cmue"
- (C) "optr"
- (D) "ompute"
- (E) Nothing is returned because an `IndexOutOfBoundsException` is thrown.

10. ——— Consider the following incomplete method that is intended to return an array that contains the contents of its first array parameter followed by the contents of its second array parameter.

```
public static int[] append(int[] a1, int[] a2)
{
    int[] result = new int[a1.length + a2.length];

    for (int j = 0; j < a1.length; j++)
        result[j] = a1[j];

    for (int k = 0; k < a2.length; k++)
        result[ /* index */ ] = a2[k];

    return result;
}
```

Which of the following expressions can be used to replace `/* index */` so that `append` will work as intended?

- (A) `j`
- (B) `k`
- (C) `k + a1.length - 1`
- (D) `k + a1.length`
- (E) `k + a1.length + 1`

Free Response

Consider the following partial declaration for a `WordScrambler` class. The constructor for the `WordScrambler` class takes an even-length array of `String` objects and initializes the instance variable `scrambledWords`.

```
public class WordScrambler
{
    private String[] scrambledWords;

    /** @param wordArr an array of String objects
     *      Precondition: wordArr.length is even
     */
    public WordScrambler(String[] wordArr)
    {
        scrambledWords = mixedWords(wordArr);
    }

    /** @param word1 a String of characters
     *      @param word2 a String of characters
     *      @return a String that contains the first half of word1 and the second half of word2
     */
    private String recombine(String word1, String word2)
    {
        /* to be implemented in part (a) */
    }

    /** @param words an array of String objects
     *      Precondition: words.length is even
     *      @return an array of String objects created by recombining pairs of strings in array words
     *      Postcondition: the length of the returned array is words.length
     */
    private String[] mixedWords(String[] words)
    {
        /* to be implemented in part (b) */
    }

    // There may be instance variables, constructors, and methods that are not shown.
}
```

(a) Write the `WordScrambler` method `recombine`. This method returns a `String` created from its two `String` parameters as follows.

- take the first half of `word1`
- take the second half of `word2`
- concatenate the two halves and return the new string.

For example, the following table shows some results of calling `recombine`. Note that if a word has an odd number of letters, the second half of the word contains the extra letter.

word1	word2	recombine(word1, word2)
"apple"	"pear"	"apar"
"pear"	"apple"	"peple"

Complete method `recombine` below.

```
/** @param word1 a String of characters
 *  @param word2 a String of characters
 *  @return a String that contains the first half of word1 and the second half of word2
 */
private String recombine(String word1, String word2)
```

- (b) Write the `WordScrambler` method `mixedWords`. This method creates and returns a new array of `String` objects as follows.

It takes the first pair of strings in `words` and combines them to produce a pair of strings to be included in the array returned by the method. If this pair of strings consists of `w1` and `w2`, the method should include the result of calling `recombine` with `w1` and `w2` as arguments and should also include the result of calling `recombine` with `w2` and `w1` as arguments. The next two strings, if they exist, would form the next pair to be processed by this method. The method should continue until all the strings in `words` have been processed in this way and the new array has been filled. For example, if the array `words` contains the following elements:

```
{"apple", "pear", "this", "cat"}
```

then the call `mixedWords(words)` should return the following array.

```
{"apar", "peple", "that", "cis"}
```

In writing `mixedWords`, you may call `recombine`. Assume that `recombine` works as specified, regardless of what you wrote in part (a).

Complete method `mixedWords` below.

```
/** @param words an array of String objects
 *      Precondition: words.length is even
 *      @return an array of String objects created by recombining pairs of strings in array words
 *      Postcondition: the length of the returned array is words.length
 */
private String[] mixedWords(String[] words)
```