ServiceNow Script-Controlled ACL - Code Implementation

Date	03/10/26
Team ID	SWTID-2026-7810
Project Name	Script-Controlled ACL - Restrict Record Access Based on Field Value

1. READ ACL - Script-Controlled Access

The READ ACL requires the **bb1** role and permits access to records where the Branch value is **EEE**. Administrators are allowed to retain access for the documented READ scenario.

```
if (gs.hasRole('admin')) {
    answer = true;
}
else if (gs.hasRole('bb1') && current.branch == 'EEE') {
    answer = true;
}
else {
    answer = false;
}
```

2. CREATE ACL

Required role: **bb2**

The CREATE ACL allows the create operation only for users with the configured role.

3. WRITE ACL

Required role: **bb3**

The WRITE ACL controls modification of permitted Institution Details records.

4. DELETE ACL

Required role: **bb4**

The DELETE ACL controls deletion of permitted Institution Details records.

5. Custom Table

Table: u_institution_details

The table contains Institution Details records with branch values such as ECE, EEE and CSE for access-control validation.

6. Access Control Logic

```
User
  |
  v
ServiceNow ACL
  |
  +--> READ: bb1 + Branch = EEE + Script
  |
  +--> CREATE: bb2
  +--> WRITE : bb3
  +--> DELETE: bb4
  |
  v
Access Granted / Denied
```

Implementation Note

The implementation above reflects the access-control rule documented for this project. The source documentation does not reproduce the exact original script text from the ServiceNow instance.