ServiceNow Script-Controlled ACL - Outputs

Date	03/10/26
Team ID	SWTID-2026-7810
Project Name	Script-Controlled ACL - Restrict Record Access Based on Field Value

1. Output of READ ACL - EEE User

When the EEE user with the required **bb1** role opens the Institution Details list, only records matching **Branch = EEE** are permitted by the configured READ rule.

User: EEE User

Role: bb1

Branch Access: EEE

Result: EEE records only

2. Output of Unauthorized READ

When a user does not satisfy the required access rule, the protected records are not available.

Required role: Missing / not authorized

Result: Restricted records are not visible

3. Output of Administrator READ

For the documented READ scenario, an administrator passes the administrative check in the script and can access the records across branches.

User: Administrator

Result: All branch records visible for the documented scenario

4. Output of CREATE / WRITE / DELETE ACLs

bb2: Create operation is controlled by the CREATE ACL.

bb3: Update operation is controlled by the WRITE ACL.

bb4: Delete operation is controlled by the DELETE ACL.

5. Overall Expected Output

```
User
  ↓
ACL Evaluation
  ↓
Role + Branch + Script Check
  ↓
Access Decision
  ↓
READ  -> EEE records for bb1 user
CREATE -> bb2
WRITE  -> bb3
DELETE -> bb4
Admin READ -> All branch records in the documented scenario
```

6. Final Output

The project demonstrates record-level security in ServiceNow by combining role-based permissions, a Branch = EEE condition and server-side ACL scripting. The four operations are controlled separately, with administrator access preserved for the documented READ scenario.

Note: The project documentation states that final UAT Pass/Fail status should be recorded after execution in the target ServiceNow instance.