

Tab 1

```

#include <stdio.h>
#include <stdlib.h>

// Define structure for BST node
struct Node {
    int data;
    struct Node* left;
    struct Node* right;
};

// Create a new node
struct Node* createNode(int value) {
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->data = value;
    newNode->left = newNode->right = NULL;
    return newNode;
}

// Insert into BST
struct Node* insert(struct Node* root, int value) {
    if (root == NULL)
        return createNode(value);

    if (value < root->data)
        root->left = insert(root->left, value);
    else
        root->right = insert(root->right, value);

    return root;
}

// Inorder traversal (sorted order)
void inorder(struct Node* root) {
    if (root != NULL) {
        inorder(root->left);
        printf("%d ", root->data);
        inorder(root->right);
    }
}

// Main function
int main() {
    int n, i, value;
    struct Node* root = NULL;

```

```
printf("Enter number of elements: ");
scanf("%d", &n);

printf("Enter elements:\n");
for (i = 0; i < n; i++) {
    scanf("%d", &value);
    root = insert(root, value);
}

printf("Sorted elements:\n");
inorder(root);

return 0;
}
```

```
10v
1  Enter number of elements: 4
2  Enter elements:
3  1
4  2
5  3
6  4
7  Sorted elements:
8  1 2 3 4
9
10 -----
11 (program exited with code: 0)
12 Press return to continue
13
14
15
16
17
18
19
20
21
22
23
24
25
```

Tab 2

