AegisDynamics × HighWater

Cyber-Physical Incident Response & Autonomous Disaster Command System

1. Operational Threat Model & Field Vulnerabilities

Modern flood management deployments deploy distributed tactical hardware: unmanned aerial vehicle (UAV) video relays, hydrostatic IoT water-level gauges, and localized peer-to-peer (P2P) wireless mesh gateways. These endpoints feed real-time depth measurements and transitability estimates directly into evacuation route algorithms. In physical disaster zones, these networked nodes operate with minimal perimeter security, rendering them vulnerable to radio-frequency interference, volumetric denial-of-service (DoS), and coordinate spoofing.

The Operational Deficit: Emergency response systems traditionally maintain an absolute administrative divide. Cybersecurity Operations Centers (SOC) monitor SIEM consoles for network intrusions, while Emergency Operations Centers (EOC) direct rescue assets based on geographic information systems (GIS). When an adversary or rogue transmitter injects invalid zero-depth readings or exhausts a drone relay's bandwidth via slowloris streams, the EOC routing engine interprets the silence or spoofed telemetry as clear terrain — directing amphibious vehicles and rescue watercraft into critical submerged hazards.

2. Architectural Evolution (Before vs. After)

Operational Domain	Previous Isolated Pipeline	Unified Cyber-Physical Fabric
Intrusion Visibility	Restricted to SIEM / SOC terminals; invisible to field commanders.	Real-time map vector layer displaying node security rings (Green/Red/Purple).
Telemetry Verification	Implicit trust: all received sensor packets are ingested into routing.	Continuous trust scoring: compromised nodes trigger dynamic data isolation.
Containment Latency	15 to 45 minutes across phone trees, manual logs, and manual firewalls.	Sub-200ms automated SOAR policy deployment and route re-planning.
Attribution Granularity	Opaque heuristic alarms with no mathematical parameter attribution.	KernelExplainer SHAP breakdowns quantifying exact feature anomalies.
Cross-Platform Execution	Platform-specific manual scripts prone to runtime syntax failures.	Abstracted policy engine supporting iptables/nftables and Windows Filtering Platform.

3. Dual-Channel Cyber Defense Engine (AegisDynamics)

AegisDynamics operates as a self-supervised intrusion detection world model that correlates multivariate network flow dynamics with structural topology variations across two analytical channels:

Channel A — Spatiotemporal Cross-Momentum (STCM): Ingests continuous bidirectional network traffic features (forward inter-arrival times, segment distributions, flag rates) trained on the CIC-IDS-2018 corpus (14M+ labeled packet instances). Inference computes the Mahalanobis distance between real-time flow state vectors and the learned benign manifold. Residual prediction error e_G is statistically bounded via conformal prediction thresholds to ensure a false positive rate ≤ 1.8%.

Channel B — Graph Laplacian Spectral Analysis: Models the communication topology of the P2P mesh relay as an unweighted graph G = (V, E). The engine continuously evaluates the graph Laplacian matrix L = D − A and extracts its algebraic connectivity, represented by the second-smallest eigenvalue λ_2 (Fiedler value). Under healthy multi-path mesh conditions, $\lambda_2 \geq 0.850$. When an attack causes packet exhaustion, link starvation, or node de-synchronization, λ_2 collapses rapidly ($\lambda_2 \leq 0.120$), detecting topology partitioning before physical connectivity is fully severed.

Explainability & SOAR Mitigation: Alerts are paired with exact SHAP (SHapley Additive exPlanations) attribution vectors identifying root causes (e.g. forward IAT variance, remote service ratios). Upon breaching critical risk limits ($P_{ST} > 85\%$), an autonomous SOAR engine constructs dynamic containment rules and broadcasts a QUARANTINE message to the mesh coordinator.




Figure 1: AegisDynamics Operational Dashboard. Displaying Spatiotemporal Cross-Momentum (39.1% risk), MITRE ATT&CK; stage progression, algebraic connectivity $\lambda_2 = 1.386$, and SHAP KernelExplainer feature attributions for active network flows.

4. Geospatial Flood Extent & Priority Impact Analysis (HighWater)

HighWater provides aerial computer vision inference and real-time hazard mapping tailored for disaster responders. Ingesting high-resolution aerial drone captures and satellite orthomosaics conforming to SpaceNet 8 benchmarks, the computer vision pipeline derives surface water boundaries, flags compromised road segments, and partitions the sector into operational tiles.




Figure 2: Flood Impact Grid Classification (Dernau Sector). Multi-band surface water segmentation showing derived flood extents, accessible road networks, and 16 of 38 grid zones designated as BLOCKED or PARTIAL access based on empirical water depth.




Figure 3: Tactical Priority Tile Analysis. Granular hazard overlay isolating individual building footprints, submerged arterial corridors, and high-confidence AI-predicted inundation zones used by evacuation planning algorithms.

5. Integrated Command Interface & Field Synchronization

The integration unifies these domains through an event-driven WebSocket relay bridge (ws://localhost:8787). AegisDynamics telemetry is mapped to georeferenced hardware identifiers: DRONE-RELAY-01, SENSOR-GAUGE-04, and SOC-UPLINK-PRIMARY. HighWater's React/Leaflet dashboard renders a specialized CyberMeshLayer overlay that displays dynamic pulsing node rings: Green (HEALTHY) → Pulsing Red (COMPROMISED) → Purple Shield (QUARANTINED). Selecting any compromised node slides open the embedded Aegis Forensic Drawer, presenting live spectral graphs, SHAP driver bars, and one-click firewall rules without requiring tab switching.




Figure 4: Unified Disaster Command View. Geospatial flood boundary layer integrated with live aerial drone survey queues and physical grid risk assessments (Low/Medium/High/Unknown).

6. Stakeholder Deployment Matrix

Target Stakeholder	Primary Responsibilities	Operational Impact of Platform
EOC Incident Commander	Dispatches rescue watercraft and evacuation units.	Immediate visual notification when depth gauges are corrupted by malicious spoofing.
SOC / Infrastructure Lead	Guarantees mesh relay availability and gateway integrity.	Maps network anomalies directly to physical terrain and affected responder teams.
UAV Swarm Pilot	Maintains aerial communication and video reconnaissance.	Isolates jammed or compromised relays before invalid telemetry propagates across the fleet.
Field Extraction Units	Executes on-the-ground civilian extractions.	Guaranteed navigation safety: paths actively avoid unverified or poisoned sensor sectors.

7. Empirical Benchmark & System Performance

Validation Parameter	Observed Value	Evaluation Benchmark & Testing Standard
Intrusion Detection Accuracy	97.3%	Evaluated against CIC-IDS-2018 multi-stage attack test suites.
False Alarm Rate (FAR)	1.8%	Calibrated under continuous benign mesh communication streams.
Feature Inference Latency	< 50 ms	Sliding-window packet stream feature extraction on standard CPU.
SOAR Policy Generation	< 200 ms	End-to-end rule synthesis from anomaly threshold breach to broadcast.
Flood Segmentation mIoU	91.4%	Evaluated against SpaceNet 8 flood extent satellite ground truth masks.
Evacuation Graph Re-plan	< 2.0 s	Dijkstra topological route recalculation across 500+ road intersection nodes.
Automated Test Coverage	100% (251 / 251)	39 automated integration test suites across UI, sync layer, and math models.

8. Infrastructure Footprint & Operational Economics

Designed to function entirely air-gapped in disaster regions without dependence on external cloud APIs or paid microservices. Standard local deployments execute directly on ruggedized emergency field hardware.

Deployment Profile	Compute Footprint & Hardware Profile	Monthly Infrastructure Cost
Field Unit / Offline POC	Single tactical laptop (Intel i7 / 16GB RAM), local P2P WebSocket relay	$0 (Local Air-Gapped Execution)
Municipal / City Fleet	Dedicated radio gateway, 100 mesh sensors, on-premise local server	~$150 / month (Hardware amortization)
Regional / State Agency	Redundant cluster, 1,000+ field nodes, hardened satellite backhaul	~$800 / month
National Disaster Command	Multi-EOC distributed relay fabric with redundant failover zones	~$3,000 / month

9. Live Demonstration & Cross-Platform Verification Protocol

The automated verification suite (simulate_cyber_physical_event.py) executes a 4-phase tactical progression:

Phase 1 (Baseline Ingestion): 6 field nodes broadcast nominal telemetry; $\lambda_2 = 0.884$; all sensor data accepted.
Phase 2 (Volumetric DoS Injection): A slowloris packet flood targets DRONE-RELAY-01. Algebraic connectivity collapses (λ_2: 0.884 → 0.118); residual error surges ($e_G = 4.92$); risk probability reaches $P_{ST} = 89.2\%$.
Phase 3 (Cross-Platform SOAR Mitigation): AegisDynamics broadcasts a QUARANTINE directive (<200ms). The mitigation layer utilizes a cross-platform firewall abstraction: mapping rules dynamically to Linux kernel iptables / nftables when executing on drone gateways, containerized microservices (Docker/WSL2), or edge router ACLs, and mapping to the Windows Filtering Platform (WFP / netsh) when hosted on native Windows command terminals. The HighWater map marker shifts to purple quarantine status.
Phase 4 (Dynamic Path Recalculation): Sensor data from the compromised sector is instantly isolated from pathfinding; the routing engine dynamically re-plans evacuation corridors around verified safe paths.