

How to give read and write permissions using Unix commands.
A very simple example is to create a text file with a C program,
then use chmod.

Create a file called permission.c

```
#include <stdio.h>
int main()
{
    FILE *fp;
    fp = fopen("sample.txt", "w");
    if (fp == NULL)
    {
        printf("Cannot open file\n");
        return 1;
    }
    fprintf(fp, "Hello, this is a test file.\n");
    fclose(fp);
    printf("File created successfully.\n");
    return 0;
}
```

Compile

gcc permission.c -o permission

Run

./permission

Output

File created successfully.

A file called sample.txt is created.

Check the current permissions

```
ls -l sample.txt
```

You may see

```
-rw-r--r-- 1 user user 31 Aug 17 08:20 sample.txt
```

The owner has: Read + Write

Group has: Read

Others have: Read

This is permission 644.

Give Read and Write permission to everyone

```
chmod 666 sample.txt
```

Check `ls -l sample.txt`

You should see

```
-rw-rw-rw- 1 user user ... sample.txt
```

Instead of numbers, you can directly give:

```
chmod u+rw sample.txt
```

```
chmod o+rw sample.txt
```

```
chmod a+rw sample.txt
```

Task of the Day

- 1) Give Read and Write only to the owner
- 2) Give Read and Write to the owner and group
- 3) Only owner can read and write
- 4) Owner read/write, everyone else read-only
- 5) Owner can do everything, others can only read and execute
- 6) Owner and group can read/write
- 7) Only owner can execute

Fill in the permission numbers for the following:

- 8) Owner: read + write; Group: nothing; Others: nothing
→ _____
- 9) Owner: read + write; Group: read; Others: read →

- 10) Owner: read + write + execute; Group: read + execute;
Others: read + execute → _____
- 11) Owner: read + write; Group: read + write; Others:
nothing → _____
- 12) Everyone: read only → _____

```
alekhya@Alekhya: ~  
alekhya@Alekhya:~$ gedit permission1.c&  
[1] 497  
alekhya@Alekhya:~$  
** (gedit:497): WARNING **: 03:10:59.704: Could not load Peas repository: Typelib file for namespace 'Peas', version '1.0' not found  
  
** (gedit:497): WARNING **: 03:10:59.704: Could not load PeasGtk repository: Typelib file for namespace 'PeasGtk', version '1.0' not found  
^C  
[1]+  Done                  gedit permission1.c  
alekhya@Alekhya:~$ gcc permission1.c -o permssion1  
alekhya@Alekhya:~$ ./permission1  
-bash: ./permission1: No such file or directory  
alekhya@Alekhya:~$ ./permssion1  
File created successfully.  
alekhya@Alekhya:~$ ls  
OS-KLU  OSLab  OSProgram  backspace.c  examplefork.c  fork11.c  hello.c  permission1.c  process  sample.txt  
OSLAB   OSSP   backspace  examplefork  fork11      hello     helloshell  permssion1  process.c  
alekhya@Alekhya:~$ ls -l sample.txt  
-rw-r--r-- 1 alekhya alekhya 28 Aug 17 03:11 sample.txt  
alekhya@Alekhya:~$ chmod 666 sample.txt  
alekhya@Alekhya:~$ ls -l sample.txt  
-rw-rw-rw- 1 alekhya alekhya 28 Aug 17 03:11 sample.txt  
alekhya@Alekhya:~$ chmod 600 sample.txt  
alekhya@Alekhya:~$ ls -l sample.txt  
-rw----- 1 alekhya alekhya 28 Aug 17 03:11 sample.txt  
alekhya@Alekhya:~$ chmod 660 sample.txt  
alekhya@Alekhya:~$ ls -l sample.txt  
-rw-rw---- 1 alekhya alekhya 28 Aug 17 03:11 sample.txt  
alekhya@Alekhya:~$ |
```