

1. The Absolute Essentials

`cy.visit()` - Navigates the browser to a specific URL. This is almost always the first command in a test.

example:

```
cy.visit('https://www.google.com');

// You can also visit a relative path if you set a
`baseUrl` in your cypress.config.js
// If baseUrl is "http://localhost:3000"

cy.visit('/login');

// Will go to http://localhost:3000/login

cy.visit('https://www.gmail.com/login');
```

`cy.get()` - Gets one or more DOM elements by a CSS selector. This is the primary way you select elements to interact with.

example:

```
// Get an element by its ID

cy.get('#main-header');
cy.get('#canvas');

// Get all elements with a class

cy.get('.list-item');
cy.get('button.submit');

// Get an input element by its attribute

cy.get('input[name="password"]');
cy.get('input[name="email"]');
```

2. Finding Elements (Querying)

`cy.contains()` - Gets an element that contains specific text. This is great for finding buttons, links, or labels in a more user-friendly way.

example:

```
// Find any element with the text "Submit"

cy.contains('Submit');
cy.contains('payment');

// Find a button that contains the text "Add to
  Cart"

cy.get('button').contains('Add to Cart');
cy.get('button').contains('sign in');
```

3. Interacting with Elements (Actions)

`cy.click()` - Clicks on a DOM element.

example:

```
cy.get('button.submit').click();
cy.get('textbutton.hotdeals').click();

// Click on the top-left corner of an element

cy.get('#canvas').click('topLeft');

// Click on multiple elements

cy.get('input[type="checkbox"]').click({ multiple:
  true });
cy.get('input[type="radio"]').click();
```

`cy.type()` - Types text into an input, textarea, or any focusable element.

example:

```
cy.get('#email-input').type('my.email@domain.com');
cy.get('#firstname-input').type('shamili');

// You can also type special key combinations

cy.get('#search').type('Hello, World{enter}');

// Types text and presses Enter
```

```
cy.get('#search').type('what is cypress{enter}');
```

`cy.clear()` - Clears the value of an input or textarea.

example:

```
cy.get('#email-input').type('some text').clear();  
  
// Now the input is empty  
  
cy.get('#search').type('what is cypress').clear();
```

`cy.select()` - Selects an <option> within a <select> dropdown.

example:

```
// Select by the value attribute  
  
cy.get('select.country-selector').select('USA');  
cy.get('select.etinicity-selector').select('south-asian');  
  
// Select by the text content  
  
cy.get('select.country-selector').select('Canada');  
cy.get('select.gender-selector').select('female');
```

`cy.check()` & `cy.uncheck()` - Checks or unchecks a checkbox or radio button.

example:

```
// Check a single checkbox  
  
cy.get('input[type="checkbox"]').check();  
cy.get('input[type="radio"]').check('keep me logged in');  
  
// Uncheck it  
  
cy.get('input[type="checkbox"]').uncheck();
```

```
cy.get('input[type="checkbox"]').unchecked('notifications');
```

```
// Check a radio button by its value
```

```
cy.get('input[type="radio"]').check('admin');
```

4. **Assertions (Verifying Behavior)** - Assertions are the most important part of a test they verify that your application is in the correct state. All assertions use the `.should()` command.

`.should()` - Creates an assertion. It's always chained off another command, like `cy.get()`.

Common Assertions:

`be.visible` - Asserts that the element is visible on the page.

example:

```
cy.get('.error-message').should('be.visible');  
cy.get('.username').should('be.visible');
```

`not.exist` - Asserts that the element is not in the DOM.

example:

```
cy.get('.success-modal').should('not.exist');  
cy.get('.login').should('not.exist');
```

`include.text` - Asserts that the element's text contains a substring.

example:

```
cy.get('p').should('include.text', 'successfully');  
cy.get('#xyz').should('include.text', 'shamili');
```

`have.class` - Asserts that the element has a specific CSS

class.

example:

```
cy.get('button').should('have.class', 'btn-  
primary');  
cy.get('textbox').should('have.class', 'txb-  
primary');
```

have.value - Asserts that an input element has a specific value.

example:

```
cy.get('input[name="email"]').should('have.value',  
  'my.email@domain.com');  
cy.get('input[neme="fstname"]').shoud('have.value',  
  'shamili');
```

be.disabled / be.enabled - Checks if a button or input is disabled.

example:

```
cy.get('button.submit').should('be.disabled');  
cy.get('button').contains('place order')  
  .should('be.disabled');
```

5. Browser and Page Commands

cy.url() - Gets the current URL of the page. You typically chain **.should()** off it.

example:

```
// Asserts the URL contains '/dashboard'  
  
cy.url().should('include', '/dashboard');
```

cy.title() - Gets the title of the current page (<title> tag).

example:

```
// 'eq' means 'equal to'

cy.title().should('eq', 'My App | Dashboard');
```

`cy.reload()` - Reloads the page, just like the browser's refresh button.

example:

```
cy.reload();
```

A Complete, Simple Example

example 1:

```
// File: cypress/e2e/login_spec.cy.js

describe('Login Page', () => {
  it('should allow a user to log in and see the
  dashboard', () => {

    // 1. Visit the login page

    cy.visit('/login');

    // 2. Find the email input, type in it, and check
    its value

    cy.get('input[name="email"]')
      .type('testuser@example.com')
      .should('have.value', 'testuser@example.com');

    // 3. Find the password input and type in it

    cy.get('input[name="passwd"]').type('xyz');

    // 4. Find the "Log In" button and click it

    cy.get('button').contains('Log In').click();

    // 5. Assert that the URL has changed to the
    dashboard
```

```

    cy.url().should('include', '/dashboard');

    // 6. Assert that the dashboard welcome message is
    //     visible

    cy.get('h1').should('have.text', 'Welcome, Test
                                User!');
  });
});

```

example 2:

```

// A test is written inside a describe() block

describe('My First Test', () => {

  // An individual test case is written with it()
  it('Visits the kitchen sink and finds an element', () =>
  {

    // 1. Visit a web page

    cy.visit('https://example.cypress.io');

    // 2. Query for an element by its CSS selector

    cy.contains('type');

    // 3. Click on that element

    cy.contains('type').click();

    // 4. Assert that the URL is now correct

    cy.url().should('include', '/commands/actions');

    // 5. Get an input, type into it, and assert the
    //     value

    cy.get('.action-email')
      .type('fake@email.com')
      .should('have.value', 'fake@email.com');
  });
});

```
