

CSE 546 HW #notes

Sam Kowash

October 11, 2018

(1) LASSO

Selects for sparse predictor w . We may want this either for efficiency or human-legibility. How do we do this? Well, greedy approach adds features one at a time based on improvement in test error, but that's pretty hacky. How do we know when to stop? How do we avoid just including a billion features?

Looking for sparse results is a type of regularization; we want to penalize feature overselection. This motivates the lasso objective:

$$\hat{w}_{lasso} = \arg \min_w \sum_{i=1}^n (y_i - x_i^T w)^2 + \lambda \|w\|_1. \quad (1.1)$$

This punishes big vectors w , which is what we want. Fact: for any $\lambda \geq 0$ for which \hat{w}_r finds the minimum, there exists $\nu \geq 0$ such that

$$\hat{w}_r = \arg \min_w \sum_{i=1}^n (y_i - x_i^T w)^2 \text{ subject to } r(w) \leq \nu. \quad (1.2)$$

That is, regularized regression problems can always be reframed as constrained optimization.




Figure 1.1: Lasso on left, ridge on right; lasso prefers solutions along coordinate axes (i.e. sparse)

If we incorporate an offset,

$$\hat{w}, \hat{b} = \arg \min_{w, b} \sum_{i=1}^n (y_i - (x_i^T w + b))^2 + \lambda \|w\|_1, \quad (1.3)$$

but joint optimization is a pain, so let's prefer to de-mean our data. This is still actually kind of tricky minimization; the 1-norm isn't differentiable at the origin and this complicates things. Do by coordinate descent, minimize one direction at a time. This is guaranteed to approach the optimum for lasso (which is nice), but how do we pick our order of coordinate descent? Options,

- Random each time
- Round robin
- Try to pick “important” coordinates (biases us).

Let's see an example. Take $j \in \{1, \dots, d\}$.

$$\sum_{i=1}^n (y_i - x_i^T w)^2 + \lambda \|w\|_1 = \sum_{i=1}^n \left(y_i - \sum_{k=1}^d x_{i,k} w_k \right)^2 + \lambda \sum_{k=1}^d |w_k| \quad (1.4)$$

$$= \sum_{i=1}^n \left(\left(y_i - \sum_{k \neq j} x_{i,k} w_k \right) - x_{i,j} w_j \right)^2 + \lambda \sum_{k \neq j} |w_k| + \lambda |w_j|. \quad (1.5)$$

So set $\hat{w}_k = 0$ for $k \in \{1, \dots, d\}$ and loop over points:

$$r_i^{(j)} = \sum_{k \neq j} x_{i,k} \hat{w}_k \quad (1.6)$$

$$\hat{w}_j = \arg \min_{w_j} \sum_{i=1}^n \left(r_i^{(j)} - x_{i,j} w_j \right)^2 + \lambda |w_j|. \quad (1.7)$$

Pulling out one 1-d problem at a time! Works b/c lasso objective is *separable*. Except...this isn't actually a lot better. Hard to optimize because of pointy bit. Need to extend some concept of derivative and convexity. Traditional definition for fn is that lines b/t points on $f(x)$ lie above $f(x)$ (epigraph is convex). We need a different one here:

$$f(y) \geq f(x) + \nabla f(x)^T (y - x) \quad \forall x, y \quad (1.8)$$

This amounts to saying that there's a “supporting hyperplane” touching the epigraph at x such that the epigraph lies entirely on one side of the plane. If the function is differentiable at x , this is going to be the tangent plane. If not, we may have *many* options, and these are called *subgradients* (denoted ∂_{w_j} for subgradient set at w_j). We call differentiable functions extremized at x where $\nabla f(x) = 0$, and similarly we will call other functions extremized when $f(x)$ admits 0 as a subgradient at x .

OK, so how do we actually take subgradients and set them to zero? Consider example,

$$\partial_{w_j} \left(\sum_{i=1}^n \left(r_i^{(j)} - x_{i,j} w_j \right)^2 + \lambda |w_j| \right) = \begin{cases} a_j w_j - c_j - \lambda & \text{if } w_j < 0 \\ [-c_j - \lambda, -c_j + \lambda] & \text{if } w_j = 0 \\ a_j w_j - c_j + \lambda & \text{if } w_j > 0 \end{cases}, \quad (1.9)$$

where

$$a_j = \left(\sum_{i=1}^n x_{i,j}^2 \right), \quad c_j = 2 \left(\sum_{i=1}^n r_i^{(j)} x_{i,j} \right). \quad (1.10)$$

This tells us how to do our minimization (look for regime that contains zero as subgrad):

$$\hat{w}_j = \begin{cases} \frac{c_j + \lambda}{a_j} & \text{if } c_j < -\lambda \\ 0 & \text{if } |c_j| \leq \lambda \\ \frac{c_j - \lambda}{a_j} & \text{if } c_j > \lambda \end{cases} \quad (1.11)$$

where, recall,

$$a_j = \sum_{i=1}^n x_{i,j}^2 \qquad c_j = 2 \sum_{i=1}^n \left(y_i - \sum_{k \neq j} x_{i,k} w_k \right) x_{i,j}. \quad (1.12)$$

This central flattening behavior provides “soft thresholding”; can make predictor entries identically zero depending on strength of regularization.

(2) Classification problems

Different from regression! Same principles though. Need a loss function; what is? Let’s start with binary classification, want to learn $f : X \rightarrow Y$ where X contains features, $Y \in \{0, 1\}$ is target class. Natural loss is 0/1 function: $\mathbf{1}\{f(X) \neq Y\}$. Expected loss is then

$$\mathbb{E}_{XY} [\mathbf{1}\{f(X) \neq Y\}] = \mathbb{E}_X [\mathbb{E}_{Y|X} [\mathbf{1}\{f(x) \neq Y\} \mid X = x]] \quad (2.1)$$

$$= \mathbb{E}_X \left\{ \mathbf{1}\{f(x) = 1\} \mathbb{P}(Y = 0 \mid X = x) + \mathbf{1}\{f(x) = 0\} \mathbb{P}(Y = 1 \mid X = x) \right\}. \quad (2.2)$$

Supposing we know $P(Y \mid X)$, the Bayes optimal classifier is

$$f(x) = \arg \max_y \mathbb{P}(Y = y \mid X = x). \quad (2.3)$$