Simba™ SP609A 全氟化彈性體密封件 Perfluoroelastomer

equator®

耐高溫、電漿氣體，泛用型高潔淨型產品

High-temperature resistant, plasma gas, versatile and high-purity products.

- 適合使用在嚴苛的電漿環境，針對O2、CF4、H2等多種特殊氣體有非常優異的抵抗表現，不論是在動態件或是靜態件上的應用，例如Slit Valve , Chamber Lid , Gate Valve等都可以完美的對應

  Suitable for use in harsh plasma environments, with excellent resistance to various special gases such as O2, CF4, H2 etc. Whether in dynamic components or static components, such as Slit Valve, Chamber Lid, Gate Valve, etc., they can all be perfectly matched.

- 在高溫環境下，依然有優異的密封表現

  Even in high-temperature environments, it maintains excellent sealing performance.

特性與優點 FEATURE

對於電漿環境有良好的耐受性
Resistant to plasma

良好的不沾粘性
Good non-stick characteristics

低的元素析出性
Low level of extractable trace elements

對各式化學溶劑有極優良的抗性
Excellent resistance to solvents and chemicals

典型物理特性 PROPERTY

硬度(Shore A)	73
顏色(Color)	Amber Black
模數(100 % Modulus , Mpa)	3
拉伸強度(Tensile strength at Break, Mpa)	21
延伸率(Elongation at Break, %)	250
壓縮變形率(Compression set 70 hr @ 200℃)	8.6
建議最高連續使用溫度(Temp. ,℃)	320

建議應用位置 APPLIED POSITION

反應槽密封件(Chamber Seals)
管線接頭密封件(Fitting Seals)
氣體管線密封件(Gas Inlet/Outlet Pumping Line Seals)
閥件密封件(Valve Seals)
閥門開關(Slit valve doors)

建議應用製程 APPLIED PROCESS

乾式蝕刻(Dry Etch)
濕式蝕刻(Wet Etch Acid,Base)
薄膜沉積(Thin-Film)
擴散(Diffusion)
離子植入(Ion Implant)
快速回火(RTP)
濕式去光阻(Wet Stripping Solvents)
濕式清潔(Wet Cleaning UPDI)

equator®
www.eqoring.com
RunSea Technology Co. Ltd
TEL : 886-3-5640969
FAX : 886-3-5640799
E-MAIL : info@runsea-t.com
Copyright © 2024 Equator Performance Elastomers. All Rights Reserved.