

test

kowodo

September 20, 2015

Contents

1	Blbnuti	1
2	.emacs	2
3	nìjaký pøeklad	3
4	ditaa	5

1 Blbnuti

$$x = \sqrt{b} \tag{1}$$

If $a^2 = b$ and $b = 2$, then the solution must be either

$$a = +\sqrt{2}$$

or

$$a = -\sqrt{2}$$

.

$\beta \Omega$
Ahoj_{dole} Ahoj_{dole} Ahoj^{nahore} Ahoj^{nahore}
Best site I have ever seen
Neljepsi stranka co znam

2 .emacs

```
(require 'package)
(add-to-list 'package-archives
              '("melpa" . "http://melpa.org/packages/") t)
(when (< emacs-major-version 24)
  ;; For important compatibility libraries like cl-lib
  (add-to-list 'package-archives '("gnu" . "http://elpa.gnu.org/packages/")))
(package-initialize)

;;
;; helm mode
;;
(require 'helm)
(require 'helm-config)

;; The default "C-x c" is quite close to "C-x C-c", which quits Emacs.
;; Changed to "C-c h". Note: We must set "C-c h" globally, because we
;; cannot change 'helm-command-prefix-key' once 'helm-config' is loaded.
(global-set-key (kbd "C-c h") 'helm-command-prefix)
(global-unset-key (kbd "C-x c"))

(define-key helm-map (kbd "<tab>") 'helm-execute-persistent-action) ; rebind tab to run
(define-key helm-map (kbd "C-i") 'helm-execute-persistent-action) ; make TAB works in t
(define-key helm-map (kbd "C-z") 'helm-select-action) ; list actions using C-z

(when (executable-find "curl")
  (setq helm-google-suggest-use-curl-p t))

(setq helm-split-window-in-side-p      t ; open helm buffer inside current window
      helm-move-to-line-cycle-in-source t ; move to end or beginning of source when
      helm-ff-search-library-in-sexp   t ; search for library in 'require' and 'd
      helm-scroll-amount                8 ; scroll 8 lines other window using M-<n
      helm-ff-file-name-history-use-recentf t)

(helm-mode 1)

;;
;; ace jump mode major function
```

```
;;

(eval-after-load "org"
  '(define-key org-mode-map "\C-c " 'nil)) ; unmap key, was org-table-blank-field

(add-to-list 'load-path "~/.emacs.d/elpa/ace-jump-mode-20140616.115")
(autoload
  'ace-jump-mode
  "ace-jump-mode"
  "Emacs quick move minor mode"
  t)
;; you can select the key you prefer to
(define-key global-map (kbd "C-c SPC") 'ace-jump-mode)

;;
;; enable a more powerful jump back function from ace jump mode
;;
(autoload
  'ace-jump-mode-pop-mark
  "ace-jump-mode"
  "Ace jump back:-)"
  t)
(eval-after-load "ace-jump-mode"
  '(ace-jump-mode-enable-mark-sync))
(define-key global-map (kbd "C-x SPC") 'ace-jump-mode-pop-mark)
```

3 nìjaký pøeklad

1. Jedu vlakem.
2. Ztratil jsem vlak.
3. Ztratil jsem se ve vlaku.
4. Ztratil jsem se v autì.
5. Ztratil jsem se s autem.
6. Ztratil jsem auto.
7. Ztratil jsem letadlo.

8. Ztratil jsem se v letadle.
9. Ztratil jsem se s letadlem.
10. Ztracen cestou do autobusu.
11. Ztracen s autobusem.
12. Ztracen v autobusu.
13. Ztracený autobus.
14. Zatracený kamarád.
15. Zatracený pas dej kamarádovi.
16. Budiž zatracen i s kamarádem.
17. Zatracen pro kamaráda.
18. Ztracen kamarádovi.
19. Zaklínadlo o kamarádovi.
20. Ztracen bez kamaráda.
21. Ztracená kamarádka.
22. Zaklínadlo o kamarádce.
23. Obřetování bez kamarádky.
24. Rituál s kamarádkou.
25. Drogy dejte ke kamarádce.
26. Jehla v paži s kamarádkou.

4 ditaa



Hello World!