

# Package ‘tempted’

May 10, 2023

**Type** Package

**Title** Temporal Tensor Decomposition, a Dimensionality Reduction Tool for Longitudinal Multivariate Data

**Version** 0.1.0

**Depends** R (>= 4.2.0), np (>= 0.60-17), ggplot2 (>= 3.4.0), methods (>= 4.2.1)

**Author** Pixu Shi

**Maintainer** Pixu Shi <pixu.shi@duke.edu>

**Description** A dimension reduction method for multivariate longitudinal data. It formats the data into a temporal tensor, with three modes representing subject, feature, and continuous time, respectively. The tensor is then decomposed into a summation of low-dimensional components, each consisting of a subject loading vector, a feature loading vector, and a temporal loading function. These loadings provide low-dimensional representation of subjects or samples, and can be used to identify features associated with clusters of subjects or samples. TEMPTED provides the flexibility of allowing subjects to have different temporal sampling, so time points do not need to be binned and missing time points do not need to be imputed.

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.2.3

## R topics documented:

aggregate_feature . . . . .	2
bernoulli_kernel . . . . .	3
count_table . . . . .	4
est_test_subject . . . . .	4
format_tempted . . . . .	5
meta_table . . . . .	6
plot_feature_summary . . . . .	7
plot_metafeature . . . . .	8
plot_time_loading . . . . .	9
processed_table . . . . .	9
ratio_feature . . . . .	10
svd_centralize . . . . .	11
tdenoise . . . . .	12
tempted . . . . .	12
tempted_all . . . . .	14

---

aggregate_feature	Aggregate features using feature loadings
-------------------	---

---

## Description

This function aggregate the features into "meta features" by calculating a weighted summation of the features using feature loading of each component as weights. It can also aggregate features by using the combination of multiple components by ranking the features by a linear combination of feature loadings from multiple components.

## Usage

```
aggregate_feature(
  res_tempted,
  mean_svd = NULL,
  datlist,
  pct = 1,
  contrast = NULL
)
```

## Arguments

res_tempted	Output of <a href="#">tempted</a> .
mean_svd	Output of <a href="#">svd_centralize</a> .
datlist	Output of <a href="#">format_tempted</a> , the original temporal tensor that will be aggregated.
pct	The percent of features to aggregate, features ranked by absolute value of the feature loading of each component. Default is 1, which means 100% of features are aggregated. Setting pct=0.01 means top 1% of features is aggregated, where features are ranked in absolute value of feature loading of each component.
contrast	A matrix choosing how components are combined, each column is a contrast of length r and used to calculate the linear combination of the feature loadings of r components.

## Value

A list of results.

**metafeature\_aggregate** The meta feature obtained by aggregating the observed temporal tensor. It is a data.frame with four columns: "value" for the meta feature values, "subID" for the subject ID, "timepoint" for the time points, and "PC" indicating which component was used to construct the meta feature.

**metafeature\_aggregate\_est** The meta feature obtained by aggregating the denoised temporal tensor. It has the same structure as metafeature\_aggregate.

**contrast** The contrast used to linearly combine the components from input.

**toppct** A matrix of TRUE/FALSE indicating which features are aggregated in each component and contrast.

**Examples**

```

datlist <- format_tempted(count_table,
                          meta_table$day_of_life,
                          meta_table$studyid,
                          pseudo=0.5,
                          transform="clr")

mean_svd <- svd_centralize(datlist, r=1)

res_tempted <- tempted(mean_svd$datlist, r=3, smooth=1e-5)

datalist_raw <- format_tempted(count_table,
                              meta_table$day_of_life,
                              meta_table$studyid,
                              transform="none")

contrast <- cbind(c(1/2,1,0), c(1/2,-1,0))

res_aggregate <- aggregate_feature(res_tempted,
                                   mean_svd,
                                   datlist,
                                   pct=1,
                                   contrast=contrast)

group <- unique(meta_table[, c("studyid", "delivery")])

plot_metafeature(res_aggregate$metafeature_aggregate, group, bws=30)

```

bernoulli\_kernel

*Calculate the Bernoulli kernel***Description**

This function is used to calculate the kernel matrix for the RKHS regression that iteratively updates the temporal loading function.

**Usage**

```
bernoulli_kernel(x, y)
```

**Arguments**

`x, y` Two values between which the Bernoulli kernel is calculated.

**Value**

The calculated kernel between `x` and `y`.

---

count_table	<i>OTU read count table from the ECAM data</i>
-------------	--

---

### Description

OTU read count table from the ECAM data

### Usage

```
count_table
```

### Format

A data.frame with rows representing samples and matching with data.frame meta\_table and columns representing microbial features (i.e. OTUs). Each entry is a read count.

### Source

Bokulich, Nicholas A., et al. "Antibiotics, birth mode, and diet shape microbiome maturation during early life." Science translational medicine 8.343 (2016): 343ra82-343ra82.

---

est_test_subject	<i>Estimate subject loading of testing data</i>
------------------	---

---

### Description

This function estimates the subject loading of the testing data based on feature and temporal loading from training data, so that both the testing data and training data have the same dimensionality reduction.

### Usage

```
est_test_subject(datlist, res_tempted, mean_svd = NULL)
```

### Arguments

datlist	Testing data formatted into datlist in the same fashion as the training data. The same transformation needs to be used for both training and testing data.
res_tempted	Result from <a href="#">tempted</a> ran on the training data.
mean_svd	Result from <a href="#">svd_centralize</a> ran on the training data.

### Value

estimated subject loading of testing data

## Examples

```
# split the example data into training and testing

id_test <- meta_table$studyid=="1"

count_train <- count_table[!id_test,]
meta_train <- meta_table[!id_test,]

count_test <- count_table[id_test,]
meta_test <- meta_table[id_test,]

# run tempted on training data

datlist_train <- format_tempted(count_train,
                                meta_train$day_of_life,
                                meta_train$studyid,
                                threshold=0.95,
                                pseudo=0.5,
                                transform="clr")

mean_svd_train <- svd_centralize(datlist_train, r=1)

res_tempted_train <- tempted(mean_svd_train$datlist,
                             r=3, smooth=1e-5)

# get the overlapping features

count_test <- count_test[,rownames(datlist_train[[1]])[-1]]

datlist_test <- format_tempted(count_test,
                                meta_test$day_of_life,
                                meta_test$studyid,
                                threshold=1,
                                pseudo=0.5,
                                transform="clr")

# estimate the subject loading of the testing subject

sub_test <- est_test_subject(datlist_test, res_tempted_train, mean_svd_train)
```

---

format\_tempted

*Format data table into the input of tempted*


---

## Description

This function applies a variety of transformations to the read counts and format the sample by feature table and meta data into a data list that can be used as the input of [tempted](#) and [svd\\_centralize](#). For data that are not read counts, or data that are not microbiome data, the user can apply their desired transformation to the data before formatting into list.

## Usage

```
format_tempted(
  featuretable,
```

```
    timepoint,  
    subjectID,  
    threshold = 0.95,  
    pseudo = NULL,  
    transform = "clr"  
  )
```

**Arguments**

featuretable	A sample by feature matrix.
timepoint	The time stamp of each sample, matched with the rows of featuretable.
subjectID	The subject ID of each sample, matched with the rows of featuretable.
threshold	A threshold for feature filtering for microbiome data. Features with zero value percentage > threshold will be excluded. Default is 0.95.
pseudo	A small number to add to all the counts before normalizing into proportions and log transformation. Default is 1/2 of the smallest non-zero value that is specific for each sample. This pseudo count is added for transform=c("logcomp", "clr", "logit").
transform	The transformation applied to the data. "logcomp" for log of compositions. "comp" for compositions. "ast" for arcsine squared transformation. "clr" for central log ratio transformation. "logit" for logit transformation. "none" for no transformation. Default transform="clr" is recommended for microbiome data. For data that are already transformed, use transform="none".

**Value**

A length n list of matrices as the input of [tempted](#) and [svd\\_centralize](#). Each matrix represents a subject, with columns representing samples from this subject, the first row representing the sampling time points, and the following rows representing the feature values.

**See Also**

Examples can be found in [tempted](#).

---

meta_table	<i>Meta data table from the ECAM data</i>
------------	---

---

**Description**

Meta data table from the ECAM data

**Usage**

```
meta_table
```

**Format**

A data.frame with rows representing samples and matching with data.frame count\_table and processed\_table and three columns:

**studyid** character denoting the subject ID of the infants.

**delivery** character denoting the delivery mode of the infants.

**day\_of\_life** character denoting the age of infants measured in days when microbiome sample was taken.

**Source**

Bokulich, Nicholas A., et al. "Antibiotics, birth mode, and diet shape microbiome maturation during early life." Science translational medicine 8.343 (2016): 343ra82-343ra82.

---

plot_feature_summary	<i>Plot nonparametric smoothed mean and error bands of features versus time</i>
----------------------	---

---

**Description**

This is a handy function to plot the smoothed mean and error bands for multiple features.

**Usage**

```
plot_feature_summary(
  feature_mat,
  time_vec,
  group_vec,
  coverage = 0.95,
  bws = NULL,
  nrow = 1
)
```

**Arguments**

feature_mat	A sample by feature matrix. Each feature will be plotted separately as a facet. The features can be original features, meta features, log ratios, or any variables of interest.
time_vec	A vector of time points matched to the rows of feature_mat.
group_vec	A vector of factor variable indicating the group membership of samples matched to the rows of feature_mat.
coverage	The coverage rate for the error band. Default is 0.95.
bws	The smoothness parameter for the smoothing lines and error bands. A larger value means a smoother line. Default is NULL and calculated by function np::npreg().
nrow	The number of rows to plot the features used in function ggplot2::facet_wrap().

**Value**

A ggplot2 object.

## Examples

```
# plot the summary of selected features

feat.names <- c("OTU4447072", "OTU4467447")

proportion_table <- count_table/rowSums(count_table)

plot_feature_summary(proportion_table[, feat.names],
                     meta_table$day_of_life,
                     meta_table$delivery,
                     bws=30)
```

---

plot_metafeature	<i>Plot nonparametric smoothed mesan and error bands of meta features versus time</i>
------------------	---

---

## Description

This function plot the smoothed mean and error band of meta features grouped by a factor variable provided by the user.

## Usage

```
plot_metafeature(metafeature, group, coverage = 0.95, bws = NULL, nrow = 1)
```

## Arguments

metafeature	It can be metafeature_ratio from the output of <a href="#">ratio_feature</a> and <a href="#">tempted_all</a> , metafeature_aggregate from the output of <a href="#">ratio_feature</a> and <a href="#">tempted_all</a> , or metafeature_aggregate_est from the output of <a href="#">ratio_feature</a> .
group	A subject by 2 data.frame with the first column for subject ID and second column for group membership.
coverage	The coverage rate for the error band. Default is 0.95.
bws	The smoothness parameter for the smoothing lines and error bands. A larger value means a smoother line. Default is NULL and calculated by function <code>np::npreg()</code> .
nrow	The number of rows to plot the features used in function <code>ggplot2::facet_wrap()</code> .

## Value

A ggplot2 object.

## See Also

Examples can be found in [tempted\\_all](#), [ratio\\_feature](#) and [aggregate\\_feature](#).



---

plot_time_loading	<i>Plot the temporal loading functions</i>
-------------------	--

---

**Description**

This function uses `ggplot2::geom_line()` in `ggplot2` to plot the temporal loading functions from [tempted](#).

**Usage**

```
plot_time_loading(res, r = NULL, ...)
```

**Arguments**

<code>res</code>	Output of function <a href="#">tempted</a> .
<code>r</code>	The number of components to plot. By default all the components estimated by <a href="#">tempted</a> will be plotted.
<code>...</code>	Arguments to put in <code>ggplot2::geom_line(aes(...))</code> .

**Value**

An `ggplot2` object.

**See Also**

Examples can be found in [tempted\\_all](#) and [tempted](#).

---

processed_table	<i>Central-log-ratio (clr) transformed OTU table from the ECAM data</i>
-----------------	---

---

**Description**

Central-log-ratio (clr) transformed OTU table from the ECAM data

**Usage**

```
processed_table
```

**Format**

A `data.frame` with rows representing samples and matching with `data.frame meta_table` and columns representing microbial features (i.e. OTUs). Entries do not need to be transformed, and will be directly used by [tempted](#). This `data.frame` is used to illustrate how [tempted](#) can be used for general form of multivariate longitudinal data already preprocessed by user.

**Source**

Bokulich, Nicholas A., et al. "Antibiotics, birth mode, and diet shape microbiome maturation during early life." *Science translational medicine* 8.343 (2016): 343ra82-343ra82.

---

ratio_feature	<i>Take log ratio of the abundance of top features over bottom features</i>
---------------	---

---

## Description

Top and bottom ranking features are picked based on feature loadings (and their contrasts). The log ratio abundance of the top ranking features over the bottom ranking features is produced as the main result. This function and its result is designed for longitudinal microbiome data, and may not be meaningful for other type of temporal data.

## Usage

```
ratio_feature(
  res_tempted,
  datlist,
  pct = 0.05,
  absolute = FALSE,
  contrast = NULL
)
```

## Arguments

res_tempted	Output of <a href="#">tempted</a> .
datlist	Output of <code>format_tempted(, transform="none")</code> , the temporal tensor that include the raw read counts.
pct	The percent of features to sum up. Default is 0.05, i.e. 5%.
absolute	<code>absolute = TRUE</code> means features are ranked by the absolute value of feature loadings, and the top pct percent of features are picked. <code>absolute = FALSE</code> means features are ranked by the original value of feature loadings, and the top and bottom pct percent of features are picked. Then ratio is taken as the abundance of the features with positive loading over the abundance of the features with negative loading.
contrast	A matrix choosing how components are combined, each column is a contrast of length r and used to calculate the linear combination of the feature loadings of r components.

## Value

A list of results:

**metafeature\_ratio** The log ratio abundance of the top over bottom ranking features. It is a `data.frame` with five columns: "value" for the log ratio values, "subID" for the subject ID, and "timepoint" for the time points, and "PC" indicating which component was used to construct the meta feature.

**contrast** The contrast used to linearly combine the components from input.

**toppct** A matrix of TRUE/FALSE indicating which features are ranked top in each component (and contrast) and used as the numerator of the log ratio.

**bottompct** A matrix of TRUE/FALSE indicating which features are ranked bottom in each component (and contrast) and used as the denominator of the log ratio.

## Examples

```

datlist <- format_tempted(count_table,
                          meta_table$day_of_life,
                          meta_table$studyid,
                          pseudo=0.5,
                          transform="clr")

mean_svd <- svd_centralize(datlist, r=1)

res_tempted <- tempted(mean_svd$datlist, r=3, smooth=1e-5)

datalist_raw <- format_tempted(count_table, meta_table$day_of_life, meta_table$studyid,
                              transform="none")

contrast <- cbind(c(1,1,0), c(1,-1,0))

res_ratio <- ratio_feature(res_tempted, datalist_raw, pct=0.1,
                          absolute=FALSE, contrast=contrast)

group <- unique(meta_table[, c("studyid", "delivery")])

plot_metafeature(res_ratio$metafeature_ratio, group, bws=30)

```

svd\_centralize

*Remove the mean structure of the temporal tensor*

## Description

This function first average the feature value of all time points for each subject to form a subject by feature matrix. Next, it performs a singular value decomposition of this matrix and construct the matrix's rank-r approximation. Then, it subtracts this rank-r subject by feature matrix from the temporal tensor.

## Usage

```
svd_centralize(datlist, r = 1)
```

## Arguments

<b>datlist</b>	A length n list of matrices. Each matrix represents a subject, with columns representing samples from this subject, the first row representing the sampling time points, and the following rows representing the feature values.
<b>r</b>	The number of ranks in the mean structure. Default is 1.

## Value

A list of results.

**datlist** The new temporal tensor after mean structure is removed.

**A\_tilde** The subject singular vector of the mean structure, a subject by r matrix.

**B\_tilde** The feature singular vector of the mean structure, a feature by r matrix.

**lambda\_tilde** The singular value of the mean structure, a length r vector.

**See Also**

Examples can be found in [tempted](#).

---

<code>tdenoise</code>	<i>Calculate the de-noised temporal tensor</i>
-----------------------	--

---

**Description**

This function constructs a de-noised version of the temporal tensor using the low-rank components obtained by [svd\\_centralize tempted](#) and uses the loadings to

**Usage**

```
tdenoise(res_tempted, mean_svd = NULL)
```

**Arguments**

- `res_tempted`      Output of [tempted](#)
- `mean_svd`        Output of [svd\\_centralize](#)

**Value**

The de-noised functional tensor

---

<code>tempted</code>	<i>Decomposition of temporal tensor</i>
----------------------	---

---

**Description**

This is the main function of [tempted](#).

**Usage**

```
tempted(  
  datlist,  
  r = 3,  
  smooth = 1e-06,  
  interval = NULL,  
  resolution = 101,  
  maxiter = 20,  
  epsilon = 1e-04  
)
```

## Arguments

<code>datlist</code>	A length <code>n</code> list of matrices. Each matrix represents a subject, with columns representing samples from this subject, the first row representing the sampling time points, and the following rows representing the feature values.
<code>r</code>	Number of components to decompose into, i.e. rank of the CP type decomposition. Default is set to 3.
<code>smooth</code>	Smoothing parameter for RKHS norm. Larger means smoother temporal loading functions. Default is set to be $1e-8$ . Value can be adjusted depending on the dataset by checking the smoothness of the estimated temporal loading function in plot.
<code>interval</code>	The range of time points to ran the decomposition for. Default is set to be the range of all observed time points. User can set it to be a shorter interval than the observed range.
<code>resolution</code>	Number of time points to evaluate the value of the temporal loading function. Default is set to 101. It does not affect the subject or feature loadings.
<code>maxiter</code>	Maximum number of iteration. Default is 20.
<code>epsilon</code>	Convergence criteria for difference between iterations. Default is $1e-4$ .

## Value

The estimations of the loadings.

**A\_hat** Subject loading, a subject by `r` matrix.

**B\_hat** Feature loading, a feature by `r` matrix.

**Phi\_hat** Temporal loading function, a resolution by `r` matrix.

**time\_Phi** The time points where the temporal loading function is evaluated.

**Lambda** Eigen value, a length `r` vector.

**r\_square** Variance explained by each component. This is the R-squared of the linear regression of the vectorized temporal tensor against the vectorized low-rank reconstruction using individual components.

**accum\_r\_square** Variance explained by the first few components accumulated. This is the R-squared of the linear regression of the vectorized temporal tensor against the vectorized low-rank reconstruction using the first few components.

## Examples

```
# for count data from longitudinal microbiome studies

datlist <- format_tempted(count_table,
                          meta_table$day_of_life,
                          meta_table$studyid,
                          pseudo=0.5,
                          transform="clr")

mean_svd <- svd_centralize(datlist, r=1)

res_tempted <- tempted(mean_svd$datlist, r=3, smooth=1e-5)

# for preprocessed data that do not need to be transformed
```

```

datlist <- format_tempted(processed_table,
                          meta_table$day_of_life,
                          meta_table$studyid,
                          pseudo=NULL,
                          transform="none")

mean_svd <- svd_centralize(datlist, r=1)

res_tempted <- tempted(mean_svd$datlist, r=3, smooth=1e-5)

# plot the temporal loading

plot_time_loading(res_tempted, r=2)

```

---

tempted_all	<i>Run all major functions of tempted</i>
-------------	---

---

## Description

This function wraps [format\\_tempted](#), [svd\\_centralize](#), [tempted](#), [ratio\\_feature](#), and [aggregate\\_feature](#).

## Usage

```

tempted_all(
  featuretable,
  timepoint,
  subjectID,
  threshold = 0.95,
  pseudo = NULL,
  transform = "clr",
  r = 3,
  smooth = 1e-06,
  interval = NULL,
  resolution = 51,
  maxiter = 20,
  epsilon = 1e-04,
  r_svd = 1,
  do_ratio = TRUE,
  pct_ratio = 0.05,
  absolute = FALSE,
  pct_aggregate = 1,
  contrast = NULL
)

```

## Arguments

featuretable	A sample by feature matrix. Input for <a href="#">format_tempted</a> .
timepoint	The time stamp of each sample, matched with the rows of featuretable. Input for <a href="#">format_tempted</a> .
subjectID	The subject ID of each sample, matched with the rows of featuretable. Input for <a href="#">format_tempted</a> .

threshold	A threshold for feature filtering for microbiome data. Features with zero value percentage $\geq$ threshold will be excluded. Default is 0.95. Input for <a href="#">format_tempted</a> .
pseudo	A small number to add to all the counts before normalizing into proportions and log transformation. Default is 1/2 of the smallest non-zero value that is specific for each sample. This pseudo count is added for transform=c("logcomp", "clr", "logit"). Input for <a href="#">format_tempted</a> .
transform	The transformation applied to the data. "logcomp" for log of compositions. "comp" for compositions. "ast" for arcsine squared transformation. "clr" for central log ratio transformation. "logit" for logit transformation. "none" for no transformation. Default transform="clr" is recommended for microbiome data. For data that are already transformed, use transform="none". Input for <a href="#">format_tempted</a> .
r	Number of components to decompose into, i.e. rank of the CP type decomposition. Default is set to 3. Input for <a href="#">tempted</a> .
smooth	Smoothing parameter for RKHS norm. Larger means smoother temporal loading functions. Default is set to be 1e-8. Value can be adjusted depending on the dataset by checking the smoothness of the estimated temporal loading function in plot. Input for <a href="#">tempted</a> .
interval	The range of time points to ran the decomposition for. Default is set to be the range of all observed time points. User can set it to be a shorter interval than the observed range. Input for <a href="#">tempted</a> .
resolution	Number of time points to evaluate the value of the temporal loading function. Default is set to 101. It does not affect the subject or feature loadings. Input for <a href="#">tempted</a> .
maxiter	Maximum number of iteration. Default is 20. Input for <a href="#">tempted</a> .
epsilon	Convergence criteria for difference between iterations. Default is 1e-4. Input for <a href="#">tempted</a> .
r_svd	The number of ranks in the mean structure. Default is 1. Input for <a href="#">\linke{svd_centraliz}</a> .
do_ratio	Whether to calculate the log ratio of features.
pct_ratio	The percent of features to sum up. Default is 0.05, i.e. 5%. Input for <a href="#">ratio_feature</a> .
absolute	absolute = TRUE means features are ranked by the absolute value of feature loadings, and the top pct_ratio percent of features are picked. absolute = FALSE means features are ranked by the original value of feature loadings, and the top and bottom pct_ratio percent of features are picked. Then ratio is taken as the abundance of the features with positive loading over the abundance of the features with negative loading. Input for <a href="#">ratio_feature</a> .
pct_aggregate	The percent of features to aggregate, features ranked by absolute value of the feature loading of each component. Default is 1, which means 100% of features are aggregated. Setting pct_aggregate=0.01 means top 1% of features is aggregated, where features are ranked in absolute value of feature loading of each component. Input for <a href="#">aggregate_feature</a> .
contrast	A matrix choosing how components are combined, each column is a contrast of length r and used to calculate the linear combination of the feature loadings of r components. Input for <a href="#">ratio_feature</a> and Input for <a href="#">aggregate_feature</a> .

## Value

A list including all the input and output of functions [format\\_tempted](#), [svd\\_centralize](#), [tempted](#), [ratio\\_feature](#), and [aggregate\\_feature](#).

- input** All the input options of function `tempted_all`.
- datalist\_raw** Output of `format_tempted` with option `transform="none"`.
- datlist** Output of `format_tempted`.
- mean\_svd** Output of `svd_centralize`.
- A\_hat** Subject loading, a subject by `r` matrix.
- B\_hat** Feature loading, a feature by `r` matrix.
- Phi\_hat** Temporal loading function, a resolution by `r` matrix.
- time\_Phi** The time points where the temporal loading function is evaluated.
- Lambda** Eigen value, a length `r` vector.
- r\_square** Variance explained by each component. This is the R-squared of the linear regression of the vectorized temporal tensor against the vectorized low-rank reconstruction using individual components.
- accum\_r\_square** Variance explained by the first few components accumulated. This is the R-squared of the linear regression of the vectorized temporal tensor against the vectorized low-rank reconstruction using the first few components.
- metafeature\_ratio** The log ratio abundance of the top over bottom ranking features. It is a `data.frame` with five columns: "value" for the log ratio values, "subID" for the subject ID, and "timepoint" for the time points, and "PC" indicating which component was used to construct the meta feature.
- toppct\_ratio** A matrix of TRUE/FALSE indicating which features are ranked top in each component (and contrast) and used as the numerator of the log ratio.
- bottompct\_ratio** A matrix of TRUE/FALSE indicating which features are ranked bottom in each component (and contrast) and used as the denominator of the log ratio.
- metafeature\_aggregate** The meta feature obtained by aggregating the observed temporal tensor. It is a `data.frame` with four columns: "value" for the meta feature values, "subID" for the subject ID, "timepoint" for the time points, and "PC" indicating which component was used to construct the meta feature.
- toppct\_aggregate** A matrix of TRUE/FALSE indicating which features are aggregated in each component and contrast.
- contrast** The contrast used to linearly combine the components from input.

## Examples

```
# for preprocessed data that do not need to be transformed

res.processed <- tempted_all(processed_table,
                             meta_table$day_of_life,
                             meta_table$studyid,
                             threshold=1,
                             transform="none",
                             r=2,
                             smooth=1e-5,
                             do_ratio=FALSE)

# for count data that will have pseudo added and clr transformed

res.count <- tempted_all(count_table,
                          meta_table$day_of_life,
                          meta_table$studyid,
```



```
threshold=0.95,
transform="clr",
pseudo=0.5,
r=2,
smooth=1e-5,
pct_ratio=0.1,
pct_aggregate=1)

# for proportional data that will have pseudo added and clr transformed

res.proportion <- tempted_all(count_table/rowSums(count_table),
                              meta_table$day_of_life,
                              meta_table$studyid,
                              threshold=0.95,
                              transform="clr",
                              pseudo=NULL,
                              r=2,
                              smooth=1e-5,
                              pct_ratio=0.1,
                              pct_aggregate=1)

# plot the temporal loading and subject trajectories grouped by delivery mode

plot_time_loading(res.proportion, r=2)

group <- unique(meta_table[,c("studyid", "delivery")])

plot_metafeature(res.proportion$metafeature_aggregate, group, bws=30)
```

# Index

## \* datasets

- count\_table, [4](#)
- meta\_table, [6](#)
- processed\_table, [9](#)

aggregate\_feature, [2](#), [8](#), [14](#), [15](#)

bernoulli\_kernel, [3](#)

count\_table, [4](#)

est\_test\_subject, [4](#)

format\_tempted, [2](#), [5](#), [14–16](#)

meta\_table, [6](#)

plot\_feature\_summary, [7](#)

plot\_metafeature, [8](#)

plot\_time\_loading, [9](#)

processed\_table, [9](#)

ratio\_feature, [8](#), [10](#), [14](#), [15](#)

svd\_centralize, [2](#), [4–6](#), [11](#), [12](#), [14–16](#)

tdenoise, [12](#)

tempted, [2](#), [4–6](#), [9](#), [10](#), [12](#), [12](#), [14](#), [15](#)

tempted\_all, [8](#), [9](#), [14](#), [16](#)