

## Multiple Inheritance Guide

Abstract Contracts

Abstract Contracts Guide

Exercise

Imports >

Errors >

The new Keyword >

Contract to Contract  
Interactions >

Events >

Address and Payable >

## Development with Foundry

Deploying a smart contract  
using Foundry

Foundry: Setting up Foundry  
with Base

## Inheritance

# Multiple Inheritance

Copy page

Learn how to have a contract inherit from multiple contracts.

Contracts can inherit from more than one contract. In this lesson, we'll explore how multiple inheritance works in Solidity.

## Objectives

By the end of this lesson you should be able to:

Write a smart contract that inherits from multiple contracts

## Multiple Inheritance

Continue working with your contracts in `Inheritance.sol` . Add a new contract called `ContractC` with another `whoAmI` function:

Reveal code

## Multiple Inheritance Guide

Abstract Contracts

Abstract Contracts Guide

Exercise

## Inheriting from Two Contracts

You can inherit from additional contracts by simply adding a comma and that contract's name after the first. Add inheritance from `ContractC` (an error is expected):

Reveal code

The error is because both `ContractB` and `ContractC` contain a function called `whoAmI` . As a result, the compiler needs instruction on which to use.

## Development with Foundry

Deploying a smart contract  
using Foundry

Foundry: Setting up Foundry  
with Base

## Multiple Inheritance Guide

Abstract Contracts

Abstract Contracts Guide

Exercise

## Development with Foundry

Deploying a smart contract  
using Foundry

Foundry: Setting up Foundry  
with Base

```
from solidity:
TypeError: Derived contract must override function "whoAmI". Two or more ba
--> contracts/Inheritance.sol:21:1:
|
21 | contract ContractA is ContractB, ContractC {
|   ^ (Relevant source part starts here and spans across multiple lines).
Note: Definition in "ContractC":
--> contracts/Inheritance.sol:6:5:
|
6 |     function whoAmI() external pure returns (string memory) {
|     ^ (Relevant source part starts here and spans across multiple lines
Note: Definition in "ContractB":
--> contracts/Inheritance.sol:12:5:
|
12 |     function whoAmI() external pure returns (string memory) {
|     ^ (Relevant source part starts here and spans across multiple line
```

## Using Virtual and Override

One method to resolve this conflict is to use the [virtual](#) [and](#) [override](#) keywords to enable you to add functionality to choose which to call.

Add the `virtual` keyword to the `whoAmI` function in both `ContractC` and `ContractB`.

They must also be made `public` instead of `external`, because `external` functions cannot be called within the contract.

## Multiple Inheritance Guide

Abstract Contracts

Abstract Contracts Guide

Exercise

```
contract ContractC {  
    function whoAmI() public virtual pure returns (string memory) {  
        return "contract C";  
    }  
}  
  
contract ContractB {  
    function whoAmI() public virtual pure returns (string memory) {  
        return "contract B";  
    }  
  
    // ... additional code  
}
```

Add an `override` function called `whoAmI` to `ContractA` :

```
// Bad code example, do not use
```



Ctrl K

GitHub

Support

Base Build



Get Started

Base Chain

Base Account

Base App

Mini Apps

OnchainKit

Cookbook

Showcase

**Learn**

### Development with Foundry

Deploying a smart contract  
using Foundry

Foundry: Setting up Foundry  
with Base

You'll get another error, telling you to specify which contracts this function should override.

## Multiple Inheritance Guide

Abstract Contracts

Abstract Contracts Guide

Exercise

## Development with Foundry

Deploying a smart contract  
using Foundry

Foundry: Setting up Foundry  
with Base

```
from solidity:
  TypeError: Function needs to specify overridden contracts "ContractB" and "
    --> contracts/Inheritance.sol:22:32:
      |
22 |     function whoAmI() public override pure returns (string memory) {
      |                                     ^^^^^^^^^^^
```

Add them both:

```
function whoAmI() external override(ContractB, ContractC) pure returns (string memory) {
    return ContractB.whoAmI();
}
```

Deploy and test. The contract is now ready to use.  **Ctrl+I** B".

## Changing Types Dynamically

Add an `enum` at the contract level in `ContractA` with members for `None`, `ContractBType`, and `ContractCType`, and an instance of it called `contractType`.

Reveal code

Add a `constructor` to `ContractA` that accepts a `Type` and sets `initialType`.

## Multiple Inheritance Guide

Abstract Contracts

Abstract Contracts Guide

Exercise

## Development with Foundry

Deploying a smart contract  
using Foundry

Foundry: Setting up Foundry  
with Base

### Reveal code

Update `whoAmI` in `ContractA` to call the appropriate `virtual` function based on its `currentType` .

### Reveal code

You'll get errors because the function now reads from state, so it is no longer `pure` . Update it to `view` . You'll also have to update the `whoAmI` `virtual` functions to `view` to match.

### Reveal code

Finally, add a function that allows you to switch `currentType` :

### Reveal code

Deploy and test. You'll need to use `0`, `1`, and `2` as values to set `contractType` , because Remix won't know about your `enum` .

## Final Code

After completing this exercise, you should have something similar to:

## Multiple Inheritance Guide

Abstract Contracts

Abstract Contracts Guide

Exercise

## Development with Foundry

Deploying a smart contract  
using Foundry

Foundry: Setting up Foundry  
with Base

// SPDX-License-Identifier: MIT



```
pragma solidity ^0.8.17;
```

```
contract ContractC {  
    function whoAmI() public virtual view returns (string memory) {  
        return "contract C";  
    }  
}
```

```
contract ContractB {  
    function whoAmI() public virtual view returns (string memory) {  
        return "contract B";  
    }  
  
    function whoAmIInternal() internal pure returns (string memory) {  
        return "contract B";  
    }  
}
```

```
contract ContractA is ContractB, ContractC {  
    enum Type { None, ContractBType, ContractCType }
```

```
    Type contractType;
```

```
    constructor (Type _initialType) {  
        contractType = _initialType;  
    }
```

## Multiple Inheritance Guide

Abstract Contracts

Abstract Contracts Guide

Exercise

```
function changeType(Type _newType) external {
    contractType = _newType;
}

function whoAmI() public override(ContractB, ContractC) view returns (string memory) {
    if(contractType == Type.ContractBType) {
        return ContractB.whoAmI();
    }
    if(contractType == Type.ContractCType) {
        return ContractC.whoAmI();
    }
    return "contract A";
}

function whoAmExternal() external pure returns (string memory) {
    return whoAmIInternal();
}
}
```

## Conclusion

In this lesson, you've explored how to use multiple inheritance to import additional functionality into a contract. You've also implemented one approach to resolving name conflicts between those contracts.

## Development with Foundry

Deploying a smart contract  
using Foundry

Foundry: Setting up Foundry  
with Base



Was this page helpful?



Yes



No



Suggest edits



Raise issue

## Multiple Inheritance Guide

[Abstract Contracts](#)[Abstract Contracts Guide](#)[Exercise](#)[< Multiple Inheritance](#)[Abstract Contracts >](#)[base.org](#)[Blog](#)[Privacy Policy](#)[Terms of Service](#)[Cookie Policy](#)

## Development with Foundry

[Deploying a smart contract  
using Foundry](#)[Foundry: Setting up Foundry  
with Base](#)