

## Functions

Introduction to Contracts

Hello World Guide

Basic Types

**Basic Functions Exercise**

Deploying to a Testnet &gt;

Control Structures &gt;

Storage in Solidity &gt;

Arrays in Solidity &gt;

The Mapping Type &gt;

Advanced Functions &gt;

Structs &gt;

Inheritance &gt;

Imports &gt;

Errors &gt;

The new Keyword &gt;

**Contracts and Basic Functions**

# Basic Functions Exercise

 Copy page

Exercise - Create and deploy a contract with simple math functions.

Each module in this course will contain exercises in which you are given a specification for a contract **without** being given specific instructions on how to build the contract. You must use what you've learned to figure out the best solution on your own!

 Once you've learned how to deploy your contracts to a test network, you'll be given the opportunity to submit your contract address for review by an onchain unit test. If it passes, you'll receive an NFT pin recognizing your accomplishment.

**You'll deploy and submit this contract in the next module.**

The following exercise asks you to create a contract that adheres to the following stated specifications.

## Contract

Ask a question...

Ctrl+I

Create a contract called `BasicMath` . It should not inherit from any other contracts and does not need a constructor. It should have the following two functions:

Introduction to Contracts

Hello World Guide

Basic Types

**Basic Functions Exercise**

## Adder

A function called `adder` . It must:

Accept two `uint` arguments, called `_a` and `_b`

Return a `uint` `sum` and a `bool` `error`

If `_a + _b` does not overflow, it should return the `sum` and an `error` of `false`

If `_a + _b` overflows, it should return `0` as the `sum` , and an `error` of `true`

## Subtractor

A function called `subtractor` . It must:

Accept two `uint` arguments, called `_a` and `_b`

Return a `uint` `difference` and a `bool` `error`

If `_a - _b` does not underflow, it should return the `difference` and an `error` of `false`

If `_a - _b` underflows, it should return `0` as the `difference` , and an `error` of `true`

Was this page helpful?

 Yes No Suggest edits Raise issue[◀ Basic Types](#)[Overview of Test Networks ▶](#)[Introduction to Contracts](#)[Hello World Guide](#)[Basic Types](#)[Basic Functions Exercise](#)E  
e.org

Blog

Privacy Policy

Terms of Service

Cookie Policy