

# Package ‘betaclust’

September 9, 2022

**Type** Package

**Title** A family of mixture models for clustering beta valued DNA methylation data.

**Version** 1.0.0

**Author** Koyel Majumdar <koyel.majumdar@ucdconnect.ie>,  
Isobel Claire Gormley <claire.gormley@ucd.ie>,  
Thomas Brendan Murphy <brendan.murphy@ucd.ie>

**Maintainer** Koyel Majumdar <koyel.majumdar@ucdconnect.ie>

**Description** A family of novel beta mixture models (BMMs) to appositely model beta valued DNA methylation data, to objectively identify methylation state thresholds and to identify the differentially methylated CpG (DMC) sites using a model-based clustering approach. The family of BMMs employ different parameter constraints applicable to different study settings. Parameter estimation proceeds via the EM algorithm, with a novel approximation during the M-step providing tractability and ensuring computational feasibility.

**License** GPL-3

**Depends** R (>= 3.5.0)

**Imports** foreach, doParallel, stats, utils, ggplot2, plotly

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.2.1

**NeedsCompilation** no

## R topics documented:

betaclust . . . . .	1
beta_k . . . . .	4
beta_kn . . . . .	5
beta_kr . . . . .	6
ecdf.betaclust . . . . .	8
em_aic . . . . .	9
em_bic . . . . .	9
em_icl . . . . .	10
legacy.data . . . . .	11
pca.methylation.data . . . . .	11
plot.betaclust . . . . .	13
summary.betaclust . . . . .	14
threshold . . . . .	15

betaclust

*The betaclust wrapper function***Description**

A family of model based clustering techniques to identify methylation states in beta valued DNA methylation data.

**Usage**

```
betaclust(
  data,
  M = 3,
  patients,
  samples,
  model_names = "K..",
  model_selection = "BIC",
  seed,
  register = NULL
)
```

**Arguments**

data	Methylation values for $C$ CpG sites from $R$ samples collected from $N$ patients.
M	Number of methylation states to be identified in a DNA sample.
patients	Number of patients in the study.
samples	Number of samples collected from each patient for the study.
model_names	Models to run from the set of models, K., KN. and K.R, default = K.. . See details.
model_selection	Information criterion used for model selection. Options are AIC/BIC/ICL/default = BIC.
seed	Seed to allow for reproducibility.
register	Setting for registering the parallel backend with the "foreach" package. To start parallel execution of R code on machine with multiple cores, "NULL" value needs to be assigned to this parameter.

**Details**

This is a wrapper function which can be used to fit all three models (K., KN., K.R) together. The K.. and KN. models are used to analyse a single DNA sample ( $R = 1$ ) and cluster the  $C$  CpG sites into the  $K$  clusters which represent the different methylation states in a DNA sample. As each CpG site can belong to either of the  $M = 3$  methylation states (hypomethylation, hemimethylation and hypermethylation), the default value for  $K = M = 3$ . The thresholds between methylation states are objectively inferred from the clustering solution. The K.R model is used to analyse  $R$  independent samples collected from  $N$  patients, where each sample contains  $C$  CpG sites, and cluster the dataset into  $K = M^R$  clusters to identify the differentially methylated CpG (DMC) sites between the  $R$  DNA samples.

## Value

The function returns an object of "betaclust" class which contains the following values:

- `information_criterion` - the information criterion used to select the optimal model.
- `ic_output` - this stores the information criterion value calculated for each model.
- `optimal_model` - the model selected as optimal.
- `function_call` - the parameters passed as arguments to the function `betaclust`.
- `K` - the number of clusters identified using the beta mixture models.
- `C` - the number of CpG sites analysed using the beta mixture models.
- `N` - the number of patients analysed using the beta mixture models.
- `R` - the number of samples analysed using the beta mixture models.
- `optimal_model_results` - this contains information from the optimal model. Specifically,
  - `cluster_size` - the total number of CpG sites identified in each of the  $K$  clusters.
  - `llk` - a vector containing the log-likelihood value at each step of the EM algorithm.
  - `data` - this contains the methylation dataset along with the cluster label for each CpG site.
  - `alpha` - this contains the first shape parameter for the beta mixture model.
  - `delta` - this contains the second shape parameter for the beta mixture model.
  - `tau` - the proportion of CpG sites in each cluster.
  - `z` - a matrix containing the probability for each CpG site of belonging to each of the  $K$  clusters.
  - `uncertainty` - the uncertainty of each CpG site's clustering.
  - `thresholds` - threshold points calculated for the  $K_{..}$  or the  $KN_{..}$  model

## References

Silva, R., Moran, B., Russell, N.M., Fahey, C., Vljajnic, T., Manecksha, R.P., Finn, S.P., Brennan, D.J., Gallagher, W.M., Perry, A.S.: Evaluating liquid biopsies for methylomic profiling of prostate cancer. *Epigenetics* 15(6-7), 715-727 (2020). doi:10.1080/15592294.2020.1712876.

Majumdar, K., Silva, R., Perry, A.S., Watson, R.W., Murphy, T.B., Gormley, I.C.: `betaclust`: a family of mixture models for beta valued DNA methylation data.

Microsoft, Weston, S. (2022): `foreach`: Provides Foreach Looping Construct. R package version 1.5.2. <https://CRAN.R-project.org/package=foreach>.

## See Also

[beta\\_k](#)

[beta\\_kn](#)

[beta\\_kr](#)

[pca.methylation.data](#)

[plot.betaclust](#)

[summary.betaclust](#)

[threshold](#)

## Examples

```
## Not run:
data(pca.methylation.data)
my.seed = 190
M = 3
patients = 4
samples = 2
data_output = betaclust(pca.methylation.data[,2:9],M,patients,samples,
                        model_names = c("K..","KN.","K.R"),model_selection = "BIC",seed = my.seed)

## End(Not run)
```

---

beta_k	<i>The K.. model</i>
--------	----------------------

---

## Description

Fit the K.. model from the family of beta mixture models for DNA methylation data. The K.. model analyses a single DNA sample and identifies the thresholds for the different methylation states.

## Usage

```
beta_k(data, M = 3, seed = NULL, register = NULL)
```

## Arguments

data	Methylation values for $C$ CpG sites from $R = 1$ samples collected from $N$ patients.
M	Number of methylation states to be identified in a DNA sample.
seed	Seed to allow for reproducibility. (default = NULL)
register	Setting for registering the parallel backend with the "foreach" package. To start parallel execution of R code on machine with multiple cores, "NULL" value needs to be assigned to this parameter.

## Details

This model clusters each of the  $C$  CpG sites into one of  $K$  methylation states, based on data from  $N$  patients for one DNA sample (i.e.  $R = 1$ ). As each CpG site can belong to either of the  $M = 3$  methylation states (hypomethylated, hemimethylated or hypermethylated), the default value of  $K = M = 3$ . Under the K.. model the shape parameters of each cluster are constrained to be equal for each patient. The return object from this function can be passed as an input parameter to the **threshold** function available in this package to calculate the thresholds for the methylation states.

**Value**

A list containing:

- cluster\_size - the total number of CpG sites identified in each of the  $K$  clusters.
- llk - a vector containing the log-likelihood value at each step of the EM algorithm.
- data - this contains the methylation dataset along with the cluster label for each CpG site.
- alpha - this contains the first shape parameter for the beta mixture model.
- delta - this contains the second shape parameter for the beta mixture model.
- tau - the proportion of CpG sites in each cluster.
- z - a matrix containing the probability for each CpG site of belonging to each of the  $K$  clusters.
- uncertainty - the uncertainty of each CpG site's clustering.

**References**

Microsoft, Weston, S. (2022): foreach: Provides Foreach Looping Construct. R package version 1.5.2. <https://CRAN.R-project.org/package=foreach>.

**See Also**

[beta\\_kn](#)  
[betaclust](#)  
[threshold](#)

**Examples**

```
## Not run:
data(pca.methylation.data)
my.seed = 190
M = 3
data_output = beta_k(pca.methylation.data[,2:5],M,seed = my.seed)
thresholds = threshold(data_output,"K..")

## End(Not run)
```

---

beta\_kn

*The KN. model*


---

**Description**

Fit the KN. model from the family of beta mixture models for DNA methylation data. The KN. model analyses a single DNA sample and identifies the thresholds for the different methylation states.

**Usage**

```
beta_kn(data, M = 3, seed = NULL, register = NULL)
```

## Arguments

data	Methylation values for $C$ CpG sites from $R = 1$ samples collected from $N$ patients.
M	Number of methylation states to be identified in a DNA sample.
seed	Seed to allow for reproducibility. (default = NULL)
register	Setting for registering the parallel backend with the 'foreach' package. To start parallel execution of R code on machine with multiple cores, 'NULL' value needs to be assigned to this parameter.

## Details

This model clusters each of the  $C$  CpG sites into one of  $K$  methylation states, based on data from  $N$  patients for one DNA sample (i.e.  $R = 1$ ). As each CpG site can belong to either of the  $M = 3$  methylation states (hypomethylated, hemimethylated or hypermethylated), the default value of  $K = M = 3$ . The KN. model differs from the C.. model as it is less parsimonious, allowing cluster and patient-specific shape parameters. The return object from this function can be passed as an input parameter to the *threshold* function available in this package to calculate the thresholds for the methylation states.

## Value

A list containing:

- cluster\_size - the total number of CpG sites identified in each of the  $K$  clusters.
- llk - a vector containing the log-likelihood value at each step of the EM algorithm.
- data - this contains the methylation dataset along with the cluster label for each CpG site.
- alpha - this contains the first shape parameter for the beta mixture model.
- delta - this contains the second shape parameter for the mixture model.
- tau - the proportion of CpG sites in each cluster.
- z - a matrix containing the probability for each CpG site of belonging to each of the  $K$  clusters.
- uncertainty - the uncertainty of each CpG site's clustering.

## References

Microsoft, Weston, S. (2022): foreach: Provides Foreach Looping Construct. R package version 1.5.2. <https://CRAN.R-project.org/package=foreach>.

## See Also

[beta\\_k](#)  
[betaclust](#)  
[threshold](#)

## Examples

```
## Not run:
data(pca.methylation.data)
my.seed = 190
M = 3
data_output = beta_kn(pca.methylation.data[,2:5],M,seed = my.seed)
```

```
thresholds = threshold(data_output,"KN.")

## End(Not run)
```

beta\_kr

*The K.R Model*

## Description

A beta mixture model for identifying differentially methylated CpG sites between  $R$  DNA samples collected from  $N$  patients.

## Usage

```
beta_kr(data, M = 3, patients, samples, seed = NULL, register = NULL)
```

## Arguments

data	Methylation values for $C$ CpG sites from $R$ samples collected from $N$ patients.
M	Number of methylation states to be identified.
patients	Number of patients in the study.
samples	Number of samples collected from each patient for study.
seed	Seed to allow for reproducibility.
register	Setting for registering the parallel backend with the "foreach" package. To start parallel execution of R code on machine with multiple cores, "NULL" value needs to be assigned to this parameter.

## Details

The K.R model allows identification of the differentially methylated CpG sites between the  $R$  DNA samples collected from each of  $N$  patients. As each CpG site in a DNA sample can belong to either of  $M$  methylation states, there can be  $K = M^R$  methylation state changes between  $R$  DNA samples. The parameters vary for each DNA sample but are constrained to be equal for each patient. An initial clustering using K-means is performed to identify  $K$  clusters. The resulting clustering solution is provided as starting values to the Expectation-Maximisation algorithm. A digamma approximation is used to obtain the maximised parameters in the M-step instead of a computationally inefficient numerical optimisation step.

## Value

A list containing:

- cluster\_size - the total number of CpG sites identified in each of the  $K$  clusters.
- llk - a vector containing the log-likelihood value at each step of the EM algorithm.
- data - this contains the methylation dataset along with the cluster label for each CpG site.
- alpha - this contains the first shape parameter for the beta mixture model.
- delta - this contains the second shape parameter for the beta mixture model.
- tau - the proportion of CpG sites in each cluster.
- z - a matrix containing the probability for each CpG site of belonging to each of the  $K$  clusters.
- uncertainty - the uncertainty of each CpG site's clustering.

## References

Microsoft, Weston, S. (2022): foreach: Provides Foreach Looping Construct. R package version 1.5.2. <https://CRAN.R-project.org/package=foreach>.

## See Also

[betaclust](#)

## Examples

```
## Not run:
data(pca.methylation.data)
my.seed = 190
M = 3
patients = 4
samples = 2
data_output = beta_kr(pca.methylation.data[,2:5],M,patients,samples,seed = my.seed)

## End(Not run)
```

---

ecdf.betaclust

*The empirical cumulative distribution function*

---

## Description

An empirical cumulative distribution function (ECDF) plot for a betaclust object.

## Usage

```
ecdf.betaclust(x, samples = 2, sample_name = NULL, title = NULL)
```

## Arguments

x	A dataframe containing methylation values of identified differentially methylated regions related to a gene. Group each sample together in the dataframe such that the columns are ordered as Sample1_Patient1, Sample1_Patient2, Sample2_Patient1, Sample2_Patient2.
samples	number of tissue samples from which DNA methylation data are collected (default samples = 2).
sample_name	The order in which the samples are grouped in the dataframe x. If no value is passed then default values of sample names, for e.g. Sample 1, Sample 2 and so on are used (default = NULL).
title	The title that the user wants to display on the graph. If no title is to be displayed the default is "NULL" value.

## Details

This function plots the ECDF graphs of the differentially methylated CpG sites identified using the K.R model for all patient samples. The graph visualises the methylation state changes between the different DNA samples for each patient.



**Value**

The ECDF plot for the selected CpG sites for all patients and their DNA samples.

**See Also**

[betaclust](#)

[beta\\_kr](#)

---

em_aic	<i>Akaike Information Criterion</i>
--------	-------------------------------------

---

**Description**

Compute the AIC value for the optimal model.

**Usage**

```
em_aic(llk, C, M, patients = 4, samples = 1, model_name = "K..")
```

**Arguments**

llk	log-likelihood value.
C	number of CpG sites.
M	number of methylation states identified in a DNA sample.
patients	number of patients.
samples	number of DNA samples collected from each patient.
model_name	fitted mixture model (method = c("K..","KN.","K.R")).

**Details**

Computes the AIC for a specified model given the log-likelihood, the dimension of the data, and the model specification.

**Value**

The AIC value for the selected model.

**See Also**

[em\\_bic](#)

[em\\_icl](#)

---

em_bic	<i>Bayesian Information Criterion</i>
--------	---------------------------------------

---

**Description**

Compute the BIC value for the optimal model.

**Usage**

```
em_bic(llk, C, M, patients = 4, samples = 1, model_name = "K..")
```

**Arguments**

llk	log-likelihood value.
C	number of CpG sites.
M	number of methylation states identified in a DNA sample.
patients	number of patients.
samples	number of DNA samples collected from each patient.
model_name	fitted mixture model (method = c("K..", "KN.", "K.R")).

**Details**

Computes the BIC for a specified model given the log-likelihood, the dimension of the data, and the model specification.

**Value**

The BIC value for the selected model.

**See Also**

[em\\_aic](#)  
[em\\_icl](#)

---

em_icl	<i>Integrated Complete-data Likelihood (ICL) Criterion</i>
--------	--

---

**Description**

Compute the ICL value for the optimal model.

**Usage**

```
em_icl(llk, C, M, patients = 4, samples = 1, model_name = "K..", z)
```

**Arguments**

llk	log-likelihood value.
C	number of CpG sites.
M	number of methylation states identified in a DNA sample.
patients	number of patients.
samples	number of DNA samples collected from each patient.
model_name	fitted mixture model (method = c("K.", "KN.", "K.R")).
z	matrix containing the probability for each CpG site of belonging to each of the K clusters.

**Details**

Computes the ICL for a specified model given the log-likelihood, the dimension of the data, and the model specification. This criterion penalises the BIC by including the entropy term favouring the well separated clusters.

**Value**

The ICL value for the selected model.

**See Also**

[em\\_aic](#)

[em\\_bic](#)

---

legacy.data	<i>MethylationEPIC manifest data.</i>
-------------	---------------------------------------

---

**Description**

The dataset contains the manifest data from the Illumina MethylationEPIC beadchip array.

**Usage**

```
data(legacy.data)
```

**Format**

A data frame with 867,525 rows and 6 columns.

- IlmnID: the unique identifier from the Illumina CG database, i.e. the probe ID.
- Genome\_Build: the genome build referenced by the Infinium MethylationEPIC manifest.
- CHR: the chromosome containing the CpG (Genome\_Build = 37).
- MAPINFO: the chromosomal coordinates of the CpG.
- UCSC\_RefGene\_Name: the target gene name(s), from the UCSC database. Note: multiple listings of the same gene name indicate splice variants.
- UCSC\_CpG\_Islands\_Name: the chromosomal coordinates of the CpG Island from UCSC.

**See Also**

[pca.methylation.data](#)

---

pca.methylation.data	<i>DNA methylation dataset of patients suffering from prostate cancer disease.</i>
----------------------	--

---

### Description

The dataset contains pre-processed beta methylation values from  $R = 2$  sample, collected from  $N = 4$  patients suffering from prostate cancer disease.

### Usage

```
data(pca.methylation.data)
```

### Format

A data frame with 694,820 rows and 9 columns. The data contains no missing values.

- IlmnID: the unique identifier from the Illumina CG database, i.e. the probe ID.
- Benign\_Patient\_1: the methylation values from benign prostate tissue collected from patient 1.
- Benign\_Patient\_2: the methylation values from benign prostate tissue collected from patient 2.
- Benign\_Patient\_3: the methylation values from benign prostate tissue collected from patient 3.
- Benign\_Patient\_4: the methylation values from benign prostate tissue collected from patient 4.
- Tumour\_Patient\_1: the methylation values from tumor prostate tissue collected from patient 1.
- Tumour\_Patient\_2: the methylation values from tumor prostate tissue collected from patient 2.
- Tumour\_Patient\_3: the methylation values from tumor prostate tissue collected from patient 3.
- Tumour\_Patient\_4: the methylation values from tumor prostate tissue collected from patient 4.

### Details

The raw methylation array data was first quality controlled and preprocessed using the RnBeads package. The array data was then normalized and probes located outside of CpG sites and on the sex chromosome were filtered out. The CpG sites with missing values were removed from the resulting dataset.

### References

- Mueller F, Scherer M, Assenov Y, Lutsik P, Walter J, Lengauer T, Bock C (2019). “RnBeads 2.0: comprehensive analysis of DNA methylation data.” *Genome Biology*, 20(55). doi: 10.1186/s13059-019-1664-9, <https://rnbeads.org>.
- Assenov Y, Mueller F, Lutsik P, Walter J, Lengauer T, Bock C (2014). “Comprehensive Analysis of DNA Methylation Data with RnBeads.” *Nature Methods*, 11(11), 1138–1140. doi: 10.1038/nmeth.3115, <https://rnbeads.org>.

**See Also**[legacy.data](#)

plot.betaclust

*Plots for visualizing the betaclust class object***Description**

This function helps visualise the clustering solution by plotting the fitted and kernel density estimates, the uncertainty and the information criterion.

**Usage**

```
## S3 method for class 'betaclust'
plot(
  object,
  what = "fitted density",
  plot_type = "ggplot",
  sample_name = NULL,
  title = NULL,
  patient_number = 1,
  threshold = FALSE,
  scale_param = "free_y"
)
```

**Arguments**

object	A betaclust object.
what	The different plots that can be obtained are either "fitted density", "kernel density", "uncertainty" or "information criterion". (default = "fitted density").
plot_type	The plot type to be displayed are either "ggplot" or "plotly". (default = "ggplot").
sample_name	The names of DNA samples in the dataset analysed by the K.R model. If no value is passed then default values of sample names, for e.g. Sample 1, Sample 2 and so on are used as legend text (default = NULL).
title	The title that the user wants to display on the graph. If no title is to be displayed the default is "NULL" value.
patient_number	The column number representing the patient in the patient-wise ordered dataset selected for visualizing the clustering solution of the K.. or KN. model. (default = 1)
threshold	The "TRUE" option displays the threshold points in the graph for the K.. and the KN. model. (default = "FALSE")
scale_param	The axis that needs to be fixed for density estimates plot for visualizing the K.R clustering solution are either "free_y", "free_x" or "free". (default = "free_y").

## Details

The fitted density estimates can be visualized under the optimal clustering solution by specifying `what = "fitted density"` in the function and kernel density estimates under the optimal clustering solution by specifying `what = "kernel density"`. The threshold inferred can be visualized by specifying `threshold = TRUE`. The KN. model calculates different pairs of threshold points for each patient as the shape parameters are allowed to vary for each patient. So the patient for whom the threshold needs to be displayed can be specified by inputting the column number representing the patient in the patient-wise ordered dataset in the parameter `patient_number`. The kernel density estimates for a particular patient can also be visualized using this parameter. Interactive plots can also be produced using `plot_type = "plotly"`. The uncertainty in the clustering solution can be plotted using `what = "uncertainty"`. The information criterion values for all fitted models can be plotted using `what = "information criterion"`.

## See Also

[betaclust](#)

## Examples

```
## Not run:
M = 3
patients = 4
samples = 2
data_output = betaclust(pca.methylation.data[,2:9],M,patients,samples,
                        model_names = c("K.", "KN.", "K.R"),model_selection = "BIC",seed = my.seed)
plot(data_output,what = "fitted density",plot_type = "ggplot")
## End(Not run)
```

---

summary.betaclust

*Summarizing the beta mixture model fits*


---

## Description

Summary method for a "betaclust" object containing the results under the optimal model selected.

## Usage

```
## S3 method for class 'betaclust'
summary(object)
```

## Arguments

`object`                      A betaclust object.

## Value

An object of class "summary.betaclust" which contains the following list of values:

- C - the number of CpG sites analysed using the beta mixture models.
- N - the number of patients analysed using the beta mixture models.
- R - the number of samples analysed using the beta mixture models.

- K - the number of methylation profiles identified in R DNA samples.
- modelName - the optimal model selected.
- loglik - the log-likelihood value for the selected optimal model.
- information\_criterion - the information criterion used to select the optimal model.
- ic\_output - this stores the information criterion value calculated for each model.
- classification - the total number of CpG sites identified in each cluster.
- prop\_data - the proportion of CpG sites identified in each cluster.

## See Also

[betaclust](#)

## Examples

```
## Not run:
M=3
patients=4
samples=2
data_output=betaclust(pca.methylation.data[,2:9],M,patients,samples,
                      model_names=c("K..", "KN.", "K.R"),model_selection="BIC",seed=my.seed)
summary(data_output)
## End(Not run)
```

---

threshold

*Thresholds for the K.. and the KN. models*

---

## Description

An objective method to calculate the threshold points for the clustering solution of the K.. and the KN. models.

## Usage

```
threshold(object, model_name)
```

## Arguments

object	A beta_k or beta_kn object.
model_name	The name of the model for which the thresholds need to be calculated.

## Details

As the K.. model constrains the shape parameters to be equal for all patients, a single pair of threshold points are calculated for all patients. The KN. model allows patient-specific shape parameters which results in a pair of threshold points calculated separately for each patient based on the shape parameters defining the beta values for that patient. The first threshold point denotes any beta value less than this value is likely to be hypomethylated. The second threshold point denotes any beta value greater than this is highly likely to be hypermethylated. A beta value lying between the two threshold points is likely to be hemimethylated.

**Value**

thresholds - the threshold points calculated for the selected model. A vector containing two threshold points are returned for the K.. model whereas a matrix containing two threshold points for each patient is returned for the KN. model.

**See Also**

[beta\\_k](#)

[beta\\_kn](#)

[betaclust](#)