



# Introduction to Optimization

K. R. Sahasranand

Data Science

sahasranand@iitpkd.ac.in

## Optimization so far...

Given  $A \in \mathbb{R}^{m \times n}$ ,  $m \geq n$  and  $b \in \mathbb{R}^m$ ,

Least squares

$$\min_{x \in \mathbb{R}^n} \|Ax - b\|^2$$

## Optimization so far...

Given  $A \in \mathbb{R}^{m \times n}$ ,  $m \geq n$  and  $b \in \mathbb{R}^m$ ,

Least squares

$$\min_{x \in \mathbb{R}^n} \|Ax - b\|^2$$

Given  $A \in \mathbb{R}^{m \times n}$ ,  $m < n$  and  $b \in \mathbb{R}^m$ ,

Minimum  $\ell_2$  norm

$$\min_{x \in \mathbb{R}^n} x_1^2 + \cdots + x_n^2 \text{ subject to } Ax = b.$$

## Optimization so far...

Given  $A \in \mathbb{R}^{m \times n}$ ,  $m \geq n$  and  $b \in \mathbb{R}^m$ ,

Least squares

$$\min_{x \in \mathbb{R}^n} \|Ax - b\|^2$$

Given  $A \in \mathbb{R}^{m \times n}$ ,  $m < n$  and  $b \in \mathbb{R}^m$ ,

Minimum  $\ell_2$  norm

$$\min_{x \in \mathbb{R}^n} x_1^2 + \cdots + x_n^2 \text{ subject to } Ax = b.$$

Given  $A \in \mathbb{R}^{m \times n}$ ,  $m < n$  and  $b \in \mathbb{R}^m$ ,

Minimum  $\ell_1$  norm?

$$\min_{x \in \mathbb{R}^n} |x_1| + \cdots + |x_n| \text{ subject to } Ax = b.$$

## Optimization so far...

Given  $A \in \mathbb{R}^{m \times n}$ ,  $m \geq n$  and  $b \in \mathbb{R}^m$ ,

Least squares

$$\min_{x \in \mathbb{R}^n} \|Ax - b\|^2$$

Given  $A \in \mathbb{R}^{m \times n}$ ,  $m < n$  and  $b \in \mathbb{R}^m$ ,

Minimum  $\ell_2$  norm

$$\min_{x \in \mathbb{R}^n} x_1^2 + \cdots + x_n^2 \text{ subject to } Ax = b.$$

Given  $A \in \mathbb{R}^{m \times n}$ ,  $m < n$  and  $b \in \mathbb{R}^m$ ,

Minimum  $\ell_1$  norm?

$$\min_{x \in \mathbb{R}^n} |x_1| + \cdots + |x_n| \text{ subject to } Ax = b.$$

Given  $A \in \mathbb{R}^{m \times n}$ ,  $m < n$  and  $b \in \mathbb{R}^m$ ,

A general function?

$$\min_{x \in \mathbb{R}^n} f(x) \text{ subject to } Ax = b.$$

## Linear program

An optimization problem of the form:

$$\begin{array}{ll}\text{maximize} & c^\top x \\ \text{subject to} & Ax \leq b\end{array}$$

where  $c \in \mathbb{R}^n$ ,  $b \in \mathbb{R}^m$ , and  $A \in \mathbb{R}^{m \times n}$ .

## Linear program

An optimization problem of the form:

$$\begin{aligned} &\text{maximize } c^\top x \\ &\text{subject to } Ax \leq b \end{aligned}$$

where  $c \in \mathbb{R}^n$ ,  $b \in \mathbb{R}^m$ , and  $A \in \mathbb{R}^{m \times n}$ .

(includes min instead of max,  $Ax = b$ ,  $Ax \geq b$  etc. also)

# Linear program

An optimization problem of the form:

$$\begin{array}{ll}\text{maximize} & c^\top x \\ \text{subject to} & Ax \leq b\end{array}$$

where  $c \in \mathbb{R}^n$ ,  $b \in \mathbb{R}^m$ , and  $A \in \mathbb{R}^{m \times n}$ .

(includes min instead of max,  $Ax = b$ ,  $Ax \geq b$  etc. also)

**Feasible solutions:** All  $x$  that satisfy  $Ax \leq b$

**Optimal solution:** a *feasible solution* that maximizes  $c^\top x$   
(a.k.a. *Optimum*)



## An example

- A factory has 20 machines and 20 parts

## An example

- A factory has 20 machines and 20 parts
- Any machine can produce any part.

## An example

- A factory has 20 machines and 20 parts
- Any machine can produce any part.
- Each part-machine production time is known.

## An example

- A factory has 20 machines and 20 parts
- Any machine can produce any part.
- Each part-machine production time is known.
- Goal: assign one part to each machine to  
minimize total production time.

## An example

- A factory has 20 machines and 20 parts
- Any machine can produce any part.
- Each part-machine production time is known.
- Goal: assign one part to each machine to  
minimize total production time.
- Total possible assignments:  $20!$

## An example

- A factory has 20 machines and 20 parts
- Any machine can produce any part.
- Each part-machine production time is known.
- Goal: assign one part to each machine to  
minimize total production time.
- Total possible assignments:  $20!$
- Brute-force approach checks all  $20!$  assignments.

## An example

- A factory has 20 machines and 20 parts
- Any machine can produce any part.
- Each part-machine production time is known.
- Goal: assign one part to each machine to  
minimize total production time.
- Total possible assignments:  $20!$
- Brute-force approach checks all  $20!$  assignments.
- With a computer taking  $1\mu s$  per assignment:

## An example

- A factory has 20 machines and 20 parts
- Any machine can produce any part.
- Each part-machine production time is known.
- Goal: assign one part to each machine to  
minimize total production time.
- Total possible assignments:  $20!$
- Brute-force approach checks all  $20!$  assignments.
- With a computer taking  $1\mu s$  per assignment:

$$\text{Total time} = 20! \times 10^{-6} \text{ seconds} \approx 77,147 \text{ years!}$$



## Another example

- A company must allocate resources to 100 different projects.

## Another example

- A company must allocate resources to 100 different projects.
- Each project uses a portion of 10 shared resources (e.g., budget, manpower).

## Another example

- A company must allocate resources to 100 different projects.
- Each project uses a portion of 10 shared resources (e.g., budget, manpower).
- Objective: Maximize total profit across all projects.

## Another example

- A company must allocate resources to 100 different projects.
- Each project uses a portion of 10 shared resources (e.g., budget, manpower).
- Objective: Maximize total profit across all projects.
- Constraints: Linear resource limits (e.g., total budget  $\leq B$ ).

## Another example

- A company must allocate resources to 100 different projects.
- Each project uses a portion of 10 shared resources (e.g., budget, manpower).
- Objective: Maximize total profit across all projects.
- Constraints: Linear resource limits (e.g., total budget  $\leq B$ ).
- Decision variables: Fraction of resources to allocate to each project (continuous).

## Another example

- A company must allocate resources to 100 different projects.
- Each project uses a portion of 10 shared resources (e.g., budget, manpower).
- Objective: Maximize total profit across all projects.
- Constraints: Linear resource limits (e.g., total budget  $\leq B$ ).
- Decision variables: Fraction of resources to allocate to each project (continuous).
- Even with discretized choices (e.g., 100 levels per variable), there are  $100^{100}$  combinations.

## Another example

- A company must allocate resources to 100 different projects.
- Each project uses a portion of 10 shared resources (e.g., budget, manpower).
- Objective: Maximize total profit across all projects.
- Constraints: Linear resource limits (e.g., total budget  $\leq B$ ).
- Decision variables: Fraction of resources to allocate to each project (continuous).
- Even with discretized choices (e.g., 100 levels per variable), there are  $100^{100}$  combinations.
- Brute-force evaluation at  $1\mu s$  per combination takes  $\approx 3.2 \times 10^{213}$  years!

# History

- Kantorovich (1939) and Koopmans (WWII)
  - resource and transportation planning



# History

- Kantorovich (1939) and Koopmans (WWII)
  - resource and transportation planning
- 1975 Nobel Prize in Economics

# History

- Kantorovich (1939) and Koopmans (WWII)
  - resource and transportation planning
- 1975 Nobel Prize in Economics
- Dantzig (1947) – [simplex method](#), a foundational LP algorithm

# History

- Kantorovich (1939) and Koopmans (WWII)
  - resource and transportation planning
- 1975 Nobel Prize in Economics
- Dantzig (1947) – **simplex method**, a foundational LP algorithm
- Efficient in practice but **exponential worst-case complexity**

# History


- Kantorovich (1939) and Koopmans (WWII)
  - resource and transportation planning
- 1975 Nobel Prize in Economics
- Dantzig (1947) – **simplex method**, a foundational LP algorithm
- Efficient in practice but **exponential worst-case complexity**
- Search for polynomial-time algorithms for LP

# History

- Kantorovich (1939) and Koopmans (WWII)
  - resource and transportation planning
- 1975 Nobel Prize in Economics
- Dantzig (1947) – **simplex method**, a foundational LP algorithm
- Efficient in practice but **exponential worst-case complexity**
- Search for polynomial-time algorithms for LP
- Khachiyan (1979) – first polynomial-time LP algorithm (ellipsoid method)

# History



- Kantorovich (1939) and Koopmans (WWII)
  - resource and transportation planning
- 1975 Nobel Prize in Economics
- Dantzig (1947) – **simplex method**, a foundational LP algorithm
- Efficient in practice but **exponential worst-case complexity**
- Search for polynomial-time algorithms for LP
- Khachiyan (1979) – first polynomial-time LP algorithm (ellipsoid method)
- Karmarkar (1984) – **first practical polynomial-time algorithm**



Narendra Krishna Karmarkar (b. 1956)

IITB-CalTech-UC Berkeley

# Reference





# Optimized diet – wholesome & cheap

Design a daily diet that satisfies basic nutritional requirements

Nutrient	Minimum Required	Unit
Protein	50	g
Iron	18	mg
Fiber	25	g

# Optimized diet – wholesome & cheap

Design a daily diet that satisfies basic nutritional requirements

Nutrient	Minimum Required	Unit
Protein	50	g
Iron	18	mg
Fiber	25	g

## Available Food Items:

$x_1$  : Sprouts

$x_2$  : Spinach

$x_3$  : Rice

$x_4$  : Fish

# Optimized diet – wholesome & cheap

Design a daily diet that satisfies basic nutritional requirements

Nutrient	Minimum Required	Unit
Protein	50	g
Iron	18	mg
Fiber	25	g

## Available Food Items:

$x_1$  : Sprouts       $x_2$  : Spinach       $x_3$  : Rice       $x_4$  : Fish

## Nutrient Content per 100g:

Nutrient	Sprouts	Spinach	Rice	Fish
Protein (g)	22	2.9	2.6	20
Iron (mg)	3.9	2.7	0.4	0.7
Fiber (g)	7	2.2	1.8	0

# Optimized diet – wholesome & cheap

Design a daily diet that satisfies basic nutritional requirements

Nutrient	Minimum Required	Unit
Protein	50	g
Iron	18	mg
Fiber	25	g

## Available Food Items:

$x_1$  : Sprouts       $x_2$  : Spinach       $x_3$  : Rice       $x_4$  : Fish

## Nutrient Content per 100g:

Nutrient	Sprouts	Spinach	Rice	Fish
Protein (g)	22	2.9	2.6	20
Iron (mg)	3.9	2.7	0.4	0.7
Fiber (g)	7	2.2	1.8	0

## Constraints:

$$22x_1 + 2.9x_2 + 2.6x_3 + 20x_4 \geq 50 \quad (\text{Protein})$$

# Optimized diet – wholesome & cheap

Design a daily diet that satisfies basic nutritional requirements

Nutrient	Minimum Required	Unit
Protein	50	g
Iron	18	mg
Fiber	25	g

## Available Food Items:

$x_1$  : Sprouts       $x_2$  : Spinach       $x_3$  : Rice       $x_4$  : Fish

## Nutrient Content per 100g:

Nutrient	Sprouts	Spinach	Rice	Fish
Protein (g)	22	2.9	2.6	20
Iron (mg)	3.9	2.7	0.4	0.7
Fiber (g)	7	2.2	1.8	0

## Constraints:

$$\begin{aligned}22x_1 + 2.9x_2 + 2.6x_3 + 20x_4 &\geq 50 && \text{(Protein)} \\3.9x_1 + 2.7x_2 + 0.4x_3 + 0.7x_4 &\geq 18 && \text{(Iron)}\end{aligned}$$

# Optimized diet – wholesome & cheap

Design a daily diet that satisfies basic nutritional requirements

Nutrient	Minimum Required	Unit
Protein	50	g
Iron	18	mg
Fiber	25	g

## Available Food Items:

$x_1$  : Sprouts       $x_2$  : Spinach       $x_3$  : Rice       $x_4$  : Fish

## Nutrient Content per 100g:

Nutrient	Sprouts	Spinach	Rice	Fish
Protein (g)	22	2.9	2.6	20
Iron (mg)	3.9	2.7	0.4	0.7
Fiber (g)	7	2.2	1.8	0

## Constraints:

$$\begin{aligned}22x_1 + 2.9x_2 + 2.6x_3 + 20x_4 &\geq 50 && \text{(Protein)} \\3.9x_1 + 2.7x_2 + 0.4x_3 + 0.7x_4 &\geq 18 && \text{(Iron)} \\7x_1 + 2.2x_2 + 1.8x_3 &\geq 25 && \text{(Fiber)}\end{aligned}$$

# Objective: Minimize Diet Cost

... while meeting the dietary requirements

Each food item has an associated cost per 100g:

Food Item	Variable	Cost (Rs. per 100g)
Sprouts	$x_1$	50
Spinach	$x_2$	20
Rice	$x_3$	30
Fish	$x_4$	120

## Objective: Minimize Diet Cost

... while meeting the dietary requirements

Each food item has an associated cost per 100g:

Food Item	Variable	Cost (Rs. per 100g)
Sprouts	$x_1$	50
Spinach	$x_2$	20
Rice	$x_3$	30
Fish	$x_4$	120

Objective: minimize total cost of the diet



## Objective: Minimize Diet Cost

... while meeting the dietary requirements

Each food item has an associated cost per 100g:

Food Item	Variable	Cost (Rs. per 100g)
Sprouts	$x_1$	50
Spinach	$x_2$	20
Rice	$x_3$	30
Fish	$x_4$	120

Objective: minimize total cost of the diet

$$\min 50x_1 + 20x_2 + 30x_3 + 120x_4$$

## Objective: Minimize Diet Cost

... while meeting the dietary requirements

Each food item has an associated cost per 100g:

Food Item	Variable	Cost (Rs. per 100g)
Sprouts	$x_1$	50
Spinach	$x_2$	20
Rice	$x_3$	30
Fish	$x_4$	120

Objective: minimize total cost of the diet

$$\min 50x_1 + 20x_2 + 30x_3 + 120x_4$$

Nonnegativity Constraints:  $x_1, x_2, x_3, x_4 \geq 0$

## Objective: Minimize Diet Cost

... while meeting the dietary requirements

Each food item has an associated cost per 100g:

Food Item	Variable	Cost (Rs. per 100g)
Sprouts	$x_1$	50
Spinach	$x_2$	20
Rice	$x_3$	30
Fish	$x_4$	120

Objective: minimize total cost of the diet

$$\min 50x_1 + 20x_2 + 30x_3 + 120x_4$$

Nonnegativity Constraints:  $x_1, x_2, x_3, x_4 \geq 0$


(continue on board)

# Flow in a network

You want to transfer your music collection from an old computer to a new one, using a local network.

## Flow in a network


You want to transfer your music collection from an old computer to a new one, using a local network.



The numbers near each data link specify the maximum transfer rate of that link (in Mbps, say)

# Flow in a network

You want to transfer your music collection from an old computer to a new one, using a local network.




The numbers near each data link specify the maximum transfer rate of that link (in Mbps, say)

→ What is the maximum transfer rate from computer  $o$  to computer  $n$ ?

# Flow in a network

You want to transfer your music collection from an old computer to a new one, using a local network.



$$\text{maximize } x_{oa} + x_{ob} + x_{oc}$$

$$\begin{aligned} \text{subject to } & -3 \leq x_{oa} \leq 3, \quad -1 \leq x_{ob} \leq 1, \quad -1 \leq x_{oc} \leq 1, \\ & -1 \leq x_{ab} \leq 1, \quad -1 \leq x_{ad} \leq 1, \quad -3 \leq x_{be} \leq 3, \\ & -4 \leq x_{cd} \leq 4, \quad -4 \leq x_{ce} \leq 4, \quad -4 \leq x_{dn} \leq 4, \\ & -1 \leq x_{en} \leq 1, \end{aligned}$$

$$x_{oa} = x_{ab} + x_{ad}$$

$$x_{ob} + x_{ab} = x_{be}$$


$$x_{oc} = x_{cd} + x_{ce}$$

$$x_{ad} + x_{cd} = x_{dn}$$

$$x_{be} + x_{ce} = x_{en}.$$

## Flow in a network

You want to transfer your music collection from an old computer to a new one, using a local network.




The number near each link is the transfer rate on that link, and the arrow determines the direction of the data flow.



# Linear regression

.. when square isn't fair



# Linear regression

.. when square isn't fair



Instead of least squares:


$$\min \sum_{i=1}^n (mx_i + c - y_i)^2$$

suppose we want:

$$\min \sum_{i=1}^n |mx_i + c - y_i|$$

# Linear regression

.. when square isn't fair



Instead of least squares:

$$\min \sum_{i=1}^n (mx_i + c - y_i)^2$$

suppose we want:

$$\min \sum_{i=1}^n |mx_i + c - y_i|$$

# Least Absolute Error

$$\min \sum_{i=1}^n |mx_i + c - y_i|$$

Find the line  $y = mx + c$  that *minimizes the sum of absolute errors* using LP:

# Least Absolute Error

$$\min \sum_{i=1}^n |mx_i + c - y_i|$$

Find the line  $y = mx + c$  that *minimizes the sum of absolute errors* using LP:

$$\text{minimize } e_1 + \cdots + e_n$$

subject to

$$e_i \geq mx_i + c - y_i \quad \text{for } i \in [n],$$

$$e_i \geq -(mx_i + c - y_i) \quad \text{for } i \in [n].$$

## Least Absolute Error

$$\min \sum_{i=1}^n |mx_i + c - y_i|$$

Find the line  $y = mx + c$  that *minimizes the sum of absolute errors* using LP:

$$\text{minimize } e_1 + \cdots + e_n$$

subject to

$$e_i \geq mx_i + c - y_i \quad \text{for } i \in [n],$$

$$e_i \geq -(mx_i + c - y_i) \quad \text{for } i \in [n].$$

The constraints guarantee that

$$e_i \geq \max \{mx_i + c - y_i, -(mx_i + c - y_i)\} = |mx_i + c - y_i|.$$

## Separation of points

A computer-controlled **rabbit trap** should be programmed so that  
it catches **rabbits**,  
but if a **weasel** wanders in, it is released.

## Separation of points

A computer-controlled **rabbit trap** should be programmed so that  
it catches **rabbits**,  
but if a **weasel** wanders in, it is released.





## Separation of points

A computer-controlled **rabbit trap** should be programmed so that  
it catches **rabbits**,  
but if a **weasel** wanders in, it is released.




The trap can **weigh the animal** inside and  
also can determine the **area of its shadow**.



# Separation of points

Find a separating line?



# Separation of points

Find a separating line – Using LP

maximize  $\delta$

subject to  $y(p_i) \geq ax(p_i) + b + \delta$  ;  $i \in [m]$ ,

$y(q_j) \leq ax(q_j) + b - \delta$  ;  $j \in [n]$ .

# Separation of points

Find a separating line – Using LP

maximize  $\delta$

subject to  $y(p_i) \geq ax(p_i) + b + \delta$  ;  $i \in [m]$ ,

$y(q_j) \leq ax(q_j) + b - \delta$  ;  $j \in [n]$ .

