

# Auto-Commit Setup for GitHub Copilot Training

## Overview

Setting up automatic commits helps track every change made during GitHub Copilot exercises, making it easy to revert to previous states and understand the progression of development.

## Recommended Approaches

### 1. VS Code Extension: GitDoc (Recommended)

**Best for:** Real-time automatic commits on every save

```
vsls-contrib.gitdoc
```

#### Setup:

1. Install GitDoc extension
2. Open Command Palette ( `Cmd+Shift+P` )
3. Run `GitDoc: Enable`
4. Configure auto-commit settings

#### Benefits:

- Commits automatically on save
- Works seamlessly with GitHub Copilot
- Maintains detailed commit history
- Easy to enable/disable per project

### 2. VS Code Extension: Git Automator

**Best for:** Automated commit messages and workflow

```
ivangabriele.vscode-git-add-and-commit
```

**Features:**

- Custom commit message templates
- Keyboard shortcuts for quick commits
- Workflow automation

### 3. AI-Powered Commit Messages

**Best for:** Intelligent commit message generation

```
michaelcurrin.auto-commit-msg,sittoi.ai-commit
```

**Features:**

- Auto-generates meaningful commit messages
- Analyzes file changes for context
- Conventional commit format support



## Manual Git Hooks Setup

### Pre-Commit Hook for Training Sessions

Create a custom pre-commit hook that automatically stages and commits Copilot-related changes:

```
# Create pre-commit hook
cat > .git/hooks/pre-commit << 'EOF'
#!/bin/bash

# Auto-commit training changes
if [ -f ".copilot-training-mode" ]; then
    echo "🧠 Copilot Training Mode: Auto-committing changes"

    # Add all changes
    git add .

    # Create commit with timestamp
    TIMESTAMP=$(date "+%Y-%m-%d %H:%M:%S")
    git commit -m "🧠 Copilot Training Progress - $TIMESTAMP" --no-verify
fi
EOF
```

## Auto-Commit Setup for GitHub Copilot Training

```
# Make executable
chmod +x .git/hooks/pre-commit
```

To enable training mode:

```
touch .copilot-training-mode
```

To disable training mode:

```
rm .copilot-training-mode
```



## VS Code Settings for Auto-Save + Auto-Commit

Add these settings to your workspace or user settings:

```
{
  // Auto-save files for faster commits
  "files.autoSave": "onFocusChange",
  "files.autoSaveDelay": 1000,


  // Git settings
  "git.autofetch": true,
  "git.autoStash": true,
  "git.enableCommitSigning": false,






  // GitDoc specific settings (if using GitDoc extension)
  "gitdoc.enabled": true,
  "gitdoc.commitValidationLevel": "none",
  "gitdoc.commitMessageFormat": "🤖 Training: {filename} - {now}",
  "gitdoc.pullOnOpen": false,
  "gitdoc.pushOnSave": false,
  "gitdoc.commitOnSave": true
}
```

## Training-Specific Commit Strategy

### Commit Message Conventions

Use consistent prefixes to track different types of changes:

-  Copilot: - Changes made with Copilot assistance

-  Manual: - Manual code changes
-  Exercise: - Specific exercise completions
-  Setup: - Configuration and setup changes
-  Fix: - Bug fixes during exercises
-  Docs: - Documentation updates

## Example Workflow Script

Create a training helper script:

```
#!/bin/bash
# save as: copilot-commit.sh

EXERCISE_NAME="$1"
DESCRIPTION="$2"

if [ -z "$EXERCISE_NAME" ]; then
    echo "Usage: ./copilot-commit.sh <exercise-name> [description]"
    exit 1
fi

# Add all changes
git add .

# Create detailed commit message
TIMESTAMP=$(date "+%H:%M:%S")
if [ -n "$DESCRIPTION" ]; then
    COMMIT_MSG="🚧 Exercise: $EXERCISE_NAME - $DESCRIPTION [$TIMESTAMP]"
else
    COMMIT_MSG="🚧 Exercise: $EXERCISE_NAME completed [$TIMESTAMP]"
fi

# Commit with message
git commit -m "$COMMIT_MSG"

echo "✅ Committed: $COMMIT_MSG"
```

### Usage:

```
./copilot-commit.sh "interface-basics" "Completed keyboard shortcuts practice"
./copilot-commit.sh "entity-creation" "Added User entity with JPA annotations"
```

## Commit History Navigation

### Useful Git Commands for Training

```
# View training session commits
git log --oneline --grep="🧠"

# View commits from last hour
git log --since="1 hour ago" --oneline

# View commits for specific file
git log --oneline -- src/main/java/com/taskmanager/app/entity/User.java

# Create checkpoint tags
git tag -a "checkpoint-$(date +%Y%m%d-%H%M)" -m "Training checkpoint"

# Quick revert to previous commit
git reset --hard HEAD~1

# View changes in last commit
git show HEAD
```





### VS Code Git Timeline


Use VS Code's built-in Git Timeline feature:

1. Open Source Control panel ( **Ctrl+Shift+G** )
2. Enable Timeline view in Explorer
3. See file-by-file commit history
4. Right-click commits to revert changes






## Best Practices

### Do's

-  Use descriptive commit messages with emojis
-  Enable auto-commit only during training sessions
-  Create checkpoint tags at major milestones
-  Review commit history regularly

-  Use consistent message formatting

### Don'ts

-  Auto-commit sensitive information
-  Leave auto-commit enabled for production code
-  Commit incomplete or broken code frequently
-  Forget to disable auto-commit after training
-  Auto-push to shared repositories without review

## Reverting Changes

### Quick Revert Options

```
# Undo last commit (keep changes)
git reset --soft HEAD~1

# Undo last commit (discard changes)
git reset --hard HEAD~1

# Revert specific file to previous version
git checkout HEAD~1 -- path/to/file.java

# Interactive revert (choose commits)
git rebase -i HEAD~10
```

### VS Code Revert

1. Open Source Control panel
2. Right-click on commit in timeline
3. Select "Revert Changes in Commit"
4. Or use "Reset to Commit" for harder reset

This setup ensures every Copilot-assisted change is tracked and easily reversible! 🎯

## Creating Restore Checkpoints

### 1. Use Timeline View (Local History) - Best for Automatic Checkpoints

VS Code automatically saves a history of your changes every time you save a file.

**Save Your File:** Before significant changes, save the file ( `Ctrl+S` or `Cmd+S` ). This creates a checkpoint in local history.

**Open the Timeline:** In the Explorer panel, see the "Timeline" view at the bottom. Or use Command Palette: "Timeline: Show Timeline".

**Restore a Checkpoint:** Click any previous save to see a diff view and use the Restore button to revert.

### 2. Use Git Commits - Best for Major Checkpoints

For significant checkpoints (e.g., before refactoring with Copilot):

#### Stage and Commit:

1. Go to Source Control view (branching icon in sidebar)
2. Stage changes with the '+' icon
3. Write commit message: "Checkpoint before Copilot refactoring"
4. Click checkmark to commit

**Revert if Needed:** Right-click on changed file → "Discard Changes"

### 3. Use Undo - Best for Immediate Reversal

If you accept a Copilot suggestion and immediately want to revert:

- **Windows/Linux:** `Ctrl+Z`
- **Mac:** `Cmd+Z`

### Recommended Checkpoint Workflow

Change Size	Method
Small changes	Undo ( <code>Ctrl+Z</code> )
Medium changes	Timeline view (Local History)

## Auto-Commit Setup for GitHub Copilot Training

Change Size	Method
Major changes	Git commits