



OpenLCB Technical Note	
Function Description Information	
Nov 9, 2014	Preliminary

1 Introduction

"Function description information" in this context refers to *fixed* information available from an OpenLCB Train device, via OpenLCB, so that other devices can properly and correctly configure it. The information is fixed, so that it can be pre-compressed, stored in the device, and just supplied when needed with minimal work on the part of the device and the device's developers. This means that e.g. the actual current configuration contents are not available as part of the FDI, as that is variable information. Similarly, the FDI cannot contain e.g. a serial number as that would require different FDI contents in each node of a single type.

- Other information may be available via e.g. manuals or the Internet, and there may be pointers to that information in the FDI, but the format of that information is not under specification here.

A key use for FDI is to enable a Configuration Tool (CT) to know how to configure the node. The configuration tool will use the FDI information to render some form of suitable Graphical User Interface to allow the user to easily and intuitively configure all aspects of the node's capabilities. An important design choice was to embed the FDI into each node so that the system has all it needs to configure the node without having to source the information externally to the OpenLCB network from the manufacturer or some other on-line repository via the Internet or a CD/DVD etc. While the CT is likely to be a program running on a PC, it could be a hand-held throttle like mobile phone or PDA or even a custom-built device.

2 Annotations to the Standard

2.1 Introduction

Note that this section of the Standard is informative, not normative.

2.2 Intended Use

- Note that this section of the Standard is informative, not normative.

2.3 Reference and Context

See Memory Configuration Protocol. That's one use for the FDI, and one way to retrieve it, but FDI is independent of that.

- CiA 306 "Electronic data sheet specification" describes the CANopen version of a similar capability.

3 Stuff to be merged into the above

3.1 Environment of Proposal

3.1.1 Requirements

- 35 • Nodes must carry enough context that a stand-alone configuration tool can provide a useful human interface without getting any data from an external source, e.g. needing an Internet download to handle a new node type.
- It must be possible to configure a node entirely over the OpenLCB, without physical interactions, e.g. pushing buttons.

3.1.2 Preferences

- 40 • Small nodes shouldn't need a lot of processing power, e.g. to compress or decompress data in real time. Memory usage should also be limited, but is a second priority.
- Configuration operations should be state-less and idempotent to simplify software at both ends.
- 45 • Multiple independent configuration operations can proceed at the same time. Specifically, multiple devices should be able to retrieve correct configuration description information at the same time.

Design Points

Basic configuration is done with the [configuration protocol](#) defined elsewhere.

50 The “Variables” described here are not exactly the same thing as “Configuration Variables” (CVs) or “Node Variables” (NVs) that are discussed elsewhere. Those are aimed at storage, and so are grouped by address. The “Variables” here are grouped by function. “Long address” might be several CVs, but would be one variable to this proposal. Similarly, CV29 has lots of variables within it, each stored as bits. Perhaps it would be better to use a different name here, such as “Setting” or “Option”?

3.2 Proposal

3.2.1 Definition

60 Function values are stored in the 0xF9 memory space. "Function Definition Information", similar in intent to Configuration Definition Information (CDI) is stored in XML format in address space 0xFA to provide user-oriented context. That includes:

65 Memory layout of the function values, allowing for multiple data types from binary (one and off for lights) through integer values (for e.g. sound intensities) and strings (sign displays?).

 Function naming, so that a throttle can display useful names to the user such as "Bell", "Coupler Clank" and "Master Volume". This includes internationalization of those labels.

 What else needs to be conveyed? "Make this prominent on the throttle"? "Have this there, just a little less prominent"? "Seriously, nobody cares about this option, bury it"?

70 At present, there are no default values that e.g. associate "Bell" with a particular location or function. These are thought to be too brittle, and there are just too many possibilities to be useful (see the unscientific and incomplete Survey of existing function names).
Sample function definition XML:

```

75 <?xml version='1.0' encoding='UTF-8'?>
    <?xml-stylesheet type='text/xsl' href='xslt/fdi.xsl'?>
    <fdi xmlns:xsi='http://www.w3.org/2001/XMLSchema-instance'
      xsi:noNamespaceSchemaLocation='http://openlcb.org/trunk/prototypes/xml/schema/fdi.xsd'>

80   <segment origin='0' space='250'>
     <group>
       <name>Lighting Functions</name>
       <description>Headlights and Markerlights and Runninglights, oh my.</description>
       <function offset="5" size="1" kind="binary">
85         <name>Headlights</name>
           <number>0</number>
         </function>
       <function size="1">
           <name>Ditch Lights</name>
90         <number>4</number>
       </function>
     </group>
     <group>
       <name>Sound Functions</name>
       <description>Toot toot!</description>
95       <function size="2" kind="analog">
           <name>Horn</name>
           <number>8</number>
         </function>
100    </group>
  </segment>
</fdi>

```

The structure is similar to CDI, with named sections that give the general location of the storage.
105 "number" is a hint that can be used to locate the function on a numbered GUI element (e.g. button);
"name" is the same if the GUI element can have a readable label.
"kind" is an enumerated type of (initially) "binary" and "analog". These are done as specific elements in CDI, and perhaps that's a better approach.

110 A sample implementation of the DCC F0-F28 functions, as described on the Function Control page:

```

    <?xml version='1.0' encoding='UTF-8'?>
    <?xml-stylesheet type='text/xsl' href='xslt/fdi.xsl'?>
    <fdi xmlns:xsi='http://www.w3.org/2001/XMLSchema-instance'
115   xsi:noNamespaceSchemaLocation='http://openlcb.org/trunk/prototypes/xml/schema/fdi.xsd'>

```

```

<segment origin='0' space='250'>
  <group>
    <name>F0-F28</name>
    <description>Standard DCC functions</description>
120    <function size="1" kind="binary">
      <name>Headlight</name>
      <number>0</number>
    </function>
    <function size="1">
125      <number>1</number>
    </function>
    ...
    <function size="1">
      <number>28</number>
130    </function>
    </group>
  </segment>
</fdi>

```

135 3.2.2 Storage

THIS IS COPIED FROM THE CDI CURRENTLY, THIS NEEDS TO BE UPDATED TO BE FDI SPECIFIC.....

140 The configuration definition is stored in a hierarchical manner.

I) In what follows:

145 A "String" must be present; an "Optional String" does not have to be. Strings are in UTF-8.

An "Integer" may be signed; if no sign, it's taken as positive.

A "Map" provides a set of named descriptive values. It contains:

150 Name: Optional String, if present required to be unique within enclosing group or node
 Description: Optional String
 1 or more "Key", "Value" pairs. Each element of the pair can be of any supported type,
 depending only on how it is to be used.

155 Map elements provide a mapping between the pairs they contain. For example, a map can relate
 numeric values for a variable to description strings. A map can also be used to provide free-form
 documentation when neither the key nor the value are specified in advance. It may be useful in the
 future to specify how maps can be defined at the group level to reduce duplication. Having the
 possibility of a "Name" is meant to ease that future effort.

160 II) At the top, root level is the information for a "node". This includes:

Manufacturer: String

Descriptive Map: May contain "Model", "Version", "URL" and "Description" keys, along with any others desired.

165

Model: If present, the human-readable model name the manufacturer gives to this node.

Version: If present, the human-readable version string for the current board.

Description: Optional String

170 URL: If present, a URL for more information. No specific content is expected at the URL; If desired, that can be dealt with in a different specification.

Any other information desired can be added via additional keys.

III) Within the node is zero or more "groups". Each group contains:

175

Name: String, required to be unique within enclosing group or node

Descriptive Map: Map of documentation information; the "Description" key is the basic item.

Replication count: Integer ≥ 1 (number of times this group is replicated within the parent item)

180 A group with a replication count > 1 (called a replicated group) can be used to represent a type of replicated device. For example, a node with 4 identical input devices and 6 identical output devices can be compactly described by two groups, with replication counts of 4 and 6 respectively.

185 Individual groups within replicated groups are numbered from 1 to the replication count. If more than one replicated group is present, the numbering for each starts again with 1.

Groups may contain one or more inner groups, with the same representation. This may continue to any desired level.

190 IV) Groups may contain "variable", "producer" and/or "consumer" descriptions.

IV-a) A "variable" description contains:

Name: String, required to be unique within enclosing group or node

195 Type: Exactly one of "boolean", "digit" (an unsigned binary-coded-decimal value), "signed" (a binary value with a sign), "unsigned" (a binary value without a sign), "string" (a UTF-8 string, not-null terminated), or "blob" (arbitrary byte vector).

Max: Integer - For string and blob variables, the maximum number of bytes that can be stored. For digit, signed and unsigned types, the maximum value allowed.

200 Min: Integer - For digit, signed and unsigned values, the minimum value allowed.

Description: Optional String

Default: value of this Type, required

Offset: Optional integer offset with in the configuration address space for this item; if not present, data is laid out by length in depth-first order.

205

A variable may contain zero or one map descriptions. If present, the map represents a mapping between possible values (the "Key" part of the map's pairs) and convenient names for them (the "Value" part of the map's pairs).

- 210 Note that the current value of a variable is not considered configuration definition information (see item 1A and 1B in the introduction).

- 215 Configuration information must not be packed into variables; each variable must represent one type of information. In particular, the use of individual bits within larger values to pack multiple pieces of information is forbidden; those must be represented as individual variables. (How the information is stored internally is up to the designer of the specific device, and is not restricted; this requirement is about access to the information, not about how it's laid out in physical memory)

- 220 IV-b) A "producer" description contains:

Name: String, required to be unique within enclosing group or node

Description: Optional String

Replication count: Integer ≥ 1 (number of times this producer definition is replicated within the parent item)

- 225 Offset: Optional integer offset with in the configuration address space for this item; if not present, data is laid out by length in depth-first order.

A producer description may contain zero or more variable descriptions for any variables that configure details of the producer's function.

230

- IV-c) A "consumer" description contains:

Name: String, required to be unique within enclosing group or node

Description: Optional String

- 235 Replication count: Integer ≥ 1 (number of times this consumer definition is replicated within the parent item)

Offset: Optional integer offset with in the configuration address space for this item; if not present, data is laid out by length in depth-first order.

- 240 A consumer description may contain zero or more variable descriptions for any variables that configure details of the consumer function. This may include e.g. variables that define how any content in incoming messages will be used.

3.2.3 Serialization

- 245 The logical layout in the previous section has to be converted to some serial set of bytes for transfer and storage.

The primary format is straight-forward XML. (Link to schema)

- 250 Another is compressed binary information. Either an aggressive compression algorithm, or some context-aware compression, can be used. Size and ease of expansion are the key criteria; ease of compression is much less important. XSLT can do some of the reformatting between compact and readable form

We need to pick one format for a lingua franca.

3.3 Example

The following is not meant to show how configuration definition information would be stored, but what kinds of information would be stored. It's a description of a complex accessory decoder, the Digitrax DS54, modified for use in a Producer-Consumer model.

Hopefully the syntax will be self-explanatory. In any case, it's just for this example, not a proposal of any kind.

```

260  Manufacturer (String): Digitrax
      Model (String): DS54
      Version (String): 2.33
      Description (Optional String): For more information, see http://digitrax.com/asdf/123

265  Group start:
      Name (String): Decoder
      Description (Optional String): These variables describe the entire board
      Replication count (integer): 1

270      Variable:
          Name: Address
          Type: Integer
          Max: 2044
          Min: 0
275      Description: This is the board address, in DCC space originally

      Group start: (Note this is nested in "Decoder")
          Name (String): Channel
280      Description (Optional String): Each Channel is one pair of output wires and contains two
          inputs
          Replication count (integer): 4

          Group start: (Note this is nested in "Channel")
285          Name (String): Input
          Description (Optional String): Each Channel has two inputs, called "Switch"
          and "Aux"
          Replication count (integer): 2

290      Producer start:
          Name: Switch Input Active
          Description: Driven by the 1st input wire for this channel. The variables control
          ....

295      Variable:

```

Name: Input Type

Type: Integer

Max: 10

Min: 0

Default: 0

Description: Specify the type of signal expected on this input

Map:

Name: Values

"0", "positive edge"

"1", "negative edge"

"2", "either edge"

...

Map End

Variable End

Variable:

Name: Input Task

Type: Integer

Max: 8

Min: 0

Default: 0

Description: Specify the local action when this input is active

Map:

Name: Values

"0", "Output toggle"

"1", "No output change"

"2", "Output thrown"

...

Map End

Variable End

Producer end:

Producer start:

Name: Aux Input Active

Description: Driven by the 2nd input wire for this channel. The variables control

Variable:

Name: Input Type

Type: Integer

Max: 10

Min: 0

Default: 0

Description: Specify the type of signal expected on this input

Map:

Name: Values

"0", "positive edge"

"1", "neither edge"
 "2", "either edge"

...

Map End

Variable End

Variable:

Name: Input Task

Type: Integer

Max: 8

Min: 0

Default: 0

Description: Specify the local action when this input is active

Map:

Name: Values

"0", "Output toggle"

"1", "No output change"

"2", "Output thrown"

...

Map End

Variable End

Producer end:

Group end: (This is the end of the input group)

Variable:

Name: Output Type

Type: Integer

Max: 40

Min: 0

Default: 0

Description: Determines what the output leads do in response to events

Consumer start:

Name: Turnout Active Thrown

Description: Set the thrown output lead active and closed lead inactive.

Consumer end:

Consumer start:

Name: Turnout Active Closed

Description: Set the closed output lead active and thrown lead inactive.

Consumer end:

Consumer start:

Name: Turnout Active Both

Description: Sets both output leads active.

Consumer end:

390 Consumer start:
Name: Turnout Inactive
Description: Sets both output leads inactive.
Consumer end:

395 Group end: (This is end of the "Channel" group)

Group end: (This is end of the "Decoder" group)

400 Some thoughts based on putting this example together:

1) In a real DS54, there are subtle differences between the Switch and Aux configuration choices on the various channels. I blurred those here by documenting them identically via replication. For a real device, they could either be separately specified or (more likely) the differences wouldn't matter in a P/C-based device.

2) A DS54 can receive messages that put its output into four states: One side on, the other side on, both sides on, and neither side on. These four interacts with the "Output Type" setting in weird and wonderful ways. This was represented as four consumers. This seems a much more logical way to configure the device, as it gives more flexibility to the rest of the layout that's originating the requests.

3) The DS54 inputs also generate messages. They are specified as two producers (for the active and inactive messages).

3.4 Implementation Notes

415 This section is non-normative notes and suggestions for implementors.

Some references for XML compression:

<http://www.ibm.com/developerworks/xml/library/x-datacompression/index.html?cmp=dw&cpb=dwxml&ct=dwnew&cr=dwnen&ccy=zz&csr=072111>

420 <http://www.cs.panam.edu/~artem/main/teaching/csci6370spring2011/papers/XML%20compression%20techniques%20A%20survey%20and%20comparison.pdf>

On the other hand, a look-back compression algorithm has the advantage that it's cheap to decompress and might do almost as well:

<http://excamera.com/sphinx/article-compression.html>

425 XML strings can start with a UTF BOM (either 0xEF, 0xFF or 0xFE in the 1st byte, since there's no need to support UTF-32BE or UTF-32LE), or the UTF-8 text for “<?xml” which starts with 0x3C. (But concern about support for too many character sets!)

A first byte of 0x80 is defined as the “Compressed” indicator(s), followed by a byte that indicates the compression type. (We don't want to have too many kinds, as receivers need to implement all of them)

430 to be able to use the FDI!) 0x80 00 is the code for our choice of default, see
<http://excamera.com/sphinx/article-compression.html>

4 Remaining items

Internationalization of the XML content?

Talk about the encoding string in the <?xml first line, and UTF-8 coding as default; ASCII as subset.

435 Mini-XML effort; we're using as simple a subset as possible.

Table of Contents

1 Introduction.....	1
2 Annotations to the Standard.....	1
2.1 Introduction.....	1
2.2 Intended Use.....	1
2.3 Reference and Context.....	1
3 Stuff to be merged into the above.....	2
3.1 Environment of Proposal.....	2
3.1.1 Requirements.....	2
3.1.2 Preferences.....	2
Design Points.....	2
3.2 Proposal.....	2
3.2.1 Definition.....	2
3.2.2 Storage.....	3
3.2.3 Serialization.....	5
3.3 Example.....	6
3.4 Implementation Notes.....	9