

This is a draft document, and has no official standing. It has not been submitted to the NMRA Technical Department or the NMRA Board of Directors for approval.

NMRA Standards

NMRANet[®]

Physical Layer

All Scales

01/08/10

Draft S-9.x.1

Introduction (Informative)

This document describes the physical layer for carrying NMRANet over a Controller Area Network (CAN) link or links. It describes nothing else. Seriously, if you want to know about Ethernet, or modular standards for power connections, or how to make really good fried chicken, look elsewhere.

Intended Use (Informative)

Suitable NMRANet nodes can be connected by cables to form a linear CAN bus with optional short stubs. Users can expect to be able to form networks within limitations:

- Total cable length of 1000 ft / 300m; stub cables count double their length in that total; nodes count as 20 ft / 6m in that total
- Never less than 1 ft / 30cm of cable between nodes, nor between a stub connection and a node.
- No more than 50 nodes connected

NMRANet nodes generally have two RJ45 modular connectors and can be daisy-chained together with suitable computer-network ("Ethernet") cables. A CAN terminator is installed by the user at each end of the main bus.

A limited amount of power can be distributed via the cable, allowing a few nodes draw limited power from a 10 ft / 3m length of the common bus.

References and Context (Normative)

In this document

- "RJ45" refers to the miniature 8 position unkeyed plug and jack defined in sections Section 6.1.1.3 and Section 6.1.1.4, respectively, of the TIA-968-A specification.
- "UTP" refers to CAT-3 or better cable as defined in TIA/EIA-568-B or the successor TIA/EIA- 568-C.
- "CAN" refers to the electrical and protocol specifications as defined in ISO 11898-1:2003 and ISO 11898-2:2003 and their successors.

External certification of parts shall be accepted for conformance to these standards. Conformance with a later version of a standard shall be accepted as conformance with the referenced versions.

30 Physical Interconnection (Normative)

CAN connections between nodes shall be made using UTP cable. Connectors are not required, but if connectors are provided, there shall be a RJ45 plug on the cable and RJ45 jack on the node. The signal, conductor and pair assignments shall be:

Conductor	Signal Name	TIA/EIA-568-A Pair (Informative)	TIA/EIA-568-B Pair (Informative)
1	CAN_H	white/green	white/orange
2	CAN_L	green	orange
3	CAN_GND	white/orange	white/green
4	reserved	blue	blue
5	reserved	white/blue	blue
6	CAN_SHIELD	orange	green
7	PWR_NEG	white/brown	white/brown
8	PWR_POS	brown	brown

- 35 Cables, including cables attached to nodes, shall carry conductors 1 & 2 as a pair, and conductors 3 & 6 as a pair. Conductors 4 and 5, if present, shall be carried as a pair. Conductors 7 and 8, if present, shall be carried as a pair.

- 40 If two or more connections are provided, conductors 1 through 7 shall be connected in parallel on all connectors with connections rated for current of at least 1A. If the node does not provide power on pin 8 on all connectors, pin 8 on all connectors must be connected in parallel with connections rated for current of at least 1A.

Nodes shall connect conductors 3 and 6 with a connection rated for a current of at least 1A.

A node may, but is not required to, connect conductor 7 with conductors 3 and 6.

- 45 Voltages of up to 100 volts AC or either polarity DC on the reserved conductors shall not damage the node nor prevent normal operation of the node.

Data Transport (Normative)

Data shall be transferred using a CAN signal at 125kbps and CAN frame protocol. The bit slew rate of the CAN signal, as transmitted, shall be less than 10V/microsecond and more than 4V/microsecond.

50 **Supply of Power (Normative)**

A node may, but is not required to, provide power to the cable PWR_VPOS/PWR_VNEG conductors.

55 If a node provides power, it shall provide at least 9VDC and no more than 15VDC from zero current draw up to its specified maximum current. Its specified maximum current shall not exceed 1A. The specified maximum current shall be permanently written on the node in a location visible to the user. This label is required whether or not the node provides power to the cable. (needs a “shall withstand” clause for applied external voltage?)(needs a “shall withstand short circuits on the output ...”?)

Consumption of Power (Normative)

60 Nodes may, but are not required to, draw power from the PWR_VPOS/PWR_VNEG conductors in the cable. Nodes shall not draw more than 250mA at any PWR_VPOS/PWR_VNEG voltage from 7.5VDC to 15VDC. Nodes shall operate properly with a supply voltage of 7.5VDC to 15VDC on the PWR_VPOS/PWR_VNEG conductors. The maximum current drawn by each node shall be permanently written on that node in a location visible to the user. This label is required whether or not the node draws power from the cable. (needs a “shall withstand” clause for applied external voltage?)

Table of Contents

Introduction (Informative).....	1
Intended Use (Informative).....	1
References and Context (Normative).....	1
Physical Interconnection (Normative).....	2
Data Transport (Normative)	2
Supply of Power (Normative)	2
Consumption of Power (Normative)	3