

Unique ID part name	Value	EventID definitions	
		Suffix	Meaning
Well-known Event Reserved UID*	01.01.00.00.00.00	0xFFFF	Emergency stop of all operations
Well-known Event Reserved UID*	01.01.00.00.00.00	0xFFFF8	Node recorded a new log entry (see Logging protocol doc)
Well-known Event Reserved UID*	01.01.00.00.00.00	0xFE00	Ident button combination pressed
Well-known Event Reserved UID*	01.01.00.00.00.00	0x0201	Duplicate Node ID Detected
Well-known Event Reserved UID*	01.01.00.00.00.00	0x0301	(Reserved)
Well-known Event Reserved UID*	01.01.00.00.00.00	0x0302	(Reserved)
Well-known Event Reserved UID*	01.01.00.00.00.00	0x0303	This node is a Train (or Train Proxy)
Well-known Event Reserved UID*	01.01.00.00.00.00	0x0304	This node is an idle Train or Train Proxy (not dedicated to any physical train)
Well-known Event Reserved UID*	01.01.00.00.00.00	0x0305	This node is an in-use Train or Train Proxy (dedicated to a train)
Well-known Event Reserved UID*	01.01.00.00.00.00	0x0401	This node is a DCC Command Station
CBUS Mapped Event reserved UID*	01.01.01.00.00.00	(any)	CBUS short-ID equivalent events

* - "Well-known Event Reserved UID*" refers to a unique ID assigned for global fixed events, 01.01.00.00.00.00

* - "CBUS Mapped Event reserved UID" refers to a unique ID assigned range for CBUS-style "short events", 01.01.01.00, see Unique Identifiers section

EventID definitions

rain)

andard