

EventID definitions			
Unique ID part name	Value	Suffix	Meaning
Well-known Event Reserved UID*	01.01.00.00.00.00	0xFFFF	Emergency stop of all operations
Well-known Event Reserved UID*	01.01.00.00.00.00	0xFFF8	Node recorded a new log entry (see Logging protocol doc)
Well-known Event Reserved UID*	01.01.00.00.00.00	0xFE00	Ident button combination pressed
Well-known Event Reserved UID*	01.01.00.00.00.00	0x0201	Duplicate Node ID Detected
Well-known Event Reserved UID*	01.01.00.00.00.00	0x0301	This node is a DCC Command Station
Well-known Event Reserved UID*	01.01.00.00.00.00	0x0302	(Reserved)
Well-known Event Reserved UID*	01.01.00.00.00.00	0x0303	This node is a Train Proxy
Well-known Event Reserved UID*	01.01.00.00.00.00	0x0304	This node is an idle Train Proxy (not dedicated to any train)
Well-known Event Reserved UID*	01.01.00.00.00.00	0x0305	This node is an in-use Train Proxy (dedicated to a train)
CBUS Mapped Event reserved UID*	01.01.01.00.00.00	(any)	CBUS short-ID equivalent events

\* - “Well-known Event Reserved UID\*” refers to a unique ID assigned for global fixed events, 01.01.00.00.00.00

\* - “CBUS Mapped Event reserved UID” refers to a unique ID assigned range for CBUS-style “short events”, 01.01.01.00, see Unique Identifiers st

## EventID definitions

andard