

Name	DID?EID?CAN Y/N/CY/N/Flags?		Wire Hex Nibble 1 (3 bits)	Wire Hex Nibble 2 (5 bits)	Wire Hex Nibble 3	Wire Hex Total	CAN Var Total	Flag bit A 0 default	Flag bit B 1 default	Flag bit C 0 default	Flag bit D 1 default	CAN Content	
			Simple Node MsgGroup (2 bits)	Priority (4 bits)	Type (3 bits)	DID/EID/Flags 16 bits hex	15 bits hex	Format 3 bits	Type Byte 8 bits	1 bit	1 bit	1 bit	1 bit
Base Messages													
Initialization Complete	N	N		0	8	0	3080	1	0x08				Full Source Node ID
Verify Node ID Number	Y	N	Y	0	10	4	30A4	6	dest NIDa				MTI byte 0x0A
Verify Node ID Number	N	N	Y	0	10	0	30A0	0	0x0A				
Verified Node ID Number	N	N		0	11	0	30B0	1	0x0B				Full Source Node ID
Optional Interaction Rejected	Y	N		0	12	4	30C4	6	dest NIDa				MTI byte 0x0C, MTI, optional information
Terminate Due to Error	Y	N		0	13	4	30D4	6	dest NIDa				MTI byte 0x0D, MTI, optional information
Event Exchange Messages													
Identify Consumers	N	Y	Y	1	4	2	3242	0	0x24				EventID (no room for DestID!)
Consumer Identify Range	N	Y		1	5	2	3252	1	0x25				EventID w mask (no room for DestID!)
Consumer Identified	N	Y	Y	1	6	3	3263	1	0x26		valid	uncertain	EventID (no room for DestID!)
Identify Producers	N	Y	Y	1	8	2	3282	0	0x28				EventID (no room for DestID!)
Producer Identify Range	N	Y		1	9	2	3292	1	0x29				EventID w mask (no room for DestID!)
Producer Identified	N	Y	Y	1	10	3	32A3	1	0x2A		valid	uncertain	EventID (no room for DestID!)
Identify Events	Y	N	Y	1	11	2	32B2	6	dest NIDa				MTI byte 0x2B
Identify Events	N	N	Y	1	11	0	32B0	0	0x2B				
Learn Event	N	Y	Y	1	12	2	32C2	0	0x2C				EventID
Producer/Consumer Event Report	N	Y	Y	1	13	2	32D2	0	0x2D				EventID
Datagram Messages													
Datagram (General)	Y	N	Y	2	0	4	3404	4,5	dest NIDa				Data (0-8 bytes)
Datagram Received OK	Y	N	Y	2	12	4	34C4	6	dest NIDa				MTI byte
Datagram Rejected	Y	N	Y	2	13	4	34D4	6	dest NIDa				MTI byte, error code
Stream Messages													
Stream Initiate Request	Y	N		2	14	4	34E4	6	dest NIDa				MTI byte, buffer size (2 bytes), Source Stream ID (1 byte), reserved byte, flags (tagged=0x80)
Stream Initiate Reply	Y	N		2	15	4	34F4	6	dest NIDa				MTI byte 0x4B,buffer size (2 bytes), Source Stream ID (1 byte), Dest Stream ID, flags (tagged=0x80; error info)
Stream Data Send	Y	N		3	9	4	3694	7	dest NIDa				(stream IDs inferred on CAN); 8 bytes data
Stream Data Proceed	Y	N		3	10	4	36A4	6	dest NIDa				MTI byte, Stream IDs (2 bytes)
Stream Data Complete	Y	N		3	11	4	36B4	6	dest NIDa				MTI byte, Stream IDs (2 bytes); optional length (4 bytes)
0 gets more priority													
coding													
1=carries EID													
2=carries DID													
0=simple MTI													
1=complex MTI													
Full value must be checked!													
4=DestID datagram													
5=DestID datagram last segment													
6=DestID non-Stream													
7=DestID stream data													
If flags not specified, send and check 1 bits													
Places these appear in code:													
prototypes/Arduino/libraries/OpenLCB/OpenLcbCan.h													
prototypes/CBUS-PIC/canlib/frametypes.c													