



OpenLCB Technical Note

OpenLCB-CAN Frame Transfer

May 6, 2012

Preliminary

1 Introduction

This Technical Note contains informative discussion and background for the corresponding “OpenLCB CAN Frame Transfer Standard”. This Technical Note is not normative in any way.

For information on format and presentation conventions, see:

- OpenLCB Common Information Technical Note

The Frame Transfer layer of the OpenLCB-CAN stack lives above the CAN Physical Layer, and below the Message Network layer. It is responsible for ensuring the reliable transport of the CAN frames that make up OpenLCB-CAN messages. CAN provides reliable transport between any two nodes on a CAN segment within limitations:

1. Every CAN header must be unique by construction. Collisions between frames with identical headers and no data can result in lost frames; collisions between frames with identical headers that do contain data do not result in well-defined behavior. Both cases must be avoided by design to avoid intermittent problems.
 2. CAN does not provide any indicator of which node sent a particular frame. Any node can send any frame, and the receiving nodes have no CAN-provided mechanism for identifying the source.
 3. It's useful to have a way of addressing a frame to be processed by a specific node, but all CAN nodes receive every frame.
 4. CAN does not provide a “link up” or “link down” notification. Nodes may come and go from a CAN segment at any time, and on an individual basis. In general, one can't assert that a particular node is always present, always comes up first, or never comes up first.
 5. On a busy segment, CAN frames are sent in a strict priority order, with the priority determined by the content of the frame headers. If multiple nodes have frames to send at the same time, the highest priority (lowest numerical value header) frame will be sent first. There is no concept of “reserved bandwidth” except through frame priority, and low-priority frames may require significant time to be sent.
 6. Nodes must be able to accept frames at the full CAN rate. Hardware filters must be usable to help with that, but even then nodes may receive adjacent frames addressed to them.
- Putting a unique source ID field in each frame ensures that the frames are unique (item 1 above), and provides a frame-level indicator of which node sent the frame for the purposes of monitoring, debugging, etc (item 2). Providing a destination address field in the frame header

allows a standard method of addressed communications (item 3). Using a distributed algorithm to determine the value for that ID field prevents needing a single “manager” to provide it, thereby
 35 handling item 4. The header bit fields discussed below are organized to handle items 5 and 6.

OpenLCB-CAN is required to work with standard CAN components, e.g. bridges and computer adapters must not require customization to operate with OpenLCB. This provides a stringent requirement on protocol design, in that OpenLCB-CAN cannot require specific timing, deliberate creation of error cases or specific error handling.

40 OpenLCB-CAN is required to work without user intervention; user presets are neither required nor permitted.

It's desirable for OpenLCB-CAN nodes to detect duplicate (non-unique) Node IDs, but 100% reliable detection is not required.

1.1 Load-Related Frame Synchronization

45 CAN networks exhibit a behavior called “load-related frame synchronization” (it also goes by other names).

Because of the CAN priority arbitration structure, the network can run at high utilization rates. Under those circumstances, all nodes attempt to send their highest-priority frame, and the node with the absolute highest priority frame (first dominant bit) wins. All other nodes wait until just after that frame
 50 and try again.

This behavior greatly increases the probability of collisions when multiple nodes attempt to send frames with the same header.

Consider 5 nodes each of which want to send the high-priority frames 1,...,5, plus one more node A that wants to send the low priority frame 15. If all those nodes attempt to send at once, the frames will
 55 arbitrate out and will be sent in the order 1,2,3,4,5,15. If another node, B, also wants to send a frame 15, and starts to send it at any point during that entire sequence, it will end up colliding with the 15 that is being sent by A.

Particularly during layout startup, when lots of nodes have frames to send, this will result in an unacceptable probability of error unless the protocols have been designed to have as few header
 60 collisions as possible, and absolutely no data collisions.

2 Annotations to the Standard

This section provides background information on corresponding sections of the Standard document. It's expected that two documents will be read together.

2.1 Introduction

65 (Nothing to add to the Standard)

2.2 Intended Use

The OpenLCB protocol suite uses 6-byte Node ID values, but this protocol layer could be useful in other contexts too. The Standard is therefore written so that any Node ID length from 12 bits through $7 \times 12 = 84$ bits can be used in a straight-forward manner.

70 2.3 References and Context

Note that the Standard references the Unique ID Standard, but only to the extent that each node is required to have a unique ID as its node ID. The Standard would work equally well with a Unique ID that was allocated via any mechanism, and with any length from 12 through 84 bits. OpenLCB uses a 48-bit unique ID as a node ID, which is assumed for the rest of this Technical Note.

75 2.4 Frame Format

Standard header frames are also known as CAN 2.0A frames. Extended header frames are also known as CAN 2.0B frames.

OpenLCB uses a straight-forward transfer of extended-header frames, using no special features, to reduce complexity and increase robustness.

80 The Standard is silent on the uses for standard CAN (11-bit header) frames. The proper-operation requirement is so nodes will tolerate them in case they're needed for other purposes. The Atmel bootloaderⁱ uses standard frames, for example, and the Microchip bootloaderⁱⁱ can use them. Allowing standard frames then allows use of these bootloaders in parallel with OpenLCB-CAN. Similarly, CBUSⁱⁱⁱ uses standard frames, and could coexist with OpenLCB on a CAN segment.

85 This proper-operation requirement could also have been phrased as “shall ignore ...”, but the current phrasing is thought to be more exact.

RTR frames are not used in the protocol because CAN semantics require a specific use for them, which has been built into some silicon implementations. There are also some arbitration issues, see: CiA Application Note 802 (2005)¹ and <http://www.thecanmancan.com/?tag=rtr> for more information.

90 A CAN node can emit an overload frame when “Due to internal conditions, the node is not yet able to begin reception of the next (frame). A node may generate a maximum of two sequential overload frames to delay the start of the next (frame).” (That's 17 to 23 extra bit times each) (from <http://rs232-rs485.blogspot.com/2009/11/can-bus-message-frames-overload.html>) Image: http://3.bp.blogspot.com/_ycHwJEosotY/SvoMDJMGf7I/AAAAAAAAA64/3Ql4_UQnoBg/s1600/Overload%2BFrame.JPG

95 The protocol does not specify transmission of overload frames because not all CAN controller hardware can deliberately send them. We require that nodes be able to handle them because some CAN controller hardware will occasionally send them automatically.

100 People will occasionally refer to a restriction against having seven 1 bits in the top 11 bits of the CAN header. There is no such restriction, and the statements are the result of a misunderstanding. There is a restriction against having seven consecutive recessive bits on the CAN segment, but sending seven

¹See <http://www.can-cia.org/>

consecutive 1 bits will not result in this. CAN uses a bit-stuffing technique to prevent that by inserting a dominant bit on the line after the fifth consecutive recessive bit, and removing it at the receiver.

105 The CAN format has been allocated on nibble boundaries to make it easier to e.g. read dumps of packets. The header is considered to be right (LSB) aligned.

110 The reserved most-significant bit (MSB) is likely to be used as a priority-boost bit in the future, e.g. so that a gateway can gain priority access to the CAN segment for various operations that require synchronization or atomicity. CAN encodes “do first” priority as 0 and “do later” as 1, so the Standard requires that a 1 bit be sent. To preserve the utility of this, nodes must not require either a 1 nor 0 on receipt. It is therefore not available as a protocol expansion bit.

The order of the header fields is chosen to get proper priority and access disambiguation via CAN's standard mechanisms.

Putting the destination alias in the header allows filtering on it with common CAN hardware.

2.5 States

115 In the Inhibited state, a node can only communicate on the CAN segment to allocate its Node ID alias(es). This involves sending CID and RID frames with a tentative Node ID alias value. Once that process is complete, the node has an assigned Node ID alias and can transfer to the Permitted state, where all communications are possible.

120 If a node fails, it should restart in the Inhibited state. In general, this state transition is not visible to other nodes until the failed node starts communicating.

For nodes that maintain alias pools, e.g. gateways, need to clarify to what extent the state applies to the entire node, and to what extent it applies to each individual alias in the gateway pool.

2.6 CAN-specific Control Frames and Interactions

2.6.1 Control Frame Format

125 RID, CID, etc frames are assigned low numbers to give them higher transmission priority.

The coding is done to allow up to 7 separate CID sequence numbers, for use by protocols with longer node IDs.

2.6.2 Interactions

130 Communications protocols are about more than formats. The protocols must also specify the interactions in which the frames are used.

2.6.2.1 Reserving a Node ID Alias

At the highest level, this algorithm is broadcasting the tentative alias to see if any other node is checking the same tentative alias. If it is in use, the algorithm tries additional ones until it finds one that's available.

135 CAN arbitration reliably avoids collisions between frames with unique headers. It does not guarantee non-overlapping transmission from separate nodes of frames with identical headers and no data; if the

140 timing is right, they may overlay each other such that only one frame appears to have been sent. It is very difficult to ensure that two nodes always send initialization packets only at different times, particularly given the load-related frame synchronization issue described earlier. In addition, CAN will eventually signal an error if two packets with the same header and different data payloads collide, but not all CAN interface hardware provides reliable indications about why that error occurred.

145 If a node sends out a check frame containing just the alias, then it could expect that another node to complain if it has the same alias. This would work, except in the (admittedly unlikely) case where both nodes send out the identical check frame simultaneously. Neither would recognize a conflict and both would consider that they own the same alias. Therefore, a method needs to be found that guarantees that the check frame(s) are unique, even if they are sent simultaneously.

150 The CID/RID algorithm for finding aliases is designed to work with CAN arbitration, but without causing any CAN errors. During execution of the algorithm, some frames might have the same header. They therefore have to have the same contents, including null contents, or else a non-arbitration error can occur.

If two nodes have taken the same tentative alias, at least one of the packets used in the broadcast will not be identical between the two nodes, because their Node IDs are different in at least one bit. CAN will successfully arbitrate this, and one node will receive the frame sent by the other node, causing it to back off.

155 CAN transmissions are not atomic operations; a node can receive a frame between the time it tells the hardware to send a frame and the time that frame is actually sent. It's therefore possible for both nodes contending for the same alias value to back off and try again. The mechanism for generating the next alias value to try must give different values in different nodes to prevent this from becoming a permanent lock-step error.

160 The delay at the end of the algorithm is to ensure that higher latency nodes, such as software nodes working through USB convertors, can reply to CID frames from nodes that come up on a working link. OpenLCB is a soft-real-time system, and software that's interacting with it needs to have response times of a couple tens of milliseconds or better to be reliable. The algorithm provides a wait of a few times that to enable those programs to take part.

165 Nodes may assign different alias values each time they are powered up. There is no requirement that they always reserve and use the same one, nor is it possible to guarantee that they will.

The sequence number MMM is sent in descending order, 0x7, 0x6, ..., to give priority on the CAN segment to frames later in the process. This lets some nodes complete as early as possible and remove themselves from contention.

170 Although it might be a useful debugging tool, putting the full NID in the data portion of the frames can cause errors. Therefore, we decided not to do that.

Reserving a node ID alias value is separate from actually using it to take a node from Inhibited to Permitted state. A gateway device, for example, might want to stockpile a few reserved alias values so that they can be rapidly associated with a specific node that wants to communicate. The node ID that's broken into four parts for the CID values needs to be unique, but it does not have to be the one that's eventually attached to the alias via a Alias Map Definition frame later on.

For example, a minimal sequence is four CID frames and a RID:

0x17123FED

0x16456FED

180 0x15789FED

0x14ABCFED

0x10700FED

185 The red nibbles show that these are four CID and one RID frames. The blue nibbles are the source ID alias being tested and allocated. The yellow nibbles are the underlying Node ID of the node, in this case 12 34 56 78 9A BC.

Other examples needed?

An address collision which causes one to back off

Address collision after several overlapping frames

Address collision which causes both nodes to back off

190 **2.6.2.2 Transition to Permitted State**

Note that there is no requirement that the node's alias value be consistent from one run to the next.

195 The Alias Mapping Enquiry provides a mechanism for determining which alias is associated with each Node ID. This can be used when e.g. a new node attaches and needs the information. Operating nodes can also track this information by watching CAN segment traffic, without having to use the Alias Mapping Enquiry protocol.

2.6.2.3 Node ID Alias validation

200 Node ID alias validation provides a way for a node joining a segment to rapidly learn the Node IDs and Node ID aliases of the reachable nodes. This may be useful for e.g. a gateway that is connecting two segments that are already in operation, or a monitor node who wants to determine that all nodes have come up properly.

In general, simple or regular nodes won't need to use this. Those nodes don't need to keep track of the Node ID to alias mapping, because they simply respond to frames they receive that contain an alias. They just work with the alias itself. They also don't need to track other nodes state, etc.

205 In order to acquire the map between CANids and node IDs, a gateway needs to be able to send a CAN frame requiring "everybody reply with your node ID". Much like Ethernet gateway mapping, this needs to return the node ID of just the specific CAN-attached hardware, not all the node IDs that can be e.g. reached through one or more gateways, so it needs to be a segment-specific frame defined only at the CAN level. It must not be an OpenLCB common message, though higher level protocols may want to provide a similar capability that spans the entire OpenLCB installation.

210 **2.6.2.4 Transition to Inhibited State**

The Alias Map Reset frame indicates that the alias value in the source address field may no longer be associated with the same NID, and mapping tables should be reset.

The full node ID in the Alias Map Reset frame allows nodes who only are aware of an alias for their conversation partner to convert that alias to a full node ID for later use.

215 This is a way to release or reuse an alias, while informing everybody that the node is no longer reachable.

The alias is only released if this node allows some other node to allocate it via CID/RID frames. The current node can still hang on to it if desired and reuse it with another Node ID.

Gateways have to obtain unique aliases for remote nodes they are proxying onto the segment.

220 Gateways maintain the mapping between remote node's node ID and the local alias. If they need to break that mapping, e.g. because they need to repurpose a local alias due to resource limitations in the mapping tables, they must send a "Alias Map Reset" frame to force nodes to drop their alias information. "Alias Map Reset" is a CAN-specific frame limited to the segment, but all gateways on the segment must act on it. This is then followed by an "Alias Map Definition" when the alias is
225 allocated to a new node ID.

Regular nodes won't need to do this. They stay active until they go instantly offline due to e.g. power-off.

2.6.2.5 Node ID Alias Collision Handling

230 During normal operation in the Permitted state on a single CAN segment, a node should never encounter a Node ID alias collision.

They can happen when network topology changes, for example when connecting two operating CAN segments. In that case, nodes on the two segments have assigned aliases independently, and can have used the same value. The underlying Node IDs do not collide, because they are assigned globally uniquely, but that's not sufficient to ensure that the shorter aliases are independent.

235 In the case of a collision, one or both nodes will release the current alias. If it's the alias that was used to go to Permitted state, e.g. the current alias being used by this node, the node must also drop back to Inhibited state. The node(s) then can, but is not required to, return to Permitted state with a new alias. In the process the node(s) will emit "Alias Map Reset" and "Alias Map Definition" frame that will allow any gateway(s) to update their maps.

240 The preceding paragraph and the language of the Standard is complicated because it has to cover the case of a gateway or similar node who has reserved a number of node ID aliases, but is not currently using them as a node. In other words, the reservation CID/RID process has completed to reserve the alias, but no mapping of the alias to a specific node ID has been published.

245 Simple leaf nodes don't keep internal mappings between full node IDs and aliases, so this transition will not cause any problems for them unless they are currently in communication with another node, e.g. in the middle of a sequence of frames for a datagram or stream. In that case, the the node may have to invoke higher-level error handling to cause the sequence to be retried.

For example, a detachable throttle will detect that it's reattaching, reserve an alias value, and then enter permitted state with that value. Since the reservation happened while connected to the current CAN segment, there is no possibility of a duplicate.

Example: Nodes A and B are in Permitted mode with different node IDs, but the same alias values. Some gateway node C requests a list of all nodes on the CAN segment:

C: 0x10702ccc (AME frame)

A: 0x10701nnn 01 02 03 04 05 06 (AMD frame with Node ID 0x0102,0304,0506)

(For simplicity, B has not transmitted yet) B discovers that its alias has been duplicated.

B: 0x10703nnn (AMR frame)

B then goes back into operation by reserving a new alias value and transitioning to Permitted state:

B: 0x17iiiimm (1st CID)

B: 0x16iiiimm (2nd CID)

B: 0x15iiiimm (3rd CID)

B: 0x14iiiimm (4th CID)

B: 0x10700mmm (RID)

B: 0x10701mmm ii ii ii ii ii (AMD with B's node ID attached)

2.6.2.6 Duplicate Node ID Handling

This should never happen, of course, but it's possible that two nodes will have the same Node ID assigned. This will result in frame loss and operational difficulties. OpenLCB-CAN does not guarantee prompt detection of this condition, at any level of the protocol stack, but it's extremely likely that it will be. At the Frame Transfer level, two nodes on the same CAN segment sharing a common Node ID will be detected when a node receives a Alias Map Definition frame that contains its own Node ID.

The “in addition to any other actions” refers to e.g. acting on identical alias values, should that also be the case.

Sending the PCER message is level jumping, in that such messages are defined at a much higher level in the protocol stack. We include it here because it allows a much cleaner set of error handling operations using the event producer/consumer techniques associated with OpenLCB. This decision can be revisited.

Example: Nodes A and B are in Permitted mode with the same node IDs, but different aliases. Some gateway node C requests a list of all nodes on the CAN segment:

C: 0x10702ccc (AME frame)

A: 0x10701aaa 01 02 03 04 05 06 (AMD frame with Node ID 0x010203040506)

(For simplicity, B has not transmitted yet) B discovers that its node ID has been duplicated.

B: 0x18ADFbbb 01 01 00 00 00 00 02 01 (Producer-Consumer Event Report (PCER) message with event ID 0x0101,0000,0000,0201)

If the two nodes have also assigned the same alias value, that interaction is also invoked here.

2.6.3 Node ID Alias Generation

285 We have a preferred implementation for node ID alias generation which is described in Section 6 “Preferred Alias Allocation Method” below.

The Standard is written to specify the minimum needed to ensure proper operation. This allows developers to create other implementations if needed.

290 “of the same type” is meant to cover “from the same manufacturer”. The idea is that manufacturer will likely number their boards sequentially, and it's possible that an OpenLCB installation will have multiple boards from the same manufacturer. This rule just says that the low bits of the sequential number appear in the alias, so that boards from a single manufacturer are not likely to collide.

Two other criteria that were considered:

- 295 • The sequence of alias values generated by a node shall depend on the node's node ID in such a way that the sequence differs from the sequence generated by every other node.
- Given sufficient iterations, the sequence of alias values generated by a node shall include every valid alias value.

Although useful criteria, they were omitted as too hard to comprehensively test.

300 What's really necessary, but hard to describe in standard language, is that two separate nodes have different sequences of generated numbers. If node A will try 3,4,5,6, then it's important that node B try some other sequence. If B also has generates values in the sequence 3,4,5,6, the two nodes can get locked to each other trying the same value, both rejecting it, and then trying the same new value.

Formally, if A_i is defined as a particular value in node A's sequence, B_i is defined as a particular value in B's sequence, then “if $A_i = B_i$, then $A_{i+1} \neq B_{i+1}$ most of the time” is the important condition.

305 It's not required that two sequential aliases be different. It's possible that the sequence generator will come up with the same value occasionally, and the RID/CID mechanism is constructed to handle that. The sequence on the CAN bus will be clearer, and in some cases the allocation process will be faster, if nodes identify duplicate aliases in sequence, and just go on to the next one.

2.7 OpenLCB Message Frame Format

310 The OpenLCB message frame format comes in two varieties, with and without a destination address included. This is included here, at frame level, to allow frame-level bridges to use the information without having to be able to completely decode the OpenLCB message-level protocols.

315 The coding is a 0b000 value in the top three bits of the 15-bit variable field to indicate that the bottom 12 bits are OpenLCB information in a global frame; other values in those three bits indicate that the bottom 12 bits are a destination node alias. Those other values can then be used by higher levels to indicate segmentation or other parts of a message-level protocol.

3 Gateways and segment management

315 *Talk about a bridge that's OpenLCB-CAN aware, and can e.g. signal that it's time to re-arbitrate, vs one that's not aware.*

Need to discuss the case of two segments being joined, to discover they've both arbitrated the same aliases, including with gateways on one or both; see above.

320 *Discuss the use of repeaters, bridges and gateways w.r.t. Timing; ref physical layer. Possibility of reordering. Refer to glossary?*

If/when a full NID is needed, it can be obtained by sending a "Alias Mapping Enquiry" frame with an appropriate Destination Node ID in local alias form. The reply will eventually come back with the Source ID in local alias form and carrying the full NID in the frame body.

4 Throughput and Temporarily Deaf Nodes

325 29-bit extended header and 8-byte payload results in a total transmission taking about 135 bit times, varying slightly with bit-stuffing.

125Kbps with max-length extended header frames is about 900 frames/second. CAN is very good at running at 100% utilization, so long as nodes can keep up and a proper set of priorities is in place.

330 CAN is designed to run at 100% usage without problem, and it's routine for CAN segments in other contexts to run at 100% for extended times. Therefore, the CAN network does not require any inter-frame spacing, limitations on bandwidth usage, etc; the segment can be allowed to run at 100%.

OpenLCB requires that CAN-attached nodes be able to handle the full frame rate on the CAN bus. There is no guarantee that frames for a given node will arrive with non-zero time between then.

335 Some nodes are not always able to process frames. For example, the node may cease processing for a short time while writing non-volatile memory. Higher-level protocols, e.g. configuration write datagrams, have mechanisms built in to prevent overrun while writing configuration memory, but there could be multiple activities going on in parallel that will result in frames arriving while the node is not processing.

340 Short outages can be covered by CAN hardware buffering, so long as the node will eventually catch up even at full arrival rate. Outages long enough that frames are lost due to e.g. buffer overflow require node to broadcast that it's back up if the hardware detected frames lost. This is because there could have been frames of some form that modified the OpenLCB node state, which are now lost (e.g. drop alias, CID/RID in absence, or even higher level events)

345 The real limitation is whether the nodes themselves can handle the full rate of frame arrival. There is (currently) no mechanism in OpenLCB to throttle the rate of frames arriving at a node, nor is it easy to create one in a CAN network. The stream and datagram protocol have been designed to allow a node to efficiently use a very limited amount of buffer memory, but don't provide mechanisms to limit the arrival of frames in general.

350 Nodes must handle full rate frames, specifically including frames not addressed to them. (The datagram and stream protocols provide ways for nodes to indicate whether or not they have sufficient buffering for the next transmission, triggering retries as needed) For long term reliability, a node must be able to

completely process an entire CAN frame in the time it takes to receive the next one, which may be as little as 64 bit times, or about 500 microseconds (header only frame, carrying e.g. configuration info)

355 Eventually OpenLCB may have to discuss use of Overload Frames to throttle for e.g. NVRAM writing, but various CAN hardware implementations may also be doing this already. This mechanism provides only a little more time, due to restrictions in the CAN specification that have become limitations on the silicon implementations.

5 On the choice of a 12-bit alias length

(Should this be here? Or elsewhere? In either case, clean it up)

360 How big should the NodeID alias field be on CAN links?

- Smaller (fewer bits) allows more payload and/or simpler coding of other parts of messages.
- Larger allows more unique nodes to be accessed.

5.1 Issues

5.1.1 Addressing

365 The Node ID size limits the number of unique nodes that can take part in communications on the CAN segment. Because Node ID aliases are assigned independently on each CAN segment, the only issue is how many different nodes are involved, not which ones they are or what pattern(s) are available in their address numbers.

370 For electrical/timing reasons, a segment itself can only support a maximum of about 100 nodes², but communication also involves nodes off the segment. For example, chaining N CAN segments via bridges will generally make up to 100*N nodes available. We have a use case of chaining small numbers of CAN segments together, implying the need to address 500 or 1000 nodes.

375 As another example, a very large network might connect many CAN segments via TCP/IP or other networked connections. Each CAN-attached node might need to communicate with a larger number of others spread across that network.

Finally, one can imagine connecting a few CAN segments in a star pattern to a central OpenLCB-CAN “backbone”, which must route the full cross-segment traffic.

380 In some cases, want 2 aliases (source and destination), plus a few more bits, in the 29 bits total available in the header. Using 12-bits for each address leaves $29 - (2 * 12) = 5$ bits for these purposes, which seemed about right.

5.1.2 Collisions during Allocation

The alias allocation process resolves collisions (attempt to use an already allocated Node ID alias), but that takes time. Minimizing the number of collisions is good. If the address space is just the size of the number of things you want to address, the collisions get hard /slow to resolve across multiple nodes.

²The OpenLCB-CAN Physical Layer Standard says in its Intended Use section uses 50 nodes as an expected size. This is merely an informative statement of expectations, however, and some layouts will no doubt exceed that. We use the larger number 100 here to avoid placing any stronger limitation on what can be achieved electrically.

385 This points to having a factor of 2, at least, between the number of nodes to be addressed and the size of the address space.

(Mostly talking about separate nodes here, not just one big interface node: Points to CAN backbone case)

5.1.3 Size

390 Streaming provides the most stringent test of alias sizes. We'd like to have all 8 bytes of CAN frame payload available for transporting stream data, which requires putting both source and destination addresses, plus whatever control information is needed, into the header.

To get the full payload (8 bytes) for streaming requires getting the rest of the protocol control, including two aliases for source and destination, in the 29 bit header. Allowing 1 bit for
395 priority/extension, 1 for protocol control, 3 for MTI and stream control (all very bare minima) leads to a 12-bit node ID alias length.

6 Preferred Alias Allocation Method

This section documents the preferred algorithm for generating unique Node ID aliases.

400 CAN transmissions are not atomic operations; you can receive a frame between the time you tell the hardware to send a frame and the time that frame is actually sent. It's therefore possible for both nodes contending for the same alias value to back off and try again. Using the pseudo-random number generator as a sequence number makes it likely that the next attempt will be made using different alias values in the two nodes. The use of the sequence generator also makes the arbitration process faster in the case of sequential Node ID values. People like to use small and sequential numbers for things, and
405 the sequence generator maps those to very different values that are less likely to collide during arbitration.

6.1 Preferred alias generation algorithm

410 The 12 bit alias has to be derived from a 48-bit sequence number in a way that keeps as much entropy (variation; randomness) as possible.

The entropy starts in the node ID values, which cover a 48-bit space (albeit non-uniformly). This provides an initial 48-bit value that can be mapped to a 12-bit value.

To create a sequence of values, you want a computationally cheap way of sequencing through all those possible 48-bit values. (Running through the 48-bit values and compressing each to a 12-bit alias value
415 is less likely to get multiple nodes attempting the same sequence than just working through a 12-bit sequence) A suitable pseudo-random number generator does exactly this; runs through full 48-bit sequence; each node joins at separate point in the sequence, so the 48 bit values are unique.

The most computationally convenient way to create a 12-bit value, while preserving as much of the randomness as possible, is to break the 48-bit value into four 12-bit values, align these, and exclusive-
420 or them. Each bit-change in the original 48-bit number then becomes a change in the final 12-bit value.

Sequentially numbered nodes will have initial seeds that differ only in the low bits of the PRNG output. For shift-register PRNGs, this can present a problem, as all bytes of the result are shifting together with just one new bit shifting in at the top. (Traditionally, shift-register PRNGs shift toward the LSB) Only one bit changes. Combining bytes (or even 12-bit chunks) via XOR or add operations results in reduced entropy.

The OpenLCB proposed PRNG (next section) uses add operations with a constant term to avoid this problem, so treating the 48-bit PRNG output as four 12-bit values, which are then XORed, works well.

6.1.1 Preferred PRNG

The proposed 48-bit PRNG is from “A 48-Bit Pseudo-Random Number Generator”, Heidi G. Kuehn, Communications of the ACM, Volume 4, Issue 8 (August 1961), pages 350-352.

$$x_{i+1} = (2^9 + 1) x_i + c$$

where $c = 29,741,096,258,473$ or $0x1B0CA37A4BA9$. The paper actually describes a PRNG that uses signed arithmetic, but for our purposes the 48th “sign” bit isn't important. This is a byte+bit shift and add, so it's quick to calculate.

Note that, unlike some other PRNGs, this one can generate a zero result, and can accept a zero seed.

It is initialized with the node ID as a 48-bit key, with the most significant byte of the node ID as the most-significant byte of the PRNG value.

6.1.2 Preferred PRNG to node ID alias mapping

The 12-bit node ID alias is made from the 48-bit PRNG value by splitting the PRNG value into four 12-bit values and XORing them together. This preserves the information content of every bit in the final result.

6.1.3 Example C implementation^{iv}

The PRNG state is stored in two 32-bit quantities:

```
uint32_t lfsr1, lfsr2; // sequence value: lfsr1 is upper 24 bits, lfsr2 lower
```

The 6-byte unique Node ID is stored in the `nid[0:5]` array.

To load the PRNG from the Node ID:

```
lfsr1 = (nid[0] << 16) | (nid[1] << 8) | nid[2];
lfsr2 = (nid[3] << 16) | (nid[4] << 8) | nid[5];
```

To step the PRNG:

```
// First, form 2^9*val
uint32_t temp1 = ((lfsr1<<9) | ((lfsr2>>15)&0x1FF)) & 0xFFFFFFFF;
uint32_t temp2 = (lfsr2<<9) & 0xFFFFFFFF;
```

```
// add
lfsr2 = lfsr2 + temp2 + 0x7A4BA91;
lfsr1 = lfsr1 + temp1 + 0x1B0CA31;
```

```
// carry
lfsr1 = (lfsr1 & 0xFFFFFFFF) | ((lfsr2&0xFF000000) >> 24);
```

460 `lfsr2 = lfsr2 & 0xFFFFFFF;`

Form a 12-bit alias from the PRNG state:

```
uint16_t LinkControl::getAlias() {
    return (lfsr1 ^ lfsr2 ^ (lfsr1>>12) ^ (lfsr2>>12) )&0xFFF;
}
```

465 7 CAN Controller Filters

This coding has been generated such that simple nodes can use three hardware filters to select frames that are of interest to them.

Purpose	Mask	Required Value
CAN-specific control frames	0x0800,0000	0x0000,0000
OpenLCB format addressed to this node	0x08FF,F000	0x08nn,n000
OpenLCB global messages	0x0F00,0000	0x0800,0000

“nnn” refers to this node's alias.

470 The “OpenLCB format addressed to this node” filter will improperly pass some global messages with an accidental match of the node alias nnn, but those would have been passed by the 3rd filter for global messages in any case.

8 Additional References

475 B. Gaujal and N. Navet, “Fault confinement mechanisms on CAN: analysis and improvements”, IEEE Transactions on Vehicular Technology, pp.1103-1113, 54(3), May 2005 (An interesting analysis of how CAN nodes react to error rates on the CAN bus by e.g. taking themselves offline, etc)

(Relevant ones from physical layer doc; Sections of Etschberger book)

“A 48-Bit Pseudo-Random Number Generator”, Heidi G. Kuehn, Communications of the ACM, Volume 4, Issue 8 (August 1961), pages 350-352.

480 Appendix A: Calculation Examples

Starting 48-bit seed	Alias	Next 48-bit seed
00 00 00 00 00 00	0	1B 0C A3 7A 4B A9
1B 0C A3 7A 4B A9	11E	4F 60 3B 8B E9 52

4F 60 3B 8B E9 52	521	2A E3 F5 D8 D8 FB
2A E3 F5 D8 D8 FB	42D	0D DC 4B 05 1A A4
0D DC 4B 05 1A A4	663	E1 7E F8 B4 AE 4D

Table: Sequence of aliases and seeds starting from zero

Starting 48-bit seed	Alias	Next 48-bit seed	Next Alias
02 01 21 00 00 12	113	1F 4F C4 7A 6F BB	62D
02 01 12 00 00 21	113	1F 31 B5 7A 8D CA	A24
02 01 11 00 00 22	113	1F 2F B4 7A 8F CB	625
02 01 22 00 00 11	113	1F 51 C5 7A 6D BA	A2C

Table: Four seeds (of 2^{36}) that give the same alias, and their different subsequent seeds and aliases

Table of Contents

1 Introduction.....	1
1.1 Load-Related Frame Synchronization.....	2
2 Annotations to the Standard.....	2
2.1 Introduction.....	2
2.2 Intended Use.....	3
2.3 References and Context.....	3
2.4 Frame Format.....	3
2.5 States.....	4
2.6 CAN-specific Control Frames and Interactions.....	4
2.6.1 Control Frame Format.....	4
2.6.2 Interactions.....	4
2.6.2.1 Reserving a Node ID Alias.....	4
2.6.2.2 Transition to Permitted State.....	6
2.6.2.3 Node ID Alias validation.....	6
2.6.2.4 Transition to Inhibited State.....	7
2.6.2.5 Node ID Alias Collision Handling.....	7
2.6.2.6 Duplicate Node ID Handling.....	8
2.6.3 Node ID Alias Generation.....	9
2.7 OpenLCB Message Frame Format.....	9
3 Gateways and segment management.....	10
4 Throughput and Temporarily Deaf Nodes.....	10
5 On the choice of a 12-bit alias length.....	11
5.1 Issues.....	11
5.1.1 Addressing.....	11
5.1.2 Collisions during Allocation.....	11
5.1.3 Size.....	12

6 Preferred Alias Allocation Method.....	12
6.1 Preferred alias generation algorithm.....	12
6.1.1 Preferred PRNG.....	13
6.1.2 Preferred PRNG to node ID alias mapping.....	13
6.1.3 Example C implementation.....	13
7 CAN Controller Filters.....	14
8 Additional References.....	14

485

- i See Atmel application note “AVR076: AVR® CAN - 4K Boot Loader”
http://www.atmel.com:80/dyn/resources/prod_documents/doc8247.pdf
- ii See Microchip application note “AN247 A CAN Bootloader for PIC18F CAN Microcontrollers”
<http://ww1.microchip.com/downloads/en/AppNotes/00247a.pdf>
- iii See <http://www.merg.org.uk/resources/lcb.html>
- iv The code in this section is from the OpenLCB C sample implementation available at
<http://www.openlcb.org/trunk/prototypes/C/libraries/OlcbCommonCAN/> The specific code is available at
<http://www.openlcb.org/trunk/prototypes/C/libraries/OlcbCommonCAN/LinkControl.cpp>