

SWE 432 -Web Application Development


Fall 2021



George Mason
University

Dr. Kevin Moran

Week 2: Asynchronous Programming





Administrivia

- HW Assignment 1 - Due Today Before Class
- HW Assignment 2 - Out on Thursday, will discuss next class
- Quiz #2: Discussion

Class Overview





Class Overview

- Part 1 - Asynchronous Programming I: Communicating between web app components?
- 10 minute Break
- Part 2 - Asynchronous Programming II: More communication strategies
- Part 3 - In-Class Activity: Exploring Asynchronous Programming

Asynchronous Programming I



Lecture I

- What is asynchronous programming?
- What are threads?
- Writing asynchronous code

For further reading:

- **Using Promises:** https://developer.mozilla.org/en-US/docs/Web/JavaScript/Guide/Using_promises
- **Node.js event loop:** <https://nodejs.org/en/docs/guides/event-loop-timers-and-nexttick/>

Closures

- Closures are expressions that work with variables in a specific context
- Closures contain a function, and its needed state
 - Closure is a stack frame that is allocated when a function starts executing and not freed after the function returns
- That state just refers to that state by name (sees updates)

Closures

- Closures are expressions that work with variables in a specific context
- Closures contain a function, and its needed state
 - Closure is a stack frame that is allocated when a function starts executing and not freed after the function returns
- That state just refers to that state by name (sees updates)

```
var x = 1;
function f() {
    var y = 2;
    return function() {
        console.log(x + y);
        y++;
    };
}
var g = f();
g();           // 1+2 is 3
g();           // 1+3 is 4
```


Closures

- Closures are expressions that work with variables in a specific context
- Closures contain a function, and its needed state
 - Closure is a stack frame that is allocated when a function starts executing and not freed after the function returns
- That state just refers to that state by name (sees updates)

```
var x = 1;
function f() {
    var y = 2;
    return function() {
        console.log(x + y);
        y++;
    };
}
var g = f();
g();           // 1+2 is 3
g();           // 1+3 is 4
```

This function attaches itself to x and y so that it can continue to access them.

Closures

- Closures are expressions that work with variables in a specific context
- Closures contain a function, and its needed state
 - Closure is a stack frame that is allocated when a function starts executing and not freed after the function returns
- That state just refers to that state by name (sees updates)

```

var x = 1;
function f() {
  var y = 2;
  return function() {
    console.log(x + y);
    y++;
  };
}
var g = f();
g();           // 1+2 is 3
g();           // 1+3 is 4
    
```

This function attaches itself to x and y so that it can continue to access them.

Closures

- Closures are expressions that work with variables in a specific context
- Closures contain a function, and its needed state
 - Closure is a stack frame that is allocated when a function starts executing and not freed after the function returns
- That state just refers to that state by name (sees updates)

```

var x = 1;
function f() {
  var y = 2;
  return function() {
    console.log(x + y);
    y++;
  };
}
var g = f();
g();           // 1+2 is 3
g();           // 1+3 is 4
  
```

This function attaches itself to x and y so that it can continue to access them.

It “**closes up**” those references

Closures




Closures

```
var x = 1;
function f() {
    var y = 2;
    return function() {
        console.log(x + y);
        y++;
    };
}
var g = f();
g();           // 1+2 is 3
g();           // 1+3 is 4
```

Closures

```
var x = 1;
function f() {
  var y = 2;
  return function() {
    console.log(x + y);
    y++;
  };
}
var g = f();
g();
g();
```


// 1+2 is 3
// 1+3 is 4




Closures

```
var x = 1;
function f() {
  var y = 2;
  return function() {
    console.log(x + y);
    y++;
  };
};
```


```
}
var g = f();
g();
g();
```




```
// 1+2 is 3
// 1+3 is 4
```



Global



1




Closure

Closures

```
var x = 1;
function f() {
  var y = 2;
  return function() {
    console.log(x + y);
    y++;
  };
}
```

```
var g = f();
g();
g();
```

```
// 1+2 is 3
// 1+3 is 4
```




Closures

```
var x = 1;
function f() {
  var y = 2;
  return function() {
    console.log(x + y);
    y++;
  };
};
```

```
var g = f();
g();
g();
```

```
// 1+2 is 3
// 1+3 is 4
```




Closures

```
var x = 1;
function f() {
  var y = 2;
  return function() {
    console.log(x + y);
    y++;
  };
};
```

```
var g = f();
g();
g();
```

```
// 1+2 is 3
// 1+3 is 4
```




Closures

```
var x = 1;
function f() {
  var y = 2;
  return function() {
    console.log(x + y);
    y++;
  };
};
```

```
var g = f();
g();
g();
```

```
// 1+2 is 3
// 1+3 is 4
```



Why Asynchronous?

- Maintain an interactive application while still doing stuff
 - Processing data
 - Communicating with remote hosts
 - Timers that countdown while our app is running
- Anytime that an app is doing more than one thing at a time, it is asynchronous



What is a thread?

Program execution: a series of sequential method calls (★s)

What is a thread?

Program execution: a series of sequential method calls (★s)

App Starts




App Ends



What is a Thread?

Program execution: a series of sequential method calls (★s)

App Starts



App Ends


Multiple threads can run at once -> allows for asynchronous code



What is a Thread?

Program execution: a series of sequential method calls (★s)

App Starts



App Ends


Multiple threads can run at once -> allows for asynchronous code

Multi-Threading in Java

- Multi-Threading allows us to do more than one thing at a time
- Physically, through multiple cores and/or OS scheduler
- Example: Process data while interacting with user

Multi-Threading in Java


- Multi-Threading allows us to do more than one thing at a time
- Physically, through multiple cores and/or OS scheduler
- Example: Process data while interacting with user



thread 0


Multi-Threading in Java

- Multi-Threading allows us to do more than one thing at a time
- Physically, through multiple cores and/or OS scheduler
- Example: Process data while interacting with user



Multi-Threading in Java

- Multi-Threading allows us to do more than one thing at a time
- Physically, through multiple cores and/or OS scheduler
- Example: Process data while interacting with user





Woes of Multi-Threading

```
public static int v;  
public static void thread1()  
{  
    v = 4;  
    System.out.println(v);  
}
```

```
public static void thread2()  
{  
    v = 2;  
}
```

This is a data race: the `println` in `thread1` might see either 2 OR 4



Woes of Multi-Threading

```
public static int v;  
public static void thread1()  
{  
    v = 4;  
    System.out.println(v);  
}
```

```
public static void thread2()  
{  
    v = 2;  
}
```

This is a data race: the `println` in `thread1` might see either 2 OR 4

Thread 1	Thread 2
----------	----------



Woes of Multi-Threading

```
public static int v;  
public static void thread1()  
{  
    v = 4;  
    System.out.println(v);  
}
```

```
public static void thread2()  
{  
    v = 2;  
}
```

This is a data race: the `println` in `thread1` might see either 2 OR 4

Thread 1	Thread 2
Write V = 4	



Woes of Multi-Threading

```
public static int v;  
public static void thread1()  
{  
    v = 4;  
    System.out.println(v);  
}
```

```
public static void thread2()  
{  
    v = 2;  
}
```

This is a data race: the `println` in `thread1` might see either 2 OR 4

Thread 1	Thread 2
Write V = 4	
	Write V = 2



Woes of Multi-Threading

```
public static int v;  
public static void thread1()  
{  
    v = 4;  
    System.out.println(v);  
}
```

```
public static void thread2()  
{  
    v = 2;  
}
```

This is a data race: the `println` in `thread1` might see either 2 OR 4

Thread 1	Thread 2
Write V = 4	
	Write V = 2
Read V (2)	



Woes of Multi-Threading

```
public static int v;  
public static void thread1()  
{  
    v = 4;  
    System.out.println(v);  
}
```

```
public static void thread2()  
{  
    v = 2;  
}
```

This is a data race: the `println` in `thread1` might see either 2 OR 4

Thread 1	Thread 2
Write V = 4	
	Write V = 2
Read V (2)	

Thread 1	Thread 2
----------	----------



Woes of Multi-Threading

```
public static int v;  
public static void thread1()  
{  
    v = 4;  
    System.out.println(v);  
}
```

```
public static void thread2()  
{  
    v = 2;  
}
```

This is a data race: the `println` in `thread1` might see either 2 OR 4

Thread 1	Thread 2
Write V = 4	
	Write V = 2
Read V (2)	

Thread 1	Thread 2
	Write V = 2



Woes of Multi-Threading

```
public static int v;  
public static void thread1()  
{  
    v = 4;  
    System.out.println(v);  
}
```

```
public static void thread2()  
{  
    v = 2;  
}
```

This is a data race: the `println` in `thread1` might see either 2 OR 4

Thread 1	Thread 2
Write V = 4	
	Write V = 2
Read V (2)	

Thread 1	Thread 2
	Write V = 2
Write V = 4	



Woes of Multi-Threading

```
public static int v;  
public static void thread1()  
{  
    v = 4;  
    System.out.println(v);  
}
```

```
public static void thread2()  
{  
    v = 2;  
}
```

This is a data race: the `println` in `thread1` might see either 2 OR 4

Thread 1	Thread 2
Write V = 4	
	Write V = 2
Read V (2)	

Thread 1	Thread 2
	Write V = 2
Write V = 4	
Read V (4)	



Multi-Threading in JS

```
var request = require('request');  
request('http://www.google.com', function (error, response,  
body) {  
    console.log("Heard back from Google!");  
});  
console.log("Made request");
```

Request is an asynchronous call



Multi-Threading in JS

```
var request = require('request');  
request('http://www.google.com', function (error, response,  
body) {  
    console.log("Heard back from Google!");  
});  
console.log("Made request");
```


Output:

Made request
Heard back from Google!

Request is an asynchronous call

Multi-Threading in JS


- Everything you write will run in a single thread* (event loop)
- Since you are not sharing data between threads, races don't happen as easily
- Inside of JS engine: many threads
- Event loop processes events, and calls your callbacks



JS Engine

Multi-Threading in JS


- Everything you write will run in a single thread* (event loop)
- Since you are not sharing data between threads, races don't happen as easily
- Inside of JS engine: many threads
- Event loop processes events, and calls your callbacks



JS Engine

Multi-Threading in JS


- Everything you write will run in a single thread* (event loop)
- Since you are not sharing data between threads, races don't happen as easily
- Inside of JS engine: many threads
- Event loop processes events, and calls your callbacks



JS Engine

Multi-Threading in JS

- Everything you write will run in a single thread* (event loop)
- Since you are not sharing data between threads, races don't happen as easily
- Inside of JS engine: many threads
- Event loop processes events, and calls your callbacks




JS Engine



The Event Loop


Event Queue



JS Engine


The Event Loop

Event Queue



The Event Loop

Event Queue



The Event Loop


Event Queue





The Event Loop


Event Queue





The Event Loop

Event Queue




Event Being Processed:

JS Engine



The Event Loop

Event Queue




JS Engine

response from
google.com



The Event Loop

Event Queue




Event Being Processed:

response from
[google.com](https://www.google.com)



The Event Loop

Event Queue



Event Being Processed:


response from
google.com

Are there any listeners registered for this event?



The Event Loop

Event Queue



Event Being Processed:

response from
google.com


Are there any listeners registered for this event?

If so, call listener with event



The Event Loop

Event Queue



Event Being Processed:

response from
google.com

Are there any listeners registered for this event?

If so, call listener with event


After the listener is finished, repeat



The Event Loop

Event Queue

response from
gmu.edu



JS Engine


response from
facebook.com



The Event Loop

Event Queue

response from
gmu.edu



JS Engine

Event Being Processed:


response from
facebook.com



The Event Loop

Event Queue

response from
gmu.edu



Event Being Processed:

response from
facebook.com

JS Engine


Are there any listeners registered for this event?



The Event Loop

Event Queue

response from
gmu.edu



Event Being Processed:

response from
facebook.com

JS Engine


Are there any listeners registered for this event?

If so, call listener with event

The Event Loop

Event Queue

response from
gmu.edu



Event Being Processed:

response from
facebook.com

JS Engine


Are there any listeners registered for this event?

If so, call listener with event

After the listener is finished, repeat

The Event Loop

Event Queue



response from
gmu.edu

The Event Loop

Event Queue



Event Being Processed:


response from
gmu.edu

JS Engine



The Event Loop

Event Queue



Event Being Processed:


response from
gmu.edu

JS Engine

Are there any listeners registered for this event?

The Event Loop

Event Queue



Event Being Processed:

response from
gmu.edu


JS Engine

Are there any listeners registered for this event?

If so, call listener with event

The Event Loop

Event Queue



Event Being Processed:

response from
gmu.edu

Are there any listeners registered for this event?

If so, call listener with event

After the listener is finished, repeat

The Event Loop

- Remember that JS is **event-driven**

```
var request = require('request');  
request('http://www.google.com', function (error, response, body) {  
    console.log("Heard back from Google!");  
});  
console.log("Made request");
```

- Event loop is responsible for dispatching events when they occur
- Main thread for event loop:

```
while(queue.waitForMessage()){  
    queue.processNextMessage();  
}
```

How do you write a “good” event handler?

- Run-to-completion
 - The JS engine will not handle the next event until your event handler finishes
- **Good news:** no other code will run until you finish (no worries about other threads overwriting your data)
- **Bad/OK news:** Event handlers must not block
 - Blocking -> Stall/wait for input (e.g. alert(), non-async network requests)
 - If you **must** do something that takes a long time (e.g. computation), split it up into multiple events



More Properties of Good Handlers


- Remember that event events are processed in the order they are received
- Events might arrive in unexpected order
- Handlers should check the current state of the app to see if they are still relevant

Prioritizing Events in node.js

- Some events are more important than others
- Keep separate queues for each event "phase"
- Process all events in each phase before moving to next

First

Last




<https://nodejs.org/en/docs/guides/event-loop-timers-and-nexttick/>

Benefits vs. Explicit Threading (Java)

- Writing your own threads is reason about and get right:
 - When threads share data, need to ensure they correctly **synchronize** on it to avoid race conditions
- Main downside to events:
 - Can not have slow event handlers
 - Can still have races, although easier to reason about

Run-to-completion semantics


- Run-to-completion
 - The function handling an event and the functions that it (transitively) synchronously calls will keep executing until the function finishes.
 - The JS engine will not handle the next event until the event handler finishes.



Implications of run-to-completion

- Good news: no other code will run until you finish (no worries about other threads overwriting your data)

processing of
event queue




j will not execute until after i

Implications of run-to-completion

- Bad/OK news: Nothing else will happen until event handler returns
- Event handlers should never block (e.g., wait for input) --> all callbacks waiting for network response or user input are **always** asynchronous
- Event handlers shouldn't take a long time either

processing of
event queue



j will not execute until i finishes

Decomposing a long-running computation

- If you ***must*** do something that takes a long time (e.g. computation), split it into multiple events
 - `doSomeWork()`;
 - ... [let event loop process other events]..
 - `continueDoingMoreWork()`;
 - ...

Dangers of Decomposition

- Application state may **change** before event occurs
 - Other event handlers may be interleaved and occur before event occurs and mutate the same application state
 - --> Need to check that update still makes sense
- Application state may be in **inconsistent** state until event occurs
 - Application
 - leaving data in inconsistent state...
 - Loading some data from API, but not all of it...



Example: Writing Asynchronous Tasks

- From an array of 10 URL's:
 - Request each URL
 - Then for each page, save it to disk
 - Then once all of the pages are downloaded and saved, print out the total size of all of the files that were saved

Sequencing events

- We'd like a better way to sequence events.
- Goals:
 - Clearly distinguish **synchronous** from **asynchronous** function calls.
 - Enable computation to occur only **after** some event has happened, without adding an additional nesting level each time (no pyramid of doom).
 - Make it possible to handle **errors**, including for multiple related async requests.
 - Make it possible to **wait** for multiple async calls to finish before proceeding.

Sequencing events with Promises

- Promises are a wrapper around async callbacks
- Promises represents how to get a value
- Then you tell the promise what to do when it gets it
- Promises organize many steps that need to happen in order, with each step happening asynchronously
- At any point a promise is either:
 - Is unresolved
 - Succeeds
 - Fails

Using a Promise

- Declare what you want to do when your promise is completed (**then**), or if there's an error (**catch**)

```
fetch('https://github.com/')  
  .then(function(res) {  
    return res.text();  
  });
```


```
fetch('http://domain.invalid/')  
  .catch(function(err) {  
    console.log(err);  
  });
```



Promise One Thing Then Another


**Promise to get some
data**

Promise One Thing Then Another







Promise One Thing Then Another



Promise One Thing Then Another



Chaining Promises



Chaining Promises

```
myPromise.then(function(resultOfPromise){  
    //Do something, maybe asynchronously  
    return theResultOfThisStep;  
})
```

Chaining Promises

```
myPromise.then(function(resultOfPromise){  
    //Do something, maybe asynchronously  
    return theResultOfThisStep;  
})  
    .then(function(resultOfStep1){  
        //Do something, maybe asynchronously  
        return theResultOfStep2;  
    })
```

Chaining Promises

```
myPromise.then(function(resultOfPromise){  
    //Do something, maybe asynchronously  
    return theResultOfThisStep;  
})  
  .then(function(resultOfStep1){  
    //Do something, maybe asynchronously  
    return theResultOfStep2;  
})  
  .then(function(resultOfStep2){  
    //Do something, maybe asynchronously  
    return theResultOfStep3;  
})
```

Chaining Promises

```
myPromise.then(function(resultOfPromise){  
    //Do something, maybe asynchronously  
    return theResultOfThisStep;  
})  
  .then(function(resultOfStep1){  
    //Do something, maybe asynchronously  
    return theResultOfStep2;  
})  
  .then(function(resultOfStep2){  
    //Do something, maybe asynchronously  
    return theResultOfStep3;  
})  
  .then(function(resultOfStep3){  
    //Do something, maybe asynchronously  
    return theResultOfStep4;  
})
```

Chaining Promises

```
myPromise.then(function(resultOfPromise){  
    //Do something, maybe asynchronously  
    return theResultOfThisStep;  
})  
  .then(function(resultOfStep1){  
    //Do something, maybe asynchronously  
    return theResultOfStep2;  
})  
  .then(function(resultOfStep2){  
    //Do something, maybe asynchronously  
    return theResultOfStep3;  
})  
  .then(function(resultOfStep3){  
    //Do something, maybe asynchronously  
    return theResultOfStep4;  
})  
  .catch(function(error){  
  
});
```


Writing a Promise

- Most often, Promises will be generated by an API function (e.g., fetch) and returned to you.
- But you can also create your own Promise.

```
var p = new Promise(function(resolve, reject) {  
  if (/* condition */) {  
    resolve(/* value */); // fulfilled successfully  
  }  
  else {  
    reject(/* reason */); // error, rejected  
  }  
});
```

Example: Writing a Promise

- loadImage returns a promise to load a given image

```
function loadImage(url){  
    return new Promise(function(resolve, reject) {  
        var img = new Image();  
        img.src = url;  
        img.onload = function(){  
            resolve(img);  
        }  
        img.onerror = function(e){  
            reject(e);  
        }  
    });  
}
```

Once the image is loaded, we'll resolve the promise

If the image has an error, the promise is rejected

Writing a Promise

- Basic syntax:
 - do something (possibly asynchronous)
 - when you get the result, call `resolve()` and pass the final result
 - In case of error, call `reject()`

```
var p = new Promise( function(resolve, reject){  
    // do something, who knows how long it will take?  
    if(everythingIsOK)  
    {  
        resolve(stateIWantToSave);  
    }  
    else  
        reject(Error("Some error happened"));  
} );
```



Promises in Action



Promises in Action

- Firebase example: get some value from the database, then push some new value to the database, then print out “OK”



Promises in Action

- Firebase example: get some value from the database, then push some new value to the database, then print out “OK”

Promises in Action

- Firebase example: get some value from the database, then push some new value to the database, then print out “OK”



Promises in Action

- Firebase example: get some value from the database, then push some new value to the database, then print out “OK”

```
todosRef.child(keyToGet).once('value')
  .then(function(foundTodo){
    return foundTodo.val().text;
  })
  .then(function(theText){
    todosRef.push({'text' : "Seriously: " + theText});
  })
  .then(function(){
    console.log("OK!");
  })
  .catch(function(error){
    //something went wrong
  });
```


Promises in Action

- Firebase example: get some value from the database, then push some new value to the database, then print out “OK”

```
todosRef.child(keyToGet).once('value')
  .then(function(foundTodo){
    return foundTodo.val().text; Do this
  })
  .then(function(theText){
    todosRef.push({'text' : "Seriously: " + theText});
  })
  .then(function(){
    console.log("OK!");
  })
  .catch(function(error){
    //something went wrong
  });
```

Promises in Action

- Firebase example: get some value from the database, then push some new value to the database, then print out “OK”

```
todosRef.child(keyToGet).once('value')
  .then(function(foundTodo){
    return foundTodo.val().text; Do this
  })
  .then(function(theText){ Then, do this
    todosRef.push({'text' : "Seriously: " + theText});
  })
  .then(function(){
    console.log("OK!");
  })
  .catch(function(error){
    //something went wrong
  });
```

Promises in Action

- Firebase example: get some value from the database, then push some new value to the database, then print out “OK”

```

todosRef.child(keyToGet).once('value')
  .then(function(foundTodo){
    return foundTodo.val().text; Do this
  })
  .then(function(theText){ Then, do this
    todosRef.push({'text' : "Seriously: " + theText});
  })
  .then(function() { Then do this
    console.log("OK!");
  })
  .catch(function(error){
    //something went wrong
  });

```

Promises in Action

- Firebase example: get some value from the database, then push some new value to the database, then print out “OK”

```
todosRef.child(keyToGet).once('value')
  .then(function(foundTodo){
    return foundTodo.val().text; Do this
  })
  .then(function(theText){ Then, do this
    todosRef.push({'text' : "Seriously: " + theText});
  })
  .then(function(){ Then do this
    console.log("OK!");
  })
  .catch(function(error){
    //something went wrong
  });
```

And if you ever had an error, do this



Testing Promises

```
function getUsername(userID) {  
  return request-promise('/users/' + userID).then(user => user.name);  
}
```

<https://jestjs.io/docs/en/tutorial-async>



Testing Promises

```
function getUserNames(userID) {  
  return request-promise('/users/' + userID).then(user => user.name);  
}
```

```
it('works with promises', () => {  
  expect(user.getUserName(4).toEqual('Mark'));  
});
```



Testing Promises

```
function getUserNames(userID) {  
  return request-promise('/users/' + userID).then(user => user.name);  
}
```

```
it('works with promises', () => {  
  expect(user.getUserNames(4).toEqual('Mark'));  
});
```

```
it('works with promises', () => {  
  expect.assertions(1);  
  return user.getUserNames(4).then(data => expect(data).toEqual('Mark'));  
});
```



Testing Promises

```
function getUserNames(userID) {  
  return request-promise('/users/' + userID).then(user => user.name);  
}
```

```
it('works with promises', () => {  
  expect(user.getUserNames(4).toEqual('Mark'));  
});
```

```
it('works with promises', () => {  
  expect.assertions(1);  
  return user.getUserNames(4).then(data => expect(data).toEqual('Mark'));  
});
```

```
it('works with resolves', () => {  
  expect.assertions(1);  
  return expect(user.getUserNames(5)).resolves.toEqual('Paul');  
});
```

<https://jestjs.io/docs/en/tutorial-async>



Testing Promises

```
function getUserNames(userID) {  
  return request-promise('/users/' + userID).then(user => user.name);  
}
```

```
it('works with promises', () => {  
  expect(user.getUserName(4)).toEqual('Mark');  
});
```



```
it('works with promises', () => {  
  expect.assertions(1);  
  return user.getUserName(4).then(data => expect(data).toEqual('Mark'));  
});
```

```
it('works with resolves', () => {  
  expect.assertions(1);  
  return expect(user.getUserName(5)).resolves.toEqual('Paul');  
});
```

<https://jestjs.io/docs/en/tutorial-async>

SWE 432 - Web Application Development



George Mason
University

Instructor:
Dr. Kevin Moran

Teaching Assistant:
David Gonzalez Samudio

Class will start in:

10:01

SWE 432 - Web Application Development



George Mason
University

Instructor:
Dr. Kevin Moran

Teaching Assistant:
David Gonzalez Samudio

Class will start in:

10:01

Asynchronous Programming II





Review: Asynchronous


- Synchronous:
 - Make a function call
 - When function call returns, the work is done
- Asynchronous:
 - Make a function call
 - Function returns immediately, before completing work!

Review: Asynchronous

- How we do multiple things at a time in JS
- NodeJS magically handles these asynchronous things in the background
- Really important when doing file/network input/output


Review: Run-to-completion semantics

- Run-to-completion
 - The function handling an event and the functions that it (transitively) synchronously calls will keep executing until the function finishes.
 - The JS engine will not handle the next event until the event handler finishes.



Review: Implications of run-to-completion

- Good news: no other code will run until you finish (no worries about other threads overwriting your data)




j will not execute until after i

Review: Implications of run-to-completion

- Bad/OK news: Nothing else will happen until event handler returns
- Event handlers should never block (e.g., wait for input) --> all callbacks waiting for network response or user input are **always** asynchronous
- Event handlers shouldn't take a long time either

processing of
event queue



j will not execute until i finishes

Review: Chaining Promises





Review: Chaining Promises

```
myPromise.then(function(resultOfPromise){  
    //Do something, maybe asynchronously  
    return theResultOfThisStep;  
})
```



Review: Chaining Promises

```
myPromise.then(function(resultOfPromise){  
    //Do something, maybe asynchronously  
    return theResultOfThisStep;  
})  
    .then(function(resultOfStep1){  
        //Do something, maybe asynchronously  
        return theResultOfStep2;  
    })
```

Review: Chaining Promises

```
myPromise.then(function(resultOfPromise){  
    //Do something, maybe asynchronously  
    return theResultOfThisStep;  
})  
    .then(function(resultOfStep1){  
        //Do something, maybe asynchronously  
        return theResultOfStep2;  
    })  
    .then(function(resultOfStep2){  
        //Do something, maybe asynchronously  
        return theResultOfStep3;  
    })
```

Review: Chaining Promises

```
myPromise.then(function(resultOfPromise){  
    //Do something, maybe asynchronously  
    return theResultOfThisStep;  
})  
  .then(function(resultOfStep1){  
    //Do something, maybe asynchronously  
    return theResultOfStep2;  
})  
  .then(function(resultOfStep2){  
    //Do something, maybe asynchronously  
    return theResultOfStep3;  
})  
  .then(function(resultOfStep3){  
    //Do something, maybe asynchronously  
    return theResultOfStep4;  
})
```

Review: Chaining Promises

```
myPromise.then(function(resultOfPromise){  
    //Do something, maybe asynchronously  
    return theResultOfThisStep;  
})  
  .then(function(resultOfStep1){  
    //Do something, maybe asynchronously  
    return theResultOfStep2;  
})  
  .then(function(resultOfStep2){  
    //Do something, maybe asynchronously  
    return theResultOfStep3;  
})  
  .then(function(resultOfStep3){  
    //Do something, maybe asynchronously  
    return theResultOfStep4;  
})  
  .catch(function(error){  
  
  });
```



Current Lecture

- Async/await
- Programming activity

Promising many things

- Can also specify that *many* things should be done, and then something else
- Example: load a whole bunch of images at once:

Promise

```
.all([loadImage("GMURGB.jpg"), loadImage("CS.jpg")])  
.then(function (imgArray) {  
    imgArray.forEach(img => {document.body.appendChild(img)})  
})  
.catch(function (e) {  
    console.log("Oops");  
    console.log(e);  
});
```



Async Programming Example

1 second each

Go get a data
item

Go get a data
item

Go get a data
item

Go get a data
item

Go get a data
item

Go get a data
item

Go get a data
item

Go get a data
item

Go get a data
item

Go get a data
item

2 seconds each

thenCombine

Group all Cal
updates

Group all news
updates

when done

Update display

Explain
example



Synchronous Version



Synchronous Version

**Go get a data
item**



Synchronous Version

**Go get a data
item**

**Go get a data
item**



Synchronous Version

**Go get a data
item**

**Go get a data
item**

**Go get a data
item**

Synchronous Version

**Go get a data
item**

**Go get a data
item**

**Go get a data
item**

**Go get a data
item**

Synchronous Version

**Go get a data
item**

**Go get a data
item**

**Go get a data
item**

**Go get a data
item**

**Go get a data
item**



Synchronous Version

Go get a data item
Go get a data item
Go get a data item
Go get a data item
Go get a data item
Go get a data item



Synchronous Version

**Go get a data
item**

**Go get a data
item**

**Go get a data
item**

**Go get a data
item**

**Go get a data
item**


**Go get a data
item**

**Go get a data
item**


Synchronous Version




Synchronous Version




Synchronous Version




Synchronous Version




Synchronous Version



Synchronous Version



Synchronous Version





Asynchronous Version



Asynchronous Version

**Go get a data
item**

**Go get a data
item**

**Go get a data
item**

**Go get a data
item**

**Go get a data
item**

**Go get a data
item**

**Go get a data
item**

**Go get a data
item**

**Go get a data
item**


**Go get a data
item**

...

**Explain
example**



Asynchronous Version



...




...

**Explain
example**



Asynchronous Version



Async Programming Example (Sync)

```
let lib = require("./lib.js");

let thingsToFetch = ['t1', 't2', 't3', 's1', 's2', 's3', 'm1', 'm2', 'm3', 't4'];
let stuff = [];
for(let thingToGet of thingsToFetch)
{
    stuff.push(lib.getSync(thingToGet));
    console.log("Got a thing");
}
//Got all my stuff
let ts = lib.groupSync(stuff, "t");
console.log("Grouped");
let ms = lib.groupSync(stuff, "m");
console.log("Grouped");
let ss = lib.groupSync(stuff, "s");
console.log("Grouped");

console.log("Done");
```



57

Async Programming Example (Callbacks)

```

let lib = require("./lib.js");

let thingsToFetch = ['t1', 't2', 't3', 's1', 's2', 's3', 'm1', 'm2', 'm3', 't4'];
let stuff = [];
let ts, ms, ss;
let outstandingStuffToGet = thingsToFetch.length;
for (let thingToGet of thingsToFetch) {
  lib.getAsync(thingToGet, (v) => {
    stuff.push(v);
    console.log("Got a thing")
    outstandingStuffToGet--;
    if (outstandingStuffToGet == 0) {
      let groupsOfStuffToGetStill = 3;
      lib.groupAsync(stuff, "t", (t) => {
        ts = t;
        console.log("Grouped");
        groupsOfStuffToGetStill--;
        if (groupsOfStuffToGetStill == 0)
          console.log("Done");
      });
      lib.groupAsync(stuff, "m", (m) => {
        ms = m;
        console.log("Grouped");
        groupsOfStuffToGetStill--;
        if (groupsOfStuffToGetStill == 0)
          console.log("Done");
      });
      lib.groupAsync(stuff, "s", (s) => {
        ss = s;
        console.log("Grouped");
        groupsOfStuffToGetStill--;
        if (groupsOfStuffToGetStill == 0)
          console.log("Done");
      });
    }
  });
}

```


Async Programming Example (Promises, no parallelism)

```
let lib = require("./lib.js");

let thingsToFetch = ['t1', 't2', 't3', 's1', 's2', 's3', 'm1', 'm2', 'm3', 't4'];
let stuff = [];
let ts, ms, ss;
let outstandingStuffToGet = thingsToFetch.length;
lib.getPromise(thingsToFetch[0]).then(
  (v)=>{
    stuff.push(v);
    console.log("Got a thing");
    return lib.getPromise(thingsToFetch[1]);
  }
).then(
  (v)=>{
    stuff.push(v);
    console.log("Got a thing");
    return lib.getPromise(thingsToFetch[1]);
  }
).then(
  (v)=>{
    stuff.push(v);
    console.log("Got a thing");
    return lib.getPromise(thingsToFetch[1]);
  }
).then(
  (v)=>{
    stuff.push(v);
    console.log("Got a thing");
    return lib.getPromise(thingsToFetch[2]);
  }
).then(
  (v)=>{
    stuff.push(v);
    console.log("Got a thing");
    return lib.getPromise(thingsToFetch[3]);
  }
).then(
  (v)=>{
    stuff.push(v);
    console.log("Got a thing");
    return lib.getPromise(thingsToFetch[4]);
  }
);
```

Async Programming Example (Promises)

```

let lib = require("./lib.js");

let thingsToFetch = ['t1', 't2', 't3', 's1', 's2', 's3', 'm1', 'm2', 'm3', 't4'];
let stuff = [];
let ts, ms, ss;

let promises = [];
for (let thingToGet of thingsToFetch) {
    promises.push(lib.getPromise(thingToGet));
}
Promise.all(promises).then((data) => {
    console.log("Got all things");
    stuff = data;
    return Promise.all([
        lib.groupPromise(stuff, "t"),
        lib.groupPromise(stuff, "m"),
        lib.groupPromise(stuff, "s")
    ])
})
    .then((groups) => {
        console.log("Got all groups");
        ts = groups[0];
        ms = groups[1];
        ss = groups[2];
        console.log("Done");
    });

```

Problems with Promises

```
const makeRequest = () => {  
  try {  
    return promise1()  
      .then(value1 => {  
        // do something  
      }).catch(err => {  
        //This is the only way to catch async errors  
        console.log(err);  
      })  
  } catch (ex) {  
    //Will never catch async errors!!  
  }  
}
```

Async/Await

- The latest and greatest way to work with async functions
- A programming pattern that tries to make async code look more synchronous
- Just “await” something to happen before proceeding
- <https://javascript.info/async-await>

Async keyword

- Denotes a function that can block and resume execution later

```
async function hello() { return "Hello" };  
hello();
```

- Automatically turns the return type into a Promise

Async/Await Example

```
function resolveAfter2Seconds() {  
  return new Promise(resolve => {  
    setTimeout(( ) => {  
      resolve('resolved');  
    }, 2000);  
  });  
}  
  
async function asyncCall() {  
  console.log('calling');  
  var result = await resolveAfter2Seconds();  
  console.log(result);  
  // expected output: 'resolved'  
}  
  
asyncCall();
```

<https://jsbin.com/jivacodefo/edit?js,console>

Async/Await -> Synchronous

```
let lib = require("./lib.js");

async function getAndGroupStuff() {
  let thingsToFetch = ['t1', 't2', 't3', 's1', 's2', 's3', 'm1', 'm2', 'm3', 't4'];
  let stuff = [];
  let ts, ms, ss;

  let promises = [];
  for (let thingToGet of thingsToFetch) {
    stuff.push(await lib.getPromise(thingToGet));
    console.log("Got a thing");
  }
  ts = await lib.groupPromise(stuff, "t");
  console.log("Made a group");
  ms = await lib.groupPromise(stuff, "m");
  console.log("Made a group");
  ss = await lib.groupPromise(stuff, "s");
  console.log("Made a group");
  console.log("Done");
}

getAndGroupStuff();
```

Async/Await

- Rules of the road:
 - You can only call **await** from a function that is **async**
 - You can only **await** on functions that return a **Promise**
 - Beware: await makes your code synchronous!

```
async function getAndGroupStuff() {  
  ...  
  ts = await lib.groupPromise(stuff, "t");  
  ...  
}
```