

# Install Jenkins Server on Ubuntu 18.04

## Table of Contents

Prerequisite .....	1
Installation .....	1

## Prerequisite

- JDK-8

## Installation

- Update Jenkins key cache.

```
$ wget -q -O - https://pkg.jenkins.io/debian/jenkins.io.key | sudo apt-key add -
```

- Add Repository.

```
$ sudo sh -c 'echo deb https://pkg.jenkins.io/debian-stable binary/ > /etc/apt/sources.list.d/jenkins.list'
```

- Update package

```
$ sudo apt-get update
```

- Install Jenkins server

```
$ sudo apt-get install jenkins
```

### This package installation will:

- Setup Jenkins as a daemon launched on start. See `/etc/init.d/jenkins` for more details.
- Create a `jenkins` user to run this service.
- Direct console log output to the file `/var/log/jenkins/jenkins.log`. Check this file if you are troubleshooting Jenkins.
- Populate `/etc/default/jenkins` with configuration parameters for the launch, e.g `JENKINS_HOME`

- Set Jenkins to listen on port **8080**. Access this port with your browser to start configuration.



If your `/etc/init.d/jenkins` file fails to start Jenkins, edit the `/etc/default/jenkins` to replace the line `----HTTP_PORT=8080----` with `----HTTP_PORT=8081----` Here, "8081" was chosen but you can put another port available.

- While configuring on UI select **Install recommended plugins**.

## Configure Email Notification using Gmail.

- Go to Manager Jenkins -> Configure System.
- Goto Extending Email Notification section. Fill details as shown in below screenshot with your email address. SMTP Server is **smtp.gmail.com**, select advanced option and set username and password(password should be your app code) set **USE SSL** with Port **465**

**Extended E-mail Notification**

SMTP server: smtp.gmail.com

Default user E-mail suffix: @gmail.com

☒ Use SMTP Authentication

User Name: your-email@gmail.com

Password: \*\*\*\*\*

Advanced Email Properties

Use SSL: ☒

SMTP port: 465

Charset: UTF-8

Additional accounts: Add

Default Content Type: HTML (text/html)

☐ Use List-ID E-mail Header

☐ Add 'Precedence: bulk' E-mail Header

Default Recipients:

Reply To List: your-email@gmail.com

Emergency reroute:






Allowed Domains:

Excluded Recipients:

Default Subject: \$PROJECT\_NAME - Build # \$BUILD\_NUMBER - \$BUILD\_STATUS!

- Goto E-mail Notification section. Fill details as shown in below screenshot with your email address. SMTP Server is **smtp.gmail.com**, select advanced option and set username and password(password should be your app code) set **USE SSL** with Port **465**

#### E-mail Notification

SMTP server	<input type="text" value="smtp.gmail.com"/>	
Default user e-mail suffix	<input type="text" value="@gmail.com"/>	
<input checked="" type="checkbox"/> Use SMTP Authentication		
User Name	<input type="text" value="your-email@gmail.com"/>	
Password	<input type="password" value="....."/>	
Use SSL	<input checked="" type="checkbox"/>	
SMTP Port	<input type="text" value="465"/>	
Reply-To Address	<input type="text" value="ypur-email@gmail.com"/>	
Charset	<input type="text" value="UTF-8"/>	
<input checked="" type="checkbox"/> Test configuration by sending test e-mail		
Test e-mail recipient	<input type="text" value="destination@gmail.com"/>	

