Chip8 Emulator in C

Kirjan Kohuladas/kprime21

Overview

Compact Hexadecimal Interpretive Programming – 8-bit

Components

- Memory - 4kB ram (4096 bytes - 4096 address lines each line is 1 byte)

- Display - 64 x 32 pixels

- Registers

    - Program Counter (16 bits)
    - Index Register (16 bits)
    - Stack - call subroutines and functions (16 bits)
    - Delay timer - decremented at 60Hz (8 bits)
    - Sound timer - decremented at 60Hz (8 bits)
    - 15 General purpose registers - V0 - VF (8 bits)

Memory

- all memory is RAM, 4096 bytes.

    - 4096 addressable lines
    - 12 bits needed
    - each addressable line represents an addresss of 1 byte.

- interpreter located 0x000-0x1FF (not in our case)

- program located 0x200 - 0x...

- font located before program 0x000-0x1FF (popular area - 0x050 - 0x09F)

Font

- font character should be 4px x 5px

- first byte is the character (draw vertically in nvim to see)

- stored in memory, index register set to specific font in memory to draw it

Display

- 60Hz - 60 times per second

- sprite consists of 8 bits

- sprites are between 1 and 15 bytes tall

- 0 bits are transparent and 1 bits flip pixel locations

Stack

- stack(LiFo) to call and return from subroutines
- 16 bit addresses (12 bits useful) are saved here

Timers

- two timer registers - the delay timer and sound timer
- one byte in size and if above 0, decremented by 1 60 times per second (60Hz)
- sound timer beeps as long as it's above 0

Keypad

- 123C
- 456D
- 789E
- A0BF

Fetch/decode/excute loop

- fetch the instruction from memory at current PC (program counter)
- decode the instruction to find what emulator should do
- execute instruction and do what it tells you
- this loop's speed has to be set so that it does not run too fast (700Hz)
- fetch: read instruction in PC, two successive bytes and combine into one 16 bit instruction, increment PC by 2
- decode: switch statement checking first half of instruction
- nibbles after first used for decoding, extract these before decoding from opcode
  - X - second nibble
  - Y - third nibble
  - N - fourth nibble
  - NN - third and fourth nibble - 8 bit immd number
  - NNN - second, third and fourth nibble - 12 bit immd address
- execute: do what each instruction should do in each case of the switch

Opcodes

1. 0nnn - ignored by modern interpreters.

2. 00E0 - CLS, clear the display.

3. 00EE - RET, return from subroutine.

4. 1nnn - JP addr, program counter set to nnn.

5. 2nnn - CALL addr, increment stack pointer then place current PC on top of stack, then set PC to nnn.

6. 3xkk - SE Vx byte, skip next instruction if Vx == kk, PC+=2.

7. 4xkk - SNE Vx byte, skip next instruction if Vx != kk, PC+=2.

8. 5xy0 - SE Vx, Vy, skip next instruction if Vx == Vy, PC+=2.

9. 6xkk - LD Vx, byte - load kk into Vx.

10. 7xkk - ADD Vx, byte - add value kk to register Vx, store result in Vx.

11. 8xy0 - LD Vx, Vy - store value of register Vy in register Vx.

12. 8xy1 - OR Vx, Vy - bitwise OR then store in Vx.

13. 8xy2 - AND Vx, Vy - bitwise AND then store in Vx.

14. 8xy3 - XOR Vx, Vy - bitwise XOR and then store in Vx.

15. 8xy4 - ADD Vx, Vy - add Vx, Vy, result greater than 255 sets VF flag, only lowest 8 bits stored in Vx.

16. 8xy5 - SUB Vx, Vy - Vx ¿ Vy, Vf set to 1, otherwise 0. Subtract Vy from Vx and store in Vx.

17. 8xy6 - SHR Vx (, Vy) - LSB of Vx is 1, set Vf to 1. Otherwise 0. Vx divided by 2.

18. 8xy7 - SUBN Vx, Vy - Vy ¿ Vx, Vf set to 1, otherwise 0. Subtract Vx from Vy and store in Vx.

19. 8xyE - SHL Vx (, Vy) - MSB of Vx is 1, set Vf to 1. Otherwise 0. Vx multiplied by 2.

20. 9xy0 - SNE Vx, Vy - Vx and Vy compared, if not equal, PC+=2.

21. Annn - LD I, addr - Index register is set to addr.

22. Bnnn - JP V0, addr - Program Counter is set to nnn+V0.

23. Cxkk - RND Vx, byte - Generate random number AND with kk, store in Vx.

24. Dxyn - DRW Vx, Vy, nibble - Read n bytes from memory staring at address stored in Index. Bytes are displayed as sprites on screen at co-ord(Vx,Vy). Sprites are XOR'd onto screen, any overlapping part of sprite will be wrapped around screen. If sprite collides with another sprite then set Vf to 1.

25. Ex9E - SKP Vx - Skip next instruction if key with value Vx is pressed, PC+=2.

26. ExA1 - SKNP Vx - Skip next instruction if key with value Vx is not pressed, PC+=2.

27. Fx07 - LD Vx, DT - Set the value of Vx to value of delay timer.

28. Fx0A - LD Vx, k - Execution stops until key is pressed, store value of key in Vx.

29. Fx15 - LD DT, Vx - Set the value of delay timer to value of Vx.

30. Fx18 - LD ST, Vx - Set the value of sound timer to value of Vx.

31. Fx1E - ADD I, Vx - Value of Index register and Vx added and stored in Index register.

32. Fx29 - LD F, Vx - Index register is set equal to the location for hexadecimal sprite corresponding to value in Vx.

33. Fx33 - LD B, Vx - Store BCD(Vx) in Index register, Index+1, Index+2.

34. Fx55 - LD [I], Vx - Store registers V0 through Vx in memory starting at location in Index register.

35. Fx65 - LD Vx, [I] - Read values from memory and store them from V0 through Vx.

Main

- Setup directory to ignore makefile outputs

Reference

- https://tobiasvl.github.io/blog/write-a-chip-8-emulator/
- http://devernay.free.fr/hacks/chip8/C8TECH10.HTM