## Write a program to demonstrate the use of JSP Directives.

Index.jsp

```
<%@ page language="java" contentType="text/html;</pre>
charset=IS0-8859-1"
pageEncoding="ISO-8859-1"%>
<%@ taglib prefix="core" uri="http://java.sun.com/jsp/jstl/core"%>
<%@ taglib prefix="fmt" uri="http://java.sun.com/jsp/jstl/fmt"%>
<title>JSPDirectivesDemo</title>
This is content from the main file (index.jsp).
<%@ include file="file1.jsp"%>
<hr>
Example of using JSTL taglibs for formatting output
<br
>
Currency =
<fmt:formatNumber value="145" type="currency" />
>
>
<core:set var="now" value=</pre>
"<%=new java.util.Date()%>" />
Current date and time is
<fmt:formatDate pattern="yyyy-MM-dd hh:mm:ss" value=</pre>
"${now}" />
```

This is content from the main file (index.jsp).

## This is content from file1.jsp

Example of using JSTL taglibs for formatting output

□ □ □ □ http://localhost:8080/jspdirectivesDemo/index.jsp

Currency = \$145.00

Current date and time is 2023-06-01 12:49:03

```
File1.jsp
```

```
<%@ page language="java" contentType="text/html;
charset=ISO-8859-1"
pageEncoding="ISO-8859-1"%>
<h3 style="background:yellow"> This is content from file1.jsp</h3></h3>
```

This is content from file1.jsp