Write a program to demonstrate the function of JSP Implicit Objects.

#### Code jSP

```
<%@ page language="java" contentType="text/html;</pre>
charset=ISO-8859-1"pageEncoding="ISO-8859-1"%>
<h3>Implicit Objects Demo</h3>
<%
String responseCheck = request.getParameter("office");
// if office parameter was set, tthen redirect the user to
response-redirect.jsp
if(responseCheck != null){
response.setStatus(response.SC MOVED TEMPORARILY); // HTTP
status code 302
response.setHeader("Location", "response-redirect.jsp?
office=" +
responseCheck);
}
%>
<%
int serverPort = request.getServerPort();
out.println("The Server is running on port " +
String.valueOf(serverPort) +
"<br>");
out.println("Servlet Name is " + config.getServletName() +
"<br>");
out.println("Server Info:" + application.getServerInfo() +
"<br>"):
String pageName = page.toString();
out.println("The name of the page is " + pageName + "<br>");
pageContext.setAttribute("userid", "John Doe");
out.println("userId attribute from pageContext: " +
pageContext.getAttribute("userid") + "<br>");
%>
```



# **Implicit Objects Demo**

The Server is running on port 8080
Servlet Name is jsp
Server Info:Apache Tomcat/9.0.80
The name of the page is org.apache.jsp.index\_jsp@60f72b4e
userId attribute from pageContext: mayur

### **Code:response -redirect**

```
<%@ page language="java" contentType="text/html;
charset=ISO-8859-1"
pageEncoding="ISO-8859-1"%>
<h3> Inside response-redirect.jsp</h3>
<%
String office = request.getParameter("office");
if (office != null)
out.println("value of Office obtained :" + office + " <br>out.println("No value of Office found <br>");
```



## Inside response-redirect.jsp

No value of Office found

#### Error.jsp

```
<%@ page language="java" contentType="text/html;
charset=ISO-8859-1"
pageEncoding="ISO-8859-1"%>
<h2>Oops! Something went wrong. <br/>Contact our customer care executive.
70XXXXXXXXXX</h2>
```



Oops! Something went wrong.
Contact our customer care executive. 70XXXXXXXX