


docker®

Docker Desktop



The screenshot shows the Docker Desktop product page on the official Docker website. At the top, there's a navigation bar with links for Products, Developers, Pricing, Blog, About Us, and Partners. A purple banner at the top of the main content area reads "DockerCon 2023: Our annual developer event is back – online & in person. [Learn more.](#)". The main headline is "Docker Desktop" followed by the tagline "The #1 containerization software for developers and teams". Below that, it says "Your command center for innovative container development". There are two prominent blue buttons: "Create an account" and "Download for Windows".

docker.com/products/docker-desktop/

DockerCon 2023: Our annual developer event is back – online & in person. [Learn more.](#)

Products ▾ Developers ▾ Pricing Blog About Us ▾ Partners

Docker Desktop

The #1 containerization software for developers and teams

Your command center for innovative container development

Create an account

Download for Windows ▾

El instalador



Installing Docker Desktop 4.24.0 (122432)

Docker Desktop

Initializing...

Verifying package



Installing Docker Desktop 4.24.0 (122432)

Configuration


Use WSL 2 instead of Hyper-V (recommended)
 Add shortcut to desktop

Ok 3


Instalando ...




Instalado ¿?




Más preguntas




Ahora parece que ya inicio



Según ya esta ejecutándose ...



Verificación de que todo esta bien



```
PowerShell 7.3.7
Loading personal and system profiles took 10298ms.
[kralos]
[~]
▶ docker -v
Docker version 24.0.6, build ed223bc
[kralos]
[~]
▶ |
```

hub.Docker.com

The screenshot shows the Docker Hub homepage at hub.docker.com. The top navigation bar includes a lock icon, the URL, a purple banner for DockerCon, the Docker Hub logo, a search bar, and links for Explore, Pricing, Sign In, and Sign up. The main visual features a large blue hexagonal graphic with white text: "Build and Ship any Application Anywhere". Below it, a sub-copy reads: "Docker Hub is the world's easiest way to create, manage, and deliver your team's container applications." To the right is a "Create your account" form with fields for Email, Username, and Password, and a checkbox for product updates. A note states the site is protected by reCAPTCHA and links to Privacy Policy and Terms of Service. At the bottom, there's a "Sign up" button and a link for existing users.

Join the DockerCon online event Oct 4-5th, live from Los Angeles. [Watch now.](#)

hub.docker.com

docker hub Search Docker Hub

Explore Pricing Sign In [Sign up](#)

Build and Ship any Application Anywhere

Docker Hub is the world's easiest way to create, manage, and deliver your team's container applications.

Create your account

Signing up for Docker is fast and free.

Email

Username

Password

Send me occasional product updates and announcements.

This site is protected by reCAPTCHA and the Google [Privacy Policy](#) and [Terms of Service](#) apply.

[Sign up](#)


By creating an account I agree to the [Subscription Service Agreement](#), [Privacy Policy](#), [Data Processing Terms](#).

Already have an account? [Sign in](#)

El hola mundo de docker

The screenshot shows the Docker Hub interface for the 'hello-world' image. At the top, there's a search bar with 'hello-world' and navigation links for 'Explore', 'Official Images', and 'hello-world'. The main content area displays the 'hello-world' image card, which includes the Docker Hub logo, the image name 'hello-world', its status as a 'Docker Official Image', its size of '1B+', and its star count of '2.1K'. Below the card is a brief description: 'Hello World! (an example of minimal Dockerization)'. There are two tabs: 'Overview' (which is selected) and 'Tags'. To the right of the card is a button labeled 'docker pull hello-world' with a copy icon. On the left side of the main content, there's a 'Quick reference' section with bullet points about maintainers and help resources. Below that is a 'Supported tags and respective Dockerfile links' section, which notes that tags are shared between 'Shared' and 'Simple' tags. It lists simple tags: 'linux', 'nanoserver-ltsc2022', and 'nanoserver-1809'. To the right of the main content are two boxes: 'Recent Tags' (listing tags like 'nanoserver-ltsc2022', 'nanoserver-1809', 'nanoserver', 'latest', 'linux', 'nanoserver-1803', 'nanoserver-1709', 'nanoserver-sac2016', and 'nanoserver1709') and 'About Official Images' (explaining that official images are curated open source repositories and designed for common use cases).

Ahora si, primeros pasos




The screenshot shows a PowerShell window with the title bar "PowerShell". The command entered was "docker pull hello-world". The output indicates that the latest tag is being pulled from the library/hello-world repository, resulting in a digest hash of 719385e32844 and a status message stating that a newer image has been downloaded for the hello-world:latest tag. A "What's Next?" section at the bottom suggests viewing image vulnerabilities and recommendations with the command "docker scout quickview hello-world".


```
[[kralos]
[D:\code\Dockers]
▶ docker pull hello-world
Using default tag: latest
latest: Pulling from library/hello-world
719385e32844: Pull complete
Digest: sha256:4f53e2564790c8e7856ec08e384732aa38dc43c52f02952483e3f003afbf23db
Status: Downloaded newer image for hello-world:latest
docker.io/library/hello-world:latest

What's Next?
  View a summary of image vulnerabilities and recommendations → docker scout quickview hello-world
[[kralos]
[D:\code\Dockers]
▶ |
```

Por si las flies ...



A pero estamos en CLI ...




The screenshot shows a PowerShell window with the following content:

```
[kralos]
[D:\code\Dockers]
▶ docker pull hello-world
Using default tag: latest
latest: Pulling from library/hello-world
719385e32844: Pull complete
Digest: sha256:4f53e2564790c8e7856ec08e384732aa38dc43c52f02952483e3f003afbf23db
Status: Downloaded newer image for hello-world:latest
docker.io/library/hello-world:latest

What's Next?
View a summary of image vulnerabilities and recommendations → docker scout quickview hello-world
[kralos]
[D:\code\Dockers]
▶ docker images
REPOSITORY      TAG          IMAGE ID      CREATED        SIZE
hello-world     latest       9c7a54a9a43c   5 months ago   13.3kB
[kralos]
[D:\code\Dockers]
▶ |
```

Comandos para imágenes docker

Imagenes
docker images
Lista las imágenes almacenadas en el host
docker search imagen
Busca una imagen en el Docker hub
docker inspect id/nombre
Muestra los detalles de una imagen a partir de un id o un nombre
docker pull nombre
Descarga la imagen correspondiente a ese nombre
docker rmi id/nombre
Elimina la imagen correspondiente a ese id o nombre



```
PowerShell
hello-world  latest  9c7a54a9a43c  5 months ago  13.3kB
[kralos]
[D:\code\Dockers]
> docker inspect 9c7a54a9a43c
[
  {
    "Id": "sha256:9c7a54a9a43cca047013b82af109fe963fde787f63f9e016fdc3384500c2823d",
    "RepoTags": [
      "hello-world:latest"
    ],
    "RepoDigests": [
      "hello-world@sha256:4f53e2564790c8e7856ec08e384732aa38dc43c52f02952483e3f003afbfb23db"
    ],
    "Parent": "",
    "Comment": "",
    "Created": "2023-05-04T17:37:03.872958712Z",
    "Container": "347ca68872ee924c4f9394b195dcadaf591d387a45d624225251efc6cb7a348e",
    "ContainerConfig": {
      "Hostname": "347ca68872ee",
      "Domainname": "",
      "User": "",
      "AttachStdin": false,
      "AttachStdout": false,
      "AttachStderr": false,
      "Tty": false,
      "OpenStdin": false,
      "StdinOnce": false,
      "Env": [
        "PATH=/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin"
      ],
      "Cmd": [
        "/bin/sh",
        "-c",
        "#(nop)",
        "CMD [\"/hello\"]"
      ],
      "Image": "sha256:62a15619037f3c4fb4e6ba9bd224cba3540e393a55dc52f6bebe212ca7b5e1a7",
      "Volumes": null,
      "WorkingDir": "",
      "Entrypoint": null,
      "OnBuild": null,
      "Labels": {}
    },
    "DockerVersion": "20.10.23",
    "Author": "",
    "Config": {
      "Hostname": "",
      "Domainname": "",
      "User": "",
      "AttachStdin": false,
      "Env": [
        "PATH=/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin"
      ],
      "Cmd": [
        "/bin/sh",
        "-c",
        "#(nop)",
        "CMD [\"/hello\"]"
      ],
      "Image": "sha256:62a15619037f3c4fb4e6ba9bd224cba3540e393a55dc52f6bebe212ca7b5e1a7",
      "Volumes": null,
      "WorkingDir": "",
      "Entrypoint": null,
      "OnBuild": null,
      "Labels": {}
    }
  }
]
```

Pull especificando una etiqueta

The screenshot shows the Docker Hub interface for the `hello-world` repository. The `Tags` tab is selected. Two sections are visible: `latest` and `linux`.

latest Section:

DIGEST	OS/ARCH	VULNERABILITIES	COMPRESSED SIZE
004d23c66201	linux/386	None found	2.65 KB
efd257c8ea08	windows/amd64	None found	114.99 MB
75043f8f1db5	windows/amd64	None found	99.65 MB

A tooltip for the `004d23c66201` row contains the command `docker pull hello-world:latest`.

linux Section:

DIGEST	OS/ARCH	VULNERABILITIES	COMPRESSED SIZE
004d23c66201	linux/386	None found	2.65 KB
7e9b6e7ba284	linux/amd64	None found	2.4 KB
084c3bdd1271	linux/arm/v5	None found	3.57 KB

A tooltip for the `004d23c66201` row contains the command `docker pull hello-world:linux`.

Otro hola mundo


```
[kralos] [D:\code\Dockers]
▶ docker pull hello-world:nanoserver-ltsc2022
nanoserver-ltsc2022: Pulling from library/hello-world
no matching manifest for linux/amd64 in the manifest list entries
[kralos][xERROR]
[D:\code\Dockers]
▶ docker images
REPOSITORY      TAG      IMAGE ID      CREATED      SIZE
hello-world     latest   9c7a54a9a43c  5 months ago  13.3kB
linuxconfig/lEMP latest   670ff9140a94  12 months ago 1.05GB
[kralos]
[D:\code\Dockers]
▶ docker pull hello-world:linux
linux: Pulling from library/hello-world
Digest: sha256:726023f73a8fc5103fa6776d48090539042cb822531c6b751b1f6dd18cb5705d
Status: Downloaded newer image for hello-world:linux
docker.io/library/hello-world:linux

What's Next?
 1. Sign in to your Docker account → docker login
 2. View a summary of image vulnerabilities and recommendations → docker scout quickview hello-wor
d:linux
[kralos]
[D:\code\Dockers]
▶ docker images
REPOSITORY      TAG      IMAGE ID      CREATED      SIZE
hello-world     latest   9c7a54a9a43c  5 months ago  13.3kB
hello-world     linux    9c7a54a9a43c  5 months ago  13.3kB
linuxconfig/lEMP latest   670ff9140a94  12 months ago 1.05GB
[kralos]
[D:\code\Dockers]
▶ |
```

A descargar imágenes

The screenshot shows the Docker Hub interface for the `linuxconfig/lemp` repository. At the top, there's a blue header bar with the Docker Hub logo, a search bar containing `lemp`, and navigation links for `Explore`, `Pricing`, `Sign In`, and `Sign up`. Below the header, the breadcrumb navigation shows `Explore > linuxconfig/lemp`. The main content area features a large image of a blue cube icon, the repository name `linuxconfig/lemp` with a star icon, the creator's name `linuxconfig`, and a note that it was updated a year ago. It also mentions that it's a "Stable build LEMP stack environment for fast application deployments". There are buttons for `Image` and `Pulls 6.4K`. Below this, there are two tabs: `Overview` (which is selected) and `Tags`. The `Overview` section contains a summary of the `LEMP Stack`, which is described as a stable automated build docker LEMP image. It can be used as a testing environment for dynamic PHP applications. It comprises of Debian GNU/Linux, lightweight and yet powerful Nginx webserver, MariaDB relational database management system and PHP scripting language. It also lists current versions: Debian Linux 11, Nginx 1.18.0, MariaDB 10.5.15-MariaDB, and PHP 7.4.30. To the right, there are two boxes: one for the `Docker Pull Command` (`docker pull linuxconfig/lemp`) and another for the `Source Repository` (Bitbucket, `linuxconfig/lemp`).

Se tardo creo ... no vi :S



```
[kralos] [D:\code\Dockers] ▶ docker pull linuxconfig/lEMP
Using default tag: latest
latest: Pulling from linuxconfig/lEMP
23858da423a6: Pull complete
f093e2ae753e: Pull complete
76746722efdb: Pull complete
f01bb3e5c192: Pull complete
b5fb6632fdb8: Pull complete
8ef1d73eaf1e: Pull complete
9e9744007207: Pull complete
9d47ac32786b: Pull complete
4ca1a0fc6965: Pull complete
c4749a27ee79: Pull complete
7f4628d340a5: Pull complete
b0f32a77797b: Pull complete
85f70c5804f8: Pull complete
20c0e6ead277: Pull complete
866ab047c448: Pull complete
49b4f7e61728: Pull complete
aa91d496c637: Pull complete
c0170ae56952: Pull complete
18d296843117: Pull complete
2b21d6a47a24: Pull complete
11ca6a93e6aa: Pull complete
Digest: sha256:7cde4689c7f08e7e4d546dc51a5fe7b4dce8acob98d30eb7bec65051a2cce39
Status: Downloaded newer image for linuxconfig/lEMP:latest
docker.io/linuxconfig/lEMP:latest

What's Next?
  View a summary of image vulnerabilities and recommendations → docker scout quickview linuxconfig/lEMP
[kralos] [D:\code\Dockers] ▶ |
```

Comandos para contenedores

Contenedores

docker create -it --name nombre imagen

Crea un contenedor denominado name a partir de imagen

docker start nombre

Arranca el contenedor denominado nombre

docker stop nombre

Para el contenedor denominado nombre

docker restart nombre

Rearranca el contenedor denominado nombre

docker rm nombre

Elimina el contenedor denominado nombre

docker ps -a

Lista todos los contenedores en ejecución (-a incluye los parados)

docker run -it imagen comando

Arranca y ejecuta el comando en un contenedor de esa imagen en modo interactivo

docker exec -it nombre comando

Ejecuta el comando en el contenedor nombre

docker run -d

Arranca el contenedor en modo daemon

docker run -P

Arranca el contenedor y expone los puertos del contenedor en puertos aleatorios del host

docker run -p

puerto_host:puerto_contenedor

Arranca el contenedor y expone el puerto_contenedor en el puerto_host

docker run -v

directorio_host:directorio_contenedor

Asigna el directorio_host para mapearlo en el directorio_contenedor

docker run --hostname nombre_host

Arranca el contenedor y asigna nombre_host al contenedor


docker run --net=mired

Arranca el contenedor y lo asigna en la red denominada mired

“Crear” un contenedor

```
Σ PowerShell × + ▾ — □ ×
[[kralos]
[D:\code\Dockers]
▶ docker images
REPOSITORY      TAG      IMAGE ID      CREATED      SIZE
hello-world     latest   9c7a54a9a43c  5 months ago  13.3kB
hello-world     linux    9c7a54a9a43c  5 months ago  13.3kB
linuxconfig/lEMP  latest   670ff9140a94  12 months ago  1.05GB
[[kralos]
[D:\code\Dockers]
▶ docker create hello-world
2bc45d52863bfde33bc68c0caf3a33b479de42e3bc2d9ddd9575bb57afc9f812
[[kralos]
[D:\code\Dockers]
▶ docker ps -a
CONTAINER ID      IMAGE      COMMAND      CREATED      STATUS      PORTS      NAMES
2bc45d52863b      hello-world      "/hello"    36 seconds ago      Created      gifted_matsumoto
[[kralos]
[D:\code\Dockers]
▶ |
```

Ejecutando un contenedor ..



```
PowerShell          X + | ▾
[kralos]
[D:\code\Dockers]
▶ docker run hello-world

Hello from Docker!
This message shows that your installation appears to be working correctly.

To generate this message, Docker took the following steps:
1. The Docker client contacted the Docker daemon.
2. The Docker daemon pulled the "hello-world" image from the Docker Hub.
   (amd64)
3. The Docker daemon created a new container from that image which runs the
   executable that produces the output you are currently reading.
4. The Docker daemon streamed that output to the Docker client, which sent it
   to your terminal.

To try something more ambitious, you can run an Ubuntu container with:
$ docker run -it ubuntu bash

Share images, automate workflows, and more with a free Docker ID:
https://hub.docker.com/

For more examples and ideas, visit:
https://docs.docker.com/get-started/


[kralos]
[D:\code\Dockers]
▶ |
```

Cuidado con los espacios

- Use comillas al especificar nombres de archivo largos o rutas de acceso con espacios. Por ejemplo, escribir el comando

```
copy c:\my file name d:\my new file name
```

- El símbolo del sistema da como resultado el siguiente mensaje de error: El sistema no puede encontrar el archivo especificado.




The image shows a terminal window with a dark background and light-colored text. At the top, it says "La sintaxis correcta es esta:". Below that, it says "Consola". In the main area, there is a command prompt followed by an error message: "copy "c:\my file name" "d:\my new file name"" and "El sistema no puede encontrar el archivo especificado.". This indicates that the command was entered without quotes around the file names, causing a syntax error.

```
La sintaxis correcta es esta:  
Consola  
copy "c:\my file name" "d:\my new file name"  
El sistema no puede encontrar el archivo especificado.
```

Ejemplo de contenedor LEMP

1. Crear un directorio llamado “html” en SO anfitrión.

D:\code\Docker\html




Ejemplo de contenedor LEMP

2. Crear y ejecutar un contendor, además se especifica el directorio referenciado entre la PC local y el contendor a crearse.

```
docker run --name=lemp -dP -v  
D:\code\Docker\html:/var/www/html linuxconfig/lemp
```

Ejemplo de contenedor LEMP



Ejemplo de contenedor LEMP

The screenshot shows the Docker Desktop interface. On the left, there's a sidebar with options like Containers, Images, Volumes, Dev Environments (BETA), Docker Scout, Learning center, Extensions, and Add Extensions. The main area is titled "Containers" and displays the following information:

- Container CPU usage: 0.03% / 400% (4 cores allocated)
- Container memory usage: 120.1MB / 3.61GB
- Search bar and filter: Only show running containers
- A table listing three stopped containers and one running container:

Name	Image	Status	CPU (%)	Port(s)	Last started	Actions
nostalgic_moser 2f5eba4f771b	hello-world	Exited	0%		2 days ago	[More]
gifted_matsumoto 2bc45d52863b	hello-world	Exited	0%		2 days ago	[More]
lemp 140a76a8ce6a	linuxconfig/lemp	Running	0.03%	32768:3306	34 minutes ago	Show all ports (2) [More]
- A message at the bottom says "Showing 3 items"
- Below the table, there's a "Walkthroughs" section with two cards:
 - "What is a container?" (5 mins) with a question mark icon.
 - "How do I run a container?" (6 mins) with a terminal icon showing commands: FROM node, RUN mkdir -p /app, WORKDIR /app, COPY packa[REDACTED]
- At the bottom, there are status icons for Engine running, RAM (3.03 GB), CPU (0.25%), and Not signed in, along with version info (v4.24.0) and a notification bell.

Ejemplo de contenedor LEMP

3. Entramos al servidor web, pero antes necesitamos saber en que Puerto esta mapeado.

Vemos que hay dos puertos abiertos:


32269 para el servidor web

32768 para el servidor de base de dato

```
▶ docker port lemp
80/tcp -> 0.0.0.0:32769
3306/tcp -> 0.0.0.0:32768
```

Ejemplo de contenedor LEMP

- El servidor web esta activo pero no tiene nada ...



Ejemplo de contenedor LEMP

- El código se debe colocar el directorio “html” creado en el paso 1.
- Podemos usar nuestro editor favorito.

The screenshot shows a code editor on the left and a terminal window on the right. The code editor displays the file `index.php` with the following content:

```
Run Terminal Help
index.php X
index.php > html > body > p
1  <!DOCTYPE html>
2  <html lang="es">
3  <head>
4      <meta charset="UTF-8">
5      <meta name="viewport" content="width=device-width, initial-scale=1.0">
6      <title>Docker</title>
7  </head>
8  <body>
9      <p>Hola contenedor</p>
10 </body>
11 </html>
```

The terminal window is titled "Docker" and shows the output of the command `curl 127.0.0.1:32769`, which is `Hola contenedor`.

Ejemplo de contenedor LEMP

4. Ingresamos a la línea de comandos del contenedor

```
▶ docker exec -it lemp /bin/bash
root@140a76a8ce6a:/# ls
bin  boot  dev  etc  home  lib  lib64  media  mnt  opt  proc  root  run  sbin
root@140a76a8ce6a:/# pwd
/
root@140a76a8ce6a:/# whoami
root
root@140a76a8ce6a:/# ls /var/www/html/
index.php
root@140a76a8ce6a:/# cat /var/www/html/index.php
<!DOCTYPE html>
<html lang="es">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Docker</title>
</head>
<body>
    <p>Hola contenedor</p>
</body>
</html>root@140a76a8ce6a:/# |
```

Actualizaciones

The screenshot shows a dark-themed software update interface. At the top, the title "Software updates" is displayed in white. Below it, a message states, "You're currently on version 4.24.0 (122432). The latest version is 4.24.2 (124339)." A list of four bullet points details the changes in the latest version:

- New Notification center available to all users.
- Compose File Watch available to all users. For more information, see [Use Compose Watch](#).
- Resource Saver available to all users. This feature can be configured from the Resources tab in Settings. For more information see [Docker Desktop's Resource Saver mode](#).
- View and manage options in the Docker Engine state, with pause, stop, and resume, directly from the Docker Dashboard.

Un poco de detalle

```
docker run --name=lemp -dP -v D:\code\Docker\html:/var/www/html linuxconfig/lemp
```

--name=nombre_de_mi contenedor

-dP

d hace que el contenedor corra en segundo plano
(daemonizará el contenedor)

P para decirle a Docker que elija un puerto

-v Cuando queremos montar un volúmen en un contenedor
ruta_origen:ruta_destino

“linuxconfig/lemp” es el nombre de la imagen a usar




Mapear puertos

`-p puerto_PC_anfitrión: puerto_contendor`

El argumento `-p 1234:1234` le indica a Docker que tiene que hacer un port forwarding del contenedor hacia el puerto 1234 de la máquina host.

Para mas información ejecutar en su terminal el comando siguiente: `docker run --help`

Practica 2



```
docker run --name=lemp2 -d -p 8081:80 -v D:\code\ Docker\html_2:/var/www/html linuxconfig/lemp
```

```
PowerShell
[[kralos]
[~]
▶ docker run --name=lemp2 -d -p 8081:80 -v D:\code\ Docker\html_2:/var/www/html linuxconfig/lemp
f3c176d990da9f34e4177e0a1556500e4ea3900e4928bdf3897e29b915c6c31c
[[kralos]
[~]
▶ docker ps -a
CONTAINER ID  IMAGE          COMMAND       CREATED      STATUS           PORTS          NAMES
f3c176d990da  linuxconfig/lemp "supervisord"  8 seconds ago Up 4 seconds   3306/tcp, 0.0.0.0:8081->80/tcp    lemp2
140a76a8ce6a  linuxconfig/lemp "supervisord"  12 days ago   Up 2 minutes   0.0.0.0:32769->80/tcp, 0.0.0.0:32768->3306/tcp  lemp
2f5eba4f771b  hello-world    "/hello"      13 days ago   Exited (0) 13 days ago
2bc45d52863b  hello-world    "/hello"      13 days ago   Exited (0) 13 days ago
[[kralos]
[~]
▶ |
```

Comportamiento de los contenedores

docker logs lemp

```
[kralos]
[~]
▶ docker logs lemp
/usr/lib/python3/dist-packages/supervisor/options.py:474: UserWarning: Supervisord is running as root and it is searching for its configuration file in default locations (including its current working directory); you probably want to specify a "-c" argument specifying an absolute path to a configuration file for improved security.
    self.warnings.warn(
2023-10-06 16:45:54,397 CRIT Supervisor is running as root. Privileges were not dropped because no user is specified in the config file. If you intend to run as root, you can set user=root in the config file to avoid this message.
2023-10-06 16:45:54,399 INFO Included extra file "/etc/supervisor/conf.d/supervisor-lemp.conf" during parsing
2023-10-06 16:45:54,421 INFO RPC interface 'supervisor' initialized
2023-10-06 16:45:54,422 CRIT Server 'unix_http_server' running without any HTTP authentication checking
```

```
▶ docker logs lemp2
/usr/lib/python3/dist-packages/supervisor/options.py:474: UserWarning: Supervisord is running as root and it is searching for its configuration file in default locations (including its current working directory); you probably want to specify a "-c" argument specifying an absolute path to a configuration file for improved security.
    self.warnings.warn(
2023-10-18 18:20:06,537 CRIT Supervisor is running as root. Privileges were not dropped because no user is specified in the config file. If you intend to run as root, you can set user=root in the config file to avoid this message.
2023-10-18 18:20:06,537 INFO Included extra file "/etc/supervisor/conf.d/supervisor-lemp.conf" during parsing
2023-10-18 18:20:06,540 INFO RPC interface 'supervisor' initialized
2023-10-18 18:20:06,543 CRIT Server 'unix_http_server' running without any HTTP authentication checking
2023-10-18 18:20:06,543 INFO supervisord started with pid 1
2023-10-18 18:20:07,548 INFO spawned: 'mysqld' with pid 7
2023-10-18 18:20:07,550 INFO spawned: 'nginx' with pid 8
2023-10-18 18:20:07,551 INFO spawned: 'php-fcgi' with pid 9
2023-10-18 18:20:08,693 INFO success: mysqld entered RUNNING state, process has stayed up for > than 1 seconds (startsecs)
2023-10-18 18:20:08,693 INFO success: nginx entered RUNNING state, process has stayed up for > than 1 seconds (startsecs)
2023-10-18 18:20:08,693 INFO success: php-fcgi entered RUNNING state, process has stayed up for > than 1 seconds (startsecs)
[kralos]
[~]
▶ |
```

Variables de entorno

Las variables de entorno se usan para definir valores que están disponibles para los procesos que se ejecutan dentro del contenedor. Estas variables se definen al construir una imagen o al ejecutar un contenedor.

-e variable_entorno:valor_nuestro
es para asignar valores a las variables de entorno. Esas variables están definidas dentro de la imagen, por lo que nosotros le damos valor, para que el contenedor a ejecutar, use esos datos.

Usaremos la imagen de mongo

- docker pull mongo
- docker run --name=mongo_server -d -p 8082:27017 mongo

```
[kralos]
[~]
▶ docker pull mongo
Using default tag: latest
latest: Pulling from library/mongo
43f89b94cd7d: Pull complete
54a7480baa9d: Pull complete
7f9301fbdf7df: Pull complete
5e4470f2e90f: Pull complete
40d046ff8fd3: Pull complete
e062d62b861e: Pull complete
72919e34fde8: Pull complete
ab22810dfc64: Pull complete
fb05c29fbdf5: Pull complete
Digest: sha256:d341a86584b96eb665345a8f5b35fba8695ee1d0618fd012ec4696223a3d6c62
Status: Downloaded newer image for mongo:latest
docker.io/library/mongo:latest
```

Practica 3

The screenshot shows a web browser window with the URL `hub.docker.com/_/mongo` in the address bar. The main content is titled "Environment Variables". It explains that when starting the `mongo` image, environment variables can be passed via the `docker run` command line. It notes that if a data directory already contains a database, existing databases will remain untouched. Two environment variables are highlighted: `MONGO_INITDB_ROOT_USERNAME` and `MONGO_INITDB_ROOT_PASSWORD`.

When you start the `mongo` image, you can adjust the initialization of the MongoDB instance by passing one or more environment variables on the `docker run` command line. Do note that none of the variables below will have any effect if you start the container with a data directory that already contains a database: any pre-existing database will always be left untouched on container startup.

`MONGO_INITDB_ROOT_USERNAME` , `MONGO_INITDB_ROOT_PASSWORD`

```
docker run --name=monguito -d -p 8083:27017  
-e MONGO_INITDB_ROOT_USERNAME=nico  
-e MONGO_INITDB_ROOT_PASSWORD=12345678 mongo
```

Practica 3

```
[kralos]--[¶main = ● ]
[D:\umar\Asignaturas\Semestre 23-24 A\912_TI_1\Notas_TI1\code\nodejs\proyecto_1]
● ▶ docker ps -a
CONTAINER ID   IMAGE      COMMAND      CREATED      STATUS          PORTS      NAMES
f3c176d990da   linuxconfig/lemp "supervisord"  23 hours ago  Exited (137) 23 hours ago
140a76a8ce6a   linuxconfig/lemp "supervisord"  13 days ago   Exited (137) 23 hours ago
2f5eba4f771b   hello-world    "/hello"     2 weeks ago   Exited (0) 2 weeks ago
2bc45d52863b   hello-world    "/hello"     2 weeks ago   Exited (0) 2 weeks ago
[kralos]--[¶main = ● ]
[D:\umar\Asignaturas\Semestre 23-24 A\912_TI_1\Notas_TI1\code\nodejs\proyecto_1]
● ▶ docker ps
● CONTAINER ID   IMAGE      COMMAND      CREATED      STATUS      PORTS      NAMES
[kralos]--[¶main = ● ]
[D:\umar\Asignaturas\Semestre 23-24 A\912_TI_1\Notas_TI1\code\nodejs\proyecto_1]
● ▶ docker run --name=monguito -d -p 8083:27017 -e MONGO_INITDB_ROOT_USERNAME=nico -e MONGO_INITDB_ROOT_PASSWORD=12345678 mongo
29293400974ad156801a24f8cc0da3ff3158116250386c3bc7d692daa3cb9e5a
[kralos]--[¶main = ● ]
[D:\umar\Asignaturas\Semestre 23-24 A\912_TI_1\Notas_TI1\code\nodejs\proyecto_1]
● ▶ docker ps
CONTAINER ID   IMAGE      COMMAND      CREATED      STATUS      PORTS      NAMES
29293400974a   mongo      "docker-entrypoint.s..."  About a minute ago  Up About a minute  0.0.0.0:8083->27017/tcp  monguito
[kralos]--[¶main = ● ]
[D:\umar\Asignaturas\Semestre 23-24 A\912_TI_1\Notas_TI1\code\nodejs\proyecto_1]
○ ▶ █
```

Practica 3

```
code > nodejs > proyecto_1 > packagejson > ...
You, 2 seconds ago | 1 author (You)
1 { You, 21 hours ago * other project
2   "name": "mongoapp",
3   "version": "1.0.0",
4   "description": "",
5   "main": "index.js",
6   "type": "module",
7     > Debug
8   "scripts": {
9     "test": "echo \"Error: no test specified\" && exit 1"
10  },
11  "author": "",
12  "license": "ISC",
13  "dependencies": {
14    "express": "4.18.1",
15    "mongoose": "6.12.1"
16  }
17 } <- #1-16 { "name": "mongoapp", "version": "1.0.0", "description": "", ...
PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS GITLENS
[kralos]--[¶main = ●]
[D:\umar\Asignaturas\Semestre 23-24 A\912_TI_1\Notas_TI1\code\nodejs\proyecto_1]
● ▶ npm install
added 87 packages, and audited 88 packages in 2m
13 packages are looking for funding
  run `npm fund` for details
2 vulnerabilities (1 moderate, 1 critical)
● To address all issues, run:
  npm audit fix --force
● Run `npm audit` for details.
[kralos]--[¶main = ●]
[D:\umar\Asignaturas\Semestre 23-24 A\912_TI_1\Notas_TI1\code\nodejs\proyecto_1]
● ▶ npm audit fix --force
● npm WARN using --force. Recommended protections disabled.
npm WARN audit Updating mongoose to 6.12.1, which is outside your stated dependency range.
added 82 packages, removed 2 packages, changed 4 packages, and audited 168 packages in 47s
14 packages are looking for funding
  run `npm fund` for details
found 0 vulnerabilities
[kralos]--[¶main = ●]
[D:\umar\Asignaturas\Semestre 23-24 A\912_TI_1\Notas_TI1\code\nodejs\proyecto_1]
● ▶ [REDACTED]
```

code > nodejs > proyecto_1 > packagejson > {} dependencies


You, 21 hours ago | 1 author (You)

```
1 {
2   "name": "mongoapp",
3   "version": "1.0.0",
4   "description": "",
5   "main": "index.js",
6   "type": "module",
7     > Debug
8   "scripts": {
9     "test": "echo \"Error: no test specified\" && exit 1"
10  },
11  "author": "",
12  "license": "ISC",
13  "dependencies": []
14    "express": "4.18.1",
15    "mongoose": "6.4.1"
16 } <- #1-16 { "name": "mongoapp", "version": "1.0.0", "description": "", ...
PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS GITLENS
code > nodejs > proyecto_1 > JS index.js M X
code > nodejs > JS index.js > ...
You, 4 minutes ago | 1 author (You)
1 import express from 'express'
2 import mongoose from 'mongoose'
3
4 const Animal = mongoose.model('Animal', new mongoose.Schema({
5   tipo: String,
6   estado: String,
7 }))
8
9 const app = express()
10
11 mongoose.connect('mongodb://nico:12345678@127.0.0.1:8083/miapp?authSource=admin')
12
13 app.get('/', async (_req, res) => {
14   console.log('listando... chanchitos...')
15   const animales = await Animal.find();
16   return res.send(animales)
17 })
18 app.get('/crear', async (_req, res) => {
19   console.log('creando...')
20   await Animal.create({ tipo: 'Chanchito', estado: 'Feliz' })
21   return res.send('ok')
22 })
23
24 app.listen(3000, () => console.log('listening...'))
```


25

Practica 3


```
[kralos]--[ψmain ≡ ● ]
[D:\umar\Asignaturas\Semestre 23-24 A\912_TI_1\Notas_TI1\code\nodejs\proyecto_1]
o ▶ node .\index.js
listening...
listando... chanchitos...
[]
```



```
[kralos]--[ψmain ≡ ● ]
[D:\umar\Asignaturas\Semestre 23-24 A\912_TI_1\Notas_TI1\code\nodejs\proyecto_1]
o ▶ node .\index.js
listening...
listando... chanchitos...
creando...
[]
```



```
[kralos]--[ψmain ≡ ● ]
[D:\umar\Asignaturas\Semestre 23-24 A\912_TI_1\Notas_TI1\code\nodejs\proyecto_1]
o ▶ node .\index.js
listening...
listando... chanchitos...
creando...
listando... chanchitos...
[]
```



Referencias

- *Comandos más usados en Docker.* (n.d.). Tutoriales.online. Retrieved October 4, 2023, from <https://tutoriales.online/chuletas/docker>
- *Docker.* (n.d.). Docker.com. Retrieved October 4, 2023, from <https://hub.docker.com/>
- *Docker.* (n.d.). Docker.com. Retrieved October 4, 2023, from <https://hub.docker.com/>
- <https://github.com/nschurmann/mongoapp-curso-docker>